



EXPLANATION

- 5
10
- ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 1 foot.
- 7000
6800
- STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet. Contour interval 200 feet (61 m). Datum is mean sea level.
- 6582
4
- DRILL HOLE - Showing altitude of top of coal bed, and thickness of coal, in feet.
- 6870
6.0
- POINT OF MEASUREMENT - Showing altitude of top of coal bed, and thickness of coal, in feet. Altitudes not shown for underground mine measured sections. Includes all points of measurement other than drill holes.
- 2.2/4
- INTERBEDDED COAL AND ROCK - Showing total coal thickness/rock thickness.
- Av-3A - Adaville No. 3A
SV[2] - Spring Valley [2]
- COAL BED SYMBOLS AND NAMES - Coal beds identified by bracketed numbers are not formally named, but are numbered for identification purposes in this quadrangle only.
- SV[2]
- TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Long dashed where inferred; short dashed where inferred by present authors.
- To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1962 Compiled in 1978



COAL RESOURCE OCCURRENCE MAP OF THE CUMBERLAND GAP
QUADRANGLE, UINTA AND LINCOLN COUNTIES, WYOMING

BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

PLATE 6
ISOPACH AND STRUCTURE CONTOUR
MAP OF THE SPRING VALLEY
[2] AND ADAVILLE NO.3A
COAL BEDS