


EXPLANATION


- 5 —
ISOPACHS - Showing thickness of coal, in feet. Isopach interval 1 foot.
 - 6400 —
STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground surface. Contour interval 200 feet (61 m). Datum is mean sea level.
 - 6295
5.5
DRILL HOLE - Showing altitude of top of coal bed, and thickness of coal, in feet.
 - Fa[15] - Fairfield coal group, coal bed [15]
 - COAL BED SYMBOL AND NAME - Coal bed identified by bracketed numbers is not formally named, but is numbered for identification purposes in this quadrangle only.
 - Fa[15] —
TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Short dashed where projected by present authors.
 - 15° -----
SUBSURFACE MINING LIMIT - Showing areas where dips of coal beds are greater than 15° and subsurface mining by conventional methods is not considered feasible. Reserve Base tonnages are calculated beyond limit; Reserve tonnages are not. Arrow points toward area where dips are greater than 15°.
 - C -----
INFERRED LIMIT OF BAKED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.
- To convert feet to meters, multiply feet by 0.3048.



Base from U.S. Geological Survey, 1966

Compiled in 1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.



COAL RESOURCE OCCURRENCE MAP OF THE AXIAL QUADRANGLE,
MOFFAT COUNTY, COLORADO

BY
DAMES & MOORE
1979

PLATE 24
ISOPACH AND STRUCTURE
CONTOUR MAP OF THE FAIRFIELD
COAL GROUP, COAL BED [15]