

EXPLANATION

— 200 —
OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval 200 feet (61 m) over strip-pable coal and 1000 feet (305 m) beyond the stripping-limit line.

— 15 —
MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping-limit (in this quadrangle, the 200-foot-overburden isopach).

Gr - Grinsted

COAL BED SYMBOL AND NAME

Gr - - - - -

TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Short dashed where projected by present authors. Dotted where concealed.

—|—

TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known.


To convert feet to meters, multiply feet by 0.3048.

NOTE: Overburden isopachs and mining ratio contours are not drawn beyond dotted line because of insufficient data.

Base from U.S. Geological Survey, 1966

Compiled in 1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.



**COAL RESOURCE OCCURRENCE MAP OF THE MEEKER
QUADRANGLE, RIO BLANCO COUNTY, COLORADO**
BY
DAMES & MOORE
1979