




EXPLANATION

- 5
6
- ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred; short dashed where projected beyond coal-bearing area. Isopach interval 1 foot.
- 5600
5680
- STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 80 feet; long dashed where vertical accuracy possibly not within 80 feet; short dashed where projected above ground surface. Contour interval 80 feet (24 m). Datum is mean sea level.
- 5539
6.0
- POINT OF MEASUREMENT - Showing altitude of top of coal bed, and thickness of coal, in feet. Includes all points of measurement other than drill holes.
- Em - Emery coal zone
- COAL BED SYMBOL AND NAME - Coal bed identified by bracketed number is not formally named, but is numbered for identification purposes in this quadrangle only.
- Em
- TRACE OF COAL ZONE OUTCROP - Showing symbol of name of coal zone as listed above. Arrow points toward coal-bearing area. Dashed where inferred.
- TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approximately located.
- To convert feet to meters, multiply feet by 0.3048.

NOTE: Structure contours are not drawn beyond those shown because of insufficient data.



This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

COAL RESOURCE OCCURRENCE MAP OF THE NORTHEAST QUARTER OF THE NOTOM 15-MINUTE QUADRANGLE, WAYNE AND GARFIELD COUNTIES, UTAH
BY
DAMES AND MOORE
1979