



Mapped, edited, and published by the Geological Survey
Control by USGS and USL&GS
Topography by photogrammetric methods from aerial photographs taken 1965. Field checked 1967.
Polyconic projection. 1927 North American datum.
10,000-foot grid based on Virginia coordinate system, north zone and West Virginia coordinate system, south zone.
1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue.

SCALE 1:24,000

CONTOUR INTERVAL 40 FEET
DATUM IS MEAN SEA LEVEL

ROAD CLASSIFICATION
Secondary highway, all weather, hard surface
Light duty road, all weather, improved surface
Unimproved road, fair or dry weather
State Route

REDDISH KNOB, VA.—W. VA.
NW/4 PARNASSUS 15 QUADRANGLE
N.3822.5—W.7907.5/7.5
1967

Landslides and related features interpreted from aerial photographs:
1:60,000 (black and white) 1959
1:79,000 (black and white) 1977

Photointerpretation and field check 1979
This map has not been edited or reviewed for conformity with Geological Survey standards and nomenclature.

LANDSLIDES AND RELATED FEATURES
OF THE REDDISH KNOB, VA.—W. VA. QUADRANGLE
by Robert J. Hackman and Roger E. Thomas
1980
U.S. Geological Survey
OPEN FILE MAP 80-194 (D-7)

NOTE
Information shown is intended as a general guide to ground conditions as of the date of field check. Additional landslides and rockfalls should be anticipated in all map units. The map unit depicts the dominant condition in the area delineated and variations in slope stability may occur at any point in the unit. This map is suitable for general planning purposes and as a supplement to more detailed studies for site selection. The map cannot be used as a substitute for detailed geologic and engineering investigations to establish design and construction criteria of specific sites. Some symbols may not appear on this map because the description is applicable to a series of maps.

- ACTIVE OR RECENTLY ACTIVE LANDSLIDE**
Complex landslide composed of earthflow, debris slides, earth and rock slump. Identified from historical records, and from scars, debris and other field evidence. Ground extremely unstable; sliding accelerated by excavation, loading and changes in drainage conditions. May include areas with several active slides too small to be shown separately. Questioned where doubtful.
- OLD LANDSLIDE**
Area of extensive hummocky ground caused by earthflow and earth and rock slump. Lacks clear evidence of active sliding. Relatively stable in natural, undisturbed state, generally not affected by small structures properly sited in areas away from the edge of the toe; can be reactivated by extensive, rapid excavation, loading, and changes in ground water and surface water conditions. Area of old landslide probably includes recent ones not identified from field evidence or otherwise documented. Upslope boundary of landslide generally defined by modified scarp, but downslope (toe) may be gradational and not well defined. Questioned where doubtful.
- COMBINATION LANDSLIDE**
Area of recent and old slides in which individual slides are not identified.
- COLLUVIAL SLOPE**
Valley wall along major streams with slope as steep as 40° (85%); stony, clayey silt soil up to 50 ft. (15 m) thick; commonly buttressed by a terrace or bench at the toe of the slope; very susceptible to sliding by cutting of toe area, removal of terrace or bench, and overloading; slide commonly activated without apparent cause.

- COLLUVIAL SLOPES WITH LANDSLIDES**
Landslides too small or obscure to map individually.
- AREAS SUSCEPTIBLE TO DEBRIS FLOWS AND DEBRIS AVALANCHES**
Primarily shallow, narrow ravines and chutes with accumulation of stony colluvium generally 10 ft. (3 m) or less in thickness; susceptible to rapid movement during intense rainfall. Most ravines and chutes designated show evidence of former debris flows and avalanches. Symbol & designates historical debris flow or debris avalanche.
- AREAS SUSCEPTIBLE TO ROCKFALL**
Steep, locally vertical, natural and man-made slopes and cliffs, 15 ft. (4.5 m) or more high; formed dominantly of sandstone, limestone, sandy shale, mudstone and claystone. Interbedded mudstone, claystone and shale weather rapidly leaving sandstone and limestone rock faces unsupported.
- SOIL AND ROCK SUSCEPTIBLE TO LANDSLIDING**
Soil and rock similar to that involved in landslides elsewhere in map area; primarily areas underlain by claystone, mudstone and shale associated with other rock types. Rock weathers rapidly on exposure forming clayey soil highly susceptible to sliding. Includes coves (U-shaped, shallow valleys) containing thick layers of clayey soil that are very susceptible to sliding where excavation breaks continuity of slope and where overloaded by artificial fill.

AREAS LEAST PRONE TO LANDSLIDES
Map areas in which no patterns or symbols are shown; primarily valley floors, ridge tops and broad benches; modification by excavation and fill may lead to local landslides.

- MAN-MADE FEATURES**
- Strip mines (combination of letter symbols indicates complex formed of more than one type of strip mine)
 - sh — bench with high wall
 - sf — furrowed with high wall
 - sd — multiple furrows and multiple benches
 - ss — hilltop removed
 - srq — reclaimed by grading
 - sru — reclaimed by secondary use
 - sh/r — regraded in part, high wall remains
 - Coal refuse banks
 - r — identified on aerial photographs; not classified in field check
 - rb — not burnt nor on fire
 - rbb — burnt
 - rbd — burning
 - rbs — sludge
 - Quarries
 - q — quarry site
 - qub — spoil bank, quarry waste
 - Gravel pits
 - g — site of gravel pit
 - Slides in man-made features
 - af — earth flow in fill
 - a/s — earth flow in strip castings
 - a/r — earth flow in coal refuse

The first five digits of the open file number designate the specific 1:250,000 scale map sheet of which this quadrangle is a part. The last two digits designate the position of the quadrangle in a subdivision of the 1:250,000 scale map based on rows and tiers shown in the diagram to the right. The location of this quadrangle is shown by the black square.

