

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

USER'S MANUAL FOR Z MP

By Carl A. Carlson

U.S. Geological Survey
Open-File Report 82-621
1982

This report is preliminary and
has not been reviewed for conformity
with U.S. Geological Survey
editorial standards.

Any use of trade names is for
descriptive purposes only
and does not imply endorsement by
the U.S. Geological Survey

Table of Contents

	<u>Page</u>
Introduction -----	1
Operating instructions -----	7
Program listings -----	9
Bibliography -----	18

List of Illustrations

Figure 1. Sample location map -----	2
2. Symbol dictionary format -----	3
3. Map data format -----	4
4. Standard extended character set -----	5
5. Composite symbol codes -----	6


INTRODUCTION

This is the user's manual for the program z_mp (zeta map plot). Z_mp plots sample location maps (see fig. 1). Z_mp is an extension of the program G239 (map plot) described by Peterson (1977). This section describes the extensions to G239. The user is directed to Peterson (1977) for further information. The next section gives step by step procedures for using z_mp. The following section contains a listing of z_mp. A bibliography completes the manual.

Z_mp implements these extensions:

- o It now runs on the U.S. Geological Survey Multics computer in Menlo Park, Calif.
- o In place of the two card decks used by G239, it uses two Multics segments. The first is the symbol dictionary. It contains the symbol codes and symbol names for use in interpreting the map data. The map data is contained in the second segment. It comprises the map title, the map scale, the map boundaries, and the sample locations. Both segments possess a format which is identical to the corresponding card decks used by G239. Examples of both formats are shown in figures 2 and 3. These figures also show optional extensions now possible with z_mp.
- o It uses an extended set of map symbols. See figure 4.
- o It will plot optional labels adjacent to each plotted symbol. These symbols can be up to 32 characters long and they can be plotted at any angle.
- o It will plot symbols and labels with any of four pens (colors).
- o It will draw a map legend.
- o It will plot composite symbols which can represent multiple data values at a given location. See figure 5; and
- o It will plot the map on a Zeta 6300s Offline Plotting System.

You can create the dictionary and map data segments either by composing them using a Multics text editor such as qedx (Honeywell Information Systems Inc., 1979) or by running the program statmap (Carlson, 1982). Statmap will automatically generate both segments from data contained in a STATPAC file. The STATPAC SYSTEM is described by VanTrump and Miesch (1977).



⊕ DEMONSTRATION OF Z MP

Figure 1. Sample location map. This is a sample of a map produced by z_mp. The following two figures contain the dictionary and the map data files used to plot this map.

```

.....
v1 210 1 90
v2 202 1 45          This is a four line dictionary
v3 203 1 0
v4 203 1 315
.....
                                Column Numbers

11111111112222222222333333333344444444445555555555666666666677777777778
1234567890123456789012345678901234567890123456789012345678901234567890

-----
---  *  -  *
*    *  *  **** Angle at which the label is written. In the case of
*    *  *      composite symbols, this is the angle at which the line,
*    *  *      the symbol, and the label are written. (measured in
*    *  *      degrees counter clock-wise from the three o'clock
*    *  *      direction, right justified)
*    *  *
*    *  ***** Pen number. Any integer between 1 and 4 is acceptable.
*    *
*    ***** Symbol code. (either standard or composite, right
*                      justified)
*
***** Symbol name used in the map data file to select the
          symbol code, pen number, and angle shown on the rest
          of this line. (any combination of 1,2, or 3 letters
          and or numbers that are left justified)

```

Figure 2. Symbol dictionary format. A sample dictionary file is shown between the two dotted lines. Below it are shown the field locations, lengths and definitions.

Column Numbers

1111111111222222222233333333334444444444555555555566666666667777777778
1234567890123456789012345678901234567890123456789012345678901234567890

```
.....
DEMONSTRATION OF Z_MP                                <----- 40 columns of map label
24000<----- map scale
.1 .1<----- map boundaries
.1 3500.0<----- ditto
3500.0 3500.0<----- ditto
3500.0 .1<----- ditto
0.0 0.0<----- flag to signal end of boundaries
0.08v1 CU 750.0 1050.0
0.15v2 PB 1850.0 1050.0
0.15v3 TI 1250.0 750.0
0.16v4 ZN 2750.0 350.0
0.09v1 AU 3050.0 1000.0
0.08v2 AG 2550.0 3350.0
0.09v3 CR 350.0 2150.0
0.10v4 SN 1750.0 1750.0
.....
```

Column Numbers

1111111111222222222233333333334444444444555555555566666666667777777778
1234567890123456789012345678901234567890123456789012345678901234567890

```
---
--- *
* *
* *
* *
* *
* *
* *
* *
* *
* ***** Symbol name. (left justified)
* ***** Symbol size. (in inches)
```

Figure 3. Map data format. A sample map data file is shown between the two dotted lines. Each field is defined and its extent shown.

1	⌈	21	≤	41)	61	≡	81	⊙	101	⊙	121	⊙	141	⊙	161	⊙	181	⊙	201	⊙
2	⊙	22	≥	42	*	62	>	82	⊙	102	f	122	Z	142	⊙	162	⊙	182	⊙	202	⊙
3	⊙	23	≡	43	+	63	?	83	⊙	103	⊙	123	{	143	⊙	163	⊙	183	⊙	203	⊙
4	⊙	24	≈	44	9	64	@	84	⊙	104	⊙	124	⊙	144	⊙	164	⊙	184	⊙	204	⊙
5	⊙	25	→	45	-	65	⊙	85	⊙	105	⊙	125	}	145	⊙	165	⊙	185	⊙	205	⊙
6	⊙	26	↑	46	⊙	66	⊙	86	⊙	106	⊙	126	⊙	146	⊙	166	⊙	186	⊙	206	⊙
7	⊙	27	←	47	/	67	⊙	87	⊙	107	k	127	-	147	⊙	167	⊙	187	⊙	207	⊙
8	⊙	28	↓	48	⊙	68	⊙	88	⊙	108	⊙	128	⊙	148	⊙	168	⊙	188	⊙	208	⊙
9	⊙	29	⊙	49	⊙	69	⊙	89	⊙	109	⊙	129	⊙	149	⊙	169	⊙	189	⊙	209	⊙
10	⊙	30	∞	50	2	70	⊙	90	⊙	110	⊙	130	⊙	150	⊙	170	⊙	190	⊙	210	⊙
11	⊙	31	⊙	51	3	71	⊙	91	⊙	111	⊙	131	⊙	151	⊙	171	⊙	191	⊙	211	⊙
12	⊙	32	⊙	52	4	72	⊙	92	⊙	112	⊙	132	⊙	152	⊙	172	⊙	192	⊙	212	⊙
13	⊙	33	⊙	53	5	73	⊙	93	⊙	113	⊙	133	⊙	153	⊙	173	⊙	193	⊙	213	⊙
14	⊙	34	⊙	54	⊙	74	⊙	94	⊙	114	⊙	134	⊙	154	⊙	174	⊙	194	⊙	214	⊙
15	⊙	35	⊙	55	7	75	⊙	95	⊙	115	⊙	135	⊙	155	⊙	175	⊙	195	⊙	215	⊙
16	⊙	36	⊙	56	⊙	76	⊙	96	⊙	116	⊙	136	⊙	156	⊙	176	⊙	196	⊙	216	⊙
17	⊙	37	⊙	57	⊙	77	⊙	97	⊙	117	⊙	137	⊙	157	⊙	177	⊙	197	⊙	217	⊙
18	⊙	38	⊙	58	⊙	78	⊙	98	⊙	118	⊙	138	⊙	158	⊙	178	⊙	198	⊙	218	⊙
19	⊙	39	⊙	59	⊙	79	⊙	99	⊙	119	⊙	139	⊙	159	⊙	179	⊙	199	⊙	219	⊙
20	⊙	40	⊙	60	⊙	80	⊙	100	⊙	120	⊙	140	⊙	160	⊙	180	⊙	200	⊙	220	⊙

Figure 4. Standard extended character set. The number to the left of each symbol is the symbol code to be used in the symbol dictionary. The small + locates the center of the symbol.







.....									
Each composite symbol is composed of one or more plotted line + symbol + label									
sets. You must have one line of text in your map data file for every set.									
This text line will have a size, a symbol name, an optional label and UTM's									
as was shown in Figure 3. The symbol name refers to a line in the									
dictionary which contains the symbol name, the symbol code, an angle,									
and a pen number as was shown in Figure 2. The angle refers to the									
angle measured counter-clock-wise from the three o'clock position along									
which the line + symbol + label are to be plotted. The meanings of the									
size and the symbol code are shown below:									
.....									
Example:									
Length of									
the line	The size		.08 in.		.15 in.		.25 in.		The size
equals:									
Height of									
the symbol	Size/3		.07 in.		The size		The size		The size
equals:									
.....									
Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard		
code +	code +	code times	code +	code +	code +	code +	code +		
300	600	-1	300 times	600 times	600 times	600 times	600 times		632
Symbol									
code									
equals:	G+300	C+600	-1*C	-1*(C+300)	-1	-1	-1		
.....									
Valid	301	601	-1	-301	-601				
codes:	to	to	to	to	to				
	517	817	217	-517	-817				632
.....									

Figure 5. Composite symbol codes. The information needed to compose the composite symbols which are shown at the top of the figure is tabulated in the columns below. Standard code refers to the codes shown in Figure 4.

OPERATING INSTRUCTIONS

Use the following procedures to run z_mp.

- Step 1. First you must create the dictionary and the map data files. Use either a Multics editor or statmap. Figures 2 and 3 illustrate the format to be used.
- Step 2. Now log on to the Multics computer using the Zeta terminal. The use of the Zeta terminal is described by Zeta Research (1977, 1978). Use the following procedure. Precede all characters intended to be capital letters with a \ (CTRL L).

```
SCA OFF or SCA X.XX Y.YY
ROT OFF or ROT ON
COR ON
COP COM PLO or COP COM TAP
```

Use the standard login procedure except that after the login message you must precede the login command with:

MAP

Continue with the login procedure as suggested below:

```
\C\CARLSON
PASSWORD
JYTVLHPESBHV
etc.
```

- Step 3. Type:

```
ASR >UDD>\W\MIN\RES>\C\CARLSON
```

- Step 4. Type:

```
Z_MP
```

Multics prints:

```
THIS IS Z_MP VERSION 3.0
WHAT IS THE NAME OF THE SEGMENT CONTAINING THE
DICTIONARY?
```

- Step 5. Type the chosen name.

Multics prints:

```
WHAT IS THE NAME OF THE SEGMENT CONTAINING THE
MAP DATA?
```

- Step 6. Type the chosen name.

Multics prints:

WHAT IS THE NAME OF THE SEGMENT WHERE YOU WANT TO
STORE THE PRINTED OUTPUT?

- Step 7. Type a name. Multics will create a segment with that name. It will contain error messages, etc.

Multics prints:

DO YOU WANT TO PLOT THE LABELS? (YES OR NO).

- Step 8. Type YES or NO depending on whether you want to label each point with the label fields found in the map data segment.

Multics will now plot your map on the plotter (if you used COP COM PLO above), or multics will store the plot on the Zeta tape drive (if you used COP COM TAP).

PROGRAM LISTINGS

```

C *****
C *
C * MINERAL MAPPING PROGRAM (G239)
C *
C * THIS PROGRAM PLOTS THE OUTLINE OF A GEOGRAPHICAL REGION
C * AND THEN MARKS THE LOCATIONS OF VARIOUS MINERAL DEPOSITS
C * WITHIN THAT REGION BY APPROPRIATE IDENTIFYING SYMBOLS.
C * ANY GEOLOGIC DATA REPRESENTABLE BY A MAP POINT IS ALSO
C * ABLE TO BE PLOTTED
C *
C *****
C *
C * MODIFIED TO ACCEPT MAP SCALE INSTEAD OF MAP DIMENSIONS,
C * TO PLOT A QUADRANGLE OR MAP NAME, TO INITIALIZE LIMITS OF
C * PEN MOVEMENTS AND SET ORIGIN, AND TO PROVIDE MORE CHECKS
C * AND ERROR MESSAGES FOR THE USER.
C * JOCELYN PETERSON 12/13/76
C *
C *****
C * REPLACED BENSON-LEHNER CALLS WITH ZETA CALLS
C * ADDED A SUBROUTINE ADJUST TO REPLACE A CALL TO SPOT
C * SAM PRIEBE 9/21/79 NEW ADJUST BY CAC REPLACES THIS ONE.
C *****
C *
C * MODIFIED TO RUN ON MULTICS. USER ENTERS SEGMENT NAMES
C * OF: DICTIONARY; MAP DATA; AND PRINTOUT DESTINATION.
C * THE PLOT DATA IS SENT DIRECTLY TO THE TERMINAL USING
C * ZETA'S ERROR CORRECTION. FEBRUARY 15,1980 CARL A CARLSON
C *
C *****
C *
C * MODIFIED TO USE DIFFERENT COLORS FOR SYMBOLS, PRINT A
C * TAG ADJACENT TO EACH SYMBOL, PRINT A KEY TO THE MAP,
C * AND USE DATA RETRIEVED FROM A STATPAC FILE BY THE PROGRAM
C * STATMAP. MAY 27, 1980. CARL A CARLSON
C * EXTENSIVE REVISIONS, FEBUARY, 1982
C *
C *****
C
CHARACTER*30 SEGNAME
CHARACTER*3 TAGS
INTEGER MINAM(40), MINCD(40), NAME, ISYM, BLANK, MPSCL,COLOR(40)
REAL LABLOCX, LABLOCY
INTEGER AGL(40)
REAL XBND(25),YBND(25),XMAX,YMAX,XMIN,YMIN
REAL XSCALE,YSCALE,XLOC,YLOC
REAL XORG,YORG,XLWR,YLWR,XUPR,YUPR
REAL QUAD(10),TAG(8)
DATA BLANK/' '/
C.....INPUT THE NAMES OF THE SEGMENTS REQUIRED

```

```

2000  FORMAT(V)
      WRITE(0,2000)"this is z_mp:  version 3.0"
      WRITE(0,2000)"what is the name of the segment containing the"
      WRITE(0,2000)"dictionary?"
      READ(0,2000)SEGNAM
      OPEN(10,FORM="FORMATTED",FILE=SEGNAM)
      WRITE(0,2000)"what is the name of the segment containing the"
      WRITE(0,2000)"map data?"
      READ(0,2000)SEGNAM
      OPEN(12,FORM="FORMATTED",FILE=SEGNAM)
      WRITE(0,2000)"what is the name of the segment where you want to"
      WRITE(0,2000)"store the printed output?"
      READ(0,2000)SEGNAM
      OPEN(11,FORM="FORMATTED",FILE=SEGNAM)
      WRITE(0,2000)"do you want to rotate the map 90 deg.? yes or no."
      READ(0,2000)SEGNAM
4000  WRITE(0,2000)"do you want to plot the labels? (yes or no)"
      READ(0,2000)TAGS
      IF ((TAGS.NE."yes").AND.(TAGS.NE."no")) GOTO 4000
C.....CALL PLOTS TO INITIALIZE THE ZETA
      CALL PLOTS(53,0,-1)
C.....CALL SYMDIC TO READ THE NEXT SET OF DICTIONARY LINES
18    CALL SYMDIC(MINAM,MINCD,COLOR,IS,AGL)
C.....READ QUADRANGLE NAME
      READ(12,1000) QUAD
1000  FORMAT(10A4)
      WRITE(11,1001) QUAD
1001  FORMAT('1',1X,10A4)
C.....READ MAP SCALE
      READ(12,19) MPSC
19    FORMAT(I10)
      WRITE(11,120) MPSC
120   FORMAT(' MAP SCALE:  1:',I10)
C.....READ CORNERS OF REGION BOUNDARY
20    DO 25 IB=1,24
      READ(12,22) XBND(IB),YBND(IB)
22    FORMAT(2F10.0)
      IF(XBND(IB)+YBND(IB) .EQ. 0.0) GO TO 30
25    CONTINUE
      WRITE(11,27)
27    FORMAT(' BOUNDARY DATA NOT TERMINATED BY BLANK CARD WITHIN 24' )
      STOP
30    IB=IB-1
      WRITE(11,130) (XBND(I),YBND(I), I=1,IB)
130   FORMAT(' REGION BOUNDARY' / (1X,F10.1,2X,F10.1))
C.....FIND MAXIMUM AND MINIMUM
      XMAX=-1.0E20
      YMAX=XMAX
      XMIN=1.0E20
      YMIN=XMIN
      DO 35 I=1,IB
      IF(XBND(I) .GT. XMAX) XMAX=XBND(I)
      IF(YBND(I) .GT. YMAX) YMAX=YBND(I)
      IF(XBND(I) .LT. XMIN) XMIN=XBND(I)

```

```

        IF(YBND(I) .LT. YMIN) YMIN=YBND(I)
35 CONTINUE
C.....COMPUTE SCALE FACTORS
        XSCALE=1./(.0254*MPSCCL)
        YSCALE=XSCALE
        WRITE(11,140) XMAX,XMIN,YMAX,YMIN,XSCALE,YSCALE
140 FORMAT(' XMAX=',F10.1,1X,'XMIN=',F10.1,1X,'YMAX=',F10.1,1X,
*         'YMIN=',F10.1 /1X,'XSCALE=',E12.5,1X,'YSCALE=',E12.5)
C.....SCALE BOUNDARY DATA
        DO 40 I=1,IB
        XBND(I)=(XBND(I)-XMIN)*XSCALE
        YBND(I)=(YBND(I)-YMIN)*YSCALE
40 CONTINUE
C.....CLOSE BOUNDARY
        IB=IB+1
        XBND(IB)=XBND(1)
        YBND(IB)=YBND(1)
        WRITE(11,150) (XBND(I),YBND(I), I=1,IB)
150 FORMAT(' SCALED BOUNDARY' / (1X,E12.5,2X,E12.5))
C.....SET PLOT LIMITS
        XORG=0.0
        YORG=0.0
        XLWR=-1.0
        YLWR=-1.0
        XUPR=(XMAX-XMIN)*XSCALE + 3.0
        YUPR=(YMAX-YMIN)*YSCALE
        YMUL=1
C.....CHECK TO INSURE MAP WILL FIT BEFORE PLOTTING
        IF(SEGNAM.EQ."yes") GOTO 5000
        IF(XUPR-XLWR .GT. 200.0) GO TO 300
        IF(YUPR-YLWR .GT. 36.0) GO TO 300
        GOTO 5001
5000 IF(XUPR-XLWR.GT.36.0) GOTO 300
        IF(YUPR-YLWR.GT.200.0) GOTO 300
5001 CONTINUE
C.....INITIALIZE PLOTTER
C        THE FOLLOWING CALL TO FACTOR CONVERTS 2.5 MIL SOFTWARE TO
C        2 MIL HARDWARE
        CALL FACTOR(1.25)
C        CALL PLOT(XLWR,YLWR,-60) COMMENTED OUT
C        CALL PLOT(XUPR,YUPR,+60) COMMENTED OUT
C        CALL PLOT(XLWR,YLWR,+3) COMMENTED OUT
C        CALL PLOT(XORG,YORG,-3) COMMENTED OUT
C        THE FOLLOWING CALL REPLACES THE PREVIOUS TWO RE-ORIGIN CALLS
        CALL PLOT(1.0,1.0,-3)
        WRITE(11,160) XORG,YORG,XLWR,YLWR,XUPR,YUPR
160 FORMAT(' PLOT LIMITS SET: XORG=',F6.2,1X,'YORG=',F6.2,1X,
*         'XLWR=',F6.2,1X,'YLWR=',F6.2,1X,'XUPR=',F6.2,1X,
*         'YUPR=',F6.2)
C.....PLOT A TIC MARK FOR CHECKING
C        CALL SPOT(-0.5,-0.5,0.12,66,0.0) COMMENTED OUT
        CALL SYMBOL(-0.5,-0.5,0.12,3,0.0,-
        WRITE(11,180)
180 FORMAT(' FIRST TIC PLOTTED')

```

1)

```

C.....PLOT QUADRANGLE NAME
      CALL SYMBOL(0.0,-0.5,0.12,QUAD,0.0,40)
C.....PLOT BOUNDARY
      X=XBND(1)
      Y=YBND(1)
      CALL PLOT(X,Y,3)
      DO 45 I=2,IB
      X=XBND(I)
      Y=YBND(I)
      CALL PLOT(X,Y,2)
45 CONTINUE
      WRITE(11,170)
170 FORMAT(' BOUNDARY PLOTTED')
C.....PLOT SECOND TIC MARK
C      CALL SPOT(-0.5,-0.5,0.06,69,0.0) COMMENTED OUT
      CALL SYMBOL(-0.5,-0.5,0.06,1,0.0,-1)
      WRITE(11,200)
200 FORMAT(' SECOND TIC PLOTTED')
C.....READ A MINERAL LOCATION CARD
      50 READ(12,52,END=80) H,NAME,TAG,XLOC,YLOC
      52 FORMAT(1X,F4.2,T6,A3,T13,8A4,T50,F9.1,T60,F9.1)
      IF(NAME.EQ. BLANK) GO TO 70
C.....FOR GROUP DATA WRITE A PARTIAL KEY AND READ A NEW DICTIONARY
      IF(NAME.EQ."NEX")CALL MAPL(XUPR,YUPR,MINAM,COLOR,MINCD,IS,YMUL)
      IF(NAME.EQ."NEX")CALL SYMDIC(MINAM,MINCD,COLOR,IS,AGL)
      IF(NAME.EQ."NEX")GOTO 50
C.....LOOK UP MINERAL SYMBOL CODE
      DO 55 I=1,IS
      IF(NAME.EQ. MINAM(I)) GO TO 65
55 CONTINUE
      WRITE(11,60) NAME
60 FORMAT(' NO SYMBOL CODE FOUND FOR: NAME=',A3)
      GO TO 50
65 ISYM=MINCD(I)
C.....TEST MINERAL LOCATION WITHIN MAP
      IF(XLOC.GT. XMAX) GO TO 302
      IF(XLOC.LT. XMIN) GO TO 302
      IF(YLOC.GT. YMAX) GO TO 302
      IF(YLOC.LT. YMIN) GO TO 302
      GO TO 303
302 WRITE(11,1003) XLOC,YLOC
1003 FORMAT(1X,F10.1,2X,F10.1,3X,'LOCATION NOT WITHIN MAP')
      GO TO 50
C.....SCALE LOCATION
303 XLOC=(XLOC-XMIN)*XSCALE
      YLOC=(YLOC-YMIN)*YSCALE
C.....PLOT LOCATION
C      CALL SPOT(XLOC,YLOC,H,ISYM,0.0) COMMENTED OUT
C      THE SUBROUTINE SPOT(BENSON-LEHRNER) IS REPLACED BY SYMBOL(ZETA)
C      VIA A CALL TO SUBROUTINE ADJUST TO CORRECTLY POSITION SYMBOLS
      RANGL=AGL(I)
C.....SELECT PEN COLOR
      CALL NEWPEN(COLOR(I))
C.....PLOT THE SYMBOL

```

```

        CALL ADJUST(ISYM,XLOC,YLOC,H,RANGL)
C.....PLOT THE LABEL (TAG)
        IF (TAGS.EQ."no") GOTO 68
        LABLEN=0
        CALL LABELLOC (H, RANGL, TAG, LABLOCX, LABLOCY, LABLEN)
        IF (LABLEN.GT.0) CALL SYMBOL(XLOC+LABLOCX,YLOC+LABLOCY,H,TAG,RANGL
+ ,LABLEN)
68      CONTINUE
        WRITE(11,190) XLOC,YLOC
        190 FORMAT(' MINERAL LOCATION PLOTTED AT',2E14.5)
        GO TO 50
C.....PLOT THIRD TIC MARK
C 70 CALL SPOT(-0.5,-0.5,0.12,69,0.0)          COMMENTED OUT
        70 CALL SYMBOL(-0.5,-0.5,0.12,1,0.0,-1)
C.....PLOT THE KEY TO THE MAP.
        CALL MAPL(XUPR,YUPR,MINAM,COLOR,MINCD,IS,YMUL)
        WRITE(11,220)
        220 FORMAT(' THIRD TIC PLOTTED')
C.....MOVE ORIGIN DOWN FOR NEXT PLOT
        CALL PLOT(XUPR,0.0,-3)
        GO TO 18
C.....READ AND IGNORE DATA WHEN MAP TOO LARGE TO PLOT
        300 WRITE(11,1002)
        1002 FORMAT(' MAP LARGER THAN PAPER. NOT PLOTTED')
        301 READ(12,52,END=80) NAME
        IF(NAME .EQ. BLANK) GO TO 18
        GO TO 301
C.....PLOT FINAL TIC MARK
C 80 CALL SPOT(-0.5,-0.5,0.12,69,0.0)          COMMENTED OUT
        80 CALL SYMBOL(-0.5,-0.5,0.12,1,0.0,-1)
C.....PLOT THE KEY TO THE MAP
        CALL MAPL(XUPR,YUPR,MINAM,COLOR,MINCD,IS,YMUL)
        WRITE(11,210)
        210 FORMAT(' FINAL TIC PLOTTED')
C.....END OF PLOT
        CALL PLOT(0.0,0.0,999)
        CLOSE(10)
        CLOSE(11)
        CLOSE(12)
        CLOSE(13)
        STOP
        END
C*****
C      THIS SUBROUTINE PLOTS THE KEY FOR THE MAP
C      CARL A CARLSON MAR 11, 1980.
C*****
        SUBROUTINE MAPL(XUPR,YUPR,MINAM,COLOR,MINCD,IS,YMUL)
        INTEGER MINAM(40),COLOR(40),MINCD(40)
        CALL NEWPEN(1)
        IF(YMUL.NE.1)GOTO 2002
        YMUL=YUPR-3.2
        CALL PLOT(XUPR-2.5,1.5,3)
        CALL PLOT(XUPR-0.5,1.5,2)
        CALL PLOT(XUPR-0.5,YUPR-1.5,2)

```

```

      CALL PLOT(XUPR-2.5,YUPR-1.5,2)
      CALL PLOT(XUPR-2.5,1.5,2)
      CALL PLOT(XUPR-2.5,1.5,3)
      CALL SYMBOL(XUPR-1.83,YUPR-2.0,0.12,5H KEY,0.0,5)
      CALL SYMBOL(XUPR-2.4,YUPR-2.5,0.1,18H NAME SYMBOL,0.0,18)
2002 DO 2001 ICC=1,IS
      ICODE=IABS(MINCD(ICC))
3000 IF (ICODE.GE.301) ICODE=ICODE-300
      IF (ICODE.GE.301) GOTO 3000
      CALL NEWPEN(1)
      X=XUPR-2.05
      Y=YMUL-(ICC-1)*(.33)
      CALL SYMBOL(X,Y,.12,MINAM(ICC),0.0,3)
      CALL NEWPEN(COLOR(ICC))
      X=X+1.1
      Y=Y+.06
      H=.12
      RANGL=0.0
      CALL ADJUST(ICODE,X,Y,H,RANGL)
2001 CONTINUE
      YMUL=Y-.33
      CALL NEWPEN(1)
      END
C*****
C      THIS READS A DICTIONARY *
C*****
      SUBROUTINE SYMDIC(MINAM,MINCD,COLOR,IS,AGL)
      INTEGER MINAM(40),MINCD(40),COLOR(40),AGL(40)
10 DO 14 IS=1,40
      READ(10,12,END=16)MINAM(IS),MINCD(IS),COLOR(IS),AGL(IS)
12 FORMAT(A3,I4,1X,I3,1X,I3)
      IF(MINCD(IS).EQ.999)GOTO 16
      IF(COLOR(IS).LT.1)COLOR(IS)=1
      IF(COLOR(IS).GT.4)COLOR(IS)=1
14 CONTINUE
      IS=31
16 IS=IS-1
      WRITE(11,110) (MINAM(I),MINCD(I),I=1,IS)
110 FORMAT(' SYMBOL DICTIONARY' / (1X,A3,2X,I2))
      END
C *****
C * SUBR: ADJUST APPROXIMATELY CENTERES SYMBOLS. PLOTS *
C * SYMBOLS AND SPAR DIAGRAMS. ADJUSTS LOCATION FOR THE *
C * TAG (LABEL) WHICH IS TO BE PLOTTED IN MAIN PROGRAM. *
C * BY CCARLSON FEB. 5, 1982 *
C *****
      SUBROUTINE ADJUST( ISYM, XLOC, YLOC, H, RANGL)
      DIMENSION POS(2,196)
      DIMENSION A(196),B(196)
      EQUIVALENCE (POS(1,1),A(1)),(POS(1,99),B(1))
      DATA A/.22,.35,.22,.35,.35,.35,.35,.35,.35,.35,.35,
+ .35,.27,.35,.27,.17,.27,.27,.27,.35,.35,.35,.35,.35,.35,
+ .22,.35,.35,.45,.22,.3,.22,.45,.22,.35,.22,.35,.22,.45,
+ .22,.35,.22,.45,.22,.45,.22,.45,.35,.35,.35,.35,.22,.4,

```



```

+ .35,.35,.22,.45,.22,.35,.35,.27,.22,.35,0.0,0.0,.35,.4,
+ .4,.75,.22,.35,.22,.45,.22,.4,.3,.4,.35,.7,.35,.4,
+ .22,.4,.22,.35,.22,.35,.05,.05,.35,.35,.05,.05,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.3,.35,.3,.3,.22,.45,.22,.35,.22,.45,
+ .35,.45,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.35,
+ .3,.35,.3,.8,.35,.22,.35,.22/
DATA B/.35,.22,.35,.22,.35,.22,
+ .3,.35,.35,.22,.35,.22,.35,.22,.35,.1,.22,.35,.35,.35,
+ .35,.22,.35,.22,.35,.22,.35,.22,.35,.22,.35,.22,.35,.22,
+ .27,.35,.35,.22,.35,.22,.35,.22,.35,.22,.35,.22,.35,.22,
+ .17,.35,.22,.35,.4,.35,.35,.35,.35,.0,.22,.17,.35,.4,
+ .22,.45,.22,.45,.35,.35,.4,.4,.4,.4,.22,.4,.22,.27,.22,.75,
+ .35,.35,.35,.35,.22,.37,.35,.22,.22,.35,.22,.4,.17,.4,
+ .17,.4,.35,.4,.4,.3,.4,.3,.27,.35,.35,0.0,.22,-.1,.22,.35,
+ .17,.4,.22,.45,.22,.35,.22,.35,.22,.35,.22,.3,.22,.3,
+ .22,.35,.22,.3,.22,.35,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .22,.4,.22,.4,.22,.4,.22,.4,.22,.4,
+ .27,.35,.4,.4,.27,.35,.22,.35,.22,.35,.22,.4,.22,.4,.0,.0/
ISPOT=ISYM
XPOS=XLOC
YPOS=YLOC
HH=H
C
C      *** SEPERATE THE CASES ***
C
5000  IF ((ISYM.GT.0).AND.(ISYM.LE.195)) GOTO 1000
      IF ((ISYM.GE.200).AND.(ISYM.LE.216)) GOTO 2000
      IF ((ISYM.GE.217).AND.(ISYM.LE.300)) GOTO 3000
      IF ((ISYM.GE.301).AND.(ISYM.LE.900)) GOTO 4000
      IF ((ISYM.LE.-1).AND.(ISYM.GE.-900)) GOTO 4000
      RETURN
C
C      *** CENTER SYMBOLS AND PLOT ***
C
1000  XPOS=XPOS-POS(1,ISYM)*HH*1.25
      YPOS=YPOS-POS(2,ISYM)*HH*1.25
      CALL SYMBOL(XPOS,YPOS,HH,ISPOT,0.0,0)
      RETURN
C
C      *** USE PRE-CENTERED SYMBOLS AND PLOT ***
C
2000  ISPOT=ISYM-200
      CALL SYMBOL(XPOS,YPOS,HH,ISPOT,0.0,-1)
      RETURN
C
C      *** PLOT A CIRCLE ***
C
3000  RAD=HH/2.0

```

```

      CALL CIRCLE(XPOS,YPOS-RAD,-90.0,270.0,RAD,2)
      RETURN
C
C      *** PLOT A SPAR DIAGRAM ***
C
4000 RLENT=HH
      IF ((ISYM.LE.-1).AND.(ISYM.GE.-300)) RLENT=.08
      IF ((ISYM.LE.-301).AND.(ISYM.GE.-600)) RLENT=.15
      IF ((ISYM.LE.-601).AND.(ISYM.GE.-900)) RLENT=.25
C
C      *** PLOT THE SPAR ***
C
      DANGL=RANGL*(3.1415926/180.0)
      XSPAR=XPOS+RLENT*COS(DANGL)
      YSPAR=YPOS+RLENT*SIN(DANGL)
      CALL PLOT(XPOS,YPOS,3)
      CALL PLOT(XSPAR,YSPAR,2)
C
C      *** SET SYMBOL SIZE ***
C
      IF ((ISYM.GE.601).AND.(ISYM.LE.900)) HH=.07
      IF ((ISYM.GE.301).AND.(ISYM.LE.600)) HH=H/3.0
      IF (ISYM.LT.0) HH=H
C
C      *** SET UP LABEL SIZE ***
C
      H=.07
C
C      *** COMPUTE CORRECT SYMBOL CODE ***
C
      IF ((ISYM.GE.301).AND.(ISYM.LE.600)) ISYM=ISYM-300
      IF ((ISYM.GE.601).AND.(ISYM.LE.900)) ISYM=ISYM-600
      IF ((ISYM.LE.-1).AND.(ISYM.GE.-300)) ISYM=-1*ISYM
      IF ((ISYM.LE.-301).AND.(ISYM.GE.-600)) ISYM=-1*(ISYM+300)
      IF ((ISYM.LE.-601).AND.(ISYM.GE.-899)) ISYM=-1*(ISYM+600)
      IF (.NOT.(ISYM.GE.1).AND.(ISYM.LE.300)) RETURN
C
C      *** ADJUST THE LOCATION OF THE PENDANT AND LABEL ***
C
      XPOS=XSPAR
      YPOS=YSPAR
      XLOC=XSPAR
      YLOC=YSPAR
      IF (ISYM.NE.32) XPOS=XSPAR+HH/2.0*COS(DANGL)
      IF (ISYM.NE.32) YPOS=YSPAR+HH/2.0*SIN(DANGL)
      IF (ISYM.NE.32) XLOC=XSPAR+HH*COS(DANGL)
      IF (ISYM.NE.32) YLOC=YSPAR+HH*SIN(DANGL)
C
C      *** GO PLOT PENDANT ***
C
      ISPOT=ISYM
      GOTO 5000
      END
(*      WRITTEN BY D. DELLINGER      *)

```

```

labelloc: proc (h, rangl, tag, labellocx, labellocy, length);
dcl (h, sz, rangl, labellocx, labellocy) float bin;
dcl (i, sgn, length) fixed bin;
dcl tag char (32);
    do while (substr (tag, 1, 1) = " ");
        tag = substr (tag, 2, 31) cc " ";
    end;
    length = 32;
    do while (substr (tag, length, 1) = " ");
        length = length - 1;
    end;
    if (rangl > 90) & (rangl <= 270) then do;
        sz = h * (length + .5);
        sgn = -1;
        rangl = rangl + 180;
        if rangl >= 360 then rangl = rangl - 360;
    end;
    else do;
        sz = h;
        sgn = 1;
    end;
    labellocx = (sz * cosd (rangl) * sgn) + ((h/2) * sind (rangl));
    labellocy = (sz * sind (rangl) * sgn) - ((h/2) * cosd (rangl));
    return;
end labelloc;

```

BIBLIOGRAPHY

- Carlson, C. A., 1982, User's manual for statmap. U.S. Geological Survey Open-File Report 82-622, 10 p.
- Honeywell Information Systems Inc., 1979. Series 60 (level 68) qedx text editor users' guide, preliminary edition: Order Number CG40-00.
- Peterson, J. C., 1977. A modification of mineral mapping program (G239): U.S. Geological Survey Open-File Report 77-713.
- VanTrump, Jr., George and Miesch, A. T., 1977. The U.S. Geological Survey RASS-STATPAC system for management and statistical reduction of geochemical data: Computers and Geosciences, v. 3, p. 475-488.
- Zeta Research Inc., 1977. Instrumentation manual, 3600 Series Incremental Plotters, Serials F/158: Zeta Research Division of Nicolet Instrument Corporation Publication No. 43-1-005.
- _____, 1978, User's manual, Model 6300 Off-line plotter controller: Zeta Research Division of Nicolet Instrument Corporation Publication No. 43-1-025.