# United States Department of the Interior Geological Survey

Coal Exploratory Drilling
during 1979 in Western
Powder River County, Montana

bу

M. A. Kirschbaum

G. A. Correia

M. McPhillips

### Contents

Introduction	1	1
Geological S	Setting	8
References-		9
Appendix		10
	Illustrations	
Figure 1.	Location of coal exploratory holes drilled in 1979	2
Figure 2.	Index map showing locations of study area, coal fields,	
	and 1° $\times$ $^{1}\!/_{2}$ ° quadrangles	6
	Tables	
Table 1.	Data for holes drilled during 1979	3

#### Introduction

In 1979, during August through November, the U. S. Geological Survey drilled 36 coal exploratory holes in the Moorhead and Birney-Broadus coal fields, western Powder River County, Montana (fig. 1). At seven locations several intervals were cored, in offset holes, to obtain samples of major coal beds (table 1). This drilling is part of a program, started in 1975, to evaluate the quantity and quality of coal in the northern Powder River Basin, and to clarify the correlation of coal beds among the Recluse, Wyoming,  $1^{\circ} \times 1^{\circ}/2^{\circ}$  quadrangle, and the Birney and Broadus, Montana,  $1^{\circ} \times 1^{\circ}/2^{\circ}$  quadrangles where coal resource investigations are now in progress (fig. 2). Previously, Hobbs and others (1977), Hobbs (1980), and Correia (1980), reported on the drilling in the Recluse geologic area, Campbell County, Wyoming; Hardie (1979) reported on a line of holes drilled northward into the Broadus area in Powder River County.

Geological study and drilling on this project were accomplished by U.S. Geological Survey equipment and personnel. Assistance in the field was provided by Robert Hobbs, Richard Babcock, Frank Spencer, Jim Boaz, and Linda Berlage. A special acknowledgement is given to project chief R. G. Hobbs. Geophysical logging was contracted to three companies; suites of geophysical logs consisting of natural gamma, calibrated density, resistivity and caliper were run on each of the holes. The geophysical logs were recorded at a vertical scale of 1 inch equals 10 feet and were reduced to approximately 1 inch equals 50 feet for publication. A lithologic description was made of samples of drill cuttings taken at 5 foot intervals. Depths and thicknesses were interpreted from geophysical logs. A strip log is provided for each of the geophysical logs showing generalized coal bed thicknesses; partings less than a foot in thickness have not been shown at this scale.




Table 1.--Drill hole location and other data

Well no.	Location	Surface elevation	Total depth	Cored interval	Remarks
MB-1C	300 fwl, 2150 fml sec. 21, T. 9 S., R. 50 E	4020	126.6	19.5-65 90 -126.6	No log available, core hole offset to rotary hole 78BR5 in 1978.
MB-2	350 fel, 2200 fsl sec. 28, T. 7 S., R. 49 E	3325	465		Completed as water well
MB-3	880 fn1, 2450 fw1 sec. 36, T. 7S., R. 49 E	3600	595		
MB-3C	900 fn1, 2450 fw1 sec. 36, T. 7S., R. 49 E.	3600	175	135-175	
MB-4	300 fs1, 1350 fwl sec. 27, T. 6 S., R. 50 F	3320	415		
MB-5	450 fel, 900 fsl sec. 17, T. 9 S., R. 48 E	3690	615		
MB-6	1050 fel, 2500 fsl sec. 22, T. 8 S., R. 47 E	4200	795		
MB-6C	1075 fe1, 2500 sec. 22, T. 8 S., R 47 E.	4200	454	236-296.2 372-406.5	
MB-7	1200 fs1, 2000 fe1 sec. 30, T. 7 S., R. 47 E	3790	535		
MB-8	100 fw1, 1100 fn1 sec. 21, T. 7 S., R. 47 E	3905	535		Completed as water well.
MB-9	450 fs1, 1650 fw1 sec. 14, T. 7 S., R. 47 E	4180	875		
MB-10	1000 fs1, 2650 fe1 sec. 4, T. 7 S., R. 47 E.	3960	535		
MB-11	1900 fe1, 2000 fn1 sec. 30, T. 7 S., R. 49 E	3340	435		
MB-12	500 fwl 2100 fnl sec. 24, T. 7 S., R. 48 E	3430	550		Completed as water well.
MB-13	550 fel, 2500 fnl sec. 16, T. 7 S., R. 48 E	3560	375		Hole abandoned due to severe caving, - no log available
MB-13A	600 fel, 2650 fnl sec. 16, T. 7 S., R. 48 E	3580	605 3		moved to 13A.

Table 1.--Drill hole location and other data--Continued

Well no.	Location	Surface elevation	Total depth	Cored interval			Remarks	3
MB-14	500 fw1, 650 fn1 sec. 30, T. 6 S., R. 48 E	4020 •	595		Hole	caved	below	350'.
MB-15	900 fe1, 2100 fn1 sec. 8, T. 6 S., R. 48 E.	4180	515					
MB-16	600 fn1, 900 fe1 sec. 30, T. 5 S., R. 48 E	4100	555					
MB-17	1850 fw1, 1900 fn1 sec. 7, T. 5 S., R. 48 E.	3905	515					
MB-18	500 fw1, 2000 fn1 sec. 33, T. 4 S., R. 48 E	3730 •	495					
MB-19	100 fe1, 2400 fn1 sec. 20, T. 4 S., R. 48 E	3730 •	615					
MB-19C	150 fe1, 2400 fn1 sec. 20, T. 4 S., R. 48 E	3730 •	426	60 - 90. 399 - 424.				
MB-20	650 fw1, 750 fn1 sec. 6, T. 4 S., R. 48 E.	3565	690					
MB-21	1700 fn1, 1750 fe1 sec. 31, T. 5 S., R. 48 E	4220 •	515					
MB-22	1400 fe1, 1900 fn1 sec. 19, T. 5 S., R. 48 E	3960 •	455					
MB-22C	1450 fel, 1900 fnl sec. 19, T. 5 S., R. 48 E	<b>3960</b>	421.6	32 - 43. 79.8-106. 172.2-186. 395 -421.	4 9			
MB-23	350 fw1, 2200 fn1 sec. 15, T. 6 S., R. 47 E	4080 •	760					
MB-24	1900 fel, 2150 fsl sec. 15, T. 5 S., R. 46 E	3735 •	275					
MB-25	1600 fs1, 2200 fwl sec. 25, T. 4 S., R. 46 E	3805 •	460					
MB-26	750 fw1, 1550 fs1 sec. 7 T. 5 S., R. 50 E.	3705	615					

Table 1.--Drill hole location and other data--Continued

Well no.	Location	Surface elevation	Total depth	Cored interval	Remarks
MB-27	700 fw1, 1050 fn1 sec. 22, T. 4 S., R. 49 E	3435	370		Logger broke down. Log Available from 235' - 367'.
MB-28	150 fe1, 1850 fn1 sec. 33, T. 4 S., R. 49 E	3510	495		
MB-29	450 fs1, 2200 fe1 sec. 10, T. 5 S., R. 49 E	3685	615		Hole caved - unable to log. No geophysical log run.
MB-30	1300 fel, 1950 fnl sec. 22, T. 5 S., R. 49 E	3410	389		
MB-30C	1250 fel, 1950 fnl sec. 22, T. 5 S., R. 49 E	3410	326.5	293-326.5	No log available.
MB-31	600 fn1, 2100 fe1 sec. 27, T. 5 S., R. 49 E	3450	395		
MB-32	350 fn1, 1800 fw1 sec. 1, T. 6 S., R. 49 E.	3425	395		
MB-33	750 fw1, 1100 fs1 sec. 19, T. 4 S., R. 49 E	3625	635		
MB-34	100 fw1, 2600 fn1 sec. 4, T. 6 S., R. 49 E.	3560	515		
MB-35	1200 fn1, 1900 fw1 sec. 25, T. 5 S., R. 48 E	3725	299		
MB-36	200 fel, 1150 fsl sec. 22, T. 4 S., R. 49 E	3435	555		




FIGURE 2. - INDEX MAP SHOWING LOCATIONS OF STUDY AREA, COAL FIELDS, AND 1° X ½° QUADRANGLES.

Cored intervals were described in the office and are presented with lithologic descriptions and geophysical logs in the appendix of this report.

In the course of drilling, assistance was provided to several Government agencies. The U. S. Department of Energy collected data for their National Uranium Resource Evaluation and Methane Desorption programs. Drill holes MB-2, MB-8, and MB-12 were completed as observation water wells for the U. S. Geological Survey and the U.S. Forest Service. Special rock core samples were collected for the Bureau of Land Management's overburden and U.S. Geological Survey's paleomagnetic studies.

#### Geologic Setting

The Moorhead and Birney-Broadus coal fields are located in the northern Powder River Basin where the Paleocene Fort Union Formation dips gently to the southwest.

In the study area the Fort Union Formation consists of two members: the lower member and the overlying Tongue River Member. Elsewhere in the basin, the lower member is differentiated into the Tullock and Lebo Shale Members.

The lower member does not crop out in the report area. A few miles to the east it is exposed on outcrop and is described as consisting of gray to dark gray shale with some interbedded sandstone, siltstone, and thin local coal beds (Bryson and Bass, 1973). Drill holes MB-26, MB-28, MB-30, MB-34 and MB-36 probably penetrated the lower member, but the location of the contact was not recognized because no sharp change in lithology was observed; consequently the lower member was not differentiated from the Tongue River Member in this report.

The Tongue River Member contains most of the coal in the Fort Union Formation. The coal-bearing rocks consist of sandstone, siltstone, shale, carbonaceous shale, and thin lenticular beds of argillaceous limestone. The rocks are poorly consolidated with the exceptions of calcareous sandstones and the argillaceous limestones. Coal beds that have burned on outcrop bake and fuse overlying rocks into brittle reddish rock called clinker that forms erosion-resistant buttes and ridges along major stream drainages.

#### References

- Bryson, R. P. and Bass, N. W., 1973, Geology of Moorhead Coal Field, Powder
  River, Big Horn, and Rosebud Counties, Montana: U. S. Geological Survey
  Bulletin 1338, 116 p.
- Correia, G. A., 1980, Preliminary results of 1978 coal assessment drilling in northern and western Recluse Geologic Analysis area, northern Campbell County and eastern Sheridan County, Wyoming: U. S. Geological Survey Open-File Report 80-80, 72 p.
- Hardie, J. K., 1979, Preliminary report of coal exploration drilling in the Broadus area, Powder River County, Montana, during 1978: U. S. Geological Survey Open-File Report 79-965, 51 p.
- Hobbs, R. G., 1980, 1976 coal exploratory drilling, core description, and coal analyses, Recluse Geologic Analysis area, northern Campbell County,

  Wyoming: U. S. Geological Survey Open-File Report 80-1160, 55 p.
- Hobbs, R. G., Malotte, D. C., Sanchez, J. D., and Windolph, Jr., J. F., 1977,

  Core description logs, 1975 USGS drilling, Recluse area, northern

  Campbell County, Wyoming: U. S. Geological Survey Open-File Report

  77-717, 46 p.

## Moorhead Broadus Drilling Project

Hole De	esigna	tion MB-1	C Elev.(ft) 4020 Total Depth(ft) 126.6
Locatio	on 30	0 fwl 2150	fnl sec. 21 T. 9 S. R. 50 E.
County	Powd	er River	State Montana Quadrangle(7.5') Bay Horse
Cored:	,	Yes <u>x</u> N	o Interval(s) 19.5' to 65' 90' to 126.6'
Date st	tarted	8/13/79	Date completed 8/16/79 Driller Arthur Clark
Geolog:	istC	orreia	Remarks: No geophysical log run.
Depth :	interv	al (feet)	
From	То	Thick- ness	Lithologic Description
0	5	5	Sandstone, light-olive, very fine grained, muddy
5 10	10 17	5 7	Shale, light-olive, silty Sandstone, medium-gray, slightly carbonaceous, interbedded with shale
17	19.5	2.5	Shale, dark-brown, carbonaceous  CORE DESCRIPTION
19.5	20.3	0.8	Siltstone, light-gray, muddy, oxidized at 19.9' with rootlets and gypsum
20.3	20.9	0.6	Claystone, blue-gray, interbedded with oxidized, very fine grained, sandstone
20.9	21.3	0.4	Sandstone, fine-grained, unconsolidated, with a clay and pyrite layer at 21.1'
21.3	23.3	2.0	Shale, dark-brown, carbonaceous, coal stringer at 22.3'; sand stringer at 22.5'
23.3	25.4	2.1	Mudstone, medium-gray, rootlets in top foot, sand stringer with pyrite nodules at 24.9'
25.4	27.6	2.2	Sandstone, medium-gray, interbedded with shale
27.6	28.3		Coal, pyrite lens at 27.7'
28.3	29.0		No recovery
29.0	31.4		Mudstone, medium-gray, carbonaceous top .3', silty toward base,
31.4	37.2		carbonaceous streaks and pyrite at 30.8' Sandstone, medium-light-gray, fine-grained; carbonaceous streaks, muddy, and pyrite nodules at 35.1'
37.2	38.0	0.8	No recovery
38.0	39.4		Sandstone, medium-gray, muddy towards base; carbonaceous at 38.3'
39.4	40.9	1.5	Shale, dark-brown, carbonaceous, sandy with pyrite nodules; coal

stringer at top

## Section MB-1C

Depth	interval	(feet)	
From	То	Thick- ness	Lithologic Description
40.9	65.0	14.1	No recovery END OF CORE DESCRIPTION
65	85	20	Sandstone, medium- to dark-gray, coarsens upward from very fine grained to coarse-grained
85	90	5	Shale, medium-gray, silty CORE DESCRIPTION
90	102.6	12.6	No recovery
102.6	106.6	4.0	Siltstone, medium-gray, muddy, with sand lenses and pyrite nodules throughout
106.6	116.1	9.5	Coal; burrowed at top, filled with sand and pyrite, badly fractured; pyrite lens at 106.9' and nodules interspersed throughout
116.1	116.3	0.2	Shale, medium-dark-gray, carbonaceous
116.3	117.3	1.0	Coal, dull black, shaly at top
117.3	122.0	4.7	Coal, black, pyritic, minor cleat fracture at 119.0'
122.0	122.3	0.3	Shale, medium-brown, carbonaceous
122.3	123.9	1.6	Coal, dark-brown-black, woody, shaly
123.9	124.8	0.9	Shale, dark-brown, coaly
124.8	126.6	1.8	Mudstone, medium-gray, coal clasts, carbonaceous rootlets, sandy towards bottom

Pag	e	1	oi	E	2

# Moorhead Broadus Drilling Project

Hole D	esigna	ation MB-2	Elev.(ft) 3325 Total Depth(ft) 465	
Locati	on3	50 fel 220	0 fsl sec. 28 T. 7 S. R. 49	Ε.
County	Powe	der River	State Montana Quadrangle (7.5') Huckins School	
Cored:		YesN	o_x_ Interval(s)	
Date s	tarte	d 8/17/79	Date completed 8/17/79 Driller Arthur Clark	
Geolog	ist_	Linda Berla	ge Remarks: Completed as water observation well.	
Depth	inter	val (feet)		
From	То	Thick- ness	Lithologic Description	
0	11	11	Alluvium, sandy and silty, light-brownish-yellow	***************************************
11	17	6	Alluvium, clay, very light gray, silty	
17	29	12	Sandstone, light-gray, very fine grained, silty, interbedded with	


From	То	Thick- ness	Lithologic Description
0	11	11	Alluvium, sandy and silty, light-brownish-yellow
11	17	6	Alluvium, clay, very light gray, silty
17	29	12	Sandstone, light-gray, very fine grained, silty, interbedded with siltstone, very light gray
29	39	10	Claystone, light-gray, carbonaceous with coaly streaks
39	52	13	Siltstone, light-gray
52	56	4	Coal, bony
56	86	30	Siltstone, medium- to dark-gray, clayey in part, argillaceous limestone 70' -72'
86	94	8	Sandstone, dark-gray to medium-brown, very fine grained, silty
94	99	5	Coal
99	102	3	Shale, medium-gray
102	124	22	Siltstone, medium- to dark-gray, sandy at base
124	141	17	Shale, dark-gray
141	157	16	Sandstone, dark-gray, very fine grained, silty
157	163	6	Shale, dark-gray
163	192	29	Siltstone, medium- to dark-brown, carbonaceous in parts, clayey in places, coal 175' to 177' and at 191'
192	254	62	Siltstone, medium- to dark-gray, sandy, carbonaceous, coal streak at 227'
254	280	26	Sandstone, light-gray, very fine grained; interbedded with, light-to-medium-gray
280	288	8	Shale, light- to medium-gray
288	305	17	Siltstone, light- to medium-gray, interbedded with carbonaceous shale; coal stringer 291' to 292' and 296-297
305	312	7	Sandstone, light-gray, very fine grained

Page 2 of 2

## SECTION MB 2

Depth interval (feet)		l (feet)	
From	to	Thick- ness	Lithologic Description
312	322	10	Shale, light-gray, silty toward base
322	403	81	Sandstone, light- to medium-gray, very fine grained, shaley in part
403	425	22	Shale, medium- to dark-gray, carbonaceous, interbedded with light to medium-gray siltstone, coal stringer at 421' to 423'
425	433	8	Siltstone, medium-gray
433	465	32	Shale, medium- to dark-gray, carbonaceous, interbedded with light- to medium-gray siltstone; pyrite nodules noted in cuttings

Hole Designation	MB-2	Logged Depth	454	(f t
Geophysical Lo	g Scales:			
Gamma (G) _	100 API units/in	Density (D)	.5 counts/sec	/in
Resistivity	(R) 20 ohms/in	Caliper (C)	2 in/in	
Remarks: 1 API	unit = .618 counts per sec	ond		



28	G		DEPTH				
STRI	G	С	D	R	F	r	М
				350	35	0 -	-100
			) 	3	40	0 -	- 120
	Carried No.	50.5	S S	454	450	0 -	-130 -140
					500	0-	-150
					550		-160 -170
		·			600	)-	-180
					650	,	·190 ·200
					700	, -	-210

### Moorhead Broadus Drilling Project

Hole D	esignat	ion MB-3	Total Depth(ft) 3000 Total Depth(ft)
Locati	on <u>880</u>	fn1 245	0 fwl sec. 36 T. 7 S. R. 49 E
County	Powde	er River	State Montana Quadrangle(7.5') Huckins School
Cored:	Y	es <u>x</u> N	oInterval(s)_135' - 175'
Date s	tarted_	8/18/79	Date completed 8/18/79 Driller Arthur Clark
Geolog	ist <u>M</u> a	ırk Kirsch	Remarks: Core description by George A. Correia.
Depth	interva	1 (feet)	
From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, yellow-brown, sandy
5	10	5	Alluvium, black, muddy, carbonaceous
10	21	11	Shale, red-brown, clayey, sandy, trace of sulfur
21	29	8	Shale, gray, clayey
29	34	5	Sandstone, gray, calcareous streaks
34	50	16	Siltstone, gray, clayey
50	73	23	Shale, gray, silty toward base, coal stringer 54'-56'
73	93	20	Siltstone, light-gray, with clayey streaks
93	116	23	Sandstone, medium-light-gray, fine- to very fine grained
116	135	19	Mudstone, light-gray, silty, limy streak at 125' CORE DESCRIPTION
135.0	139.3	4.3	Claystone, gray-green, shaly, carbonaceous
139.3			Coal, black
144.0		3.9	Coal, black, alternating shiny and dull bands, disseminated pyrite on fracture surfaces
	149.3	1.4	Mudstone, medium-gray, coaly streak at 148.6', silty toward bottom
	150.6	1.3	Siltstone, medium-dark-gray, sandy streaks with pyrite nodules, carbonaceous
150.6	153.9	3.3	Sandstone, light-gray, fine-grain, pyrite nodules, slightly carbonaceous
153.9	156.0	2.1	Coal, black, shiny, pyrite on fractures, gypsum on fractures, top .3 ft of coal weathered
156.0	165.5	9.5	Coal, black, alternating dull and shiney bands, pyrite throughout,

shaly at bottom

### SECTION MB-3 & MB-3C

Depth	interva	ıl (feet)	
From	То	Thick- ness	Lithologic Description
165.5	168.0	2.5	Sandstone, yellow-brown, with pyrite and organic material to 167.1' then green-gray, fine-grain
168.0	172.9	4.9	Mudstone, gray-green, coaly at top, sandy pockets with pyrite nodules
172.9	175.0	2.1	Mudstone, gray-green, sandy, fine- to very fine grained, pyrite nodules  END OF CORE DESCRIPTION
175	189	14	Shale, gray, silty toward base
189	242	53	Sandstone, light-gray, very fine grained
242	252	10	Mudstone, gray-brown
252	254	2	Shale, carbonaceous
254	256	2	Coal, black
256	262	6	Shale, black, carbonaceous, grades to siltstone toward bottom
262	328	66	Sandstone, light-gray, fine- to very fine grained, silty at top
328	336	8	Shale, light-gray, silty, pyrite nodules in cuttings
336	348	12	Siltstone, gray, coaly, clayey
348	351	3	Coal, black, bony
351	356	5	Shale, gray-brown, carbonaceous
356	393	37	Siltstone, gray, sandy toward base
393	399	6	Coal, black
399	423	24	Shale, gray-green, interbedded with sandstone
423	431	8	Siltstone, gray-green
431	440	9	Mudstone, light-gray, silty
440	489	49	Siltstone, light-gray, sandy, interbedded with light-gray shale; coal stringers at 468' and 483'
489	509	20	Sandstone, gray, very fine grained, silty at top
509	528	19	Shale, dark-gray, silty and sandy in places
528	551	23	Siltstone, gray, with interbedded sandstone
551	561	10	Sandstone, gray, very fine grained
561	585	24	Shale, gray- to dark-gray, silty, carbonaceous shale noted in cuttings; coal stringer at 580' - 582'
585	595	10	Shale, dark gray, with carbonaceous shale and bony coal streaks

Hole Designation	MB-3	Logged Depth	. 589	(ft)
Geophysical L	og Scales:			•
Gamma (G)	100 API units/in	Density (D)	.5 counts/se	c/in
Resistivit	y (R) 10 ohms/in	Caliper (C)	l in/in	
Remarks: 1 AP	I unit = .618 counts per sec	ond		-
•				

	· · · · ·		
STRIP LOG	GEOPHYSICAL LOGS	DEI	PTH
STI	G C D R	FT	м
		50 —	-10 -20
	100	100 —	-30
	150	150 –	-40 -50
	200	200-	-60
	750	250—	-70 -80
		300-	-90

10	GEOPHYSICAL LOGS	DE	PTH
STRI	G C D R	FT	M
	50	350 -	-100
			-110
		400 -	- 120
	3		130
	550	450 -	-140
	500	500-	-150
	555	550-	-160 -170
	250.5  APPRICAL LUCK  EXCIPTE 10  EXCIPTE	600 -	-180
			190
		650 -	-200
		700 -	-210


## Moorhead Broadus Drilling Project

Hole Designation MB-4	Elev.(ft) 3320	Total	Depth(ft)	415	
Location 300 fsl 1350 fwl	sec. 27	т. 6	S R	50	Ε.
County Powder River	State Montana	Quadrang1	e(7.5') Lones	some Peak	
Cored: Yes No x	Interval(s)				
Date started 8/20/79	_ Date completed_	8/20/79	Drille	er Arthur Clar	k
Geologist Mark Kirschbaum	Remarks	•			

## Depth interval (feet)

From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, yellow-gray, sand with small chert granules
5	35	30	Alluvium, light-yellow, fine- to medium-grained, ironed stained
35	69	34	Sandstone, light-yellowish-brown, very fine to medium-grained, iron stained, coaly stringers
69	73	4	Siltstone, medium gray
73	84	11	Sandstone, light- to medium-gray, silty
84	102	18	Shale, medium-gray, silty
102	107	5	Coal, bony, interbedded with carbonaceous shale
107	137	30	Siltstone, dark- to medium-gray, clayey in parts, with calcareous sandstone stringers
137	138	1	Coal, black, shiny, sandy, with pyrite balls
138	145	7	Shale, medium-gray
145	149	4	Coal
149	226	77	Siltstone, medium- to dark-gray, clayey toward bottom, calcareous in places
226	238	12	Siltstone, dark-gray, clayey, pyrite balls at top, coal stringer at 237'
238	250	12	Sandstone, brown-gray, very fine grained
250	279	29	Siltstone, medium-gray, clayey or sandy in places, with a coal stringer at 268'
279	283	4	Sandstone, medium-gray, very fine grained, and light-gray siltstone, coal stringers
283	304	21	Siltstone, medium- to green-gray, some clay
304	395	91	Sandstone, medium- to dark-gray, fine- to medium-grained, calcareous in places, some pyrite
395	415	20	Shale, medium- to dark-gray, clayey, some fine-grained sandstone at top

Hole Desig	gnation	MB-4	Logged Depth	415	(ft)
Geophys	sical Log S	cales:			
Gamm	na (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resi	istivity (F	20 ohms/in	Caliper (C)	l in/in	
Remarks:	I API ur	nits = .618 counts per	second		
_					



STRIP LOG	GEOPHYSICAL LOGS DEI			
ST	G C D R	FT	М	
	350	350 -	-100	
	400	400 -	110	
	1750.5 2.5 415  1750.5 2.5 415  1750.5 2.5 415  1750.5 2.5 415  1750.5 2.5 415  1750.5 2.5 415	450 -	-130	
			-140 -150	
	•	550 -	·160	
			170	
			190	
		650 -	200	
		700 -	·210	

### Moorhead Broadus Drilling Project

Hole Designation MB-5	Elev.(ft) 3690	Total Dep	th(ft)	615	
Location 450 fel 900 fsl	sec. 17	т9	5 R	48	Ε.
County Powder River	State Montana	Quadrangle(7	.5)' Moorhe	ad	
Cored: Yes No x	Interval(s)	······································			<u></u>
Date started 8/21/79	Date completed	8/22/79	Driller	Arthur Clark	
Geologist Mark Kirschbaum	Remarks:	Geophysical I	log to 547′		


### Depth interval (feet)


From	То	Thick- ness	Lithologic Description
0	10	10	Alluvium
10	26	16	Siltstone, light-gray, iron stained
26	47	21	Sandstone, light-gray, very fine grained, calcareous cement, hard, iron stained
47	53	6	Shale, black, carbonaceous, coaly at bottom
53	61	8	Shale, light-blue-gray to light-gray, carbonaceous
61	95	34	Siltstone, medium- to dark-gray, interbedded with medium- to light-gray, shale
95	98	3	Sandstone, gray, fine-grained
98	101	3	Coal, shaly
101	114	13	Sandstone, light-gray, fine-grained, shaly streaks, iron stained
114	134	20	Shale, light- to medium-gray, silty at base
134	190	56	Sandstone, light-gray, fine- to very fine grained, calcareous, silty at top
190	199	9	Shale, medium-gray
199	205	6	Shale, medium-gray, silty
205	227	22	Shale, medium-gray, with interbedded siltstone
227	232	5	Coal
232	238	6	Claystone, gray
238	253	15	Siltstone, medium-gray, clayey
253	306	53	Sandstone, medium-gray, fine-grained, calcareous
306	334	28	Siltstone, medium-gray, trace carbonaceous shale in cuttings
334	339	5	Shale, medium-gray
339	353	14	Coal, black, shale parting 345'-346'
353	370	17	Shale, medium-gray, carbonaceous in parts, silty toward bottom
370	375	5	Coal
375	384	9	Siltstone, medium-gray

### SECTION MB-5

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
384	389	5	Sandstone, medium-gray
389	404	15	Shale, dark-brown, silty at top
404	413	9	Sandstone, gray, clayey at base
413	416	3	Coal
416	465	49	Shale, medium-gray, silty, grading to light-gray siltstone toward bottom
465	508	43	Sandstone, medium-gray, very fine grained, calcareous at top
508	586	78	Shale, medium-gray, clayey, carbonaceous, coal beds at 511'-514' and 562'-563', sandstone at 522' to 525'
586	593	7	Sandstone, medium-gray, calcareous
593	614	21	Shale, medium-gray, silty, traces of coal and carbonaceous shale

Hole Designation	MB-5	Logged Depth	547	_(ft)
Geophysical Log Sca	ales:		,	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R)	20 ohms/in	Caliper (C)		
Remarks:				





## Moorhead Broadus Drilling Project

Hole Designation MB-6 & MB-	6C Elev.(ft) 4200	Total	Depth(ft)	795	
Location 1050 fel 2500 fsl	sec. 22	т. 8	S. R	47	Ε.
County Powder River	State Montana	Quadrangl	e(7.5') Brads	haw Creek	
Cored: Yes_x No	Interval(s) 236' to	296.2',	372' to 406.5	·	
Date started 8/29/79	Date completed 9	/1/79	Drille	r Arthur Clark	
Geologist Frank Spencer	Remarks:_	Core desc	ription by Ge	orge A. Correia	

Depth	interval	(feet)
-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	1	1	Alluvial soil
1 7	7	6	Shale, carbonaceous, medium- to dark-brown, weathered
7	9	2	Coal Coal
9	16	7	Shale, medium- to dark-gray
16	39	23	Sandstone, light-yellow-gray, very fine grained, clayey, calcareous streak at 26'
39	51	12	Shale, medium- to dark-gray at bottom, sandy
51	54	3	Sandstone, medium-dark-gray
54	93	39	Shale, medium-dark-gray, sandy, trace carbonaceous shale in cuttings at 76'
93	99	6	Coal, brown-black; shale parting 95' to 96'
99	141	42	Sandstone, light- to medium-gray, fine-grained grading to shale, light- to medium-gray at the bottom
141	191	50	Siltstone, light- to medium-gray interbedded with shale, medium gray, sandy at the top
191	230	39	Sandstone, light- to medium-gray, very fine grained, grading to siltstone, medium- to dark-gray toward bottom
230	236	6	Shale, dark-brown, carbonaceous  CORE DESCRIPTION
236	243.5	7.5	Shale, medium-dark-brown, carbonaceous, silty
243.5	248.6	5.1	Coal, brown, bony, woody
248.6	253.6	5.0	Coal, brown, bony, disseminated pyrite
253.6	264.5	10.9	Coal, brown, bony, woody
264.5	273.2	8.7	Coal, brown, bony, woody, disseminated pyrite
273.2	275.5	2.3	Sandstone, light-gray, very fine grained, clayey and shaly
275.5	295.1	19.6	Coal, brown, woody, shale at 279.8' to 280.7' with disseminated pyrite shale at 287.1' to 289.8'


### SECTION MB-6

Depth	interv	al (feet)	
From	То	Thick- ness	Lithologic Description
295.1	295.8	0.7	Shale, dark-brown, carbonaceous
295.8	296.2	0.4	Sandstone, light-gray, coaly END OF CORE DESCRIPTION
296.2	316	19.8	Shale, medium-gray, carbonaceous towards top
316	362	46	Siltstone, light- to medium-gray, sandy, carbonaceous material in cuttings
362	372	10	Shale, medium- to dark-gray  CORE DESCRIPTION
372.0	376.6	4.6	Shale, medium-dark-gray, carbonaceous
376.6			Sandstone, light- to medium-gray, fine- to very fine grained, coaly streaks
379.0	381.2	2.2	Coal, banded, woody, with vitrinite
381.2	385.3	4.1	Shale, medium-gray-brown, carbonaceous, sandy at top with coal streaks
385.3	386.0	0.7	Coal, brown, bony, shaly
386.0	388.0	2.0	Coal, brown, woody
388.0			Coal, dark-brown, woody with vitrinite streaks
403.5			Sandstone, light-gray, fine- to medium-grained, cherty END OF CORE DESCRIPTION
406.5	439	32.5	Siltstone, medium-gray, shaly with coal streak at 416', calcareous, argillaceous limestone at 430'
439	450	11	Shale, light-gray, coaly shale at top
450	454	4	Siltstone, light-gray
454	460	6	Claystone, light-gray
460	489	29	Siltstone, light-to-medium gray, sandy
489	492	3	Shale, medium-gray
492	503	11	Sandstone, light- to medium-gray, fine to very fine grained, calcareous streaks
503	537	34	Shale, medium-gray, interbedded with light-gray, fine- to very fine grained sandstone, coal stringer 521' to 523'
537	542	5	Shale, dark brown, carbonaceous, coal stringer
542	550	8	Coal, brown-black
550	557	7	Shale, medium-gray
557	559	2	Coal, shaly
559	599	40	Siltstone, light- to medium-gray, sandy at top, carbonaceous shale at the bottom
599	609	9	Shale, black to medium-gray, carbonaceous
609	611	2	Coal
611	632	21	Shale, gray, interbedded with light-gray siltstone
632	637	5	Shale, black, carbonaceous, bony coal from 634-636
637	660	23	Siltstone, medium-brown-gray, argillaceous limestone at 647'
660	668	8	Shale, medium-gray, carbonaceous at 669'

### SECTION MB-6

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
668	672	4	Siltstone, medium-brown-gray, sandy
672	679	7	Shale, medium-brown-gray
679	684	5	Siltstone, medium-brown-gray, sandy
684	691	7	Shale, carbonaceous and bony coal
691	726	35	Shale, dark-gray, carbonaceous and silty in places.
726	736	10	Sandstone, light-gray
736	741	5	Shale, black, carbonaceous, coaly, silty at bottom
741	745	4	Coal
745	763	18	Shale, dark-gray, carbonaceous, coal at 750', 757' and 760'
763	775	12	Siltstone, light-gray, sandy at top
775	795	20	Siltstone, light-gray, coal from 776' to 782, sandy at bottom


Hole Designat	ion MB-6	Logged Depth	763	(f t)
Geophysical	1 Log Scales:			
Gamma (	G) 100 API units/in	Density (D)	.5 counts/sec/in	
Resisti	vity (R) 20 ohms/in	Caliper (C)	2 in/in	
Remarks: 1	API unit = .618 counts per	second		



STRIP LOG	GEOPHYSICAL LOGS			DE	PTH	
ST.	G	С	D	R	FT	М
				300	350 -	-100
				400	400 -	- 120
		7 - 3	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	150	450 -	-130 -140
			W. N. W.		500-	-150 -160
				\$50x	550 -	-170
				500	600 -	·180 ·190
				650	650 -	·200
	- Z		2 5		700 -	-210

CIP	GEOPHYSICAL LOGS .	DE	PTH
STRIP	G C D R	FT	М
-		750-	-220 -230
	279 Tabeled 1 To 1784    Control of the Control of	800-	- 240
	L \ \ \ \ \ \ \_	850-	- 250 - 260
		900-	- 270
		950-	- 280 - 290
	·	1000-	-300
		1050-	-310 -320
		1100-	-330
- -			- 340

Hole Designat:	ion MB-6C	Logged Depth	454	(ft)
Geophysical	L Log Scales:			
Gamma ((	G) 100 API units/in	Density (D)	.5 counts/sec/in	
Resisti	vity (R) 20 ohm/in	Caliper (C)	1 in/in	· · · · · · · · · · · · · · · · · · ·
Remarks:	1 API unit = .618 counts pe	r second		÷ •




<b>E</b> 8_	GEOPHYSICAL LOGS		PTH
STRIP LOG	G C D R	FT	М
	350	350 -	-100
			110
	400	400 -	- 120
		450 -	-130
	CONTRACTOR		-140
		500~	-150
		550 -	-160
			-170
		600 -	-180
			-190
		650 -	-200
		700 -	-210

### Moorhead Broadus Drilling Project

Hole I	Designat	ion MB-7	Elev.(ft) 3790 Total Depth(ft) 535
Locati	Ion_ 120	00 fsl 200	0 fel sec. 30 T. 7 S. R. 47
County	Powde	er River	State Montana Quadrangle(7.5') Reanus Cone
Cored	. Y	YesN	o_xInterval(s)
Date s	started_	9/1/79	Date completed 9/2/79 Driller Arthur Clark
Geolog	gistFr	ank Spenc	er Remarks:
Depth	interva	ıl (feet)	
From	То	Thick- ness	Lithologic Description
0	15	15	Alluvium, unconsolidated sand, light-yellow to brown with yellow clay
15	17	2	Sandstone, light-brown, fine- to medium-grained, silty
17	27	10	Sandstone, light-yellow-brown, silty, with iron stains, some clay
27	32	5	Shale, black, with coal stringer at 28'
32	36	4	Siltstone, light-gray, very fine grained
36	42	6	Siltstone, medium-gray, shaly toward bottom
42	44	2	Shale, medium-gray
44	55	11	Siltstone, medium-gray, with shale
55	59	4	Sandstone, light-gray, very fine grained, calcareous
59 70	70 76	11	Siltstone, light-gray to dark-gray, clayey
70 76	76	6	Shale, carbonaceous with coal stringer at top
90	90 92	14 2	Siltstone, medium-gray, shaly toward bottom
92	92 98	6	Shale, carbonaceous Shale, medium-gray, silty
98	115	17	Coal, bony, woody, with siltstone parting from 105' to 110'
115	148	33	Siltstone, light-gray, increasingly sandy towards bottom
148	154	6	Coal, bony, woody
154	188	34	Shale, light-gray, silty, interbedded with thin sandstone, light-gray
188	204	16	Sandstone, light-gray, very fine grained
204	209	5	Shale, black, carbonaceous, coal stringer at top
209	219	10	Sandstone, light-gray, very fine grained
219	226	7	Shale, light-gray
226	237	11	Siltstone, light-gray, sandy toward bottom
237	242	5	Coal, bony, woody, shaly
242	269	27	Siltstone, light-gray, sandy

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
269	272	3	Shale, carbonaceous, dark-gray
272	291	19	Siltstone, light-gray, sandy at bottom
291	300	9	Shale, medium-gray, carbonaceous, silty at top
300	316	16	Siltstone, medium-gray, clayey at top
316	339	23	Sandstone, dark-brown, very fine grained
339	349	10	Siltstone, medium-gray, clayey in places
349	358	9	Shale, dark-brown, carbonaceous at bottom, silty
358	372	14	Coal
372	380	8	Shale, medium-gray, silty,
380	390	10	Siltstone, medium-gray,
390	393	3	Shale, black, carbonaceous
393	401	8	Siltstone, medium-gray
401	420	19	Siltstone, light-gray, sandy
420	462	42	Sandstone, light- to medium-gray, fine-grained
462	467	5	Coal
467	470	3	Coal, shaly
470	477	7	Siltstone
477	498	21	Siltstone, medium-gray, sandy, interbedded with carbonaceous shale
498	500	2	Carbonaceous shale, dark-gray
500	507	7	Shale, medium-gray, silty
507	535	28	Sandstone, light-gray, very fine grained, silty, clayey in places

Hole Designation	мв-7	Logged Depth	533	(ft)
Geophysical Log	g Scales:			
Gamma (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resistivity	(R) 2.5 ohms/in	Caliper (C) _1	in/in	
Remarks: 1 API	unit = .618 counts per sec	ond		



STRIP	GEOPHYSICAL LOGS	DE	PTH
ST	CC DR	FT	M
	350	350 -	-100
	100	400 -	- 120
	450	450 -	-130
		500-	-140
	S33 S74 PERSON DE PROSENTATION DE P	550-	·160 ·170
		600 -	180
		+	190
		650 -	200
		700 -	210

### Moorhead Broadus Drilling Project

Hole Designation MB-8	Elev.(ft)_3905	Total De	pth(ft)	535	
Location 100 fwl 1100 fnl	sec. 21	T. 7 S	. R	47	Ε.
County Powder River	State Montana	Quadrangle(7	.5') Sayle		
Cored: Yes No x	Interval(s)				
Date started 9/2/79	Date completed_	9/3/79	Driller	Arthur Clark	
Geologist Frank Spencer	Remarks	: Completed as	observatio	n water well.	


# Depth interval (feet)

From	To	Thick-	-
110111	10	ness	Lithologic Description
0	1	1	Alluvium
1	5	4	Coal and shale, carbonaceous, oxidized
5	25	20	Sandstone, light-yellow, fine- to very fine grained, iron stained, grading to siltstone at bottom
25	30	5	Shale, dark-brown, carbonaceous, coal stringer at top
30	44	14	Sandstone, light-yellow, fine- to very fine grained quartz, angular to sub-angular, silty, badly washed out in spots
44	49	5	Shale, black, carbonaceous, coaly
49	54	5	Sandstone, fine- to very fine grained, angular to subangular, micaceous, silty
54	58	4	Coal, dark-brown
58	70	12	Shale, dark-brown, carbonaceous
70	84	14	Coal, dark-brown, woody
84	109	25	Siltstone, medium-gray, fine- to medium-grained sand, shaly 92' to 97'
109	112	3	Shale, dark-brown, carbonaceous, badly washed out
112	129	17	Siltstone, dark-brown, shaly and washed out 120' to 122'
129	151	22	Sandstone, light-gray, medium- to very fine grained, quartz, subangular, calcareous cement, hard
151	159	8	Sandstone, light-gray, large percentage of coaly material
159	202	43	Sandstone, light-gray, very fine- to coarse-grain, silty in spots, calcareous, black chert grains at top
202	205	3	Sandstone, light-brown, fine- to medium-grain, coaly, calcareous
205	229	24	Siltstone, light- to medium-gray, calcareous, sandy in part, concretionary and hard 215' to 217', shaly coal streak 227'
229	254	25	Shale, medium-gray to dark-brown, carbonaceous, interbedded with siltstone, light- to medium-gray, sandy, calcareous concretions
254	269	15	Coal, black
269	283	14	Shale, light-gray, carbonaceous, silty

Depth	interv	al (feet)	
From	То	Thick- ness	Lithologic Description
283	292	9	Coal, black
292	306	14	Shale, light-gray, silty
306	309	3	Limestone, argillaceous
309	314	5	Siltstone, medium-gray
314	317	3	Limestone, argillaceous
317	327	10	Shale, medium- to light-gray, silty, carbonaceous
327	342	15	Siltstone, light-gray, sandy
342	345	3	Coal, black, shaly
345	382	37	Sandstone, light-yellow, very fine grained, grading to light-gray, clayey sandstone
382	387	5	Sandstone, light-gray, fine- to medium-grained, calcareous cement, hard
387	393	6	Shale, black, carbonaceous, coaly, silty
393	421	28	Siltstone, light-gray, calcareous
421	449	28	Sandstone, light- to medium-gray, very fine grained, calcareous, carbonaceous shale stringers
449	489	40	Siltstone, medium-gray, interbedded carbonaceous shale, calcareous sandy concretions
489	503	14	Coal, black
503	535	32	Siltstone, light-gray, calcareous sandy concretions

Pag	e	1	of	2

Hole Designation	MB-8	Logged Depth	515	(f t
Geophysical Log Sc	ales:		•	
Gamma (G)	100 API units/in	Density (D)	.5 counts/in	
Resistivity (R)	2.5 ohms/in	Caliper (C)	l in/in	
Remarks: 1 API uni	t = .618 counts per sec	ond		
·				




e i	GEOPHYSICAL LOGS	DE	PTH
STRIP	G C D R	FT	м
		350 -	-100
	400	400 -	-120
		450 -	-140
	500  250  350  350  3515  361707777  36131311717 6-41 8	500-	-150 -160
		550 -	-170
·	·	600 -	-180 -190
		650 -	- 200
		700 -	-210

Hole I	esignat	ion MB-9	Elev.(ft) 4180 Total Depth(ft) 8/5	<del></del>	
Locati	on_450	) fsl 165	0 fwl sec. 14 T. 7 S. R. 47	]	
County	Powde	er River	State Montana Quadrangle(7.5') Sayle		
Cored:	: 3	KesN	o_x Interval(s)		
Date s	tarted	10/15/79	Date completed 10/15/79 Driller Arthur Clar	k	
		rk Kirsch	baum Remarks: Hole caved below 761': caliper arm	iid	
	en unti				
Depth	interva	al (feet)			
From	То	Thick-			
		ness	Lithologic Description		
1	10	10	Alluvium, sand, very pale orange to gray-orange, fine-grained		
10	24	14	Sandstone, light-olive-gray, fine-grained		
24	47	23	Shale, light to- medium-gray, silty		
47	51	4	Coal		
51	66	15	Siltstone, light-gray, clayey		
66	71	5	Shale, coaly		
71	90	19	Coal, black, shale parting 83' to 87'		
90	100	10	Shale, light-gray, interbedded with light-gray siltstone		
100	182	82	Siltstone, medium- to light-gray, shaly in places, calcareously cemented 108' to 112'		
182	186	4	Coal		
186	200	14	Shale, black, carbonaceous, interbedded with coal at 190' to 192	,	
200	207	7	Shale, medium-light-gray, silty toward bottom		
207	212	5	Coal		
212	217	5	Shale, light-gray, clayey		
217	220	3	Coal, shaly		
220	264	44	Shale, light-gray, interbedded with light-gray siltstone		
264	270	6	Sandstone, light-gray, very fine grained, shaly toward bottom		
270	<b>27</b> 2	2	Coal		
272	281	9	Siltstone, light-gray, shaly at top		
281	289	8	Shale, brown-gray		
289	305	16	Coal		
305	312	7	Shale, brown-gray, washed out		
312	321	9	Siltstone, light-gray, washed out		
321	329	8	Sandstone, light-gray, very fine grained		
329	339	10	Siltstone, light-gray		

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
339	356	17	Shale, brown-gray, silty, washed out
356	383	27	Siltstone, medium- to light-gray, shaley
383	407	24	Shale, light- to medium-gray, washed out
407	430	23	Sandstone, medium-light-gray, shale stringers, carbonaceous
430	449	19	Mudstone, medium-light-gray, interbedded with medium-light-gray sandstone
449	453	4	Shale, brown-gray, carbonaceous, sandy towards bottom
453	482	29	Coal, black, shale parting 470' to 473'
482	489	7	Shale, black, carbonaceous
489	634	145	Siltstone, light- to medium-dark-gray, sandy, interbedded with shale, light-gray
634	691	57	Sandstone, light-gray, very fine grained
691	705	14	Coal
705	714	9	Shale, brown-gray, clayey, coal stringers
714	762	48	Siltstone, light- to medium-gray, sandy (very fine grained) toward bottom
762	783	21	Shale, medium-gray, clayey
783	816	33	Coal
816	875	59	Shale, light- to medium-gray, hard calcareous lenses, silty at top, clayey toward bottom

Pag	e 1	of	3	

Hole Designation	MB-9	_ Logged Depth	761	(ft)
Geophysical Log Sc.	ales:		•	
Gamma (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resistivity (R)	20 ohms/in	- Caliper -(C)	2 in/in	
Remarks: 1 API uni	t = .618 counts per second	đ		



STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
ST	G C D R	FT	M
	750	350 -	-100
	100	400 -	- 120
	50	450 -	·130 ·140
		500-	150
	550	550-	160 170
	1000	600 -	180
•	650	650 -	190 200
	100	700 -	210

a S	GEOPHYSICAL LOGS	DE	PTH
STRIE	G · C D R	FT	м
	750 750 750 750	750-	- 220 - 230
		800-	-240
			250
		850-	<b>26</b> 0
	·	900-	-270
	•		- 280
		950-	- 290
		1000-	-300
			-310
		1050-	-320
		1100-	-330
-			-340


Pag	e	1	o	f	2

#### Moorhead Broadus Drilling Project

Hole 1	Designat	ion MB-1	.0	Elev.	(ft) <u>39</u>	60		Total	Dept	h(ft)	535	
Locat	ion 100	0 fs1 26	50 fel		sec	4	т	7	s.	R	47	E
Count	y Powde	r River		State_Mo	ntana		Quad	lrang1	e(7.5	') Phill:	ips Butte	
Cored	: Y	esN	io_x	Inter	val(s)_							
Date :	started_	9/11/79		Date	comp1e	ted_	9/11/7	9		Drille:	r Arthur Cla	ark
Geolo:	gist <u>M</u> a	rk Kirsch	lbaum		Rem	arks						
Depth	interva	1 (feet)										
From	То	Thick- ness				Lit	nologic	Desc	ripti	on		
0	14	14					-				e grained	
14	37	23		one, yel ned, cal			to dark	:-ye11	.ow-or	ange, fi	ne- to very	fine
37	42	5	Shale,	dark-br	own							
42	71	29	Siltst to 5		ht-gray	, sai	ndy in	spots	, wit	h dark-bi	rown shale a	t 56′
71	73	2	Shale,	brown-b	lack, c	arboi	naceous	3				
73	76	3	Coa1									
76	84	8	Shale,	brown-b	lack, c	arboi	naceous	3				
84	102	18	Coal,	shaly at	bottom	1						
102	114	12		one, lig um-gray			ry fine	grai	ned,	grading o	downward to	
114	117	3		light-g								
117	133	16	Sandst	one, lig	ht-gray	, ve	ry fine	grai	ned,	interbed	ded with sha	le
133	136	3								ted, hard		
136	150	14	Siltst	one, lig	ht-gray	, sai	ndy tow	ard b	ottom			
150	156	6	Sandst	one, lig	ht-gray	, vei	ry fine	grai	ned,	silty		
156	159	3	Shale,	light-g	ray							
159	168	9	Siltst	one, med	ium-lig	ht-gi	ray, sa	ındy				
168	191	23	Shale,	medium-	light-g	ray,	silty					
191	239	48		one, lig .nger at		, ve	ry fine	grai	ned,	silty at	top, shale	
239	267	28	Siltst	one, lig	ht- to	medi	um-gray	, sha	1y			
267	298	31	Coal,	shale pa	rting 2	283′ 1	to 286'	,				
298	360	62	bott		areous1	у сет	nented				sandy toward 35', coal	

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
360	431	71	Sandstone, light- to medium-gray, interbedded with siltstone, bony coal from 378' to 380' and 398' to 400'
431	438	7	Shale, medium-gray
438	444	6	Sandstone, light-gray, very fine grained, calcareously cemented and very hard
444	475	31	Sandstone, light- to medium-gray, medium-grained, some interbedded with siltstone
475	492	17	Sandstone, light-gray, silty in part
492	535	43	Siltstone, light-gray

Hole Designation	MB-10	Logged Depth	529	(ft)
Geophysical Log	Scales:		•	
Gamma (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resistivity (	R) 20 ohms/in	Caliper (C)	2 in/in	
Remarks: 1 API u	nit = .618 counts per secon	nd		



SCIP CIP	GEOPHYSICAL LOGS	DE	PTH
STRII LOG	G C D R	FT	M
		350 -	-100
	100	400 -	-120
	150	450 -	-130 -140
	500	500-	-150 -160
	TANDER IN THE PROPERTY OF THE	550-	-1 <b>7</b> 0
	•	600 <b>~</b>	-180 -190
		650 -	-200
-		700 <b>~</b>	-210

### Moorhead Broadus Drilling Project

Hole I	esignat:	ion MB-1	11	Elev.(ft)_3	340		Total	Dept	h(ft)_	435	
Locati	on 190	0 fel 20	000 fn1	sec.	30	т	7	S.	R	49	
County	Powde	r River	State	Montana		Quadi	rangle	(7.5	') Blo	om Creek	
Cored	Y	esl	No_x	Interval(s)			_				
Date s	started_	9/1/79		Date compl	.eted_	9/1/79	9		Dril.	ler Steve Gra	nt
Geolog	gist <u>Ma</u>	rk Kirsch	nbaum	Re	marks	3 <b>:</b>					
Depth	interva	l (feet)				Top of the second se					
From	То	Thick- ness			Lit	hologi	c Desc	ripti	.on		
0	14	14	Alluviu	m, sand, ligh	t-bro	wn, wit	th cli	nker	chips		
14	22	8		ne, light-oli		•			_	calcareous at	
22	45	23	Siltsto					erbed	ded wi	th shale, blac	k,
45	81	36		medium-áark-g				y tow	ard the	e bottom	
81	91	10	Coal, b	lack, shaly t	op an	d botto	om				
91	113	22	Sandsto 94'	ne, medium-gr	ay, v	ery fir	ne gra	ined,	silty	, coaly string	er at
113	123	10	Shale,	medium-dark-g	ray,	silty					
123	130	7		lack, shale p							
130	142	12		ne, medium-da							
142	146	4								y cemented and	hard
146	175	29		ne, light- to		um-gray	y, ver	y fin	e grai	ned	
175	179	4		ne, light-gra	<b>.y</b>						
179	185	6	Coal, b					_			
185	212	27		light- to med m-gray siltst		ray, si	ilty,	inter	bedded	with sandy,	
212	225	13	Sandsto	<b>T</b>	ay, v	ery fir	ne gra	ined,	calca	reously cement	:ed
225	237	12		medium-gray,		at top	, car	bonac	eous		
237	251	14		ne, medium-gr							
251	256	5		lack, shale p				253′			
256	276	20		ne, medium-gr							
276	281	5		lack, shale p							
281	301	20	Sandsto	ne, light-gra	y, ve	ry fine	e grai	ned,	silty :	toward bottom	

Sandstone, medium-light-gray, very fine grained, silty in places

301

341

341

354

40

13

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
354	360	6	Sandstone, light-gray, very fine grained, silty
360	362	2	Coal
362	385	23	Siltstone, medium-dark-gray, sandy at top
385	435	50	Sandstone, light- to medium-gray, fine- to very fine grained, silty

Page of 12

		U.S. Geological Sur	vey		Page of 12
Hole Designation	MB-1	1 Logged D	epth	433	(ft)
Geophysical Log Sca	les:				•
Gamma (G)	100	API units/in Density	(D) _	.5 counts/s	ec/in
		ohms/in Caliper	(C) _	2 in/in	
Remarks: 1 API unit	= .6	18 counts per second			
	d <sub>C</sub>	GEOPHYSICAL LOGS	D	ЕРТН	
•	STRIP LOG	G C D R	FT	М	
		166	50 100 150	-20 30 40 50	


300-

i e	GEOPHYSICAL LOGS	S DEPTH	
STRIP LOG	G C D R	FT	M
	300 350 350	350 -	-100
	400	400 -	- 120
	250 433  MINIOLE IN PESISTING ON A	450 -	-130 -140
		500-	-150
		550 -	-160 -170
	•	600 -	-180
		650 <b>-</b>	190 -200
		700 -	-210

Hole I	Designat	ion MB-1	2 Elev.(ft) 3430 Total Depth(ft) 550
Locati	Lon_500	fw1 210	0 fnl sec. 24 T. 7 S. R. 48
County	Powde	r River	State Montana Quadrangle(7.5') Bloom Creek
Cored	: У	esN	o x Interval(s)
Date s	started_	9/2/79	Date completed 9/2/79 Driller Steve Grant
Geolog	gist <u>Ma</u>	rk Kirsch	baum Remarks: Completed as water well
Depth	interva	1 (feet)	
From	То	Thick- ness	Lithologic Description
0	9	9	Alluvium, sandy, yellowish-brown, fine-grained
9	15	6	Sandstone, yellow-brown, oxidized, clayey toward bottom
15	24	9	Coal, bony, shaly at top
24	43	19	Sandstone, medium-gray, very fine grained, silty
43	71	28	Shale, medium-gray, interbedded with light-olive-gray siltstone
71	86	15	Siltstone, brown-gray, trace carbonaceous, shale in cuttings
86	101	15	Sandstone, medium-gray, very fine grained, silty
101	103	2	Coal
103	132	29	Sandstone, light-brown-gray, very fine grained, interbedded with light-gray siltstone, clayey, coaly streak at 109'
132	135	3	Coal
135	160	25	Sandstone, medium-gray, very fine grained, interbedded with light-gray shale
160	169	9	Shale, medium-gray, coal stringer 164'-166'
169	189	20	Siltstone, light- to medium-gray, shaley
18 <b>9</b>	208	19	Sandstone, light-gray, very fine grained, silty
208	236	28	Siltstone, light- to medium-gray, sandy
236	245	9	Coal
245	262	17	Siltstone, light-gray, clayey, coal streak at 250'
262	288	26	Sandstone, light-gray, fine- to very fine grained, calcareous and hard at 266', silty
288	298	10	Sandstone, light-gray, very fine grained
298	305	7	Coal
305	326	21	Shale, light-gray, silty, calcareous and hard at 314'
326	334	8	Coa1
334	344	10	Sandstone, light-gray, very fine grained
344	352	8	Shale, light-gray, silty

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
352	377	25	Sandstone, light-gray, very fine grained
377	401	24	Siltstone, light- to medium-gray, interbedded with very fine grained sandstone, coal streak from 392' to 393'
401	407	6	Coal
407	428	21	Siltstone, light-gray, clayey toward bottom
428	432	4	Coal
432	442	10	Sandstone, light-gray, silty
442	450	8	Shale, medium-gray, silty
450	471	21	Siltstone, light-gray, clayey towards bottom
471	485	14	Sandstone, light-gray, silty
485	495	10	Shale, medium-gray, silty
495	500	5	Sandstone, medium-gray
500	511	11	Shale, medium-gray, silty
511	514	3	Coal
514	550	46	Siltstone, light- to medium-gray, clayey

Hole Designation	MB-12	Logged Depth	545	(ft
Geophysical Log S	Scales:			
Gamma (G)	100 API units/in	Density (D)	5 counts/sec/in	- ···
Resistivity (	2.5 ohms/in	Caliper (C) 2	in/in	
Remarks: 1 API un	nit = .618 counts per se	cond		



±8	GEC	PHYS	ICAL	LOGS		DE	PŤH	
LOG	G	C	D	R		FT	М	
-		A CANAL CONTRACTOR OF THE PARTY		250		350 -	-100	
		\$ - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		3 -00		400 <b>-</b>	- 120	
		A. C.		150		450 -	-130 -140	
				500	-	500 –	-150	
		9	ent ext		!	550 -	160	
	1 :	: "1"	:- <b>1</b> - 1-:	[·]·j <del>·</del>	6	500 -	180	
						İ	190	
						50 -	200	

Hole Designation MB-13A	Elev.(ft) 3580	Total Dept	:h(ft)	605
Location 600 fel 2650 fnl	sec. 16	T. 7 S.	R	48 E.
County Powder River	State_Montana	Quadrangle(7.5	Bloom C	reek
Cored: Yes No_x	Interval(s)			
Date started 9/13/79	Date completed 9/	'13/79	Driller	Arthur Clark
Geologist Mark Kirschbaum	Remarks:	Hole 13 abando	ned due to	surface caving
and moved to 13 A				


Depth	interval	(feet)
-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	5	5	Soil, yellow-gray
5	54	49	Sandstone, yellow-gray to very pale orange, fine grain, badly washed 38' to 54'
54	63	9	Shale, medium-gray
63	75	12	Siltstone, medium-gray
75	91	16	Shale, medium-light-gray, silty top
91	99	8	Coal, parting at 95-96'
99	125	26	Shale, medium-gray to gray-brown, silty
125	160	35	Coal, black, shale streak at 147'
160	226	66	Siltstone, medium-light to medium-gray, sandy in places
226	233	7	Shale, medium-light-gray, clayey
233	244	11	Coal, black, bony 233' to 235', shale parting 235' to 237'
244	256	12	Siltstone, medium-gray, clayey at top
256	274	18	Shale, medium-light-gray, silty
274	279	5	Siltstone, medium-light-gray
279	291	12	Shale, medium-gray; carbonaceous, brown-black toward bottom
291	346	55	Shale, medium-gray to olive-gray with interbedded medium-light-gray
			siltstone
346	362	16	Sandstone, olive-gray, very fine grained
362	368	6	Coal, black, bony top 1', shale parting from 263' to 265'
368	389	21	Shale, medium-light-gray, silty
389	391	2	Coal Coal
391	406	15	Shale, medium-gray
406	408	2	Sandstone, medium-light-gray, very fine grained, calcareous
408	431	23	Siltstone, medium-gray, clayey
431	437	6	Sandstone, medium-gray
437	444	7	Shale, medium-gray

#### SECTION MB-13A

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
444	456	12	Coal, black, shale parting 448' to 450'
456	464	8	Shale, medium-light-gray, coaly at 459'
464	466	2	Coal, bony
466	499	33	Sandstone, light-gray, silty, with some interbedded light-gray shale
499	507	8	Coal
507	514	7	Shale, medium-gray, carbonaceous
514	525	11	Sandstone, medium-gray, very fine grained, calcareous and hard at 524'
525	542	17	Shale, medium-gray, carbonaceous and coaly streaks
542	559	17	Siltstone, medium-gray
559	584	25	Coal, black, bony top 1', shale partings 560' to 562' and 568' to 571'
584	588	4	Shale, light-gray
588	605	17	Siltstone, light-gray, sandy at top

Hole Designation	MB-13A	Logged Depth	607	(ft)
Geophysical Lo	og Scales:			
Gamma (G) _	100 API units/in	Density (D)	.5 counts/sec/in	
Resistivity	(R)20 ohms/in	Caliper (C)	2 in/in	
Remarks: 1 AP	I unit = .618 counts per second	<u> </u>		



350 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 -	STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
350 - 110 - 120 - 130 - 140 - 140 - 140 - 150 - 160 - 170 - 170 - 170 - 170 - 170 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 - 190 -	ST	G C D R	FT	M
130 450 - 140 140 150 160 170 180 600 - 180 650 - 200		950	350 -	
450 - 140 - 150 - 150 - 150 - 160 - 170 - 170 - 180 - 190 - 190 - 190 - 200		\$ - \$ - + - \$ - = - = - = - = - = - = - = - = - =	400 -	- 120
500 - 160 - 170 - 170 - 180 - 190 - 200			450 -	
170 180 600 - 180 650 - 200		5600	500-	
600 - 190 650 - 200		550		
-200		Committee of the second of the	600 -	
			ŀ	200


Pag	e 1	of	2
rag	<b>-</b>	OI	~

Hole Designation MB-14	Elev.(ft) 4020	Total I	Depth(ft)	595	
Location 500 fwl 650 fnl	sec30	т. 6	S. R.	48	Ε.
County Powder River	State Montana	Quadrangle(	(7.5') Philli	lps Butte	
Cored: Yes No x	Interval(s)				
Date started 9/13/79	Date completed 9/	15/79	Driller	Steve Grant	
Geologist Mark Kirschbaum	Remarks:	Hole caved	below 350'		
Depth interval (feet)		<del></del>			
From To Thick-	7.4.11		<b>.</b>		

From	То	Thick- ness	Lithologic Description
0	11	11	Alluvium, silt, grayish-yellow to light-olive-brown
11	15	4	Coal, highly oxidized
15	24	9	Siltstone, brown-gray to light-yellow-brown, leached, clayey
24	30	6	Mudstone, medium-light-gray
30	44	14	Sandstone, light-olive-gray to very light gray, very fine grained, silty at top, well cemented and hard in places
44	49	5	Shale, light-gray
49	52	3	Coal, shaly
52	61	9	Siltstone, light-medium-gray
61	88	27	Siltstone, medium-gray, sandy
88	<b>9</b> 0	2	Coal, shale, carbonaceous
90	103	13	Shale, medium- to light-gray, sandy at top
103	116	13	Coal Coal
116	133	17	Shale, light-gray, silty
133	156	23	Siltstone, medium-light-gray, clayey
156	195	39	Shale, medium- to medium-dark-gray interbedded with light-gray siltstone
195	206	11	Sandstone, light-olive-gray, very fine grained
206	220	14	Siltstone, olive-gray to light-olive-gray, clayey
220	228	8	Mudstone, medium-gray
228	286	58	Sandstone, light olive-gray to medium-light-gray, very fine grained, silty with interbedded medium gray shale
286	305	19	Coal, some carbonaceous shale
305	328	23	Siltstone, light-to medium-gray, clayey
328	340	12	Coal

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
340	442	102	Siltstone, medium-gray to medium-dark-gray, interbedded with medium-light-gray to medium-gray shale, with medium-light-gray, very fine grained sandstone, calcareous, hard from 368' to 376'; coal stringer at 441'
442 564	564 595	122 31	Sandstone, light- to medium-dark-gray, very fine grained Siltstone, olive-gray, clayey

Hole Design	ation	MB-14	Logged Depth	350	(ft)
Geophysi	cal Log Sca	les:			•
Gamma	(G)	10 counts/sec/in	Density (D)	.53 counts/sec/in	
Resis	tivity (R)		Caliper (C)	2 in/in	
Remarks:	The densit	y log is plotted with	increasing densi	ty to the left	



STRIP	GEOPHYSICAL LOGS	DE	PTH	
STI	G C D	FT	М	
		350 -	-100 -110	
		400 -	-120	
		450 -	-140	
		500-	-150	
		550 -	-170	
		600 –	-180	
		650 -	-200	
		700 -	-210	-


Pag	e	1	of	1	

Hole Designation MB-15	Elev.(ft)_4180	Total	Depth(ft)	515	
Location 900 fel 2100 fnl	sec. 8	т. 6	S. R	48	Ε.
County Powder River	State Montana	Quadrang1	(7.5') Hods	on Flats	<del> </del>
Cored: Yes No x	Interval(s)				
Date started 9/15/79	Date completed	9/15/79	Drill	er Arthur Clark	•
Geologist Mark Kirschbaum	Remarks:				

Depth	interval	(feet)
-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, gray-yellow
5	14	9	Alluvium, yellow-brown
14	26	12	Sandstone, light-brown to yellow-gray, very fine grained, silty
26	42	16	Siltstone, light-gray
42	49	7	Sandstone, light-brown, very fine grained, silty
49	53	4	Shale, dark-gray, some silt
53	55	2	Coal
55	58	3	Carbonaceous shale
58	61	3	Coal Coal
61	85	22	Siltstone, medium-light-gray to medium-gray, clayey
85	94	9	Shale, medium-gray, coal stringer
94	100	6	Sandstone, light-gray, very fine grained
100	103	3	Coal Coal
103	146	43	Sandstone, light-blue-gray to light-gray, very fine grained, clayey in places
146	183	37	Shale, medium-gray, silty, with coal at 146' to 148' and 181' to 182'
183	195	12	Shale, brown-black, silty
195	204	9	Coal
204	254	50	Interbedded shale, medium-light-gray, and medium-gray to medium-dark-gray, siltstone, numerous washouts
254	273	19	Sandstone, medium-gray, very fine grained
273	336	63	Shale, light-to-medium gray with clay at 324'; silty in places; trace coal in cuttings at 277'
336	420	84	Sandstone, medium-light-gray, very fine grained, silty
420	449	29	Siltstone, light- to medium-light-gray, clayey toward bottom
449	489	40	Coal, shale parting from 471' to 476'
489	497	8	Shale, medium-light-gray
497	515	18	Shale, medium-gray, silty
			68

Hole Designati	Lon	MB-15		Logged De	pth_	5	514	(ft
Geophysical	Log Sca	les:						•
Gamma (G	;)	10 API u	nits	Density (	(D) _	.53 count	s/sec/in	
Resistiv	vity (R)	Dry 200	ohms/in Wet 1	0 ohms/in	Cali	per (C)	2 in/in	
Remarks: Dr	y resist	ivity run	until 330'.	Density log	plot	ed with	increasing	density
to the left.	1 API un	it = .618	counts per se	econd				



-100 350 -110 400 - 120 -130 450 - 140 -150 -160 -170 600 - 180 600 - 190 650 - 200	STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
100 350- 110 400-120 130 450- 140 500-150 -160 550- -170 600-180 600-200	STI	G C D R	FT	M
400 - 120 130 450 - 140 500 - 150 160 550 - 170 600 - 180 600 - 200			350 -	
450 - 140 500 - 150 -160 550 170 600 - 180 600 - 200			400 -	- 120
-160 -550 -170 -180 -190 -200			450 <b>-</b>	
-170 -180 -190 -200			500-	
650200				
			600	
700 -		·		200


# Moorhead Broadus Drilling Project

Hole 1	Designa	ation MB-	16
Locat	ion 60	00 fn1 90	0 fel sec. 30 T. 5 S. R. 48
County	y Pow	ier River	State Montana Quadrangle(7.5') Hodson Flats
Cored	:	Yes	No_x_ Interval(s)
Date :	starte	d 9/18/79	Date completed 9/18/79 Driller Steve Grant
Geolo;	gist	Mark Kirsc	hbaum Remarks:
Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, dark-yellow-orange sand to yellow-brown clay
5	10	5	Alluvium, sand and clay, yellow-brown to gray-brown
10	12	2	Alluvium, sand, yellow-orange
12	19	7	Coal, highly oxidized, carbonaceous shale parting from 16' to 17'
19	30	11	Sandstone, yellow-brown to yellow-gray, very fine grained, clayey
30	44	14	Shale, medium-light to medium-gray, trace carbonaceous shale
44	48	4	Coal
48	60	12	Shale, medium-dark-gray to brown-black
60	64	4	Coal, bony
64	75 <b>7</b> 5	11	Shale, medium-light-gray
75 70	78	3	Coal, shale, carbonaceous
78	87	9	Shale, medium-gray, silty
87	92	5	Sandstone, light-gray, very fine grained, calcareous, hard
92	95	3	Mudstone, medium-gray, silty
95 06	96	1	Sandstone, light-gray, very fine grained, calcareous, hard
96 125	125	29	Sandstone, green-gray to medium-gray, very fine grained, clayey
138	138 147	13 9	Siltstone, medium-dark-gray, clayey Coal
147	156	9	Shale, medium-gray, silty
156	160	4	Shale, medium-dark-gray
160	200	40	Shale, medium-dark-gray Shale, medium-light to medium-dark-gray, silty
200	219	19	Coal
219	236	17	Siltstone, medium-light-gray, sandy
236	304	68	Sandstone, medium-light-gray, very fine grained, grading silty to top
304	315	11	Coal
315	326	11	Shale, medium-dark-gray, silty towards bottom
326	347	21	Sandstone, very light to light-gray, grading shaly to base
347	365	18	Sandstone, light- to medium-gray grading silty to base

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
365	415	50	Sandstone, medium-gray, very fine grained, silty at top
415	445	30	Siltstone, light gray, interbedded with medium-light- to medium-gray, shale
445	473	28	Shale, brown-gray to brown-black, silty
473	502	29	Sandstone, light-gray, very fine grained, silty
502	523	21	Coal
523	555	32	Siltstone, medium-light- to medium-gray, clayey

Pag	e	_of_	2
-----	---	------	---

Hole Designation	MB-16	Logged Depth	546	(ft)
Geophysical Lo	og Scales:			
Gamma (G) _	100 API units	Density (D)	.5 counts/sec/in	
Resistivity	7 (R) 20 ohms/in	Caliper (C)	3 in/in	•
Remarks: 1 AP	I unit = .618 counts per se	cond		



#2L	GEOPHYSICAL LOGS	DEPTH		
STRI	G C D R	FT	М	
	350	350 -	-100	
		400 -	- 120	
	450	<b>4</b> 50 <b>-</b>	-130 -140	
	500	500-	-150	
	250 APPARCAL GOCC - '546  CAUTHA API APPARCAL GOCC	550-	-1 <b>6</b> 0 -170	
-		600 -	-180	
		+	190	
		650 -	200	
		700 -	-210	

# Moorhead Broadus Drilling Project

Hole Designation MB-17	Elev.(ft)_3905	Total Depti	h(ft)	515	
Location 1850 fw1 1900 fn1	sec. 7	T. 5 S.	R	48	Ε.
County Powder River	State Montana	Quadrangle(7.5	) Sonnette		
Cored: Yes No x	<pre>Interval(s)</pre>	<del></del>			
Date started 9/27/79	Date completed	9/27/79	Driller_	Steve Grant	
Geologist Frank Spencer	Remarks	•			


Depth	interval	(feet)
-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, sand, light-yellow-gray, medium- to fine grained
5	10	5	Alluvium, sand, medium-yellow-brown, very fine grained to fine grain
10	65	55	Sandstone, light-yellow-gray to medium-gray, very fine grained to fine-grained, silty, silty toward base
65	75	10	Coal, woody, shale at top
75	77	2	Shale
77	82	5	Sandstone, light- to medium-gray, very fine grained, silty
82	84	2	Coal stringer
84	101	17	Shale, light-gray, silty
101	112	11	Coal, bony, woody
112	115	3	Shale
115	127	12	Siltstone, light-gray
127	131	4	Shale, carbonaceous
131	158	27	Siltstone, light- to medium-gray, sandy, with shaley coal stringers at 141' and 145'
158	180	22	Sandstone, light-gray, very fine grained, silty, clayey
180	200	20	Sandstone, medium brown-gray, medium- to coarse-grained, with calcareous streaks
200	260	60	Sandstone, light- to medium-gray, cherty, silty
260	262	2	Coal stringer
262	288	26	Siltstone, light-gray, clayey
288	304	16	Interbedded shaley coal and shale
304	317	13	Siltstone, light-gray, sandy
317	340	23	Coal
340	378	38	Sandstone, light- to medium-gray, very fine to medium-grained, silty
378	406	28	Siltstone, medium-gray, sandy
406	409	3	Coal

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
409	419	10	Shale, dark-brown, silty, carbonaceous
419	444	25	Sandstone, medium-gray, very fine grained to medium-grained
444	451	7	Shale
451	462	11	Coal Coal
462	471	9	Shale, medium-gray, silty
471	490	19	Siltstone, medium-gray
490	494	4	Shale, medium-gray
494	515	21	Siltstone, medium-gray, sandy toward base

Pag	e	1	of	2	

Hole Desig	nation	MB-17	Logged Depth	480	(ft)
Geophys	ical Log Sca	les:		•	
Gamm	a (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resi	stivity (R)	2.5 ohms/in	Caliper (C)	1.5 in/in	
Remarks:	l API unit	618 counts per sec	ond		



RIP OC	GEOPHYSICAL LOGS	DE:	PTH
STRII LOC	G C D R	FI	М
	350	350 -	-100
		400 -	- 120
		450 <b>-</b>	-130 -140
	SSD1 CAR	500 -	-150
	• ·	550-	-160 -170
		600 -	-180
			-190
		650 -	200
-		700 -	-210

78


Pag	e <sup>j</sup>	L	οf	:	2

			Moorhead Broadus I	Orilling Pr	oject			
Hole D	esignat	tion MB-1	8 Elev.(ft) 3730	Total	L Deptl	n(ft)	495	
Locati	on500	0 fw1 200	00 fnl sec. 33	T. 4	s.	R	48	Ε.
County	Powde	er River	State_Montana	Quadrang	Le(7.5	) Sonnett	e	
Cored:	3	YesN	o <u>x</u> Interval(s)					
Date s	tarted_	10/15/79	Date completed_	10/24/79		Driller_	Steve Grant	
Geolog	ist Ma	ark Kirsch	baum Remarks:					
J					-			
	····							
Depth	interva	al (feet)				W		
From	То	Thick- ness	Lith	ologic Des	cripti	on		
0	5	5	Soil, clay, yellow-orange	to gray-br	own			
5	10	5	Soil, clay, light-olive-gr	ay				
10	15	5	Soil, clay, medium-gray					
15	29	14	Shale, medium-gray					
29	36	7	Carbonaceous shale, coal a	t 30'				
36	39	3	Shale, clayey, medium-gray	•				
39	41	2	Shale, carbonaceous, coaly	•				
41	44	3	Mudstone, light-gray, clay	ey, silty				
1.1.			0.14					

#### Siltstone, medium-light-gray, sandy Mudstone, olive-gray Coa1 Sandstone, light-olive-gray, very fine grained, silty Coal, bony and carbonaceous shale Mudstone, green-gray, clayey Siltstone, light-gray, silty Shale, carbonaceous, coal 167'-169' Shale, brown-black Mudstone, medium-light- to medium-gray, silty Siltstone, medium- to medium-light-gray, clayey Mudstone, brown-gray, coal stringers Sandstone, medium-gray, very fine grained Siltstone, medium gray

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
240	260	20	Shale, olive-gray to brown-gray
260	265	5	Mudstone, brown-black
265	270	5	Mudstone, olive-gray, and, medium-gray, very fine grained sandstone
270	300	30	Shale, medium-gray to green-gray
300	310	10	Siltstone, medium-light-gray
310	320	10	Shale, medium-light-gray
320	325	5	Siltstone, medium-light-gray
325	<b>33</b> 0	5	Shale, medium-light-gray
330	332	2	Siltstone, medium-light-gray, calcareous, hard
332	345	13	Shale, medium-gray
345	367	22	Coal
367	375	8	Carbonaceous shale and medium-gray, very fine grained sandstone
375	380	5	Carbonaceous shale and mudstone
380	400	20	Mudstone, brown-gray
400	405	5	Mudstone, dark-green-gray
405	410	5	Siltstone, light-gray
410	420	10	Siltstone, medium-light-gray, and sandstone, light-gray, very fine grained, calcareous, hard
420	437	17	Sandstone, medium-gray, very fine grained, clayey
437	439	2	Coal
439	459	20	Siltstone, light-gray, sandy
459	462	3	Coal
462	470	8	Siltstone, green-gray, clayey
470	475	5	Siltstone, light-olive-gray
475	480	5	Siltstone, light-gray, and sandstone, light-gray, very fine grained, calcareous, hard
480	495	15	Siltstone, light-gray, coal stringer

		U.S. Ged	ological Surv	ey			
Hole Designation	MB-18		Logged De	pth _	219		(ft)
Geophysical Log Sca	ales:					•	
Gamma (G)	20 co	unts/sec/in	_ Density (	D) <u>1</u>	00 counts/s	ec/in	
Resistivity (R)			Caliper (	c) _2	in/in		man over
Remarks:	•				•		
	<del></del>						
				ı —			
	STRIP LOG	GEOPHYSICAL	LOGS	DE	PTH		
	SI	G D	C	FT	М		




# Moorhead Broadus Drilling Project

Hole D	esignat	ion MB-1	9 & MB-19C Elev.(ft) 3730 Total Depth(ft) 615
Locati	on_100	fel 240	0 fnl sec. 20 T. 4 S. R. 48
County	Powde	r River	State Montana Quadrangle(7.5') Sonnette
Cored:	Y	es <u>x</u> N	o Interval(s) 60' to 90.2', 399' to 424.5'
Date s	tarted_	10/26/79	Date completed 10/26/79 Driller Arthur Clark
Geolog	ist Ma	rk Kirsch	baum Remarks: Core description by George A. Correia
Depth	interva	ıl (feet)	
From	То	Thick-	
		ness	Lithologic Description
0	4	4	Soil, yellow-brown
4	9	5	Siltstone, yellow-gray
9	15	6	Shale, yellow-orange, clayey
25	35	10	Siltstone, yellow-gray, with stringers of mudstone, yellow- orange, clayey
35	43	8	Mudstone, light- to medium-light-gray, clayey
43	48	5	Shale, light-gray, coaly streak at 46'
48	60	12	Shale, light-gray, silty, shell fragments, clayey CORE DESCRIPTION
60.0	61.3	1.3	Claystone, light-gray, silty toward bottom
61.3	62.4	1.1	Claystone, gray, silty, sand pockets, sharp contact with coal
62.4	75.2	12.8	Coal, black, hard, dull with bright streaks, conchoidal fracture, slicken side on top .6', clay streaks with gypsum crystals on fractures 71.8' to 72.3', gypsum and pyrite (disseminated) at 72.6', moisture on fresh fractures 72.3' to 73.0'
75.2	75.8	0.6	Shale, light brown, carbonaceous with rootlets and plant material, coal streak at base
75.8	78.1	2.3	Shale, gray, carbonaceous streaks - coal clasts - small streaks of coal to 76.5', scattered rootlets 76.5' to 77.8', slightly carbonaceous 77.8' to 78.1'
78.1	78.5	•4	Coal, black, hard, 60% shiny, clay pockets
78.5	79.1	•6	Shale, olive-brown, carbonaceous
79.1	79.6	•5	Shale, medium gray, carbonaceous on bedding planes, grades basal .2' into coal
79.6	89.4	9.8	Coal, black, hard, dull with shiny bands, conchoidal fracturing, clay streaks at 85.6', 86.3', and 87.6', disseminated pyrite and gypsum 86.2' to 86.4' on fractures, sharp basal contact with

siltstone below


Depth	interv	al (feet)	
From	То	Thick- ness	Lithologic Description
89.4	90.2	.8	Siltstone, medium-light-gray, clayey, shaly top .1', gypsum, scattered rootlets END OF CORE DESCRIPTION
90.2	122	31.8	Shale, medium-light-gray, silty
122	129	7	Siltstone, light-gray, slightly sandy
129	152	23	Shale, light-gray, silty
152	155	3	Coal, black, bony
155	158	3	Claystone, very light gray
158	162	4	Coal, black, bony
162	167	5	Shale, medium-light-gray, carbonaceous at top, silty
167	193	26	Siltstone, medium-light-gray, sandy at bottom
193	211	18	Sandstone, light-gray, very fine grained, calcareous and hard at 195'
211	219	8	Shale, medium-light-gray
219	222	3	Coal
222	228	6	Shale, medium-dark-gray, carbonaceous, silty
228	256	28	Siltstone, light-gray, sandy, coaly from 238' - 240'
256	262	6	Shale, brown-black, carbonaceous in part
262	286	24	Siltstone, medium- to light-gray
286	289	3	Shale, medium-gray
289	298	9	Shale, olive-gray, silty, carbonaceous with some coaly material
298	338	40	Mudstone, medium- to olive-gray, silty, shaly with coaly streak 321' to 322', clay streak at bottom
338	383	45	Sandstone, light-gray, very fine grained, silty toward bottom
383	399	16	Shale, light- to medium-light-gray, silty CORE DESCRIPTION
399.0	399.4	. 4	Claystone, medium-gray, silty, sharp basal contact with coal
399.4	420.4	21.0	Coal, black, dull with shiny bands, fractured 399.4' to 403.3', medium hard, crumbles when fractured 399.4 to 407.8, badly broken with clay streaks 412.5' to 413.4'
420.4	422.2	1.8	Claystone, medium-gray, slightly silty, carbonized rootlets, coal lense bottom .1'
422.2	424.5	2.3	Sandstone, medium-light-gray, fine grain, subrounded, mostly quartz END OF CORE DESCRIPTION
424.5	446	22.5	Siltstone, medium-to medium-light-gray
446	454	8	Sandstone, medium-light-gray, very fine grained
454	461	7	Shale, medium-light-gray, silty
461	468	7	Coal
468	475	7	Siltstone, very-light-gray
475	485	10	Shale, medium-light-gray, silty
485	514	29	Sandstone, medium-light-gray, silty
514	522	8	Coal
522	564	42	Shale, light- to medium-gray, silty
564	575	11	Sandstone, medium-light-gray, silty
575	615	40	Shale, medium-light-to light-gray, silty

Hole Designation	MB-19	Logged Depth	610	(ft)
Geophysical Log	Scales:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity	(R) 10 ohms	Caliper (C)	2 in/in	
Remarks:				



GEOPHYSICAL LOGS	DE	PTH
GEOPHYSICAL LOGS  G D C R	FT	М
350	350 -	-100
420'	400 - 450 -	-130 -140
- 500	500~	-150 -160
550	550 -	-170
Campelly) -600' -RES  1° 20 C.p.S400' S. C.M. POR 1° = 10 de 10 10 10 10 10 10 10 10 10 10 10 10 10	600 -	-180
PE 1733 Sc.p.S.	650 <b>-</b>	-210

Hole Designation	MB-19C	Logged Depth	426	(ft)
Geophysical Log S	Scales:			
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (F	2)	Caliper (C)	2 in/in	
Remarks:	- " - '	-	-	



\*

STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
ST	G D C	FT	М
	380	350 -	-100
		400 -	110
	Pagoepas426 CALIPER TO Parloaps.  Lowis 132 255 cps.  metro 25 cps.	450 -	-130 -140
	SOOCAS DEFINITY O	500-	-150
		550-	·160 ·170
		600 -	·180
		650 -	200
		700 -	-210

# Moorhead Broadus Drilling Project

Hole D	esignat	ion MB-2	0
Locati	on 650	fw1 750	fnl sec. 6 T. 4 S. R. 48 E
County	Powde	er River	State Montana Quadrangle(7.5') Samuelson Ranch
Cored:	Y	es <u>x</u> N	oInterval(s)
Date s	tarted_	10/29/79	Date completed 10/29/79 Driller Arthur Clark
Geolog	gist <u>M</u> a	irk Kirsch	baum Remarks:
Depth	interva	ıl (feet)	
From	То	Thick- ness	Lithologic Description
0	5	5	Soil, light-olive-gray
5	14	9	Mudstone, very-light-gray to yellow-gray
14	30	16	Sandstone, yellow-gray, very fine grained
30	36	6	Shale, medium-gray
36	43	7	Shale, light- to medium-light-gray, coaly at bottom
43	50	7	Shale, medium-light-gray, silty
50	80	30	Siltstone, medium-light-to medium-gray, sandy
80	81	1	Coal, bony
81	87	6	Claystone, light-gray
87	90	3	Shale, carbonaceous, clayey
90	118	28	Siltstone, green-gray to medium-gray
118	126	8	Claystone, medium-dark-gray
126	257	131	Mudstone, light-gray, interbedded with gray siltstone, sandy in places
257	290	33	Siltstone, medium-light-gray, clayey
290	311	21	Coal with shale parting from 300'-302'
311	319	8	Shale, brown-gray
319	328	9	Coal, shaley? at top
328	356	28	Shale, medium-light-gray to brown-gray, with some tan, very fine grained, well cemented sandstone
356	358	2	Coal Coal
358	395	37	Siltstone, light- to medium-light-gray, clayey in places
395	466	71	Sandstone, light-green-gray to tan to green-gray, very fine grained, well cemented in places, silty at top
466	473	7	Coal with olive-gray shale stringer at 469'
473	493	20	Shale, olive-gray to brown-gray
493	497	4	Shale, brown-gray, carbonaceous in part
497	539	42	Siltstone, light-gray

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
539	543	4	Coal and carbonaceous shale
543	609	66	Shale, light- to medium-light-gray, silty, with coal stringers
609	631	22	Sandstone, medium-light-gray, very fine grained
631	634	3	Coal
634	644	10	Shale, light-gray, silty
644	653	9	Sandstone, light-gray
653	655	2	Carbonaceous shale, coal, hard
655	663	8	Shale, medium-light-gray, clayey
663	668	5	Coal
668	675	7	Shale, light-gray
675	690	15	Sandstone, light-gray, very fine grained

		U.S. Geolo	gical Surve	e y	Page	of <u>2</u>
Hole Designation	MB-20		Logged Dep	oth	685	(ft
Geophysical Log Sc	ales:				•	
Gamma (G)	20 co	unts/sec/in	Density (I	0) 100 cou	ints/sec/in	
Resistivity (R)			-Caliper ((	2 in/ir	1	
	G	GEOPHYSICAL LO	ogs	DEPTH		
	STRIP LOG	G D	c ·	FT M		
		-100'- -100'- -150'		-10 50 - 20 100 - 30 -40 150 - 50 -70 250 - 80		

	-		
GEOPHYSICAL LOGS	DE	PTH	7
GEOPHYSICAL LOGS  G D C	FT	М	1
3.	350 -	-100	
-4eo'	400 -	- 120	
4987	450 -	-130 -140	
500	500-	150	
- 5580	550-	160 170	
<b>400'</b>	600 -	180	
- (so')	650 -	200	
Passens US Britis Carper		210	

				Moorhead Br	oadus	Drilli	ng Pro	ject			
Hole :	Designa	ation M	B-21	Elev.(ft)_	4220		Total	Depth(ft)	515		
Locat	ion 17	700 fn1	1750 fel	sec.	31	т.	5	S. R	48	Е	-
Count	y Powe	ler Rive	r	State Montana	<del></del>	Qua	drang1	e(7.5') <u>H</u>	dson Flats		
Cored	:	Yes	No_x	Interval(s	)		<del> </del>				
Date	started	1 10/14	/79	Date comp	leted_	10/14	/79	Dr:	iller Stev	e Grant	
Geolo	gist 1	Mark Kir	schbaum	Ro	emarks	s <b>:</b>					
						<del> </del>					
Depth	interv	val (fee	t)	······································	<del> </del>	<del></del>					_
From	То	Thick- ness			Lit	hologi	c Desc	ription			
0	5	5	Soil,	sand, medium-	gray						
5	15	10	•	sand, yellow-	_	2					
15	20	5	-	sand, gray-ye							
20	45	25		one, medium-y		to gra	y-ye11	ow, very	ine graine	d, silty	
45	60	15		one, light-gr	ay						
60	70	10		brown-gray							
70	79	9	Coal,	•							
79	99	20		cone, light- to		_	_	y, silty			
99	101	2		bony, and car							
101	132	31		light-olive-						:	
132	162	30	Sandst	one, brown-gra	ay to	medium	-dark-	gray, sil	<b>:y</b>		
162	171	9	Coal.	bony, shale p	arting	from	166' t	o 168'			

#### Siltstone, medium-light-gray, clayey Siltstone, medium-gray to brown-gray, sandy Shale, medium-gray to brown-gray Coal, bony, and carbonaceous shale Shale, brown-gray to brown-black Coal, with carbonaceous shale parting at 227' Shale, medium-light to medium-gray, silty Siltstone, medium-light to medium-gray, clayey in places Sandstone, medium-light to medium-gray, very fine grained, silty in part Coal, with mudstone parting from 439' to 441' Mudstone, medium-light-gray Siltstone, green-gray, sandy, clayey Shale, light- to medium-light-gray, with coal stringers Sandstone, medium-gray, very fine grained Shale, medium- to medium-light-gray, slightly silty

Page	1	of	2
- 45 -			

Hole Design	nation	MB-21	Logged Depth	514	(ft)
Geophysi	cal Lo	Scales:			
Gamma	(G) _	100 API units/in	Density (D)	.5 counts/sec/in	
Resis	tivity	(R)20 ohms/in	Caliper (C)	2 in/in	
Remarks:	1 API	unit = .618 counts per second			

G 1007 G	EOPHYS	CAL L	OGS	DEI	TH
G	C	ם	R	FT	н
		A STANANTA	50-	50 —	-10 -20
			100	100 —	-30 -40
			150	150 —	-50
			208	200-	-60
	\$   \$   \$   \$   \$   \$   \$   \$   \$   \$		258	250—	<b>-7</b> 0
		, -   -   -   -   -   -   -   -   -   -		300-	-80 -90

128 128	GEOPHYSICAL LOGS	DE	DEPTH	
STRI	G C D R	FT	М	
	350	350 -	-100 -110	
	400	400 -	- 120	
	450	450 -	-130 -140	
	-3	500-	-150	
	A STORY OF A R.	550-	-160 -170	
	•	600 –	-180	
	·	650 -	·190 ·200	
-		700 -	-210	

Pag	e	1	of	2	

# Moorhead Broadus Drilling Project

Hole Designation MB-22 & MB	$\frac{22C}{\text{Elev.}(ft)} \frac{396}{396}$	T 00	otal Dept	h(ft)	455	
Location 1400 fel 1900 fnl	sec1	9 T	5 S.	R	48	Ε.
County Powder River	State Montana	Quadr	angle(7.5	) Sonnette	2	
Cored: Yes_x No_Intervals_	32.0 to 43.3, 7	9.8 to 106.	4, 172.8	to 186.9,	395 to 421.6	
Date started 9/28/79	Date complet	ed 9/28/79	)	Driller	Steve Grant	<del>*************************************</del>
Geologist Frank Spencer	Rema	rks: Core	descripti	on George	A. Correia	


Depth	interval	(feet)
-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	5	5	Alluvium, clay, medium-yellowish-brown
10	21	11	Siltstone, yellow-brown, sandy, calcareous and hard at 10', clayey at bottom
21	32	11	Sandstone, medium-yellow-brown, very fine-grained CORE DESCRIPTION
32.0	32.6	0.6	Coal, black, mostly vitrinite, clay on fractures, oxidation first .2'
32.6	37.8	5.2	Coal, black, 75% dull, hard, conchoidal fracture pyrite rosettes between 43.1' and 44.8'
37.8	39.5	1.7	Coal, black, alternating bands of shaly coal and hard dull coal, gypsum on fractures
39.5	43.3	3.8	Coal, black, 75% dull, conchoidal fractures END OF CORE DESCRIPTION
43.3	51	7.7	Shale, medium-gray, carbonaceous at top, silty
51	59	8	Siltstone, medium-gray
59	66	7	Shale, medium-gray
66	79.8	13.8	Siltstone, medium-gray, clayey top and bottom, carbonaceous at top CORE DESCRIPTION
79.8	84.5	4.7	Claystone, medium-gray, slightly silty, carbonaceous on bedding planes, coaly 81.6 to 81.8
84.5	93.3	8.8	Coal, black, alternating dull clean and dull dirty bands, hard, conchoidal, fractures, shaly 84.5' to 84.9', small clay streaks 90.9' to 91.8'
93.3	95.1	1.8	Coal, black, dull, very hard, large conchoidal fractures
95.1	97.7	2.6	Coal, black, dull clean and dull dirty bands, scattered clay pockets, gypsum on fractures, disseminated pyrite 96.2'
97.7	100.5	2.8	Coal, black, dull with some shiny bands, dirty, scattered gypsum, scattered clay pockets 95

Depth	interv	al (feet)	
From	То	Thick- ness	Lithologic Description
100.5	105.1	4.6	Coal, black, dull with shiny streaks, gypsum on fractures, diseminated pyrite band at 100.8'
105.1	106.4	1.3	Claystone, dark-gray, carbonaceous, scattered gypsum crystals END OF CORE DESCRIPTION
106.4	108	1.6	Claystone, dark-gray, carbonaceous
108	135	27	Shale, medium-gray, interbedded with medium-gray siltstone
135	172.8	37.8	Sandstone, medium-gray, medium- to coarse-grain, calcareous at top, grades toward bottom to siltstone, badly washed out  CORE DESCRIPTION
172.8	173.5	0.7	Siltstone, medium-gray, carbonaceous bands, clayey, sandy in spots, sharp basal contact with coal
173.5	176.0	2.5	Coal, black, shaly, 60% dull, scattered clay pockets
176.0	185.5		Coal, black, hard, 80% dull, conchoidal fracture, some gypsum on fractures, resin pockets toward bottom
185.5	186.2	0.7	Shale, dark-gray, carbonaceous
186.2	186.9	0.6	Coal, black, very shaly, sandy END OF CORE DESCRIPTION
186.9	196	9.1	Claystone, light-gray, silty toward bottom, coaly streaks
196	217	21	Siltstone, light-gray, sandy
217	227	10	Shale, black-brown, carbonaceous, coaly streaks
227	<b>3</b> 54	127	Siltstone, light- to medium-gray, interbedded with light- to medium-gray, very fine to medium-grain, sandstone stringers of shale, carbonaceous, coaly material, and hard calcareous lenses
354	384	30	Sandstone, medium-to dark-gray, very fine grained, clayey, carbonaceous toward bottom
384	395	11	Shale, medium- to dark-gray  CORE DESCRIPTION
395.0	395.9	0.9	Sandstone, dark-gray, fine-grained, claystone stringers, carbonaceous
395.9	407.7	11.8	Coal, black, hard, alternating dull and shiny bands, conchoidal fracturing, sandy streaks and resin pockets top .2'
407.7	420.1	12.4	Coal, black, hard, dull and shiny bands, conchoidal fracturing, cleat fractures 414.6 to 419.4', clay streak 417.8', shaly, 419.4' to 420.1'
420.1	420.5	0.4	Claystone, medium-gray, carbonaceous, scattered coal clasts
420.5	421.6	1.1	Siltstone, medium-gray, rootlets END OF CORE DESCRIPTION
421.6	455	33.4	Siltstone, medium-gray, calcareous, sandy


Page 1 of 2

Hole Design	nation	MB-22	Logged Depth	451	(ft)
Geophysi	lcal Log Sca	ales:			
Gamma	(G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resis	stivity (R)	2.5 ohms/in	Caliper (C)	2 in/in	
Remarks:	1 API uni	t = .618 counts per second			
		•			



a E E	GEOPHYSICAL LOGS	DE	РТН
STRIP LOG	G C D R	FT	М
	356	350 -	-100 -110
	400	400 -	- 120
	STATE OF THE STATE	450 -	-130 -140
		500-	-150
	•	550 -	160
		600-	180
		1	190
		650 -	200
	·	700	210

Hole Designation	MB-22C	Logged Depth	425	(ft)
Geophysical Log Sc	ales:		. •	
Gamma (G)	100 API units/in	Density (D)	.5 counts/sec/in	
Resistivity (R)	20 ohms/in	Caliper (C)	2 in/in	
Remarks: 1 API uni	t = .618 counts per second			



STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
STI	G C D R	FT	М
	<b>7</b>	350 -	-100
		400 -	- 120
	250 Experiment of the control of the	450 -	-130
			-140 -150
		500-	-160
		550-	-170
		600 -	-180
	·		-190
		650 -	-200
		700 -	-210

# Moorhead Broadus Drilling Project

Hole Designation MB-23	Elev.(ft) 4080	Total Depth(ft)	760
Location 350 fwl 2200 fnl	sec. 15	T. 6 S. R.	47 E.
County Powder River	State Montana	Quadrangle(7.5') Ph	illips Butte
Cored: Yes No x	Interval(s)		
Date started 10/24/79	Date completed_	10/25/79 Dri	ller Arthur Clark
Geologist Mark Kirschbaum	Remarks	<u> </u>	


	Depth	interval	(feet)
--	-------	----------	--------

From	То	Thick- ness	Lithologic Description
0	5	5	Soil, gray-yellow to light-olive-gray
5	19	14	Shale, light-olive-gray to medium-light-gray, silty
19	21	2	Shale, carbonaceous
21	31	10	Shale, medium-light-gray to light-olive-brown, silty, carbonaceous shale 24' to 26'
31	33	2	Sandstone, medium-gray to light-brown, very fine grained, well cemented, calcareous
33	46	13	Siltstone, medium-gray, sandy
46	59	13	Shale, medium-gray to brown-gray to brown-black
59	65	6	Shale, medium-gray
65	79	14	Mudstone and siltstone, medium-gray, interbedded
79	83	4	Coal, black
83	102	19	Siltstone, light- to medium-gray
102	104	2	Coal, black
104	133	29	Siltstone, medium-light-gray, sandy
133	136	3	Coal, black
136	146	10	Shale, medium-gray
146	154	8	Coal, black
154	160	6	Shale, light-blue-gray, silty
160	164	4	Shale, light-blue-gray
164	190	26	Siltstone, light-gray, sandy, and light-gray shale
190	197	7	Shale, brown-gray
197	231	34	Shale, light-gray to green-gray, silty
231	240	9	Sandstone, medium-light-gray
240	252	12	Shale, medium-light-gray
252	260	8	Sandstone, medium-gray
260	280	20	Siltstone, light-gray, clayey

Depth	inter	val (feet)	
From	То	Thick- ness	Lithologic Description
280	286	6	Shale, light-gray
286	292	6	Siltstone, light-gray
292	294	2	Shale, light-gray
294	313	19	Siltstone, medium-light-gray
313	316	3	Shale, medium-light-gray
316	372	56	Siltstone, light- to medium-gray
372	384	12	Shale, medium-light-gray, silty at bottom
384	402	18	Coal, black
402	407	5	Claystone, medium-light-gray
407	418	11	Coal, black
418	436	18	Siltstone, light-gray to brown-gray clayey top and bottom
436	439	3	Shale, brown-gray
439	511	72	Interbedded shale, medium-light-gray to brown-gray, and siltstone, light-gray to medium-light-gray, sandy in places
511	514	3	Coal
514	521	7	Shale, light-gray to brown-gray
521	543	22	Sandstone, light-gray, silty at top
543	574	31	Shale, light-gray to medium-light-gray
574	576	2	Sandstone, light-gray
576	583	7	Siltstone, light-gray, to light-gray shale towards bottom
583	623	40	Siltstone, light-to medium-light-gray, clayey in places
623	668	45	Sandstone, light-gray to brown-gray, silty towards bottom
668	692	24	Coal, with shale parting from 684' to 686'
692	737	45	Shale, olive-gray to medium-gray, sandy
737	755	18	Shale, medium-light to medium-gray
755	760	5	Siltstone, light-gray

Pag	$e^{-1}$	of	2
_		•	

Hole Designation	MB-23	Logged Depth	737	(ft)
Geophysical Log	Scales:			
Gamma (G)	20 counts/sec/in	Density (D) 100	counts/sec/in	•
Resistivity (	R) 10 ohms/in	Caliper (C) <u>2</u> i	n/in	
Remarks:			-	



<b>⊒8</b> L	GEOPHYSICAL LOGS		DE	PTH	·
STRII	G	R	FT	M	
				-100	·
	358		350 -	-110	-
			400 -	- 120	
		stear   Hel	450 -	-130	
			500-	-150	
-			550-	170	
			600-	180	
	(a)	=	650 -	200	
		_	700 -	210	·

Page 1 of 1

# U. S. Geological Survey


# Moorhead Broadus Drilling Project

Hole Designation MB-24	Elev.(ft) 3735	Total	Depth(f	t)	
Location 1900 fel 2150 fsl	sec. 15	T. 5	S. R.	46	Ε.
County Powder River	State Montana	Quadrang1	e(7.5′)	Yager Butte	
Cored: Yes No x	Interval(s)				
Date started 10/27/79	Date completed 10	)/27/79	D	riller Steve Grant	
Geologist Mark Kirschbaum	Remarks:		· · · · · · · · · · · · · · · · · · ·		

# Depth interval (feet)

From	То	Thick- ness	Lithologic Description
0	5	5	Soil, yellow-brown
5	20	15	Siltstone, yellow-brown, and yellow-brown mudstone
20	50	30	Sandstone, light-gray to yellow-gray, fine-grained
50	80	30	Interbedded siltstone, light-olive-gray, and medium-light-gray to yellow-orange shale
80	102	22	Siltstone, medium-light-gray, grading to medium-light-gray, very fine grained, sandstone toward bottom
102	121	19	Sandstone, medium-light-gray, very-fine-grained
121	136	15	Coal, bony
136	143	7	Shale, light-gray, carbonaceous at top
143	157	14	Siltstone, light-to medium-light-gray, clayey
157	170	13	Coal, bony
170	206	36	Shale, medium-gray, silty toward bottom
206	260	54	Sandstone, medium-light-gray, fine-grained
260	275	15	Shale, medium-gray, sandy

Hole Designation	MB-24	Logged Depth	274	(ft)
Geophysical Log	Scales:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (	R)	Caliper (C)	2 in/in	
Remarks:				



#### Moorhead Broadus Drilling Project

Hole I	Designa	ation MB-2	5 Elev.(ft) 3805 Total Depth(ft) 460
Locati	lon 16	600 fsl 22	00 fwl sec. 25 T. 4 S. R. 46 E.
County	Powe	ier River	State Montana Quadrangle(7.5') Yager Butte
Cored	:	YesN	o_x Interval(s)
Date s	started	i 10/25/79	Date completed 10/26/79 Driller Steve Grant
Geolog	gist	Mark Kirsch	Remarks:
Donth		val (feet)	
From	То	Thick- ness	Lithologic Description
0	5	5	Soil, silt, pale-brown
5	28	23	Shale, yellow-gray to dark yellow-orange, silty
28	39	11	Siltstone, yellow-gray to light-gray
39	58	19	Siltstone, light-gray to medium-dark-gray, clayey
58	73	15	Interbedded shale, light-to medium-dark-gray, and light- to medium-light-gray siltstone
73	105	32	Shale, medium-to medium-light-gray, silty toward bottom
105	115	10	Coal, bony
115	152	37	Interbedded siltstone, medium-light- to medium-gray, and shale, light-gray to medium-light-gray
152	176	24	Sandstone, medium-light-gray, silty in part
176	195	19	Shale, medium-light to medium-gray, silty
195	216	21	Coal
216	218	2	Carbonaceous shale
218	220	2	Coal
220	225	5	Shale, medium-light-gray
225	235	10	Siltstone, medium-light-gray, hard

Coa1

Coa1

Shale, medium-light-gray

Shale, medium-gray

Siltstone, medium-gray, sandy

Shale, light-gray; shale, carbonaceous


shale at top, bony coal from 256' to 257'

Shale, medium-gray to brown-black, silty in part with carbonaceous

Shale, light-gray, silty, with carbonaceous shale from 365' to 368'

Sandstone, medium-light-gray, very fine grained, well-cemented

Hole Designation	MB-25 `	Logged Depth	459	(ft)
Geophysical Log	Scales:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (	R) 10 ohms/in	Caliper (C) _2	2 in/in	
Remarks:				



Z Z	GEOPHYSICAL LOGS	DE	PTH
STRIP LOG	G D C R	FT	M
	Amiliani	350 -	-100
	400'	400 -	- 120
	GAMMENTON 450'  GAMMENTON 450'  TO 300 pt. 7555  TO 750 pt. 750 pt. 755 pt. 750 pt. 75	450 -	-130
	INCITE 1350 PS.  INCITE	500-	-150
	O CANNA 1995	550-	-16 <b>0</b> -170
	·	600 -	-180
	,		190
		650 -	200
		700 -	-210

Page 1 of 2

# U. S. Geological Survey

## Moorhead Broadus Drilling Project


Hole Designation MB-26	Elev.(ft) 3705	Total De	pth(ft)	615	
Location 750 fwl 1550 fsl	sec. 7	T5S	R	50	Ε.
County Powder River	State Montana	Quadrangle(7	.5') <u>Epsie</u>	NE	
Cored: Yes No x	Interval(s)				
Date started 11/9/79	Date completed	11/10/79	Driller	Arthur Clark	
Geologist Jim Boaz	Remarks	•			

From	То	Thick- ness	Lithologic Description
0	10	10	Soil, brown, sandy, clay, gray with yellow streaks, clinker pieces red
10	12	2	Shale, brown
12	53	41	Siltstone, gray-green, trace coal in cuttings
53	71	18	Sandstone, gray-green to gray, clayey
71	80	9	Shale, gray
80	104	24	Siltstone, brown-gray
104	131	27	Siltstone, brown-gray to dark-gray, sandy
131	134	3	Coal
134	161	27	Shale, green-gray to gray
161	164	3	Coal
164	173	9	Shale, gray-green
173	187	14	Sandstone, light-gray, silty
187	190	3	Shale, light-gray
190	231	41	Siltstone, light-gray to gray, clayey
231	234	3	Coal
234	268	34	Shale, gray, silty
268	271	3	Coal
271	274	3	Siltstone, gray
274	276	2	Shale, gray
276	347	71	Interbedded siltstone, gray, and shale, trace coal in cuttings
347	351	4	Coal
351	357	6	Shale, brown-gray, silty
357	361	4	Shale, gray
361	397	36	Siltstone, gray, interbedded with shale, gray
397	400	3	Coal
400	407	7	Shale, gray
407	438	31	Siltstone, gray, clayey

#### SECTION MB-26

Depth interval (feet)		val (feet)	
From	То	Thick- ness	Lithologic Description
438	441	3	Coal
441	471	30	Siltstone, brown-gray, with carbonaceous shale stringer
471	523	52	Shale, brown-gray
523	541	18	Coal
541	615	74	Sandstone, fine-grained, silty at top

Hole Designation	MB-26	Logged Depth	611	(ft)
Geophysical Log	Scales:			•
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (		Caliper (C)	2 in/in	
Remarks:				



∄gL	GEOPHYSICAL LOGS	DE	PTH
STRIP LOG	G C D	FT	M
		350 -	-100
		400 -	110
	1950	450 -	-130 -140
	500'-	500 -	-150
	SSO'	550-	-160
	Carrier Coo'.	600 -	-180
	Leck LN 255cp4  pairs Steps  R 26 Neps	650 -	·190 ·200
	- Dincha Mannil	700 -	-210

#### Moorhead Broadus Drilling Project

Hole Designation MB-27	Elev.(ft)_3435	Total	L Dept	h(ft)	370	
Location 700 fwl 1050 fnl	sec. 22	T. 4	s.	R •	49	Ε.
County Powder River	State Montana	Quadrang	Le(7.5	') <u>Epsie</u>		
Cored: Yes No x	Interval(s)	· · · · · · · · · · · · · · · · · · ·	·····			
Date started 11/11/79	Date completed 1	1/11/79	<del> </del>	Driller_	Arthur Clark	
Geologist Jim Boaz	Remarks:_					

From	То	Thick- ness	Lithologic Description
0	15	15	Soil, orange-gray, sand and clay mixture
15	26	11	Sandstone, gray, fine-grained
26	32	6	Coal
35	40	5	Shale, gray
40	49	9	Sandstone, gray, fine-grained, silty
49	52	3	Coal, bony
52	55	3	Sandstone, yellow-gray
55	57	2	Coal
57	70	13	Shale, dark- to light-gray
70	105	<b>3</b> 5	Sandstone, gray, fine-grained
105	110	5	Shale, gray, silty and sandy
110	145	35	Sandstone, gray
145	165	20	Shale, green-gray
165	170	5	Sandstone, fine-grained
170	180	10	Shale, gray
180	192	12	Sandstone, fine-grained
192	200	8	Coal
200	245	45	Shale, green-gray, hard sandstone at approximately 213'
245	<b>25</b> 5	10	Sandstone
255	265	10	Shale, green-gray
265	277	12	Sandstone
277	298	21	Shale, sandy
298	325	27	Coal, parting at 321'
325	335	10	Shale, dark-brown-gray
335	370	35	Shale, green-gray, sandy towards bottom

Hole Desig	nation	MB-27	Logged Depth	230 to 367	(ft)
Geophys	ical Log Sc.	ales:		•	
Gamm	a (G)	20 counts/sec/in	Density (D)	100 counts/in	
Resi	stivity (R)		Caliper (C)	2 in/in	
Remarks:	Equipment	failure; no log available	above 240 fe	et	
_					

GEOPHYSICAL LOGS	DEPTH.	
	FT M	
•	150 -	;
	200-60	
	70	
	250—	
	300-90	
	-100	
32,	350 -	•
LECTH 128 225cps.   400 - 120		
O GAMMA MOCPS	-	


P	ag	e	1	o	f	1
	_	_				

# Moorhead Broadus Drilling Project

Hole Designation MB-28	Elev.(ft) 3510	Total	1 Dept	h(ft)	495	
Location 150 fel 1850 fnl	sec33	T. 4	s.	R •	49	Ε.
County Powder River	State_Montana	Quadrang:	1e(7.5	') Epsie		
Cored: Yes No x	Interval(s)				· · · · · · · · · · · · · · · · · · ·	
Date started 11/5/79	Date completed 1	1/5/79		Driller	Arthur Clark	·
Geologist Jim Boaz	Remarks:					

From	То	Thick- ness	Lithologic Description
0	10	10	Soil, mixed clinker, sand, gravel
10	27	17	Shale, brown to dark-brown
27	29	2	Coal
29	45	16	Siltstone, green-gray, sandy
45	63	18	Shale, green-gray
63	100	37	Siltstone, green-gray, increasingly sandy towards bottom
100	111	11	Sandstone, fine-grained
111	113	2	Coal, bony
113	124	11	Siltstone, green-gray, clayey
124	190	66	Sandstone
190	194	4	Coal
194	209	15	Sandstone, fine-grained, silty
209	254	45	Siltstone, light-gray to green-gray, sandy in places, interbedded with light-gray shale
254	290	36	Interbedded sandstone, fine-grained, and siltstone, green-gray
290	293	3	Coal
293	362	69	Interbedded sandstone, fine-grained, and light-gray shale and siltstone, coal stringer at 325'
362	390	28	Sandstone, fine-grained, silty
390	400	10	Sandstone, fine-grained
400	427	27	Coal
427	495	68	Sandstone, fine-grained

Hole Designation	MB-28	Logged Depth	490	(ft)
Geophysical Log Sca	les:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R)	10 ohms/in	Caliper (C)	2 in/in	
Remarks:		-		



STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
STI L(	G DCR	FT	M
		350 -	-100
		400 -	110
	755	450 -	-130
	990	500 -	-140 -150
	Leufe 128 235c.ps.  RELIEF SSC.ps.  RELLE ISC.ps.	550-	- <b>160</b> -170
	O GARMA MORAL O 2° 4° CAUPER NING 38	600 -	-180
		650 -	-190 -200
		700 -	-210

## Moorhead Broadus Drilling Project

Elev.(ft) 3685	Total	Depth(ft)	615	
sec. 10	T. 5	S. R	49	Ε.
State Montana	Quadrangle	(7.5') Epsie		
Interval(s)				
Date completed	11/8/79	Driller	Arthur Clark	
Remarks:	Hole caved	, no geophysi	cal log	
	sec. 10  State Montana  Interval(s)  Date completed	sec. 10 T. 5  State Montana Quadrangle  Interval(s)  Date completed 11/8/79	sec. 10 T. 5 S. R.  State Montana Quadrangle(7.5') Epsie  Interval(s)  Date completed 11/8/79 Driller	sec. 10 T. 5 S. R. 49  State Montana Quadrangle(7.5') Epsie  Interval(s)

From	То	Thick- ness	Lithologic Description
0	5	5	Soil, orange, clinker pieces, yellow-gray, very fine grained, clayey sand
5	25	20	Sandstone, yellow-orange, very fine grained, silty
25	30	5	Coal, black, dull, medium-soft
30	115	85	Shale, medium- to dark-gray, sand at bottom, coaly at 45'
115	141	26	Sandstone, gray, fine-grained, silty, clay
141	145	4	Coal, black
145	167	22	Shale, medium-gray, silty
167	195	28	Sandstone, gray, fine-grained, silty, shale streak 175'
195	210	15	Shale, light-gray, silty
210	280	70	Sandstone, light- to dark-gray, fine-grained, shaly at top and bottom
280	308	28	Shale, light-gray, silty
308	320	12	Coal, black, shaly
320	370	50	Shale, light-gray, silty, interbedded with light-gray, fine-grained, silty, sandstone
370	375	5	Coal, black
375	478	103	Shale, dark-gray, silty
478	530	52	Sandstone, gray, very fine grained, silty, shaly at bottom
530	575	45	Shale, gray
575	600	25	Coal, black, hard
600	615	15	Shale, brown-gray, medium-hard, silty

## Moorhead Broadus Drilling Project

Hole Designation MB-30	Elev.(ft) 3410	Total Depth	(ft)	389	
Location 1300 fel 1950 fnl	sec. 22	T. 5 S.	R	49	Ε.
County Powder River	State Montana	Quadrangle(7'5)	Epsie		
Cored: Yes x No	Interval(s) 293'	:o 326.5′			
Date started 11/6/79	Date completed	1/6/79	Driller_	Arthur Clark	
Geologist Jim Boaz	Remarks:	Core descriptio	n by Geor	ge A. Correia	<b></b>


Depth	interval (	reet)

From	То	Thick- ness	Lithologic Description
0	13	13	Soil, dark brown, clay, silt, sand, organics
13	18	5	Sand, yellow-orange, fine
18	21	3	Coal, hard, shiny
21	52	31	Siltstone, light-gray to gray, and light-gray shale
52	55	3	Coal
55	103	48	Siltstone, green-gray, shaley in places, with coal stringers at 61' and 79'
103	107	4	Coal Coal
107	140	33	Shale, green-gray to light-gray, clayey
140	177	37	Siltstone, light-gray, sandy, clayey at 150'
177	203	26	Siltstone, light-gray, with coal stringer, clayey
203	242	39	Sandstone, fine-grained
242	261	19	Siltstone, green-gray, and sand, fine-grained
261	267	6	Sandstone, fine-grained
267	277	10	Shale, green-gray
277	291	14	Sandstone, fine-grained, coaly at bottom
291	293	2	Shale, brown-gray CORE DESCRIPTION
293.0	294.0	1	Siltstone, medium gray, clayey, coal streaks (woody) at 293.2, 293.4, 293.9, and 294.0, soft sediment deformation prominent, pyrite balls at 293.8
294.0	295.8	1.8	Claystone, medium-dark-gray, carbonaceous, coal streak 294.5 to 294.7, sharp basal contact with underlying coal, .5 foot loss
295.8	304.0	8.2	Coal, black, dull with shiny bands, fractured 295.8 to 298.1, heavily desseminated pyrite in fractures, clay streak 297.1 to 297.3, conchoidal fracturing below 298.1, disseminated pyrite on fractures 300.4 to 302.2 feet
304.0	313.9	9.9	Coal, black, hard, dull with shiny streaks, conchoidal fracturing, sharp basal contact

#### SECTION MB-30

Depth interval (feet)		al (feet)	
From	То	Thick- ness	Lithologic Description
313.9	315.3	1.4	Claystone, medium-gray, carbonaceous and shaly top .1', (woody with rootlets)
315.3	322.7	7.4	Coal, black, dull with shiny streaks, cleat fracturing throughout, conchoidal fracturing, clay streak at 321.4 and 322.0, resin on fractures at 322.4
322.7	323.3	.6	Claystone, medium-gray, carbonaceous and shaly from 322.7 to 322.8, rootlets below with woody streak at 323.0
323.3	326.5	3.2	Siltstone, medium-light-gray, clayey, rootlets from 323.5 to 324.1 END OF CORE DESCRIPTION
326.5 376 378	376 378 389	49.5 2 11	Shale, green-gray Coal Siltstone, green-gray

Hole Designation	MB-30	Logged Depth	389	(ft)
Geophysical Log Sca	ales:			
Gamma (G)	20 counts/sec/in	Density (D) _	100 counts/sec/in	
Resistivity (R)	10 ohms/in	Caliper (C) _	2 in/in	
Remarks:	· · · · · · · · · · · · · · · · · · ·			




				_
STRIP LOG	GEOPHYSICAL LOGS	DE	PTH	
STI	G C D R	FT	М	
		350 -	-100 -110	
	Lecit Lie 25cps.	400 -	- 120	
	SOOC PS DENSITY O	450 -	-130	
		500-	-140 -150	
		550-	-160	
			-170 -180	
	·	600 -	-190	-
		650 -	-200	
		700 -	-210	_

## Moorhead Broadus Drilling Project

Hole Designation MB-31	Elev.(ft) 3450	Tota	1 Dept	h(ft)	395	
Location 600 fnl 2100 fel	sec. 27	T5	S.	R	49	Ε.
County Powder River	State Montana	Quadrang	1e(7.5	') Yarge	r Butte	<del></del>
Cored: Yes No x	Interval(s)					<del></del>
Date started 11/7/79	Date completed	11/7/79		Drille	r Steve Grant	
Geologist Jim Boaz	Remarks:					

From	То	Thick- ness	Lithologic Description
0	5	5	Soil, sand, yellow-gray, fine, silty, clayey
5	15	10	Shale, brown-gray, clayey
15	20	5	Shale, brown-gray, and gravel, subrounded to rounded, with sandstone and mudstone
20	32	12	Siltstone, dark-yellow to gray, coaly
32	35	3	Coal, very soft
35	58	23	Siltstone, gray, and light-gray to gray shale
58	62	4	Coal, soft
62	120	58	Shale, gray, silty, sandy in places, with coal stringer at 67' and coal from 92'-94' and 112'-114'
120	124	4	Coal
124	158	34	Shale, green-gray, silty toward bottom, coal stringer at 156'
158	165	7	Sandstone, gray fine-grained
165	171	6	Shale, gray
171	187	16	Sandstone, gray, fine-grained
187	210	23	Shale, dark-gray, silty
210	301	91	Sandstone, gray, fine, shaly in places
301	307	6	Shale, gray
307	317	10	Siltstone, gray
317	326	9	Shale, gray, coaly
326	334	8	Sandstone, gray, fine-grained
334	338	4	Shale, gray
338	355	17	Coal
355	368	13	Siltstone, green-gray
368	380	12	Coal
380	395	15	Sandstone, fine-grained

Hole Designation	MB-31	Logged Depth	376	(ft)
Geophysical Log S	cales:		_	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R	) 100 ohms/in	Caliper (C)	2 in/in	
Remarks:				-



STRIP	COMMA MOSS.  CALIFER ORTS CALIFORN  CRESC MAN COMMA CO	350 -	-100 -110 -120
_	Seeche Demity 0  GANNA MARK  CALIPER  CALIPER  GREENE DEMITY  GREENE DEMITY	350 -	-110
	LOUITE 127 23SEPS  MEIASE SEEPS  ME 24 18c.p.S.  SOUCHS DEPUTY 0  GAMMA MOUSE  CALIFORN ORSE 400 change	400 -	
	CALIPER ORES LES CAME		-130
	* Tamest	450 -	-140
		500-	-150
	•	550-	-1 <b>60</b> -170
	,	600 -	180
			190
		650 -	200
		700 -	-210

#### Moorhead Broadus Drilling Project

Hole 1	Designa	ation M	32 Elev.(ft) 3425 Total Depth(ft) 395	
Locat	ion_3	50 fn1	300 fwl sec. 1 T. 6 S. R. 49	E
Count	y Powe	ler Rive	State Montana Quadrangle(7.5) Yarger Butte	
Cored	:	Yes	No_x Interval(s)	
Date	starte	<u>11/8/</u>	Date completed 11/9/79 Driller Steve Gra	ant
Geolo:	gist	Jim Boaz	Remarks: Natural Gamma logged through stee	1.
Depth	inter	val (fee	_	
From	То	Thick- ness	Lithologic Description	
0	5	5	Soil, sand, clinker, yellow to orange	
5	10	5	Sandstone, yellow-gray, fine, silty, and gray shale	
10	38	28	Sandstone, yellow-gray to orange-gray, fine-grained, silty	
38	55	17	Sandstone, gray, fine-grained	
55	85	30	Sandstone, orange-gray, fine-grained, with coaly stringers	
85	87	2	Coal stringer	
87	106	19	Shale, gray	
106	111	5	Coal Coal	
111	155	44	Interbedded sandstone, fine-grained, and shale or siltstone, gray to gray, with bony coal at 151' to 153'	light-
155	160	5	Coal Coal	
160	175	15	Shale, light-gray to light-green-gray	
175	234	59	Shale, green-gray to gray, silty in places, with coal stringe 218'	r at
234	283	49	Sandstone, fine, silty or shaly in places	
283	310	27	Interbedded siltstone, gray to light gray, and sandstone, fingrained	e-
310	332	22	Sandstone, dark-green-gray, fine-grained	
332	333	1	Coal stringer	
333	338	5	Interbedded sandstone, fine-grained, and shale, dark-gray	
200	0 = 0		, , , , , , , , , , , , , , , , , , , ,	


Coa1

Shale, dark-green-gray

Sandstone, fine-grained

Pag	e	1	of	2	
_					_

Hole Designation	MB-32	Logged Depth	395	(ft)
Geophysical Log S	Scales:		•	
Gamma (G)	50 counts/sec/in	Density (D) _	10 counts/sec/in	
Resistivity (I	8)	Caliper(C)		·
Remarks:				
1				



MB	-3	2	

	TID-32		
STRIP	GEOPHYSICAL LOGS	DE	PTH
ST	G D	FT	М
		350 -	-100 -110
		400 -	- 120
		450 -	-130 -140
		500-	-150
		550 -	-160
	·	600 -	-180
			-190
	-	650 -	-200
		700 -	-210

Page 1 of 2	2	
-------------	---	--


				Moorhea	ad Broadu	s Drilli	ng Pi	roject	:		
Hole D	esigna	ition MB-	-33	Elev.(	ft) 3625		Tota	1 Dep	th(ft)	635	
Locati	on75	50 fw1 11	100 fs1	· · · · · · · · · · · · · · · · · · ·	sec. 19	т.	4	s.	R	49	Ε.
County	Powe	ier River		State Mon	itana	Qua	drang	le(7.	5') Epsie		
Cored:		Yes	No_x	Interv	val(s)	<del> </del>					<del></del>
Date s	tarte	10/30/7	79	Date	complete	d 10/30	/79		Driller_	Arthur Cl	ark
Geolog	ist	Jim Boaz			Remar	ks:					
					-						
											**************************************
Depth	interv	val (feet)	)					<del></del>			
From	To	Thick-	-								
		ness			L	ithologi	c Des	cript	ion		
0	21	21	Sand,	fine- to	medium-g	rained,	silic	a, mi	caceous		
21	27	6	Shale	, light- t	o dark-g	ray					
27	29	2		tone, ligh		•					
29	46	17		, medium-g							
46	50	4		dull blac	. •						
50	62	12		, dark-gra							
62	76	14		tone, medi	•						
76	87	11		, medium-g							
87	89	2	Coal	, 8	,,						

0	21	21	Sand, fine- to medium-grained, silica, micaceous
21	27	6	Shale, light- to dark-gray
27	29	2	Sandstone, light-gray
29	46	17	Shale, medium-gray
46	50	4	Coal, dull black, hard
50	62	12	Shale, dark-gray
62	76	14	Siltstone, medium-gray
76	87	11	Shale, medium-gray
87	89	2	Coal
89	112	23	Siltstone, medium-gray
112	156	44	Shale, medium-gray, silty
156	159	3	Claystone, light-green-gray
159	180	21	Siltstone medium-gray
180	183	3	Shale, medium-gray
183	190	7	Siltstone, dark-gray-green
190	195	5	Shale, medium-gray
195	215	20	Sandstone, dark-gray-green
215	256	41	Shale, dark-gray-green, and dark-gray-green siltstone
256	271	15	Coal, dull black, with siltstone(?) parting from 262' to 264'
271	282	11	Shale, green-gray
282	<b>29</b> 0	8	Siltstone, light-green-gray, sandy
290	319	29	Shale, light-green-gray to dark-brown-gray, clayey; coal stringers
319	336	17	Siltstone, green-gray to gray-brown, with coal stringers
336	367	31	Shale, gray-brown, silty
367	373	6	Coal and siltstone(?) parting at 370'
373	385	12	Sandstone, brown, silty
385	428	43	Siltstone, gray, clayey in places
428	514	86	Sandstone, gray, silty towards bottom, washout 483' to 485'

#### SECTION MB-33

Depth interval (feet)			
From	То	Thick- ness	Lithologic Description
514	518	4	Coal
518	562	44	Shale, dark-gray, clayey
562	580	18	Siltstone, light-gray, clayey at bottom
580	614	34	Coal, with siltstone(?) parting from 604' to 607'
614	635	21	Siltstone, dark-gray

Hole Designation	MB-33	Logged Depth	626	(ft)
Geophysical Log Sc.	ales:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R)	10 ohms/in	Caliper (C)	2 in/in	
Remarks:				



MR	-3	3
пD	-0	Э.

SIP OG	GEOPHY	SICAL L	ogs		DE:	PTH
STRIE LOG	G	D	C I	R	FT	М
-		350(-)			350 -	-100 -110
		400			400 -	- 120
					<b>450</b> -	-130 -140
		5ca ±			500 -	-150
					550 -	-160
		\( \sigma \)		5	600 -	-180
	P. 204-pt-	-(26 km/r) 	COUPER		650 -	-190
					700 -	-210


Page	1	of	1

# Moorhead Broadus Drilling Project

Hole Designation MB-34	Elev.(ft) 3560	Total Dept	h(ft)	515	
Location 100 fwl 2600 fnl	sec4	T. 6 S.	R	49	E.
County Powder River	State_Montana	Quadrangle(7.5	') Yarger	Butte	
Cored: YesNo_x	Interval(s)				
Date started 11/9/79	Date completed 11	/10/79	Driller_	Steve Grant	
Geologist Jim Boaz	Remarks:				<del></del>

From	То	Thick- ness	Lithologic Description
0	27	27	Soil, brown, red clinker pieces
27	58	31	Siltstone, dark-gray, clayey near top
58	84	26	Shale, dark-brown-gray
84	88	4	Coal
88	99	11	Shale, dark-gray, silty
99	113	14	Siltstone, gray
113	132	19	Shale, gray- to dark-gray, coal stringer at 113'
132	133	1	Coal stringer
133	190	57	Shale, gray, silty
190	235	45	Siltstone, gray- to dark-gray, with sandstone lenses, coal stringer
			at top
235	243	8	Coal
243	255	12	Siltstone, dark-gray, with some coal near top, clayey at bottom
255	311	56	Siltstone, brown-gray to dark-gray, sandy in places
311	334	23	Sandstone, fine-grained, silty
334	343	9	Coal, shale parting from 335' to 337'
343	353	10	Shale, dark-gray to gray
353	358	5	Coal
358	390	32	Siltstone, gray, clayey in places
390	396	6	Coal, with shale parting at 392'
396	447	51	Siltstone, gray, sandy, clayey in places
447	459	12	Siltstone, gray, sandy, with trace coal in cuttings
459	515	56	Sandstone, dark-green-gray to dark brown-gray, fine-grained

Hole Designation	MB-34	Logged Depth	512	(f t
Geophysical Log	Scales:			
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in .	
Resistivity	(R) 10 ohms/in	Caliper (C)	2 in/in	
Remarks:				



STRIP LOG	GEOPHYSICAL LOGS	DE	PTH
ST	G C D R	FI	M
	30	350 -	-100
		400 -	-120
	150	450 -	-140
	Siente Saper SIZ Berliff Produce	500-	·150 ·160
			170
		600 -	190
		650 -	200
		700 -	210


# Moorhead Broadus Drilling Project

Hole Designation MB-35	Elev.(ft) 3725	Tota	al Dept	h(ft)	299	
Location 1200 fn1 1900 fw1	sec. 25	T5	s.	R	48	Ε.
County Powder River	State Montana	Quadrang	gle(7.5	o') Yarger	Butte	
Cored: Yes No x	Interval(s)	<del></del>				<del></del>
Date started 11/12/79	Date completed_	11/12/79		Driller	Steve Grant	
Geologist Jim Boaz	Remarks	:				

From	То	Thick- ness	Lithologic Description
0	31	31	Soil, brown, gravel to clay
31	56	25	Shale, gray to dark-brown-gray, sandy, clayey in places
56	71	15	Siltstone, gray
71	88	17	Shale, gray
88	110	22	Coal
110	134	24	Shale, gray to dark-gray, silty in places, with sandstone stringer from 127' to 128'
134	167	33	Siltstone, gray, sandy toward bottom, clayey in places
167	169	2	Coal
169	187	18	Siltstone, gray, clayey at bottom
187	189	2	Coal
189	215	26	Siltstone, gray, clayey at top, with very hard sandstone stringer, orange-gray, very fine grained
215	221	6	Sandstone, gray
221	227	6	Siltstone, gray
227	231	4	Coa1
231	243	12	Siltstone, gray to dark-gray
243	261	18	Shale, gray, silty
261	299	38	Shale, gray, clayey, with sandstone stringer at 264'

Pag	e 1	0	f	1
_	_		_	

Hole Designation	MB-35	Logged Depth	299	(ft)
Geophysical Log S	cales:		•	
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R	1) 10 ohms/in	Caliper (C)	2 in/in	
Remarks:				




Page 1	of	1
--------	----	---

# Moorhead Broadus Drilling Project

Hole Designation MB-36	Elev.(ft)_3435	Total Der	oth(ft)	555	
Location 200 fel 1150 fsl	sec. 22	T. 4 S.	. R.	49	Ε.
County Powder River	State Montana	Quadrangle(7,	.5') Epsie		
Cored: Yes No x	Interval(s)	والمعارف المراوع والمعارف والمعارف والمعارف والمعارف والمعارف المعارف المعارف المعارف المعارفة والمعارف			
Date started 11/13/79	Date completed_	11/13/79	Driller_	Arthur Clark	
Geologist Jim Boaz	Remarks				
	<del></del>	<del></del>			
Depth interval (feet)					
From To Thick-					

From	То	Thick- ness	Lithologic Description		
0	30	30	Sand, orange-gray to yellow-gray, fine-grained, silty, clayey at bottom		
30	32	2	Coal		
32	42	10	Shale, dark-brown-gray to very dark gray		
42	67	25	Siltstone, gray		
67	71	4	Coal		
71	103	32	Siltstone, gray, clayey in places		
103	105	2	Coal		
105	136	31	Shale, light-green-gray to gray, silty toward bottom		
136	161	25	Shale, gray		
161	195	34	Siltstone, gray, sandy		
195	205	20	Sandstone, gray		
205	220	15	Siltstone, gray, clayey in places		
220	225	5	Coal		
225	252	27	Siltstone, green-gray, sandy		
252	275	23	Shale, green-gray		
275	315	40	Shale, green-gray, silty		
315	338	23	Coal Coal		
338	378	40	Siltstone, gray-green, less clay at bottom		
378	475	97	Sandstone, fine-grained		
475	495	20	Shale		
495	519	24	Sandstone, fine-grained		
519	555	36	Sandstone, gray, fine-grained, and gray shale		

Hole Designation	MB-36	Logged Depth	554	(f
Geophysical Log Sc	ales:			
Gamma (G)	20 counts/sec/in	Density (D)	100 counts/sec/in	
Resistivity (R)	10 ohms/in	Caliper (C)	2 in/in	
Remarks:				· ·



_	MB-36			
STRIP LOG	GEOPHYSICAL LOGS	DE	PTH	]
S	G C D R	FI	M	
	339	350 -	-100	
	400	400 -	- 120	
	450	450 -	-130 -140	
	500'		150	
	Carrier SSO' Paleops Carrier SSO' Paleops 158 perior 158 arms	550-	160 170	
	Local L28 2556.p.s.  pa 1/133 856.ps.  pl 24 Naps.	600 -	180	
	Soocpt Directly O	650 -	200	
			210	-