

DEPARTMENT OF THE INTERIOR  
UNITED STATES GEOLOGICAL SURVEY

Distributions of total lead in samples of  
nonmagnetic heavy-mineral concentrate and of total and  
partially extractable lead in samples of stream sediment from  
the Wallace 1° x 2° quadrangle, Montana and Idaho

By

D. L. Leach, D. M. Hopkins, J. A. Domenico, and H. E. Dawson

Open-File Report 83-304

This report has not been reviewed for conformity with U.S. Geological Survey editorial standards. Any use of trade names is for descriptive purposes only and does not imply endorsement by the U.S.G.S.

## INTRODUCTION

These maps are part of a folio of maps of the Wallace 1° x 2° quadrangle, Montana and Idaho, prepared under the Conterminous United States Mineral Assessment Program (CUSMAP). This report presents the distributions of total and partially extractable lead in the minus-80-mesh (<180  $\mu\text{m}$ ) fraction of stream sediments and in nonmagnetic heavy-mineral concentrates from stream sediments collected in the Wallace 1° x 2° quadrangle, Montana and Idaho. The Flathead Indian Reservation, in the eastern part of the quadrangle, was not included in this study. No data interpretations are presented in the report. The purpose of this report is to present the data at the map scale (1:250,000) used for displaying other Wallace CUSMAP information to aid users of the data in making their own interpretations. A complete tabulation of the data for each sample collected in the Wallace quadrangle has been provided by Leach and others (1982); this report also presents a detailed discussion of the sampling and analytical methods, and includes statistical summaries of the data. A tabulation of the data is also available on computer tape from the National Technical Information Service (McDanaI and others, 1982). The distribution of other selected elements for the Wallace quadrangle are available as 1:250,000 maps (Leach and others, 1983a,b,c,d,e).

## METHODS

Samples were collected from 1229 sites on small-order stream drainages at a minimum density of one site per cell where the cell is an area of 4 square miles (10.4  $\text{km}^2$ ). Some cells may not contain a sample site because of various factors including lack of a small-order stream drainage or inaccessibility. Some cells contain more than one sample site because of resampling for various reasons. Samples were not collected from the most active part of the Coeur d'Alene mining district because of probable contamination.

A sampling site consists of a 10-m stretch of the active stream channel. At least five grab samples of stream sediment were collected at each site using a polyethylene or aluminum scoop. The grab samples were composited and air dried. The composited sample was sieved using a stainless steel, 80-mesh (180  $\mu\text{m}$  opening) screen. The material which passed through the 80-mesh screen was analyzed.

A heavy-mineral-concentrate sample was collected at most sites using a generic gold pan. Heavy-mineral concentrates were not collected from some sites because of the paucity of heavy minerals in some stream sediments. Commonly, 3 to 4 kg of composited sediment would yield the desired 30 to 60 gm of concentrate. At the laboratory, the sample was air dried, and the highly magnetic material was removed by a magnet. Any light-weight material remaining in the concentrate was separated by allowing the heavier fraction to settle through bromoform (specific gravity, 2.82). The resulting heavy-mineral fraction was separated into a nonmagnetic and magnetic fraction using a Frantz Isodynamic Separator at a setting of 0.6 ampere, with 15° forward and 15° side settings. The nonmagnetic fraction was pulverized in an agate mortar before analysis.

Each nonmagnetic heavy-mineral-concentrate sample was analyzed semi-quantitatively for lead and 30 other elements using an optical emission spectrograph according to the method outlined by Grimes and Marranzino (1968). The semiquantitative spectrographic values are reported as the approximate geometric midpoints: 1.0, 0.7, 0.5, 0.3, 0.2, 0.15 (or appropriate powers of ten) of ranges whose respective boundaries are: 1.2, 0.83, 0.56, 0.38, 0.26, 0.18, 0.12 (or appropriate multiples). The lower limit of determination for lead is 20 ppm.

Each stream sediment was analyzed by atomic absorption spectrometry for total and partially-extractable concentrations of lead. The partially extractable method used a 3.6N hydrochloric-acid solution containing 20 percent ascorbic acid and 10 percent potassium iodide in contact with the sample for 30 minutes at room temperature. The partially solubilized metals are selectively extracted into an organic phase composed of Aliquat-336 (tricaprylylmethylammonium chloride) and methyl isobutyl ketone. The concentration of lead is determined from the organic phase by atomic absorption spectroscopy. This partially extraction technique is similar to the method described by Viets and others (1979) and dissolves the loosely-bound metals associated with clays and with surface coatings of Fe-Mn oxides, possibly associated with oxidized sulfide occurrences. The extraction also dissolves the majority of the secondary minerals, such as sulfates, carbonates, and oxides, that are stable under oxidizing conditions. The extraction does not dissolve significant amounts of most sulfide minerals. Total metal concentrations are determined by digestion of the sample in a solution of hydrofluoric and nitric acids, extraction into the Aliquat-336/methyl isobutyl ketone phase, and analysis by atomic absorption spectrometry. The lower limit of determination for lead attained by the partially extractable and total metal methods are 1 ppm.

## RESULTS

The distributions of lead in the nonmagnetic heavy-mineral and total and partially extractable lead in stream sediments are shown in plates 1, 2, and 3, respectively. Because the data consist of a number of populations derived from a variety of rock types, we arbitrarily chose the concentration ranges plotted to approximate the top 1, 99-95, 95-75, 75-50, 50-25, and lower 25 percentiles. Histograms of the data using spectrographic reporting intervals as class widths are shown for each sample type on the respective plots, plates 1, 2, and 3. The detection ratios, geometric means, and geometric deviations for the data are given in Table 1.

The lead distributions shown in figures 1, 2, and 3 were contoured using the STPMAP program in the U.S. Geological Survey's STATPAC computer program (VanTrump and Miesch, 1977). These plots are useful in evaluating general regional trends in the data. These contour maps were generated by contouring weighted average concentrations computed at the corners of a square grid. This grid consisted of 660 squares, where each square is an area of 10.4 square miles (26.4 km<sup>2</sup>). Therefore, each square will average 2.6 of the sample cells. The computed concentrations at the corners of the squares are averages of concentration occurring within a given radius from the corner point and weighted according to the distance from the corner point. The lowest contour value shown is generally at or slightly above the geometric mean of the data.

TABLE 1.

	Detection <sup>1</sup> ratio	Geometric <sup>2</sup> mean (ppm)	Geometric <sup>2</sup> deviation (ppm)
Heavy-mineral concentrates	0.92	94	4.0
Total metal in stream sediments	1.00	20	2.2
Partially extractable in stream sediments	.99	13	2.6

<sup>1</sup>The number of uncensored data divided by total number of samples.

<sup>2</sup>Cohen's (1959) method was used for calculating the maximum-likelihood estimates for normal and singly censored distributions.

## REFERENCES

- Cohen, A. C., Jr., 1959, Simplified estimators for the normal distribution when samples are singly censored or truncated: *Technometrics*, v. 1, no. 3., p. 217-237.
- Grimes, D. J., and Marranzino, A. P., 1968, Direct-current arc and alternating-current spark emission spectrographic field methods for semiquantitative analyses of geologic materials: U.S. Geological Survey Circular 591, 6 p.
- Harrison, J. E., Griggs, A. B., and Wells, J. D., 1981, Generalized geologic map of the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Miscellaneous Field Studies Map MF-1354-A.
- Leach, D. L., Domenico, J. A., Hopkins, D. M., Dawson, H. F., and Goldfarb, R. J., 1982, Data report and statistical summary for samples of stream sediment and nonmagnetic heavy-mineral concentrates from the Wallace 1° x 2° quadrangle, Idaho and Montana: U.S. Geological Survey Open-File Report 82-494.
- Leach, D. L., Hopkins, D. M., Domenico, J. A., and Dawson, H. E., 1983a, Distributions of total copper in samples of nonmagnetic heavy-mineral concentrate and of total and partially-extractable copper in samples of stream sediment from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Open-File Report 83-307.
- 1983b, Distributions of total antimony in samples of nonmagnetic heavy-mineral concentrate and of total and partially-extractable antimony in samples of stream sediment from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Open-File Report 83-306.
- Leach, D. L., Hopkins, D. M., Domenico, J. A., and Goldfarb, R. J., 1983c, Distributions of total silver in samples of nonmagnetic heavy-mineral concentrate and of total and partially-extractable silver in samples of stream sediment from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Open-File Report 83-309.

- \_\_\_\_\_ 1983d, Distributions of total zinc in samples of nonmagnetic heavy-mineral concentrate and of total and partially-extractable zinc in samples of stream sediment from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Open-File Report 83-308.
- Leach, D. L., Hopkins, D. M., Domenico, J. A., and Dawson, H. E., 1983e, Distributions of cadmium in samples of nonmagnetic heavy-mineral concentrate and in samples of stream sediment from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Open-File Report 83-305.
- McDanal, S. K., Hopkins, D. L., and Domenico, J. A., 1982, Spectrographic and chemical analysis of stream sediments and concentrate sample from the Wallace 1° x 2° quadrangle, Montana and Idaho: U.S. Geological Survey Report GS-82-013; available only from U.S. Department of Commerce National Technical Information Service, Springfield, VA, 22151.
- VanTrump, G., and Miesch, A. T., 1977, The U.S. Geological Survey RASS-STATPAC system for management and statistical reduction of geochemical data: Computers and Geosciences, v. 3, p. 475-488.
- Viets, J. G., Clark, J. R., and Campbell, W. L., 1979, A rapid partial leach and organic separation for the determination of Ag, Bi, Cd, Cu, Pb, Sb, and Zn by atomic absorption spectrometry: Abs. in Exploration Geochemistry in the Basin and Range Province, Tucson, Arizona, April 9 and 10, 1979: Program and Abstracts, p. 32.

WALLACE 1° x 2° QUADRANGLE





Figure 1.--Contour map of Lead (Pb) in Non-magnetic Heavy Mineral Concentrates  
 Concentrations (ppm) plotted: 100, 1000, 3000, 5000, 7000  
 [Concentrations plotted are weighted average; see text]



WALLACE 1° X 2° QUADRANGLE





Figure 2.--Contour Map of Total Lead (Pb) in Stream Sediments  
Concentrations (ppm) plotted: 23, 40, 56, 100, 200  
[Concentrations plotted are weighted averages; see text]



WALLACE 1° X 2° QUADRANGLE




Figure 3.--Contour Map of Partially Extractable Lead (Pb) in Stream Sediments  
 [Concentrations (ppm) plotted: 13, 25, 56, 125, 175  
 [Concentrations plotted are weighted averages; see text]

