

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

MRDS - REV

A Mineral Occurrence/Deposit Data Base for Microcomputer

by

Paul G. Schruben

Open file report 86-34

"This report is preliminary and has not been reviewed for conformity with U.S. Geological Survey editorial standards. Any use of trade names is for descriptive purposes only and does not imply endorsement by the USGS."

1985

## Table of contents

I.	Abstract .....	1
II.	Introduction .....	2
	A) Rationale for developing MRDS-REV	
	B) Software components developed in-house	
III.	Initial setup procedures .....	4
	A) Hardware and software requirements	
	B) Installation instructions for fixed disk machines	
	C) Installation instructions for dual floppy drive machines	
IV.	Entering and editing deposit records .....	8
V.	The MRDS-REV retrieval program .....	10
	A) Rationale for developing the retrieval program	
	B) Retrieval program description and operating instructions	
VI.	Running retrievals at command level .....	12
VII.	Transferring records between MRDS-GIPSY and MRDS-REV	15
VIII.	Creating and moving files .....	16
	A) Copying files to floppy disk	
	B) Copying files on dual floppy machines	
	C) Copying files between accounts with different names	
IX.	Programming in Revelation BASIC .....	19
X.	Reference .....	21

## Appendices

A.	Retrieval program command file structure .....	22
B.	MRDS-REV field name dictionary .....	23
C.	Program listings	
	1) Retrieval program .....	26
	2) GIPSY => Revelation program .....	44
	3) Revelation => GIPSY program .....	48
D.	MRDS-REV menus and data entry screens .....	51

## I. Abstract

A data base management system, MRDS-REV, was developed for micro-computers, using commercially available software as well as in-house programs. The system simulates the Survey's mainframe-based mineral occurrence/deposit file known as the Mineral Resources Data System (MRDS). Each MRDS-REV record contains 147 fixed and variable length alpha-numeric fields with location and geologic information on mineral deposits. A menu-driven retrieval and printing program was developed for the system as well as programs for exchanging information between the mainframe MRDS file and microcomputer files.

## II. Introduction

This report describes MRDS-REV, a mineral deposit data base management system developed for microcomputer. The system simulates the Mineral Resources Data System (MRDS), currently in use on the Amdahl mainframe computer in Reston, Virginia. This report shows MRDS-REV's capabilities to enter, edit, retrieve and print deposit data. The features and capabilities of the commercial software (COSMOS, 1985) documented in this report relate to a specialized application and do not constitute an evaluation or review of the product.

### A) Rationale for developing MRDS-REV

MRDS-REV was developed for the following reasons:

1) Data entry is particularly suited to the microcomputer environment. Menus and input screens appear almost instantly, making interactive updating preferable to batch updating. In contrast, interactive updating on mainframe computers through a modem link is slow and cumbersome. For remote mainframe users, batch input remains preferable.

2) An increasing percentage of MRDS participants prefer to manipulate subsets of the deposit file on their own microcomputers instead of the mainframe. There are many reasons for this:

- a) to avoid mainframe on-line charges;
- b) mainframe phone connections can be unreliable or nonexistent, especially in foreign countries;
- c) they are familiar with their machine and wish to avoid learning a new system and
- d) they wish to exert more control over their data and operating environment.

3) Microcomputer software and hardware are approaching the capabilities of some mainframe computers. The Revelation data base management system used in MRDS-REV is one of the first on microcomputers allowing variable length fields and records up to 65,000 bytes each. Indexed data-base managers for microcomputers are becoming available at the time this report is prepared. These programs speed retrieval times because an indexed file is searched much more rapidly than a sequentially searched file. Indexing and other developments make the use of larger files on microcomputers more practical.

### B) Software components developed in-house

The non-commercial components of the MRDS-REV system are:

- 1) a fully prompted retrieval and printing program developed by the author;
- 2) the dictionary, data validation files, report generator files, data input screens and menus developed by the author to accept MRDS data and
- 3) programs for translating data to and from mainframe MRDS, which is in General Information Processing System (GIPSY) format.

### III. Initial setup procedures

#### A) Hardware and software requirements

MRDS-REV is a large system by microcomputer standards. The Revelation programs occupy 350K bytes of disk space, whereas an IBM PC floppy disk only holds 320K bytes with DOS on it. The MRDS programs, dictionaries and screens occupy an additional 200K bytes of disk space. Consequently, a working MRDS-REV system starts with an overhead of 550K bytes. An IBM-XT/AT fixed disk machine or equivalent is recommended to avoid file storage problems.

The hardware requirements follow:

- 1) IBM-PC/XT/AT or compatible computer capable of running Microsoft MS-DOS;
- 2) 320K bytes RAM (640K recommended);
- 3) Two 360K byte disk drives. A fixed disk of higher capacity is strongly recommended and
- 4) Math co-processor 8087 chip recommended but not required.

The software requirements follow:

- 1) Microsoft MS-DOS or PC-DOS, version 1.x, 2.x, 3.x or higher.
- 2) Revelation by COSMOS, Inc. Distributed by:  
ELF Software Distributors, Inc.  
PO Box 1237  
Longview, WA 98632  
phone: 1-800-422-2511

#### B) Installation instructions for IBM XT/AT fixed disk machines

Insert the system disk for MS- or PC-DOS and reboot by pressing the Ctrl, Alt and Del keys simultaneously. IBM XT/AT's boot from the fixed disk by powering up with the floppy drive door open. IBM XT/AT machines usually observe the following disk drive designation convention:

A = floppy disk drive  
C = fixed disk drive

If there is uncertainty about the designation for your machine, find out which drive letter designation applies to the fixed disk and floppy disk drives.

Type: DIR A:  
Type: DIR B:  
Type: DIR C:  
Type: DIR D:  
Type: DIR E:

Type: DIR F:

and observe which drive lights up. Then

Type: C: On IBM XT machines, "C" is the main drive.

Type: DIR Displays the number of remaining bytes on this drive. If it is less than 700,000 bytes, delete excess files or change to another drive by typing "A:" or "B:", etc.

Create a sub-directory on the fixed disk for MRDS-REV. This avoids cluttering up the root directory with the large number of files which MRDS-REV generates. The resulting directory tree is displayed in Figure 1.




Figure 1. Directory tree on fixed disk drive

To set up the directory:

Type: MD MRDS This sets up a directory called MRDS under the root directory.

Type: CD MRDS This makes MRDS the current directory

Place the Revelation Program disk (not the Utilities disk) in the floppy drive. Then

Type: COPY A:\*.\*/v If the floppy drive is not the "A" drive, then substitute the appropriate letter.

Place the MRDS-REV disk in the floppy drive.

Press: Capslock key

Type: REV SYSPROG

Prompt: REVELATION LOGON MENU

Type: <cr> This selects the ATTACH option

Prompt: ENTER DRIVE TO ATTACH OR TYPE 'END'?

Type: A

Type: F9 Function key 9 on left-hand side.

Prompt: :

Type: RUN SETUP CM

Prompt: ENTER DRIVE LETTER DESIGNATION FOR FLOPPY DRIVE.  
DEFAULT = A

```

Type:      <cr>          Type the drive letter for the MRDS-REV
                        floppy disk.
Prompt:    REVELATION LOGON MENU
Type:      F9            Function key 9 on left-hand side.
Prompt:    :
Type:      DELETE-FILE VOC
Prompt:    :
Type:      OFF
Prompt:    C>
Type:      REV SYSPROG
Prompt:    REVELATION LOGON MENU
Type:      <cr>          This selects the 'ATTACH' option.
Prompt:    DRIVE TO ATTACH OR TYPE 'END'?
Type:      A            Type the drive letter for the MRDS-REV
                        floppy disk.
Prompt:    REVELATION LOGON MENU
Type:      F9            Function key 9 on left hand side.
Prompt:    :
Type:      RUN SETUP M2M
Prompt:    ENTER DRIVE LETTER DESIGNATION FOR FLOPPY DRIVE.
                        DEFAULT = A.
Type:      <cr>          Type the drive letter for the MRDS-REV
                        floppy disk.
Prompt:    MRDS-REV MASTER MENU

```

Each time you run MRDS-REV after the above installation for fixed disk machines, use the following procedure:

Power up the machine and boot normally.

```

Prompt:    C>
Type:      MRDS
Prompt:    MRDS-REV MASTER MENU

```

#### C) Installation instructions for dual floppy drive machines

Power up the computer with the DOS system disk in drive A. Then

```
Type:      diskcopy a: b:
```

The computer will prompt you to insert the correct disks in the drives.

Use the above command to make a copy on a blank disk of the Revelation program disk (not the Utility disk). Label it REV.B. Use the above command to make a copy on a blank disk of the MRDS-REV disk supplied by the author of this report. Label it MRDS.DATA1.

Place the DOS system disk you booted with in drive B. Take a blank disk, label it REV.BOOT and place it in drive A.

```
Type:      b:format a:/s
```

Place the MRDS.DATA1 disk in drive B.



Type: copy b:autoexec.bat  
Type: copy b:capslock.com  
Type: copy b:keybuff.exe

Place the REV.B disk in drive B.

Type: copy b:rev.exe  
Type: del b:rev.exe  
Type: Ctrl-Alt-Del           Depress the three keys simultaneously.  
Type: SYSPROG  
Prompt: :  
Type: DELETE-FILE CUSTOMERS  
Prompt: Are you sure? (Y/N)  
Type: Y  
Prompt: :  
Type: DELETE-FILE CUST.STATUS  
Prompt: Are you sure? (Y/N)  
Type: Y  
Prompt: :  
Type: CREATE-ACCOUNT MRDS  
Prompt: PASSWORD:  
Type: <cr>           Press "RETURN" or enter a password. If a  
                    password is entered at this prompt, it must be  
                    entered at every subsequent login to MRDS-REV.  
Prompt: :  
Type: LOGTO MRDS  
Prompt: :  
Type: DELETE-FILE VOC  
Prompt: Are you sure ? (Y/N)  
Type: Y  
Prompt: :  
Type: OFF  
Prompt: B>  
Type: Ctrl-Alt-Del           Press the three keys simultaneously.  
Prompt: YOUR ACCOUNT PLEASE:  
Type: MRDS  
Prompt: Enter Selection ?           This is the MRDS master menu.

Each time you run MRDS-REV after the above installation for dual floppy machines, use the following procedure:

Place the REV.BOOT disk in drive A and the REV.B disk in drive B. Power up the machine or warm boot by pressing Ctrl-Alt-Del simultaneously.

Prompt: YOUR ACCOUNT PLEASE:

Remove the REV.BOOT disk from drive A and substitute the MRDS.DATA1 disk.

Type: MRDS  
Prompt: MRDS-REV MASTER MENU

#### IV. Entering and editing deposit records

The following menu appears after booting MRDS-REV:

##### MRDS-REV MASTER MENU

- 1) Enter or edit deposit records
- 2) Retrievals and printouts
- 3) Transfer records to PC-DOS or mainframe MRDS
- 4) REVELATION command level
- 5) PC-DOS command level. (type "EXIT" to return to REVELATION)
- 6) End session

Select #1 above by pressing the "Enter" key. The following menu appears:

##### DATA ENTRY MENU

1. Record ID (RECORD NUMBER to SYNONYMS)
2. Location (MINING DISTRICT to LONGITUDE)
3. Location (cont.) (ACC to LOCATION COMMENTS)
4. Commodities (COMMODITIES PRESENT to PROD)
5. Exploitation or Development + Description of Deposit
6. Description of Deposit and Workings (DEP SIZE to COMMENTS)
7. Geology (to ALTERATION)
8. Geology (cont.) (CONC/ENRICHMENT to COMMENTS)
9. General Comments
10. References
11. Production
12. Reserves and Resources

The MRDS Site Form is split into the above 12 screens for data entry and editing. Select screens from this menu with the up and down cursor arrows on the right hand key-pad. The right and left arrows will not work.

Once a screen has been selected, use the up and down arrow keys to change fields and the right and left arrow keys to move within a field. The "HOME" and "END" keys move to the beginning or end of a field. Use the "Ins" and "Del" keys to insert and delete data in a field.

When a screen is complete, a prompt appears at the bottom of the screen for the number of the field to be edited. The up and down cursor movement keys are not operational at this time on an existing record. Once the field number is entered, the user may be prompted for a multi-value number to edit. The following fields are currently set up as multi-value fields:

ANNUAL PRODUCTION  
CUMULATIVE PRODUCTION  
RESERVES AND POTENTIAL RESOURCES

RESERVES  
POTENTIAL RESOURCES  
FORMATION NAME  
FORMATION AGE  
IGNEOUS FORMATION NAME  
IGNEOUS FORMATION AGE

If the data in all the fields has been entered correctly, press "RETURN". The screen is automatically saved on disk, an input screen with blank fields appears, ready for the next record number. If there are no more records to enter, type "END".

Many fields are checked against data validation lists on entry. For instance, it is impossible to enter an incorrect state code in MRDS-REV. Also, several fields are mandatory and must be filled in before proceeding with the rest of the record. A help message about the required information or validation lists can be displayed by typing a "?". Further information can be obtained from the MRDS Instructions for Reporters Manual.

The fields and descriptions are identical with those in the MRDS Instructions for Reporters, except in the following cases:

1) The first field on each screen is the MRDS-REV record number. This number is mandatory in the MRDS-REV system but is not transferred to the MRDS mainframe file. Consequently, the user may wish to enter the same number in field #4, DEPOSIT NUMBER, so records can be cross-referenced when transferred to the main file in Reston.

2) The fields under ACCURACY, (ACC and EST) are combined in MRDS-REV. If the location is known accurately, enter "ACC". If not, enter "EST " and any comments that apply.

3) The fields PROD, YES, SML, MED, LGE, UND and NO have been combined into a single field called PRODUCTION. Enter Y, S, M, L, U, or N.

4) The fields SURFACE, UNDERGROUND and BOTH are combined into WORKINGS DESCRIPTION. Enter S, U or B.

5) The following fields have been deleted:

SECOND FORMATION NAME  
SECOND FORMATION AGE  
SECOND IGNEOUS UNIT NAME  
SECOND IGNEOUS UNIT AGE

The data can be entered in the appropriate multi-value field: FORMATION NAME, FORMATION AGE, etc.

## V. The MRDS-REV retrieval program

### A) Rationale for developing the retrieval program

The retrieval program developed by the author serves as an interface between Revelation command language and the user. There are several reasons the author developed the retrieval program:

1) The Revelation data base manager program is a complex system owing to its mini-computer heritage. It has an extensive list of commands and capabilities. The manual, consisting of three volumes plus several smaller booklets; may be more than the average user wishes to read. Although Revelation has a tutorial for a business application, the user would have to spend several hours translating the general capabilities and features of Revelation to MRDS-REV tasks. Consequently, a completely menu-driven environment was developed which prompts the user with alternative actions rather than requiring him to remember a specific command sequence.

2) The retrieval program helps the user create complicated retrievals and printout commands. Retrieval conditions connected with OR relations need not appear on the same line as in retrievals from Revelation command level. Retrieval and display commands can be saved, recalled and re-executed at a later time. This is particularly valuable for routine reports with complex systems such as MRDS-REV which contains 147 fields per record. MRDS users commonly retrieve records for 10 or 12 different commodities.

3) Revelation's report capabilities are oriented towards column type listings. However, column widths cannot be changed at run time. The author's retrieval program allows such changes.

MRDS personnel make frequent use of another type of report format in which each field is placed on a separate line. However, the Revelation report generator cannot be instructed to skip blank fields when printing line reports. Blank lines are particularly undesirable for sparse data matrices as is the case for some MRDS records. The author's retrieval program skips blank fields.

4) Revelation has no simple provision for copying selected fields and records to a PC-DOS file for plotting, statistical work or interfacing with other data base systems. The Revelation COPY DOS command does not operate from a SELECT list so each record must be specified by record number. Furthermore, the COPY DOS command sends only complete records to a file, not selected fields. They are written in line as opposed to column format. Rather than force the user to write a computer program every time the need for a DOS file arises, the author has incorporated this feature in the retrieval program.

## B) Retrieval program description and operating instructions

Select item #2 on the MRDS-REV master menu. The retrieval program is divided into 3 main steps:

RETRIEVAL => SORT => OUTPUT

The program guides the user through the following sequence:

- 1) Type of retrieval:
  - a) create a new retrieval or
  - b) re-execute a set of retrieval commands saved in an previous session.

A complete retrieval and output sequence can be recalled from a previous session or created and edited in the Revelation editor and submitted to the retrieval program. See Appendix A for the file format. If the re-execute option is selected, all of the following steps are skipped.

- 2) Select a file to conduct retrievals on.
- 3) Choose one of three methods to extract records:
  - a) select all records;
  - b) select records by record number only or
  - c) select records based on the contents of any field(s) in the record, i.e. "STATE EQ VA". These commands can be selected from menus if desired.
- 4) Execute the retrieval and display the number of records in the resulting sub-file.
- 5) Edit or append the current retrieval command or a past command, and re-execute it against the current sub-file or select from previous sub-files.
- 6) Sort the currently active sub-file against any field(s) in MRDS-REV.
- 7) Select from several report types:
  - a) default fields column listing: (deposit number, site name, state, lat, long, commodities);
  - b) user selected fields column listing or
  - c) line listing of entire record.
- 8) Select output device:
  - a) display on screen;
  - b) printer or
  - c) PC-DOS file,
- 9) After viewing results, change the sort criteria, report type or output device and re-execute.
- 10) Save the current retrieval commands for execution in a later session.

The retrieval program consists of over 1000 lines of modular Revelation Basic code, which is easily modified for special applications.

## VI. Running retrievals at command level

MRDS-REV can also be operated from Revelation terminal command level (TCL). Revelation has four retrieval commands but the MRDS user need only concern himself with two:

```
SELECT
LIST
```

SELECT is the best choice for the first command because it allows the user to iterate (re-select) on the resulting sub-file. The general form of the command is:

```
SELECT {filename} {connector} {field {operator} {comparison
                                name}          value}
```

There are two connectors:

```
WITH
WITHOUT
```

The complete list of operators follows:

EQ NE	equals, not equal to
GT LT	greater than, less than
GE LE	greater than or equal to, less than or equal to
[]	containing
]	starts with
[	ends with

For example:

```
Prompt:  :
Type:    SELECT MRDS WITH STATE EQ "VA"
Prompt:  >
```

Notice the prompt changes to ">" when a select list is active. Another condition can be logically connected with an "AND" to the first one by typing:

```
Type:    SELECT MRDS WITH COUNTY EQ "RAPPAHANNOCK"
```

If the second condition is to be connected by an "OR" with the first, they would have to be typed on the same line because select lists cannot be added together. For example:

```
:SELECT MRDS WITH STATE EQ "VA" OR WITH STATE EQ "MD"
```

This is equivalent to:

```
SELECT MRDS WITH STATE EQ "VA" "MD"
```

The "OR" is implied between "VA" and "MD". There is no hierarchy of execution for logical connectors. Revelation evaluates the command strictly from left to right. Parentheses are not allowed. For instance, the following command would give erroneous results:

```
:SELECT MRDS WITH STATE EQ "VA" AND WITH COUNTY EQ  
"RAPPAHANNOCK" OR WITH COUNTY EQ "FAUQUIER"
```

The above command retrieves all records with VA and RAPPAHANNOCK first, then looks in the same subset for FAUQUIER and finds no entries. Fortunately, there is an easy solution to this particular problem:

```
:SELECT MRDS WITH STATE EQ "VA" AND COUNTY EQ "RAPPAHANNOCK" "FAUQUIER"
```

The OR is implied between the two counties. This is a one line retrieval. Alternatively, type:

```
:SELECT MRDS WITH STATE EQ "VA"  
>SELECT MRDS WITH COUNTY "RAPPAHANNOCK" "FAUQUIER"
```

This is a two step process and may be easier for most users to type in. Occasionally, the solution may not be so easy. Logic such as

(a and b) or (c and d)

is impossible in Revelation release G. Future releases may correct this problem. For example, in retrieving two types of bi-metallic ore deposits, those containing both Pb and Zn or both Sn and W, two separate lists would result:

```
:SELECT MRDS WITH COMMOD [] "ZN" AND WITH COMMOD [] "PB"  
>LIST MRDS BY SITE.NAME (P)  
:SELECT MRDS WITH COMMOD [] "SN" AND WITH COMMOD [] "W"  
>LIST MRDS BY SITE.NAME (P)
```

The operator, [] means "containing". It is used very often in MRDS-REV because the value ZN can appear anywhere in the COMMOD field. When selecting the contents of numeric fields, the quotes are unnecessary.

```
:LIST MRDS WITH NUM EQ 67 70 82 (P)
```

This command selects record numbers 67, 70 and 82

The (P) parameter directs output to the printer as opposed to the screen.

The BY connector tells it to sort by the following field(s).

Notice the LIST command terminates retrievals from the active select list. Use LIST last for sorting and printing. The format of the resulting list is columnar. If no fields are

specified in the list command, the displayed fields defaults to:

DEPOSIT.NUMBER    SITE.NAME    STATE    LATITUDE    LONGITUDE    COMMODITY

To list fields other than the default fields, type the dictionary names from Appendix B of this paper.

>LIST MRDS DEP.TYPE HR.AGE QUAD1 etc

The column widths default to the value set in the MRDS-REV dictionary. Use the author's retrieval program (Section V., this paper) or the FORM command (see below) to change the display length of fields in listings and printouts.

#### The Dot Processor

A very useful feature of Revelation is the ".L" command. It lists the last 9 commands the user has issued. Any one of the 9 commands can be retrieved for editing and re-execution with ".Xn" where "n" is the command number.

#### The FORM command

Revelation's report generator, the FORM command, requires using the Revelation TEXT editor. TEXT is screen orientated and uses the convenient PC arrow keys to move the cursor on the screen. However, casual users may find the commands difficult to learn. The author has avoided FORM for another reason. It cannot be instructed to skip blank fields in a record.



## VII. Transferring records between MRDS-GIPSY and MRDS-REV

MRDS has operated on an Amdahl mainframe using the GIPSY data base manager program since 1972. This author has written conversion programs that accept GIPSY data in CONVERT format as input and produce GIPSY data in BUILD format as output. Conversion programs between GIPSY and Revelation are necessary for the following reasons:

- 1) The Revelation COPY command produces only one record at a time in PC-DOS format.
- 2) Some of the fields differ between MRDS-GIPSY and MRDS-REV, as outlined in Section IV, this paper. The author's programs convert the fields in the most logical possible way. However, with ambiguous data, they display the converted data and ask if the user wishes to change the results.
- 3) The two data bases store data in different formats and the dictionaries are sorted in different orders.
- 4) The field names differ from MRDS-GIPSY to MRDS-REV.

To convert from MRDS-GIPSY to MRDS-REV use the following procedure:

- 1) Have your MRDS representative prepare a GIPSY CONVERT file using dictionary VG9225M.CVD01.DATA.
- 2) Instruct him to download it to a DOS file on floppy disk. If you have a modem you can download it directly to your machine. Ask your MRDS representative for details.
- 3) Boot MRDS-REV and select item #3 on the master menu. You will be prompted for the necessary file names and record numbers.

To convert from MRDS-REV to MRDS-GIPSY use the following procedure:

- 1) Boot with a PC-DOS system disk. Then type  
  
FORMAT A:            Place a blank disk in floppy drive A and  
                     press "RETURN". Make sure you are not  
                     formatting your fixed disk.
- 2) Run MRDS-REV. Select item #3 on the MRDS-REV master menu.
- 3) When the program prompts you for the output file name, specify the floppy drive in front of the name, i.e. "A:filename".
- 4) Send the floppy disk to your MRDS representative who will add MRDS record numbers and use the GIPSY BUILD program to install the records in the main file.

## VIII. Creating and moving files

Revelation uses a separate, non-PC-DOS file system and directory. Each disk must be given a MEDIA NAME to establish a directory and each drive must be ATTACHED in order for its files to be accessible. In addition, files must be CREATED before data can be copied to them.

A single Revelation data file may consist of many DOS files. These files are visible as separate DOS files under a DOS DIRectory command but are combined in the Revelation directory listing which is evoked by the LISTMEDIA command. A Revelation data file contains both data and dictionary. COPY moves the data record(s) or the dictionary. MOVE moves both at once but only the entire file. MOVE cannot put records into an existing file. The old file must be deleted first.

A) Copying files to floppy disk with the same account name.

- 1) Boot MRDS-REV normally.
- 2) Put a formatted disk in the floppy drive.
- 3) Go to Revelation command level by selecting item #4 on the master menu.

Type:	NAMEMEDIA A DATA1	This command establishes a disk named DATA1
Prompt:	:	
Type:	CREATE-FILE MRDS1 A	Creates a file named MRDS1. Maximum intended size is 64K bytes.

or

CREATE-FILE MRDS1 1 64000      Creates file MRDS1.  
Maximum expected file size is 128K bytes. Type  
"2 64000" for 192K bytes, etc. MRDS-REV records  
average 2K bytes each.

Prompt:	:	
Type:	COPY DICT MRDS	
Prompt:	TO:	
Type:	(MRDS1	
Prompt:	:	
Type:	COPY MRDS 3 5	Copies record number 3 and 5 in file MRDS to MRDS1
Prompt:	TO:	
Type:	(MRDS1	

or

COPY MRDS \*      Copies all the records in file MRDS.

This disk can be transported to any similar machine with MRDS-REV

with the following procedure:

- 1) Boot MRDS-REV normally.
- 2) Put the source disk in the floppy drive.
- 3) Go to Revelation command level by selecting item #4 on the master menu.

```
Type:    ATTACH A
Prompt:   :
Type:    COPY MRDS1 3 5
Prompt:   TO:
Type:    (MRDS 46 47      Copies records 3 and 5 to records
                        46 and 47 on the destination machine.
```

or

```
Type:    COPY MRDS1 3 5 (0)
Prompt:   TO:
Type:    (MRDS           To overlay the existing records 3
                        and 5 on the destination machine.
```

#### B) Copying files on dual floppy machines

Dual floppy disk machine owners must use a multi-step procedure to move files from floppy to floppy, unless there is enough room on drive B for the file. If so, the MOVE command can be used to transfer the file from A to B then back to a new disk placed in A. Otherwise, follow the procedure below.

- 1) Boot MRDS-REV normally. Go to Revelation command level.
- 2) Place a formatted, bootable destination disk in drive A.

```
Prompt:   :
Type:    NAMEMEDIA A      Type this only if the disk does not already
                        have a ROSMEDIA.MAP file on it.
Prompt:   :
Type:    PC
Prompt:   B>
Type:    TYPE A:ROSMEDIA.MAP  Write down the numeric
                        portion of the first file name in the directory.
                        The file names all start with ROS. This is the
                        next file number used on a Revelation CREATE-FILE
                        command.
Prompt:   B>
Type:    EXIT
Prompt:   :
Type:    LISTMEDIA A      Put the source disk back in drive A.
                        Write down the ROS number of the
                        file to be transferred.
Prompt:   :
Type:    PC
Prompt:   B>
Type:    COPY A:ROSxxxxxx.* B:ROSy-yyyyy.* /V  Put destination disk in drive B.
                        where "xxxxxx" is
                        the source number and "yyyyyy" is the destination
                        number.
```

Prompt: B>  
Type: EXIT  
Prompt: : Put destination disk in A, MRDS-REV.B back in B.  
Type: CREATE-FILE filename A  
Prompt: :  
Type: ATTACH A

#### C) Copying files between accounts with different names

The MOVE command must be used to copy between different accounts. Only whole files can be moved. However, the copy command can be used first to create a sub-file of the source file.

The general form of the move command is:

MOVE account file drive TO: account file drive

The command seems to work best when all the parameters are specified. Accepting default parameters sometimes causes it to fail.

MOVE MRDS MRDS C TO: CMRDS MRDS A

This command moves file MRDS in account MRDS on drive C to account CMRDS on drive A.

## IX. Programming in Revelation Basic

Revelation contains an interface language called R/BASIC. It is called BASIC because of its many string functions. However, it also has many of the structures of a higher level language such as Pascal. In addition, there are some unique features found in few other languages. Arrays are called matrices but find little use compared to dynamic string arrays which are really the core of the power of Revelation. Dynamic string arrays are three dimensional arrays, up to 65K bytes each, requiring no dimension statements. Revelation has a multitude of string function commands tailored to these arrays as well as simple strings. They make many programming tasks easier, especially interfacing with data files, but most users would do well to read the following tips before writing code in R/BASIC.

1) Initialize all dynamic string arrays to '' (null string) to avoid an error message when putting data in them.

```
STR = ''
```

2) Setting a dynamic string array's 0'th member equal to anything will erase the entire array.

3) C := CHAR(X) appends fields to the array "C" according to the following rules:

- a) if X = 252, 253, 254 it adds another sub-value, value or field mark.
- b) if X = any other number, it appends a field mark, CHAR(254), plus that character.

4) The number of sub-values, values or fields is always one more than the COUNT function returns.

Some considerations with other R/BASIC statements follow:

1) PERFORM executes all the TCL commands such as LIST, COPY, etc. except ".Xn", the DOT PROCESSOR command that re-executes an old command. It executes the command but does not return to the calling program. Use a dynamic string array to store commands in a program.

2) There is no provision for restricting variables to string, integer or real. Also, there is no floating point or double precision. The fixed decimal precision displays F19.4 but this author has not determined what precision is stored. Microsoft BASIC double precision is 17 digits.

Converting values from string to numeric is possible but all leading or trailing blanks must be stripped. Convert the blanks to sub-value marks or use the TRIM function. Also, read the page on "Null and Zero" in the R/BASIC Section for the rules about zeroed variables.

3) The CONVERT command operates on dynamic string arrays but array elements cannot be specified in the CONVERT command. For instance,

```
CONVERT 'ab cd' TO C<1,1> IN D<X>
```

is illegal because of the arguments in the <>. Instead type

```
C1 = C<1,1>
D1 = D<X>
CONVERT 'ab cd' TO C1 IN D1
D<X> = D1
```

If C = 'abcd' then

CONVERT 'bc' TO 'x' IN C	yields	C = 'axd'.
CONVERT 'yc' TO 'x' in C	yields	C = 'abd'
CONVERT 'cy' TO 'x' IN C	yields	C = 'abxd'
CONVERT 'c' to 'xx' in C	yields	C = 'abxd'

CONVERT cannot insert more than is removed. Instead, use

```
Z=INDEX(C,'c')
C = C[1,Z-1]:'xx':C[Z+1,65000]
```

The manual's program example in Technical Reference, Appendix VI, (COSMOS, 1985), for converting files from DOS to Revelation cannot be used for Revelation to DOS. See the author's conversion programs in Appendix C, part 2 of this paper for alternative methods. Also, there is a mistake in line 7. It should read:

```
OPEN '', 'REV.FILE' TO FILE.VISI ELSE STOP
```

4) The @RECCOUNT variable, Technical Reference, Appendix IX (COSMOS, 1985), does not work. Use a loop with READNEXT @ID and a counter against a select list instead. See author's retrieval program, Appendix C, part 1 of this paper, subroutine RETR:.

5) The @RECORD<n> convention works for all field numbers n > 0. Use @ID to retrieve the 0'th field. If n = '', the entire record is returned. This is equivalent to simply @RECORD.

## X. Reference

- 1) COSMOS, Inc., 1985, Revelation users manuals, ELF Software Distributors, Inc., P.O. Box 1237, Longview, WA, 98632.

## Appendix A. Retrieval program command file structure

The author's retrieval program is capable of saving each session's commands in a file called RETRIEVALS. Since the command file is a Revelation text file, it can be edited in the line or text editor. Alternatively, the entire command file can originate in the editor in the following format:

General form:

```
filename
retrieval conditions
output device
    crt screen - type nothing, no blank line
    printer    - type PRINTER
    PC-DOS file - type DOS
DOS file name (optional)
listing type
    default column listing - type DEFAULT
    selected columns       - type COLUMNS
    line listing           - type LINES
fields to be listed
```

Example:

```
MRDS
WITH
COMMOD [] 'PB' 'ZN' 'CU'
AND WITH
STATE
EQ 'VA'
DOS FILE
FILEX
LIST
COLUMNS
SITE.NAME 30
LAT 9
LONG 10
STATE 2
DEP.TYPE 20
HR.TYPE 20
```



N.. FIELD.CODE.. DESCRIPTION.....

1	NUM	REVELATION RECORD NUMBER
2	REC.NUM	MRDS RECORD NUMBER
3	REC.TYP	RECORD TYPE
4	DEP.NUM	DEPOSIT NUMBER
5	REP.DATE	REPORT DATE
6	INFO.SRC	INFORMATION SOURCE
7	FIL.LINK	FILE LINK ID
8	REP	REPORTER
9	REP.AFF	REPORTER AFFILIATION
10	SITE.NAME	SITE NAME
11	SYN	SYNONYM NAME
12	DIST	MINING DISTRICT
13	COUNTY	COUNTY
14	STATE	STATE
15	COUNTRY	COUNTRY
16	PHYS	PHYSIOGRAPHIC PROVINCE
17	DRAIN	DRAINAGE AREA
18	LAND.ST	LAND STATUS
19	QUAD1	QUADRANGLE NAME
20	Q1.SCALE	QUADRANGLE SCALE
21	QUAD2	SECOND QUADRANGLE NAME
22	Q2.SCALE	SECOND QUAD SCALE
23	ELEV	ELEVATION
24	UTM.N	UTM NORTHING
25	UTM.E	UTM EASTING
26	UTM.Z	UTM ZONE NUMBER
27	ACC	ACCURACY OF LOCATION
28	LAT	LATITUDE
29	LONG	LONGITUDE
30	TOWNSHIP	TOWNSHIP
31	SECTION	SECTION
32	RANGE	RANGE
33	SECT.FRACT	SECT.FRACT
34	MERIDIAN	MERIDIAN
35	POS	POSITION FROM NEAREST LOCALITY
36	LOCATION	LOCATION COMMENTS
37	COMMOD	COMMODITIES PRESENT
38	ORE.MAT	ORE MATERIALS
39	COM.SUB	COMMODITY SUBTYPES
40	GEN.ANAL	GENERAL ANALYTICAL DATA
41	COM.INFO	COMMODITY INFO COMMENTS
42	MAJOR	MAJOR COMMODITITS
43	MINOR	MINOR COMMODITIES
44	POTEN	POTENTIAL COMMODITIES
45	OCCUR	OCCURRENCES COMMODITIES
46	NP.MAIN	MAIN NON-PRODUCER
47	NP.MINOR	MINOR NON-PRODUCER
48	PROD	PRODUCTION
49	STATUS	STATUS AND ACTIVITY
50	DISC	DISCOVERER
51	YR.DISC	YEAR OF DISCOVERY
52	NAT.DISC	NATURE OF DISCOVERY
53	YR.1ST.PROD	YEAR OF FIRST PRODUCTION
54	YR.LAST.PROD	YEAR OF LAST PRODUCTION
55	OWNER	OWNER
56	OPER	OPERATOR
57	EXPL.COM	EXPLORATION COMMENTS
58	DEP.TYPE	DEPOSIT TYPE
59	DEP.FORM	DEPOSIT FORM
60	DEPTH.TOP	DEPTH TO TOP OF DEPOSIT

N.. FIELD.CODE.. DESCRIPTION.....

61	DEP.T.U	UNITS
62	DEPTH.BOT	DEPTH TO BOTTOM OF DEPOSIT
63	DEP.B.U	UNITS
64	MAX.LEN	MAXIMUM LENGTH OF DEPOSIT
65	M.L.U	UNITS
66	MAX.WID	MAXIMUM WIDTH OF DEPOSIT
67	M.W.U	UNITS
68	MAX.THICK	MAXIMUM THICKNESS OF DEPOSIT
69	M.T. U	UNITS
70	DEP.SIZE	DEPOSIT SIZE
71	STRIKE	
72	DIP	
73	PLUNGE.DIR	PLUNGE DIRECTION
74	PLUNGE	
75	DEP.DESC.COM	DEPOSIT DESCRIPTION COMMENTS
76	DESC.WORK	WORKINGS ARE (SURFACE UNDERGROUND BOTH)
77	DEPTH.WK	DEPTH OF WORKINGS
78	D.WK.U	UNITS
79	LEN.WK	LENGTH OF WORKINGS
80	L.WK.U	UNITS
81	OV.LEN.WK	OVERALL LENGTH
82	O.L.U	UNITS
83	OV.WID.WK	OVERALL WIDTH
84	O.W.U	UNITS
85	OV.AREA.WK	OVERALL AREA
86	O.A.U	UNITS
87	DESC.WORK.CO	DESCRIPTION OF WORKINGS COMMENTS
88	HR.AGE	HOST ROCK AGE
89	HR.TYPE	HOST ROCK TYPE
90	IG.AGE	IGNEOUS ROCK AGE
91	IG.TYPE	IGNEOUS ROCK TYPE
92	MIN.AGE	AGE OF MINERALIZATION
93	NON.ORE.MINS	PERTINENT MINERALOGY (NON ORE)
94	ORE.CNTL	ORE CONTROL/LOCUS
95	REG.STRUCT	MAJOR REGIONAL TRENDS OR STRUCTURE
96	TECT.SET	TECTONIC SETTING
97	LOCAL.STRUCT	SIGNIFICANT LOCAL STRUCTURE
98	ALTER	SIGNIFICANT ALTERATION
99	CONC	PROCESS OF CONCENTRATION OR ENRICHMENT
100	FORM.AGE	FORMATION AGE
101	FORM.NAME	FORMATION NAME
102	IG.UNIT.AGE	IGNEOUS UNIT AGE
103	IG.UNIT.NAME	IGNEOUS UNIT NAME
104	GEOLOG.COM	GEOLOGY COMMENTS
105	GEN.COM	GENERAL COMMENTS
106	RF1	REFERENCE 1
107	RF2	REFERENCE 2
108	RF3	REFERENCE 3
109	RF4	REFERENCE 4
110	AP.ITEM	ANNUAL PRODUCTION ITEM (type of ore, metal, conc.)
111	AP.ACC	ACCURACY OF AMOUNT
112	AP.AMT	AMOUNT OF PRODUCTION
113	AP.U	UNITS (tons, ounces, etc.)
114	AP.YEAR	YEAR OF PRODUCTION
115	AP.GRADE	GRADE OF ITEM
116	CP.ITEM	CUMULATIVE PRODUCTION (type of ore, metal, conc.)
117	CP.ACC	ACCURACY OF AMOUNT
118	CP.AMT	AMOUNT OF PRODUCTION
119	CP.U	UNITS
120	CP.YEAR	YEARS OF PRODUCTION

N.. FIELD.CODE.. DESCRIPTION.....

121 CP.GRADE	GRADE OF ITEM
122 P.COM	PRODUCTION COMMENTS
123 P.SOURCE	PRODUCTION SOURCE OF INFORMATION
124 RPR.ITEM	RESERVES AND RESOURCES ITEM (type of ore, metal, etc)
125 RPR.ACC	ACCURACY OF AMOUNT
126 RPR.AMT	AMOUNT OF RESERVES AND RESOURCES
127 RPR.U	UNITS (tons, ounces, etc.)
128 RPR.YEAR	YEAR OF ASSESSMENT
129 RPR.GRADE	GRADE OF ITEM
130 RPR.COM	RESERVES AND RESOURCES COMMENTS
131 RPR.SOURCE	RESERVES AND RESOURCES SOURCE OF INFORMATION
132 R.ITEM	RESERVES ITEM (type of ore, metal, etc)
133 R.ACC	ACCURACY OF AMOUNT
134 R.AMT	AMOUNT OF RESERVES
135 R.U	UNITS
136 R.YEAR	YEARS OF ASSESEMENT
137 R.GRADE	GRADE OF ITEM
138 R.COM	RESERVES COMMENTS
139 R.SOURCE	RESERVES SOURCE OF INFORMATION
140 PR.ITEM	POTENTIAL RESOURCES ITEM (type of ore, metal, etc)
141 PR.ACC	ACCURACY OF AMOUNT
142 PR.AMT	AMOUNT OF POTENTIAL RESOURCES
143 PR.U	UNITS (tons, ounces, etc.)
144 PR.YEAR	YEAR OF ASSESSMENT
145 PR.GRADE	GRADE OF ITEM
146 PR.COM	POTENTIAL RESOURCES COMMENTS
147 PR.SOURCE	POTENTIAL RESOURCES SOURCE OF INFORMATION

147 Records Processed

Appendix C. Program listings  
1) Retrieval program

```

0001      GOSUB SETUP
0002 REFILE:
0003      GOSUB RUN.RERUN
0004      GOSUB SET.RET.TYPE
0005      GOSUB ITERATE
0006 RESORT:
0007      GOSUB SORT
0008 REPRINT:
0009      GOSUB OUTPUT
0010 RELIST:
0011      GOSUB TERMINUS
0012      BEGIN CASE
0013      CASE A18=1; GOTO RESORT
0014      CASE A18=2; GOTO REPRINT
0015      CASE A18=3; GOTO REFILE
0016      CASE A18=4
0017          GOSUB SAVE.RET
0018          GOSUB WRITE.RET
0019          GOTO RELIST
0020      CASE A18=5
0021          GOTO EOP
0022      CASE 1; PRINT BEL; GOTO RELIST
0023      END CASE
0024      *
0025 SETUP:
0026      DIM FORMAT(200)
0027      DIM FLD(200)
0028      PROMPT ''
0029      BEEP=CHAR(7)
0030      CR=CHAR(13)
0031      LF=CHAR(10)
0032      FM=CHAR(254)
0033      VM=CHAR(253)
0034      SM=CHAR(252)
0035      LN=0
0036      CM=''
0037      CM1=''
0038      CO=''
0039      O.DEVICE=''
0040      LIST=''
0041      OUT=''
0042      OPEN '', 'LISTS' TO L.V ELSE
0043          PERFORM 'CREATE-FILE LISTS'
0044          RETURN
0045      END
0046      PERFORM 'CLEAR-FILE LISTS'
0047      @LPTRWIDE=80
0048      RETURN
0049      *
0050 RET.REV.NO:
0051      *ERFORM "SORT":REV.FILE
0052      GOSUB START.CO
0053      PRINT
0054      CO<2> = 'WITH NUM GE ?"STARTING NUMBER"? AND WITH NUM LE
- - > ?"ENDING NUMBER"?
0055      GOSUB RETR
0056      RETURN
0057      *
0058 OUTPUT:
0059      PRINT @(-1),@(-2)
0060      PRINT
0061      PRINT 'CHOOSE OUTPUT FORMAT';PRINT

```

```

0062      PRINT;PRINT '      1) COLUMNS (ONE FIELD PER COLUMN)'
0063      PRINT;PRINT '      2) LINES (ONE FIELD PER LINE, ENTIRE
      - - > RECORD)'
0064      PRINT;PRINT '      3) NO OUTPUT DESIRED FOR THIS FILE'
0065      PRINT;PRINT 'ENTER "1", "2" OR "3": '
0066      INPUT ANS
0067      BEGIN CASE
0068      CASE ANS=1
0069          GOSUB SFIELD.COLS
0070      CASE ANS=2
0071          GOSUB LIST.LINES.ALL
0072      CASE ANS=3
0073      CASE 1: GOTO OUTPUT
0074      END CASE
0075      PRINTER OFF
0076      RETURN
0077      *
0078  RET.ANY:
0079      GOSUB START.CO
0080      GOSUB CMD.BUILD
0081      GOSUB CMD.BUILD1
0082      IF A3='P' THEN GOTO CMD.HELP
0083      CO<2>=A3
0084      GOSUB RETR
0085      RETURN
0086      *
0087  CMD.BUILD:
0088      PRINT @(-1),@(-2)
0089      PRINT 'THE GENERAL FORM OF RETRIEVAL COMMANDS IS AS FOLLOWS:'
0090      PRINT
0091      PRINT '      SELECT MRDS "connector" "field name" "operator"
      - - > "comparison value"'
0092      PRINT
0093      PRINT 'HERE ARE SOME EXAMPLES:'
0094      PRINT
0095      PRINT '      SELECT MRDS WITH STATE EQ
      - - > "VA"'
0096      PRINT '      SELECT MRDS WITH COMMOD [ ]
      - - > "PB"'
0097      PRINT '      SELECT MRDS WITH LAT GE
      - - > "22-22-22W"'
0098      PRINT '      SELECT MRDS WITHOUT LONG ]
      - - > 086'
0099      PRINT '      SELECT MRDS 1 3 22'
0100      PRINT
0101      PRINT
0102      RETURN
0103      *
0104  CMD.BUILD1:
0105      PRINT 'PLEASE FINISH TYPING THE FOLLOWING COMMAND OR TYPE "P" TO
      - - > BE PROMPTED:'
0106      PRINT
0107      PRINT CO<1>:
0108      INPUT A3
0109      RETURN
0110      *
0111  CMD.HELP:
0112  SUBCOM.AGAIN:
0113      SUBN=SUBN+1
0114      GOSUB CMD.BUILD
0115      GOSUB CURRENT
0116      PRINT

```

```

0117      PRINT 'CHOOSE A CONNECTOR: '
0118      PRINT
0119      PRINT '      1) WITHOUT '
0120      PRINT
0121      PRINT '      2) WITH '
0122      PRINT
0123      PRINT 'ENTER 1 OR 2: '
0124      INPUT A6
0125      BEGIN CASE
0126      CASE A6=1 OR A6='WITHOUT'; CO<SUBN>='WITHOUT'
0127      CASE A6=2 OR A6='WITH' OR A6=''; CO<SUBN>='WITH'
0128      CASE 1: GOTO COMD.HELP
0129      END CASE
0130      SUBN=SUBN+1
0131  FIELD.AGAIN:
0132      GOSUB COMD.HELP1
0133      BEGIN CASE
0134      CASE A7=''
0135          PERFORM 'CLEAR'
0136          PERFORM 'LIST FIELD.DESC ID-SUPP'
0137          GOTO FIELD.AGAIN
0138      CASE 1
0139          CO<SUBN>=A7
0140      END CASE
0141      GOSUB COMD.HELP2
0142      GOSUB COMD.HELP3
0143      GOSUB COMD.HELP4
0144  HELP4.AGAIN:
0145      BEGIN CASE
0146      CASE A16=''
0147          GOSUB RETR
0148          RETURN
0149      CASE A16=1 OR A16='AND'
0150          SUBN=SUBN+1
0151          CO<SUBN>='AND'
0152          GOTO SUBCOM.AGAIN
0153      CASE A16=2 OR A16='OR'
0154          SUBN=SUBN+1
0155          CO<SUBN>='OR'
0156          GOTO SUBCOM.AGAIN
0157      CASE 1
0158          GOTO HELP4.AGAIN:
0159      END CASE
0160      *
0161  COMD.HELP1:
0162      GOSUB COMD.BUILD
0163      GOSUB CURRENT
0164      PRINT
0165      PRINT 'ENTER A DICTIONARY FIELD NAME OR'
0166      PRINT;PRINT 'PRESS "RETURN" TO SEE A LIST OF AVAILABLE FIELD
- - > NAMES:  ':
0167      INPUT A7
0168      RETURN
0169      *
0170  COMD.HELP2:
0171      GOSUB COMD.BUILD
0172      GOSUB CURRENT
0173      PRINT
0174      PRINT 'REVELATION OPERATORS      EQ NE'
0175      PRINT '                                GT LT GE LE'
0176      PRINT '                                [] (contains)'
0177      PRINT '                                ] (starts with)'

```

```

0178      PRINT '          [ (ends with) '
0179      PRINT;PRINT 'ENTER AN OPERATOR FROM THE ABOVE LIST:
0180      INPUT A8
0181      A7 := ' ':A8
0182      CO<SUBN>=A7
0183      RETURN
0184      *
0185  COMD.HELP3:
0186      GOSUB COMD.BUILD
0187      GOSUB CURRENT
0188      PRINT;PRINT 'ENTER COMPARISON VALUE(S).  QUOTES ARE UNNECESSARY.'
0189      PRINT;PRINT 'PRESS "Esc" TO END ENTRIES:  ':
0190      INPUT A9
0191      IF A9 <> CHAR(27) THEN
0192          A7 := ' ':QUOTE(A9)
0193          CO<SUBN>=A7
0194          GOTO COMD.HELP3
0195      END
0196      RETURN
0197      *
0198  COMD.HELP4:
0199      GOSUB COMD.BUILD
0200      GOSUB CURRENT
0201      PRINT;PRINT 'ENTER CONNECTOR FOR NEXT SUBCOMMAND'
0202      PRINT;PRINT '      1) AND'
0203      PRINT;PRINT '      2) OR'
0204      PRINT;PRINT 'RETURN) TERMINATE COMMAND'
0205      PRINT;PRINT 'ENTER 1, 2 OR "RETURN":  ':
0206      INPUT A16
0207      RETURN
0208      *
0209  CURRENT:
0210      PRINT 'YOUR CURRENT COMMAND IS:  ':
0211      FOR I=1 TO SUBN
0212          PRINT CO<I>: ' ':
0213      NEXT I
0214      PRINT
0215      RETURN
0216      *
0217  SFIELD.COLS:
0218      PRINT @(-1),@(-2)
0219      PRINT
0220      PRINT 'SELECT FIELDS FOR COLUMN LISTING'
0221      PRINT
0222      PRINT;PRINT '      1) DEFAULT LISTING (SITE NAME, COUNTRY, STATE,
- - > LAT, LONG, COMMODITY)'
0223      PRINT;PRINT '      2) CHOOSE FROM COMPLETE LIST OF DICTIONARY
- - > ITEMS'
0224      PRINT
0225      PRINT;PRINT 'ENTER 1 OR 2:  ':
0226      INPUT ANS
0227      BEGIN CASE
0228      CASE ANS=' ' OR ANS=1
0229          GOSUB O.DEVICE
0230          GOSUB DEFAULT
0231      CASE ANS=2
0232          GOSUB MAKE.LIST
0233          GOSUB O.DEVICE
0234          GOSUB COLS.OUT
0235      CASE 1: GOTO SFIELD.COLS
0236      END CASE
0237      RETURN

```

```

0238      *
0239  DEFAULT:
0240      LIST = 'DEFAULT'
0241      IF O.DEVICE = 'DOS FILE' THEN
0242          GOSUB SEL.DOS.FILE
0243          GOSUB DEFAULT.DOS
0244          RETURN
0245      END
0246      CP='LIST ':REV.FILE
0247      IF O.DEVICE = 'PRINTER' THEN CP := ' (P)'
0248      PRINT @(-1),@(-2)
0249      PERFORM 'GET-LIST LIST.S'
0250      PERFORM CP
0251      RETURN
0252      *
0253  DEFAULT.DOS:
0254      PERFORM 'GET-LIST LIST.S'
0255      R=''
0256      LOOP
0257          READNEXT @ID ELSE
0258              WRITE R TO DOS.FILE.V, DOS.FILE
0259              RETURN
0260          END
0261          READ @RECORD FROM REV.FILE.V, @ID ELSE
0262              PRINT;PRINT 'ERROR IN FILE ':REV.FILE
0263              GOSUB PAUSE
0264              RETURN
0265          END
0266          S=SPACE(80)
0267          S[1,4] = @ID 'R#4'
0268          S[7,20] = @RECORD<33> 'L#20'
0269          S[29,2] = @RECORD<12> 'L#2'
0270          S[33,9] = @RECORD<34> 'L#9'
0271          S[44,10] = @RECORD<35> 'L#10'
0272          S[56,24] = @RECORD<38> 'L#24'
0273          R := S[1,79]:CR:LF
0274      REPEAT
0275      *
0276  SEL.DOS.FILE:
0277      PRINT @(-1),@(-2)
0278      PRINT 'ENTER DOS FILE TO WRITE DATA TO. (DEFAULT = A:MDOS.O):'
0279      INPUT DOS.FILE
0280      IF DOS.FILE = '' THEN DOS.FILE = 'A:MDOS.O'
0281      GOSUB OPEN.DOS
0282      IF DOS.FILE THEN RETURN
0283      GOTO SEL.DOS.FILE
0284      *
0285  OPEN.DOS:
0286      OPEN '', 'DOS' TO DOS.FILE.V ELSE
0287          PRINT BEL;PRINT 'CANNOT OPEN FILE ':DOS.FILE
0288          GOSUB PAUSE
0289          DOS.FILE=''
0290      END
0291      RETURN
0292      *
0293  MAKE.LIST:
0294      LIST = 'COLUMNS'
0295      I=0;NC=0
0296  FIELDS:
0297      PRINT
0298      PRINT 'ENTER "FIELD NAME" AND "LENGTH" IE.      SITE.NAME 25'

```



```
0299      PRINT '
0300      PRINT '
0301      PRINT
0302      PRINT 'OR ENTER "." TO SEE DICTIONARY LIST '
0303      PRINT 'OR PRESS "RETURN" TO EDIT OR END ENTRIES'
0304      PRINT
0305      *
0306  ENTER:
0307      PRINT 'ENTER FIELD AND LENGTH:
0308      INPUT ANS
0309      IF ANS = '' THEN GOTO EDIT
0310      BEGIN CASE
0311      CASE ANS = ''
0312          GOTO EDIT
0313      CASE ANS = '.'
0314          PERFORM 'LIST FIELD.DESC ID-SUPP'
0315          GOTO EDIT
0316      CASE 1
0317          I=I+1;NC=I
0318          GOSUB STORE
0319          GOTO ENTER
0320      .END CASE
0321  EDIT:
0322      GOSUB FLIST
0323  ACTION:
0324      PRINT
0325      PRINT 'ENTER A FIELD NUMBER TO CHANGE OR'
0326      PRINT 'PRESS "." TO SEE A LIST OF DICTIONARY LIST'
0327      PRINT 'PRESS "RETURN" TO EXECUTE LIST AS IS: '
0328      INPUT A13
0329      BEGIN CASE
0330      CASE NC=0
0331          RETURN
0332      CASE A13='.'
0333          PERFORM 'LIST FIELD.DESC ID-SUPP'
0334      CASE A13=NC+1
0335          GOSUB APPEND1
0336      CASE A13=''
0337          RETURN
0338      CASE A13 > 0 AND A13 <= NC
0339          GOSUB CHANGE1
0340      CASE 1
0341          GOTO EDIT
0342      END CASE
0343      GOTO EDIT
0344      *
0345  APPEND1:
0346      PRINT;PRINT 'ENTER "FIELD NAME" AND "LENGTH":
0347      INPUT ANS
0348      NC=I
0349      GOSUB STORE
0350      GOSUB FIX.LIST
0351      RETURN
0352      *
0353  CHANGE1:
0354      GOSUB FLIST
0355      PRINT
0356      PRINT
0357      PRINT 'ENTER NEW FIELD AND LENGTH'
0358      PRINT;PRINT FLD(A13):' ':FORMAT(A13)
0359      PRINT
0360      INPUT ANS
```

```

0361      I=A13
0362      GOSUB STORE
0363      GOSUB FIX.LIST
0364      RETURN
0365      *
0366 COLS.OUT:
0367      BEGIN CASE
0368      CASE 0.DEVICE=''
0369          GOSUB LIST.COLS
0370      CASE 0.DEVICE='PRINTER'
0371          PRINTER ON
0372          GOSUB LIST.COLS
0373      CASE 0.DEVICE='DOS FILE'
0374          GOSUB SEL.DOS.FILE
0375          GOSUB LIST.COLS.DOS
0376      END CASE
0377      RETURN
0378      *
0379 LIST.COLS:
0380      PRINT @(-1),@(-2)
0381      PERFORM 'GET-LIST LIST.S'
0382      READNEXT @ID ELSE
0383          PRINT;PRINT 'NO RECORDS IN SELECT LIST'
0384          GOSUB PAUSE
0385          RETURN
0386      END
0387      IF 0.DEVICE='PRINTER' THEN PRINTER ON
0388      S=''
0389      FOR I=1 TO NC
0390          SP=FORMAT(I)-LEN(FLD(I))+2
0391          S := FLD(I):SPACE(SP)
0392      NEXT I
0393      PRINT S
0394      PRINT
0395      LOOP
0396      READ @RECORD FROM REV.FILE.U, @ID ELSE
0397          PRINT;PRINT 'ERROR READING FILE ':REV.FILE
0398          GOSUB PAUSE
0399          RETURN
0400      END
0401      S=''
0402      FOR I=1 TO NC
0403          F='L#':FORMAT(I)
0404          S := CALCULATE(FLD(I)) F:
0405      NEXT I
0406      PRINT S
0407      READNEXT @ID ELSE
0408          IF 0.DEVICE='PRINTER' THEN
0409              PRINT;PRINT CM1<1,2>: 'RECORDS PROCESSED'
0410              PRINTER OFF
0411          END
0412          GOSUB PAUSE
0413          RETURN
0414      END
0415      REPEAT
0416      *
0417 LIST.COLS.DOS:
0418      PERFORM 'GET-LIST LIST.S'
0419      R=''
0420      LOOP
0421      READNEXT @ID ELSE
0422          WRITE R TO DOS.FILE.U, DOS.FILE

```

```

0423         RETURN
0424     END
0425     READ @RECORD FROM REV.FILE.V, @ID ELSE
0426     PRINT;PRINT 'ERROR IN FILE ':REV.FILE
0427     GOSUB PAUSE
0428     END
0429     S=SPACE(255)
0430     COL = 1
0431     FOR I=1 TO NC
0432         F = 'L#':FORMAT(I)
0433         S[COL,FORMAT(I)] = CALCULATE(FLD(I)) F
0434         COL += FORMAT(I)+2
0435     NEXT I
0436     R := S[1,COL]:CR:LF
0437     REPEAT
0438     RETURN
0439     *
0440 FLIST:
0441     PRINT @(-1),@(-2)
0442     IF I=0 THEN RETURN
0443     PRINT '        FIELD NAME        LENGTH'
0444     .PRINT
0445     FOR I=1 TO NC
0446         PRINT I:@(4): FLD(I): '        ':@(20):FORMAT(I)
0447     NEXT I
0448     PRINT I
0449     RETURN
0450     *
0451 STORE:
0452     CONVERT ' ' TO FM IN ANS
0453     FLD(I)=ANS<1>
0454     FORMAT(I)=ANS<2>
0455     RETURN
0456     *
0457 FIX.LIST:
0458     IF FLD(I)='' THEN
0459         FOR J=I TO NC
0460             FLD(J)=FLD(J+1)
0461             FORMAT(J)=FORMAT(J+1)
0462         NEXT J
0463         NC=NC-1
0464     END
0465     RETURN
0466     *
0467 O.DEVICE:
0468     PRINT @(-1),@(-2)
0469     PRINT @(1,5): 'CHOOSE OUTPUT DEVICE'
0470     PRINT;PRINT '        1) PRINTER'
0471     PRINT;PRINT '        2) DOS FILE'
0472     PRINT;PRINT '        3) SCREEN'
0473     PRINT;PRINT
0474     PRINT 'ENTER 1, 2 OR 3:'
0475     INPUT ANS
0476     BEGIN CASE
0477     CASE ANS=1: O.DEVICE='PRINTER'
0478     CASE ANS=2: O.DEVICE='DOS FILE'
0479     CASE ANS=3: O.DEVICE=''
0480     CASE 1
0481         PRINT BEL
0482         GOTO O.DEVICE
0483     END CASE
0484     RETURN

```

```

0485      *
0486  LIST.LINES.ALL:
0487      LIST = 'LINES'
0488      GOSUB 0.DEVICE
0489      PRINT @(-1),@(-2)
0490      OPEN ' ', 'LINE.LABELS' TO TITLE.V ELSE
0491      PRINT;PRINT 'CANNOT FIND FILE "LINE.LABELS"'
0492      GOSUB PAUSE
0493      RETURN
0494  END
0495  READ T FROM TITLE.V, 1 ELSE
0496      PRINT;PRINT 'CANNOT READ FILE "LINE.LABELS"'
0497      GOSUB PAUSE
0498      RETURN
0499  END
0500  F=COUNT(T,FM)+1
0501  PERFORM 'GET-LIST LIST.S'
0502  READNEXT @ID ELSE
0503      PRINT;PRINT 'NO RECORDS IN SELECT LIST'
0504      GOSUB PAUSE
0505      RETURN
0506  END
0507  IF 0.DEVICE = 'PRINTER' THEN PRINTER ON
0508  IF 0.DEVICE = 'DOS FILE' THEN
0509      GOSUB LIST.LINES.DOS
0510      RETURN
0511  END
0512  *
0513  LISTM:
0514      READ @RECORD FROM REV.FILE.V, @ID ELSE
0515      PRINTER OFF
0516      PRINT;PRINT 'CANNOT READ FILE ':REV.FILE
0517      GOSUB PAUSE
0518      RETURN
0519  END
0520  K=0
0521  PRINT 'MRDS-REV RECORD NUMBER..... ':@ID
0522  FOR I=1 TO F
0523      LINE=' '
0524      FN=T<I,1,1>
0525      *
0526      - - > FOR DATA
0527      IF FN<0 THEN
0528          FN=T<I+1,1,1>
0529          IF @RECORD<FN> THEN
0530              TI=T<I,1>
0531              HC=COUNT(TI,SM)+1
0532              FOR J=2 TO HC
0533                  LINE=T<I,1,J>
0534                  GOSUB PRINTM
0535              NEXT J
0536          END
0537          *
0538          END ELSE
0539          IF @RECORD<FN> THEN
0540              R=@RECORD<FN>
0541              MVC=COUNT(R,VM)+1
0542              TI=T<I>
0543              COLS=COUNT(TI,VM)+1
0544              FOR MV=1 TO MVC
0545                  FOR J=1 TO COLS
0546                      FN=T<I,J,1>

```

```

0546             LINE := T<I,J,2>: @RECORD<FN,MV> T<I,J,3>
0547             NEXT J
0548             GOSUB PRINTM
0549             NEXT MV
0550             END
0551             END
0552             NEXT I
0553             READNEXT @ID ELSE
0554             PRINT;PRINT CM1<1,2>: ' RECORD(S) PROCESSED '
0555             PRINTER OFF
0556             IF 0.DEVICE='' THEN GOSUB PAUSE
0557             RETURN
0558             END
0559             GOTO LISTM
0560             *
0561 PRINTM:
0562             K=K+1
0563             L=ABS(LEN(LINE)-21)
0564             L=INT(L/59)
0565             L1=LINE[1,79]:CR:LF
0566             IF L>0 THEN
0567             .   FOR M=1 TO L
0568             .       L1 := SPACE(20):LINE[21+(M*59),59]:CR:LF
0569             .       NEXT M
0570             .   END
0571             .   PRINT L1:
0572             .   K += L
0573             .   IF MOD(K,22)=0 AND 0.DEVICE='' THEN PRINT 'PRESS "RETURN"':;
0574             .   - - > INPUT A
0575             .   LINE=''
0576             .   RETURN
0577             *
0578 LIST.LINES.DOS:
0579             PRINT 'LINE LIST TO PC-DOS NOT IMPLEMENTED AT THIS TIME'
0580             GOSUB PAUSE
0581             RETURN
0582             *
0583 SORT:
0584             PERFORM 'GET-LIST LIST':LN
0585             CS='SELECT ':REV.FILE
0586             PRINT @(-1),@(-2)
0587             PRINT
0588             PRINT 'DO YOU WISH OUTPUT TO BE SORTED (Y/N) ?  DEFAULT = N ':
0589             INPUT ANS
0590             IF ANS = '' OR ANS[1,1] = 'N' THEN
0591             .   PERFORM 'SAVE-LIST LIST.S'
0592             .   CS=''
0593             .   RETURN
0594             .   END
0595 ENTERSORT:
0596             PRINT
0597             PRINT 'ENTER DICTIONARY FIELD NAMES TO CONDUCT THE SORT ON '
0598             PRINT 'OR TYPE "." TO SEE DICTIONARY ITEM NAMES'
0599             PRINT 'OR PRESS "RETURN" TO END ENTRIES '
0600             PRINT
0601             LOOP
0602             PRINT 'ENTER FIELD NAME TO SORT ON:
0603             INPUT ANS
0604             IF ANS='.' THEN PERFORM 'LIST FIELD.DESC ID-SUPP':GOTO
0605             - - > ENTERSORT
0606             WHILE ANS
0607             CS := ' BY ':ANS

```

```

0606      REPEAT
0607      PERFORM CS
0608      GOSUB PAUSE
0609      PERFORM 'SAVE-LIST LIST.S'
0610      RETURN
0611      *
0612  SET.RET.TYPE:
0613      PERFORM 'CLEAR'
0614      PRINT @(-1),@(-2)
0615      PRINT
0616      PRINT 'SELECT RETRIEVAL TYPE'
0617      PRINT
0618      PRINT 'HOW DO YOU WISH TO SELECT RECORDS?'
0619      PRINT
0620      PRINT '      1) ALL RECORDS IN FILE ':QUOTE(REV.FILE)
0621      PRINT
0622      PRINT '      2) BY SPECIFYING REVELATION RECORD NUMBER ONLY'
0623      PRINT
0624      PRINT '      3) BY SPECIFYING FIELD NAMES AND THE CONTENTS OF
- - >  FIELDS'
0625      PRINT '      IE. "SELECT MRDS WITH STATE=EQ VA"'
0626      PRINT
0627      PRINT
0628      PRINT 'ENTER 1,2 OR 3: '
0629      INPUT A
0630      BEGIN CASE
0631      CASE A=1: GOSUB RET.ALL
0632      CASE A=2: GOSUB RET.REV.NO
0633      CASE A=3: GOSUB RET.ANY
0634      CASE 1:  GOTO SET.RET.TYPE
0635      END CASE
0636      RETURN
0637      *
0638  ITERATE:
0639      PRINT @(-1),@(-2)
0640      GOSUB LCOM
0641      PRINT
0642      PRINT 'COURSE OF ACTION?'
0643      PRINT '      1) ANOTHER RETRIEVAL ?'
0644      PRINT '      2) GO TO "SORT" OR "PRINT"'
0645      PRINT
0646      PRINT 'CHOOSE 1 OR 2: '
0647      INPUT A2
0648      BEGIN CASE
0649      CASE A2=1
0650          GOSUB FILER
0651          GOSUB COMMANDER
0652          GOTO ITERATE
0653      CASE A2=2 OR A2=' '
0654          CASE 1 ; GOTO ITERATE
0655      END CASE
0656      RETURN
0657      *
0658  FILER:
0659      PRINT @(-1),@(-2)
0660      GOSUB LCOM
0661      PRINT;PRINT
0662      PRINT 'YOU ARE CURRENTLY RETRIEVING FROM FILE "LIST ':LN:'"'
0663      PRINT
0664      PRINT 'SELECT COURSE OF ACTION.  RETRIEVE ON:'
0665      PRINT '      1) CURRENT LIST'
0666      PRINT '      2) AN OLD LIST (SEE LIST ABOVE)'

```

```
0667      PRINT '      3) MAIN :QUOTE(REV.FILE):' FILE: '
0668      INPUT A4
0669      BEGIN CASE
0670      CASE A4=1; PERFORM 'GET-LIST LIST':LN
0671      CASE A4=2; GOSUB FILER1
0672      CASE A4=3;
0673      CASE 1; GOTO FILER
0674      END CASE
0675      RETURN
0676      *
0677  COMMANDER:
0678      PRINT @(-1),@(-2)
0679      GOSUB LCOM
0680      PRINT;PRINT
0681      PRINT 'TO EDIT, APPEND OR RE-RUN AN OLD COMMAND,'
0682      PRINT '      TYPE THE COMMAND NUMBER FROM THE LIST ABOVE'
0683      PRINT
0684      PRINT 'TO START A NEW RETRIEVAL COMMAND,'
0685      PRINT '      PRESS "RETURN"'
0686      PRINT
0687      PRINT 'ENTER NUMBER OR PRESS "RETURN":'
0688      INPUT CN
0689      BEGIN CASE
0690      CASE CN > 0 AND CN < 11
0691          GOSUB SWITCH
0692          GOSUB RECOMMAND
0693      CASE CN=''; GOSUB RET.ANY
0694      CASE 1; GOTO COMMANDER
0695      END CASE
0696      RETURN
0697      *
0698  SWITCH:
0699      CO=''
0700      C=COUNT(CM<CN>,VM)+1
0701      FOR I=1 TO C
0702          CO<I>=CM<CN,I>
0703      NEXT I
0704      RETURN
0705      *
0706  RECOMMAND:
0707      PRINT @(-1),@(-2)
0708      NSUB=COUNT(CO,FM)+1
0709      FOR I=1 TO NSUB
0710          PRINT I:'. ':CO<I>
0711      NEXT I
0712      PRINT I
0713      PRINT;PRINT
0714      PRINT 'ENTER SUBCOMMAND NUMBER TO CHANGE'
0715      PRINT '      OR'
0716      PRINT 'PRESS "RETURN" TO RUN RETRIEVAL AS IS:'
0717      INPUT SUBCN
0718      BEGIN CASE
0719      CASE SUBCN > 0 AND SUBCN <= NSUB
0720          GOSUB CHANGE
0721          GOTO RECOMMAND
0722      CASE SUBCN=''
0723          GOSUB RETR
0724      CASE SUBCN = NSUB+1
0725          GOSUB APPEND:
0726          GOTO RECOMMAND
0727      CASE 1
0728          PRINT BEL
```

```

0729      GOTO RECOMMAND
0730      END CASE
0731      RETURN
0732      *
0733 CHANGE:
0734      PRINT;PRINT
0735      PRINT 'ENTER NEW SUBCOMMAND TO REPLACE:'
0736      PRINT;PRINT '      ':CO<SUBCN>
0737      PRINT;PRINT '      ':
0738      INPUT A14
0739      CO<SUBCN>=A14
0740      IF A14 = '' AND SUBCN < NSUB THEN
0741          FOR I=SUBCN TO NSUB-1
0742              CO<I> = CO<I+1>
0743          NEXT I
0744          CO<NSUB>=''
0745      END
0746      RETURN
0747      *
0748 APPEND:
0749      PRINT;PRINT
0750      PRINT 'ENTER NEXT SUBCOMMAND:'
0751      INPUT A14
0752      CO<SUBCN>=A14
0753      RETURN
0754      *
0755 LCOM:
0756      PRINT @(-1),@(-2)
0757      FOR I=10 TO 1 STEP -1
0758          C=CM1<I,1>
0759          IF C > 0 THEN
0760              PRINT I:". ":
0761              FOR J= 1 TO C
0762                  PRINT CM<I,J>:" ":
0763              NEXT J
0764              PRINT;PRINT '      ':CM1<I,2>:" RECORD(S) SELECTED':
0765              PRINT ' AND STORED IN LIST ' :CM1<I,3>
0766          END
0767      NEXT I
0768      RETURN
0769      *
0770 FILER1:
0771      GOSUB LCOM
0772      PRINT;PRINT
0773      PRINT 'SPECIFY "LIST #" FILE NUMBER TO RETRIEVE ON'
0774      PRINT;PRINT 'ENTER LIST NUMBER: ':
0775      INPUT A10
0776      IF A10<1 OR A10>LN THEN PRINT BEEP;GOTO FILER1
0777      PERFORM 'GET-LIST LIST':A10
0778      RETURN
0779      *
0780 PAUSE:
0781      PRINT @(-1,25): 'PRESS "RETURN" TO CONTINUE: ':
0782      INPUT A11
0783      RETURN
0784      *
0785 SAVER:
0786      LN=LN+1
0787      PERFORM 'SAVE-LIST LIST':LN
0788      CM1<1,3>=LN
0789      RETURN
0790      *

```



```

0791  RETR:
0792      GOSUB PUSH
0793      NSUB=COUNT(CO,FM)+1
0794      CM1<1,1>=NSUB
0795      CMD=''
0796      FOR I=1 TO NSUB
0797          CMD := CO<I>:
0798          CM<1,I>=CO<I>
0799      NEXT I
0800      PERFORM CMD
0801      GOSUB PAUSE
0802      GOSUB SAVER
0803      PERFORM 'GET-LIST LIST':LN
0804      I=0
0805      LOOP
0806          READNEXT @ID ELSE GOTO CONT1:
0807          I=I+1
0808          PRINT @ID
0809      REPEAT
0810  CONT1:
0811      CM1<1,2>=I
0812      .RETURN
0813      *
0814  PUSH:
0815      FOR I=10 TO 2 STEP -1
0816          CM<I>=CM<I-1>
0817          CM1<I>=CM1<I-1>
0818      NEXT I
0819      CM<1>=''
0820      CM1<1>=''
0821      RETURN
0822      *
0823  RET.ALL:
0824      GOSUB START.CO
0825      GOSUB RETR
0826      RETURN
0827      *
0828  RUN.RERUN:
0829      PRINT @(-1):@(-2)
0830      PRINT @(14,3):'GENERAL PURPOSE RETRIEVAL AND PRINTING PROGRAM'
0831      PRINT @(25,6):'by PAUL SCHRUBEN, MRDS'
0832      PRINT @(16,13):'CHOOSE COURSE OF ACTION:'
0833      PRINT @(19,16):'1) CREATE NEW RETRIEVAL'
0834      PRINT @(19,18):'2) RE-RUN A RETRIEVAL SAVED IN AN EARLIER
- - > SESSION'
0835      PRINT @(16,21):'CHOOSE 1 OR 2: '
0836      INPUT ANS
0837      BEGIN CASE
0838      CASE ANS = 1
0839          GOSUB IFILE
0840          RETURN
0841      CASE ANS=2
0842          GOSUB USE.RET
0843          GOTO RUN.RERUN
0844      CASE ANS=''
0845          STOP
0846      CASE 1
0847          PRINT BEL
0848          GOTO RUN.RERUN
0849      END CASE
0850      *
0851  IFILE:

```

```

0852      PRINT @(-1),@(-2)
0853      PRINT @(5,10):'ENTER NAME OF FILE TO BE RETRIEVED.  DEFAULT =
      - - > MRDS : '
0854      INPUT REV.FILE
0855      PRINT
0856      IF REV.FILE='' THEN REV.FILE='MRDS'
0857      GOSUB OPEN
0858      IF REV.FILE THEN RETURN
0859      GOTO IFILE
0860      *
0861  OPEN:
0862      OPEN '', REV.FILE TO REV.FILE.U ELSE
0863          PRINT BEL;PRINT 'CANNOT OPEN FILE "':REV.FILE:''
0864          REV.FILE=''
0865          GOSUB PAUSE
0866          RETURN
0867      END
0868      OPEN 'DICT', REV.FILE TO @DICT ELSE
0869          PRINT BEL;PRINT 'CANNOT FIND DICTIONARY FOR FILE "':REV.FILE:''
0870          REV.FILE=''
0871          GOSUB PAUSE
0872      .END
0873      RETURN
0874      *
0875  START.CO:
0876      CO=''
0877      CO<1>='SELECT ':REV.FILE
0878      SUBN=1
0879      RETURN
0880      *
0881  SAVE.RET:
0882      CO=''
0883      FOR I=1 TO CM1<1,1>
0884          CO<I>=CM<1,I>
0885      NEXT I
0886      C=CO<1>
0887      CONVERT ' ' TO VM IN C
0888      CO<1>=C<1,2>
0889      IF CS THEN
0890          CO<I>='SORT'
0891          CONVERT 'BY' TO FM IN CS
0892          J=2
0893          LOOP
0894              WHILE CS<J>
0895                  I=I+1
0896                  CO<I>=CS<J>
0897                  J=J+1
0898              REPEAT
0899                  I=I+1
0900      END
0901      BEGIN CASE
0902      CASE 0.DEVICE='PRINTER'
0903          CO<I>='PRINTER'
0904          I=I+1
0905      CASE 0.DEVICE='DOS.FILE'
0906          CO<I>='DOS FILE'
0907          CO<I+1>=DOS.FILE
0908          I=I+2
0909      END CASE
0910      BEGIN CASE
0911      CASE LIST = 'DEFAULT'
0912          CO<I> = 'LIST'

```

```

0913      CO<I+1> = 'DEFAULT'
0914      CASE LIST = 'COLUMNS'
0915      CO<I> = 'LIST'
0916      I=I+1
0917      CO<I>='COLUMNS'
0918      FOR J=1 TO NC
0919          CO<I+J,1>=FLD(J):' ':FORMAT(J)
0920          *      CO<I+J,2>=FORMAT(J)
0921      NEXT J
0922      CASE LIST = 'LINES'
0923      CO<I>='LIST'
0924      CO<I+1>='LINES'
0925      END CASE
0926      RETURN
0927      *
0928  WRITE.RET:
0929      OPEN '', 'RETRIEVALS' TO R.V ELSE
0930          PERFORM 'CREATE-FILE RETRIEVALS 100 1000'
0931      OPEN '', 'RETRIEVALS' TO R.V ELSE
0932          PRINT 'CANNOT OPEN FILE RETRIEVALS'
0933          GOSUB PAUSE
0934          RETURN
0935      END
0936      END
0937      PERFORM 'LIST ONLY RETRIEVALS'
0938      PRINT;PRINT 'ENTER A SUB-FILE NAME TO SAVE THE RETRIEVAL
- - >  COMMANDS IN: '
0939      INPUT ANS
0940      IF ANS='' THEN RETURN
0941      READ R FROM R.V, ANS ELSE
0942  WRITE:
0943      WRITE CO TO R.V, ANS
0944      RETURN
0945      END
0946      PRINT;PRINT 'FILE "'ANS'" ALREADY EXISTS!  OVERWRITE? (Y/N):
- - > '
0947      INPUT A
0948      IF A[1,1] = 'Y' THEN
0949          PERFORM 'DELETE R.V, ANS'
0950          WRITE CO TO R.V, ANS
0951          PRINT;PRINT 'SUB-FILE ':QUOTE(ANS):' HAS BEEN SAVED IN FILE
- - >  "RETRIEVALS"
0952          PRINT; GOSUB PAUSE
0953      END
0954      RETURN
0955      *
0956  TERMINUS:
0957      PRINT @(-1),@(-2)
0958      PRINT;PRINT 'CHOOSE A COURSE OF ACTION:'
0959      PRINT
0960      PRINT;PRINT '      1) SORT AGAIN'
0961      PRINT;PRINT '      2) PRINT AGAIN'
0962      PRINT;PRINT '      3) RETRIEVE AGAIN'
0963      PRINT;PRINT '      4) SAVE SESSION'
0964      PRINT;PRINT '      5) END SESSION'
0965      PRINT @(-1,20):'ENTER 1, 2, 3, 4 OR 5:'
0966      INPUT A18
0967      RETURN
0968      *
0969  USE.RET:
0970      OPEN '', 'RETRIEVALS' TO R.V ELSE
0971          PRINT 'CANNOT OPEN FILE RETRIEVALS'

```

```

0972      GOSUB PAUSE
0973      RETURN
0974      END
0975      PERFORM 'LIST ONLY RETRIEVALS'
0976      PRINT;PRINT 'CHOOSE FROM THE ABOVE LIST OF RETRIEVAL COMMAND
- - > FILES: ':
0977      INPUT ANS
0978      IF ANS = '' THEN RETURN
0979      READ R FROM R.V, ANS ELSE
0980          PRINT 'CANNOT FIND FILE "'ANS:" IN FILE RETRIEVALS'
0981          GOSUB PAUSE
0982          GOTO USE.RET
0983      END
0984      REV.FILE=R<1>
0985      GOSUB OPEN
0986      CO='SELECT ':R<1>
0987      CS='SELECT ':R<1>
0988      O.DEVICE=''
0989      J=2
0990      LOOP
0991      UNTIL R<J>='SORT' OR R<J>='PRINTER' OR R<J>='DOS FILE' OR
- - > R<J>='LIST' OR R<J>=''
0992      CO := ' ':R<J>
0993      J=J+1
0994      REPEAT
0995      GOSUB RETR
0996      PERFORM 'GET-LIST LIST':LN
0997      IF R<J>='SORT' THEN
0998          J=J+1
0999          LOOP
1000          UNTIL R<J>='PRINTER' OR R<J>='DOS FILE' OR R<J>='LIST'
1001          CS := ' BY ':R<J>
1002          J=J+1
1003          REPEAT
1004          PERFORM CS
1005      END
1006      PERFORM 'SAVE-LIST LIST.S'
1007      PERFORM 'GET-LIST LIST.S'
1008      IF R<J>='PRINTER' THEN
1009          O.DEVICE=R<J>
1010          J=J+1
1011      END ELSE
1012          IF R<J>='DOS FILE' THEN
1013              O.DEVICE=R<J>
1014              DOS.FILE=R<J+1>
1015              GOSUB OPEN.DOS
1016              J=J+2
1017          END
1018      END
1019      IF R<J>='LIST' THEN
1020          J=J+1
1021          BEGIN CASE
1022          CASE R<J>=''
1023              OUT='DEFAULT'
1024          CASE R<J>='DEFAULT'
1025              OUT=R<J>
1026          CASE R<J>='COLUMNS'
1027              OUT=R<J>
1028              NC=0
1029              LOOP
1030                  J=J+1
1031              WHILE R<J>

```

```
1032          NC=NC+1
1033          F=R<J>
1034          CONVERT ' ' TO FM IN F
1035          FLD(NC)=F<1>
1036          FORMAT(NC)=F<2>
1037          REPEAT
1038          CASE R<J>='LINES'
1039          OUT='LINES'
1040          CASE 1
1041          PRINT; PRINT 'CANNOT UNDERSTAND COMMAND "':R<J>:'
1042          GOSUB PAUSE
1043          RETURN
1044          END CASE
1045          END
1046          BEGIN CASE
1047          CASE OUT='DEFAULT'
1048          IF O.DEVICE='' THEN PERFORM 'LIST ':R<1>
1049          IF O.DEVICE = 'PRINTER' THEN PERFORM 'LIST ':R<1>:' '
1050          IF O.DEVICE = 'DOS FILE' THEN GOSUB DEFAULT.DOS
1051          CASE OUT = 'COLUMNS'
1052          IF O.DEVICE='' OR O.DEVICE='PRINTER' THEN
1053          GOSUB LIST.COLS
1054          END
1055          IF O.DEVICE='DOS FILE' THEN
1056          GOSUB OPEN.DOS
1057          GOSUB LIST.COLS.DOS
1058          END
1059          END CASE
1060          RETURN
1061 EOP:
1062          END
```

```

0001      BEL=CHAR(7)
0002      LF=CHAR(10)
0003      CR=CHAR(13)
0004      CZ=CHAR(26)
0005      VM=CHAR(253)
0006      FM=CHAR(254)
0007      RM=CHAR(255)
0008      TC=' '
0009      T2=' '
0010      F=' '
0011      V=' '
0012      FLD=0
0013      PROMPT ' '
0014  START:
0015      PRINT @(-1),@(-2)
0016      PRINT;PRINT 'THIS PROGRAM CONVERTS A GIPSY FILE TO REVELATION
- - > FORMAT'
0017      PRINT;PRINT
0018      PRINT 'INPUT FORMAT:      GIPSY DICTIONARY "UG9225M.CVD01.DATA"'
0019      PRINT '                  PC-DOS FORMAT'
0020      PRINT '                  "@" = RECORD MARKER'
0021      PRINT '                  "-" = FIELD MARKER'
0022      PRINT
0023      PRINT 'OUTPUT FORMAT:      MRDS REVELATION FILE FORMAT'
0024      PRINT;PRINT
0025      PRINT 'ENTER PCDOS GIPSY INPUT FILE NAME .....DEFAULT =
- - > "C:MDOS.0":'
0026      INPUT DOS.FILE
0027      IF DOS.FILE = ' ' THEN DOS.FILE='C:MDOS.0'
0028      OPEN ' ', 'DOS' TO DOS.FILE.V ELSE STOP
0029      READ T FROM DOS.FILE.V, DOS.FILE ELSE
0030          PRINT;PRINT BEL
0031          PRINT 'CANNOT READ FILE "':DOS.FILE:' ". ARE YOU SURE IT
- - > EXISTS?'
0032          GOSUB PAUSE
0033          GOTO START
0034      END
0035      CONVERT '_' TO VM IN T
0036      CONVERT '@' TO FM IN T
0037      CONVERT CR:LF:CZ TO ' ' IN T
0038      *
0039      L=COUNT(T,FM)
0040      FOR I=1 TO L
0041          PRINT @(-1),@(-2)
0042          PRINT 'DATA VALIDATION AND TRANSLATION FOR RECORD ':I
0043          PRINT
0044          P=T<I,116>
0045          Y=T<I,117>
0046          NO=T<I,118>
0047          LG=T<I,119>
0048          M=T<I,120>
0049          S=T<I,121>
0050          U=T<I,122>
0051          BEGIN CASE
0052          CASE Y
0053              IF LG THEN A='L'; GOTO E:
0054              IF M THEN A='M'; GOTO E:
0055              IF S THEN A='S'; GOTO E:
0056              A='Y'
0057  E:
0058          CASE NO
0059              A='N'

```

```

0060      CASE P='PROD';A='Y'
0061      CASE P[1,1]='Y'; A='Y'
0062      CASE P[1,1]='N'; A='N'
0063      CASE 1
0064          A='U'
0065      END CASE
0066      T<I,116>=A
0067      PRINT
0068      PRINT 'GIPSY      PROD:      ':P:      REVELATION:      ':A
0069      PRINT '      YES      ':Y
0070      PRINT '      LARGE:      ':LG
0071      PRINT '      MEDIUM:      ':M
0072      PRINT '      SMALL:      ':S
0073      PRINT '      NO:      ':NO
0074      PRINT '      UND:      ':U
0075      A=T<I,41>
0076      E=T<I,42>
0077      BEGIN CASE
0078      CASE A='' AND E<>''
0079          T<I,41>=E
0080      CASE A<>'' AND E=''
0081      CASE A<>'' AND E<>''
0082          PRINT 'ACC = ':A:      EST = ':E
0083          PRINT 'YOUR TRANSLATION IS : '
0084          INPUT A
0085          T<I,41>=A
0086      CASE 1
0087      END CASE
0088      PRINT
0089      PRINT 'GIPSY      ACC:      ':A:      REVELATION      ':S
0090      PRINT '      EST:      ':E
0091      S=T<I,102>
0092      U=T<I,103>
0093      SU=T<I,104>
0094      BEGIN CASE
0095      CASE S='S' OR S='SURFACE'
0096          T<I,102>='S'
0097      CASE U='U' OR U='UNDERGROUND'
0098          T<I,102>='U'
0099      CASE SU='SU' OR SU='SURFACE AND UNDERGROUND'
0100          T<I,102>='B'
0101      CASE S='' AND U='' AND SU=''
0102      CASE 1
0103          PRINT 'ENTRY FOR SURFACE, UNDERGROUND = ':C
0104          PRINT 'YOUR TRANSLATION IS (S,U,B) ? '
0105          INPUT C
0106          T<I,102>=C
0107      END CASE
0108      PRINT
0109      PRINT 'GIPSY      SURFACE:      ':S:      REVELATION      ':T<I,
- - > 102>
0110      PRINT '      UNDERGROUND:':U
0111      PRINT '      SURF & UND6:':SU
0112      PRINT
0113      GOSUB PAUSE
0114      NEXT I
0115      REV.FILE:
0116      PRINT @(-1),@(-2)
0117      PRINT 'ENTER REVELATION FILE NAME (DESTINATION FILE)'
0118      PRINT:PRINT 'DEFAULT = "MRDS": '
0119      INPUT REV.FILE
0120      IF REV.FILE='' THEN REV.FILE = 'MRDS'

```

```

0121      OPEN '', REV.FILE TO REV.FILE.V ELSE
0122      PERFORM 'CREATE-FILE ':REV.FILE
0123      OPEN '', REV.FILE TO REV.FILE.V ELSE
0124      PRINT;PRINT BEL
0125      PRINT 'CANNOT OPEN FILE "':REV.FILE:'"'
0126      GOSUB PAUSE
0127      GOTO REV.FILE
0128      END
0129      D='(DICT ':REV.FILE
0130      DATA D
0131      PERFORM 'COPY DICT MRDS * (OS)'
0132      END
0133      PERFORM 'SORT ':REV.FILE
0134      PRINT;PRINT 'ENTER STARTING RECORD NUMBER FOR NEW RECORDS:
0135      INPUT N
0136      OPEN '', 'DR' TO DR.V ELSE GOTO ND
0137      READ GDICT FROM DR.V, 'GIPDICT' ELSE
0138 ND:      PRINT;PRINT 'CANNOT FIND GIPSY DICTIONARY IN "DR" FILE'
0139      GOSUB PAUSE
0140      STOP
0141      .END
0142      CDICT=COUNT(GDICT,FM)+1
0143      PRINT @(-1),@(-2)
0144      PRINT @ (1,10): 'PATIENCE.....READING DICTIONARY FILE'
0145      FOR J=1 TO CDICT
0146          FLD=GDICT<J>
0147          FLD=FLD[60,3]
0148          FLD=TRIMF(FLD)
0149          F<J>=FLD
0150          VAL=GDICT<J>
0151          VAL=VAL[65,3]
0152          VAL=TRIMF(VAL)
0153          V<J>=VAL
0154      NEXT J
0155      FOR I=1 TO L
0156          PRINT @(-1),@(-2)
0157          PRINT @ (1,10): 'WORKING ON RECORD NUMBER ':I:' OF ':L
0158          T2=''
0159          FOR J=1 TO CDICT
0160              FLD=F<J>
0161              VAL=V<J>
0162              IF VAL='' THEN VAL=1
0163              IF FLD AND T<I,J> THEN
0164                  T2<FLD,VAL>=T<I,J>
0165                  IF FLD=118 OR FLD=124 OR FLD=132 OR FLD=140 OR FLD=148 THEN
0166                      *SPLIT "ITEM" AND "ACC" FIELDS
0167                      T0=T<I,J>
0168                      ITEM=T0[1,9]
0169                      ACC=T0[11,3]
0170                      T2<FLD,VAL>=ITEM
0171                      T2<FLD+1,VAL>=ACC
0172                  END
0173              END
0174          NEXT J
0175          WRITE T2 TO REV.FILE.V, I+N-1
0176      NEXT I
0177      STOP
0178      *
0179      PAUSE:
0180      PRINT @ (1),@ (25)
0181      PRINT 'PRESS "RETURN" TO CONTINUE:

```



PROGRAM LISTING FOR 62R

11:59:52 29 OCT 1985

0183 INPUT A

0184 RETURN

0185 END

```

0001      * CONVERTS MRDS-REV FILE TO PC-DOS FILE, GIPSY ORDER
0002      *
0003      * T<> = REV FIELDS IN GIPSY ORDER
0004      * R<> = REV FIELDS IN REV ORDER
0005      * GF<> = GIPSY FIELD NUMBER
0006      * RN<> = REV FIELD NUMBER
0007      * RV<> = REV VALUE NUMBER
0008      LF=CHAR(10)
0009      CR=CHAR(13)
0010      Z=CHAR(26)
0011      SM=CHAR(252)
0012      VM=CHAR(253)
0013      FM=CHAR(254)
0014      RM=CHAR(255)
0015      BEL=CHAR(7)
0016      K=''
0017      L=''
0018      T=''
0019      RN=''
0020      RV=''
0021      GN=''
0022      GD=''
0023      GF=''
0024      TC=''
0025      RO=''
0026      FLD=0
0027      VAL=0
0028      PROMPT ' '
0029      *
0030  START:
0031      PRINT @(-1),@(-2)
0032      PRINT 'THIS PROGRAM CONVERTS REVELATION FILES TO PC-DOS FORMAT'
0033      PRINT;PRINT '      INPUT FORMAT:      MRDS DICTIONARY, REVELATION
- - > FORMAT'
0034      PRINT;PRINT '      OUTPUT FORMAT:      GIPSY "BUILD", PC-DOS FORMAT'
0035      GOSUB GDICT
0036      *
0037  REV.FILE:
0038      PRINT;PRINT 'ENTER REVELATION FILE NAME (SOURCE FILE)'
0039      PRINT;PRINT 'DEFAULT = "MRDS": '
0040      INPUT REV.FILE
0041      IF REV.FILE='' THEN REV.FILE = 'MRDS'
0042      OPEN ' ', REV.FILE TO REV.FILE.V ELSE
0043          PRINT 'CANNOT FIND ' :REV.FILE
0044          GOSUB PAUSE
0045          GOTO START
0046      END
0047  LST:
0048      PERFORM 'SORT ' :REV.FILE
0049      PRINT;PRINT 'ENTER STARTING RECORD NUMBER TO BE TRANSFORMED:
0050      INPUT M
0051      IF M='' THEN GOTO REV.FILE
0052      PRINT;PRINT 'ENTER ENDING RECORD NUMBER TO BE TRANSFORMED:
0053      INPUT N
0054      *
0055      GOSUB OF:
0056      *
0057      FOR I= M TO N
0058          PRINT @(-1),@(-2)
0059          PRINT @(1,10): 'WORKING ON RECORD NUMBER ' :I-M+1: ' OF ' :N-M+1
0060          READ R FROM REV.FILE.V, I ELSE
0061          PRINT @(-1),@(-2)

```

```
0062      PRINT:PRINT 'CANNOT FIND RECORD ':I
0063      GOSUB PAUSE
0064      GOTO LST
0065      END
0066      *                PUT REV RECORD IN GIPSY ORDER
0067      T=' '
0068      FOR J=1 TO GC
0069          K=RN<J>
0070          L=RV<J>
0071          IF R<K,L> THEN
0072              T<J>=R<K,L>
0073              IF K=118 OR K=124 OR K=132 OR K=140 OR K=148 THEN
0074                  T1=T<J>:SPACE(10)
0075                  *      COMBINE "ITEM" AND "ACC" FIELDS
0076                  T<J>=T1[1,10]:R<K+1,L>
0077              END
0078          END
0079      NEXT J
0080      *
0081      *  SPECIAL CHANGES FOR GIPSY FORMAT
0082      P=T<116>
0083      T<116>=' '
0084      IF P THEN
0085          IF P='Y' THEN T<117>=' '
0086          IF P='L' THEN T<119>=' '
0087          IF P='M' THEN T<120>=' '
0088          IF P='S' THEN T<121>=' '
0089          IF P='N' THEN T<118>=' '
0090          IF P='U' THEN T<122>=' '
0091      END ELSE
0092          T<116>=' '
0093      END
0094      S=T<102>
0095      IF S THEN
0096          IF S='S' THEN T<102>=' '
0097          IF S='U' THEN T<103>=' '
0098          IF S='B' THEN T<104>=' '
0099      END ELSE
0100          T<102>=' '
0101      END
0102      IF T<41> THEN
0103          IF T<41> NE 'ACC' THEN
0104              T<42>=T<41>
0105              T<41>=' '
0106          END
0107      END
0108      *
0109      L=1
0110      RO<I,L>=SPACE(9):'CRIB':CR
0111      RECNO=R<1>:SPACE(9)
0112      RECNO=RECNO[1,9]
0113      FOR J=1 TO GC
0114          IF T<J> THEN
0115              L=L+1
0116              T1=GF<J>:'<':T<J>:'>'
0117              LN=LEN(T1)
0118              NSV=INT((LN+70)/71)
0119              FOR K=1 TO NSV
0120                  RO<I,L,K>=RECNO:T1[71*K-70,71]:CR
0121              NEXT K
0122          END
0123      NEXT J
```

```

0124      C=SPACE(9):'@':CR
0125      RO<I,L+1>=C
0126      NEXT I
0127      CONVERT SM TO LF IN RO
0128      CONVERT VM TO LF IN RO
0129      CONVERT FM TO LF IN RO
0130      WRITE RO TO DOS.FILE.V, DOS.FILE
0131      PRINT BEL
0132      STOP
0133      *
0134  OF:
0135      PRINT;PRINT 'ENTER PC DOS-GIPSY OUTPUT FILE NAME (DESTINATION
- - > FILE)'
0136      PRINT;PRINT 'DEFAULT = "C:MDOS.0" ' :
0137      INPUT DOS.FILE
0138      IF DOS.FILE = '' THEN DOS.FILE='C:MDOS.0'
0139      OPEN '', 'DOS' TO DOS.FILE.V ELSE
0140          PRINT;PRINT 'CANNOT OPEN FILE ':DOS.FILE
0141          GOSUB PAUSE
0142          GOTO OF:
0143      END
0144      RETURN
0145      *
0146  PAUSE:
0147      PRINT
0148      PRINT @(1),@(25)
0149      PRINT 'PRESS "RETURN" TO CONTINUE: ' :
0150      INPUT A
0151      RETURN
0152      *
0153  GDICT:
0154      PRINT;PRINT;PRINT 'PATIENCE..... READING GIPSY DICTIONARY
- - > FILE'
0155      OPEN '', 'DR' TO DR.V ELSE GOTO ND
0156      READ GD FROM DR.V, 'GIPDICT' ELSE
0157  ND:
0158          PRINT;PRINT 'CANNOT FIND GIPSY DICTIONARY IN "DR" FILE'
0159          GOSUB PAUSE
0160          STOP
0161      END
0162      GC=COUNT(GD,FM)+1
0163      RF=0
0164      FOR I=1 TO GC
0165          FLD=GD<I>
0166          FLD=FLD[60,3]
0167          FLD=TRIMF(FLD)
0168          RN<I>=FLD
0169          *
0170          VAL=GD<I>
0171          VAL=VAL[65,3]
0172          VAL=TRIMF(VAL)
0173          RV<I>=VAL
0174          IF NOT(RV<I>) THEN RV<I>=1
0175          *
0176          G=GD<I>
0177          G=G[1,4]
0178          GF<I>=TRIMB(G)
0179      NEXT I
0180      RETURN
0181      END

```

[illegible]

F5=Toggle MAIN/LAST menu    Ctl-F5=TCL    F9=END menu    Retrnr=Run menu option

[illegible]

F5=Toggle MAIN/LAST menu    Ct1-F5=TCL    F9=END menu    Retrnr=Run menu option

1) RECORD IDENTIFICATION

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 REC NUMBER B10

03 REC TYPE B20

04 DEP NO. B40

05 REP DATE G1

06 INFO SOURCE B30

07 FILE LINK ID B50

08 REPORTER (SUPERVISOR) G2

09 REPORTER AFFILIATION G5

10 SITE NAME A10

11 SYNONYMS A11

MRDS-REV RECORD NUMBER (DEFAULT=1)

2) LOCATION

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 MINING DISTRICT/AREA A30

03 COUNTY A60

04 STATE A50

05 COUNTRY A40

06 PHYSIOGRAPHIC PROVINCE A63

07 DRAINAGE AREA A62

08 LAND STATUS A64

09 QUADRANGLE NAME A90

10 QUADRANGLE SCALE A100

11 SECOND QUAD NAME A92

12 SECOND QUAD SCALE A91

13 ELEVATION A107

UTM COORDINATES

GEODETTIC COORDINATES

14 NORTHING A120

17 LATITUDE A70

15 EASTING A130

18 LONGITUDE A80

16 ZONE NUMBER A110

3) LOCATION (cont.)

E1 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 ACC or EST

CADASTRAL

03 TOWNSHIP A77

04 RANGE A79

05 SECTION A79

06 SECTIONAL FRACTION(S) A76

07 MERIDIAN(S) A81

08 POSITION FROM NEAREST LOCALITY A82

09 LOCATION COMMENTS A83

4) COMMODITIES

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 COMMODITIES PRESENT

03 ORE MATERIALS

04 COMMODITY SUBTYPES

05 GENERAL ANALYTICAL DATA

06 COMMODITY INFO COMMENTS C50

PRODUCER

NON-PRODUCER

07 MAJOR

11 MAIN

08 MINOR

12 MINOR

09 POTEN

10 OCCUR

13 PRODUCTION SML MED LGE NO UND

14 STATUS

5) EXPLORATION OR DEVELOPMENT  
02 DISCOVERER L20

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

03 YEAR OF DISCOVERY L10  
05 YEAR OF FIRST PROD. L10  
07 PRESENT/LAST OWNER A12

04 NATURE OF DISCOVERY L30  
06 YEAR OF LAST PROD. L45

08 PRESENT/LAST OPERATOR A13

09 EXPL./DEV. COMMENTS L110

DESCRIPTION OF DEPOSIT  
10 DEPOSIT TYPE C40

11 DEPOSIT FORM/SHAPE M10

12 DEPTH TO TOP                      UNITS  
14 DEPTH TO BTM                     UNITS

16 MAX. LENGTH                    UNITS  
18 MAX. WIDTH                    UNITS  
20 MAX. THICK                    UNITS

6) DESCRIPTION OF DEPOSIT (cont.)  
02 DEPOSIT SIZE M15  
03 STRIKE M70  
04 PLUNGE DIRECTION M110  
07 DEPOSIT DESCRIPTION COMMENTS M110

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

04 DIP M80  
06 PLUNGE M90

#### DESCRIPTION OF WORKINGS

08 WORKINGS ARE: (SURFACE, UNDERGROUND, BOTH)

09 DEPTH BELOW SURFACE M160	10 UNITS M161
11 LENGTH OF WORKINGS M170	12 UNITS M171
13 OVERALL LENGTH M190	14 UNITS M191
15 OVERALL WIDTH M200	16 UNITS M201
17 OVERALL AREA M210	18 UNITS M211
19 DESCRIPTION OF WORKINGS COMMENTS M220	



7) GEOLOGY  
02 AGE OF HOST ROCK(S) K1  
03 HOST ROCK TYPE(S) K1A  
  
04 AGE OF IGNEOUS ROCK(S) K2  
05 IGNEOUS ROCK TYPE(S) K2A  
  
06 AGE OF MINERALIZATION K3  
07 PERT. MINERALS (NOT ORE) K4  
  
08 ORE CONTROL/LOCUS K5  
  
09 MAJ. REG. TRENDS/STRUCT. N5  
  
10 TECTONIC SETTING N15  
  
11 SIGNIFICANT LOCAL STRUCT. N70  
  
12 SIGNIFICANT ALTERATION N75

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

8) GEOLOGY (cont.)  
02 PROCESS OF CONC./ENRICH. N80  
  
03 FORMATION AGE N30  
04 FORMATION NAME N30A  
  
  
  
07 IGNEOUS UNIT AGE N50  
08 IGNEOUS UNIT NAME N50A  
  
  
11 GEOLOGY COMMENTS

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

9) GENERAL COMMENTS

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 GENERAL COMMENTS GEN

10) BIBLIOGRAPHIC REFERENCES

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 REFERENCE 1

03 REFERENCE 2

04 REFERENCE 3

05 REFERENCE 4

11) ANNUAL PRODUCTION

01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 ITEM	ACC	AMOUNT	TH UNITS	YEAR	GRADE
---------	-----	--------	----------	------	-------

CUMULATIVE PRODUCTION

08 ITEM	ACC	AMOUNT	TH UNITS	YEARS	GRADE
---------	-----	--------	----------	-------	-------

14 SOURCE OF INFORMATION

15 COMMENTS

12) RESERVES AND POTENTIAL RESOURCES 01 MRDS-REV RECORD NUMBER \_\_\_\_ (I-1)

02 ITEM	ACC	AMOUNT	TH UNITS	YEAR	GRADE
---------	-----	--------	----------	------	-------

08 SOURCE OF INFORMATION

09 COMMENTS

RESERVES ONLY

10 ITEM	ACC	AMOUNT	TH UNITS	YEAR	GRADE
---------	-----	--------	----------	------	-------

16 SOURCE OF INFORMATION

17 COMMENTS

POTENTIAL RESOURCES

18 ITEM	ACC	AMOUNT	TH UNITS	YEAR	GRADE
---------	-----	--------	----------	------	-------

24 SOURCE OF INFORMATION

25 COMMENTS