

Stratum	SAMPLER* TYPE	BLOW COUNT ⁺		PERCENT RECOVERY (See note below)				DRILLING RATE [†] MINUTES PER FOOT					REVES. PER MINUTE	
		● WATER CONTENT, %		20	40	60	80	WEIGHT ON BIT, KIPS						
		20	40					5	10	15	20	25		
1000														
XX V														
1010														
1020														
XX VI														
1030														
1040														
1050														
1060														
1070														
1080														
1090														
1100														
1110														
1200														
1300														
1400														
1500														
1600														
1700														
1800														
1900														
2000														
Job No. : 0185-1032 Final Penetration : 1045.9' Date Completed : March 31, 1985 †Water Depth Measured : at 1910 hrs on March 15, 1985		*SAMPLER TYPE SS - 3 00-in split-barrel TW - 3 00-in thick-wall TT - 2 25-in thin-wall TS - 3 00-in thin-wall LY - Longyear system CD - Christensen system		†Number of blows of a 300-lb weight dropped approx 5-ft required to produce a 12-in. pen- etration, except where noted, of a 3 00-in-OD, 2 50-in-ID taper tube sampler.				$\% \text{ Rec.} = \frac{\text{Total Sample Recovered}}{\text{Total Interval Drilled}}$ $\% \text{ Rec.} = \frac{\text{Total Sample Recovered}}{\text{Total Interval Sampled}}$ (Solid line indicates total interval drilled)					†The drilling rate is expressed by a solid line and the weight on bit by a dashed line. No line is given for drilling rate when the core barrel spun through the formation.	

LOG AND TEST RESULTS
 BORING KBZ-4, KOA CRATER
 ENEWETAK ATOLL, MARSHALL ISLANDS