

PLATE 20B

Stratum	Description	SAMPLER TYPE	BLOW COUNT †		PERCENT RECOVERY (See note below)				DRILLING RATE † MINUTES PER FOOT					REVES. PER MINUTE		
			● WATER CONTENT, %						WEIGHT ON BIT, KIPS							
			20	40	20	40	60	80	5	10	15	20	25	100	200	
200	Light brown fine to coarse carbonate silty sand	TW														
210	-with coral and shell fragments, 210.2' to 234.3'	TW														
220		TW														
230	-brown, 230.4' to 234.3' (234.3')	TW														
240	Light brown fine to coarse carbonate sand intermixed with coral gravel (243.3')	TW														
250	Light brown medium to coarse carbonate sand with coral and limestone gravel (258.5')	TW														
260	Light brown fine to coarse carbonate silty sand with coral and limestone fragments	TW														
270		TW														
280		TW														
283.5'		TW														
290																
300																
310																
320																
330																
340																
350																
360																
370																
380																
390																
400																

Job No.: 0185-1032
 Final Penetration: 283.5'
 Date Completed: June 2, 1985
 †Water Depth Measured: at 0555 hrs on June 1, 1985

*SAMPLER TYPE
 SS - 3.00-in split-barrel
 TW - 3.00-in. thick-wall
 TT - 2.25-in. thin-wall
 TS - 3.00-in. thin-wall
 LY - Longyear system
 CD - Christensen system

†Number of blows of a 300-lb weight dropped approx. 5-ft required to produce a 12-in. penetration, except where noted, of a 3.00-in.-OD, 2.50-in.-ID taper tube sampler.

% Rec. = $\frac{\text{Total Sample Recovered}}{\text{Total Interval Drilled}}$
 % Rec. = $\frac{\text{Total Sample Recovered}}{\text{Total Interval Sampled}}$
 (Solid line indicates total interval drilled)

†The drilling rate is expressed by a solid line and the weight on bit by a dashed line. No line is given for drilling rate when the core barrel spun through the formation.

LOG AND TEST RESULTS
BORING OFT-8, OAK CRATER
ENEWETAK ATOLL, MARSHALL ISLANDS