

Stratum	SAMPLER TYPE	BLOW COUNT†				PERCENT RECOVERY (See note below)				DRILLING RATE‡ MINUTES PER FOOT					REVS. PER MINUTE	
		● WATER CONTENT, %								WEIGHT ON BIT, KIPS						
		20	40	60	80	20	40	60	80	5	10	15	20	25	100	200
600																
610																
620																
630																
640																
650																
660																
670																
680																
690																
700																
710																
720																
730																
740																
750																
760																
770																
780																
790																
800																
Job No. : 0185-1032 Final Penetration: 765.8' Date Completed: June 13, 1985 †Water Depth Measured: at 1540 hrs on June 7, 1985		*SAMPLER TYPE SS - 3.00-in. split-barrel TW - 3.00-in. thick-wall TT - 2.25-in. thin-wall TS - 3.00-in. thin-wall LY - Longyear system CD - Christensen system		†Number of blows of a 300-lb weight dropped approx 6-ft required to produce a 12-in. penetration, except where noted, of a 3.00-in.-OD, 2.50-in.-ID taper tube sampler.				% Rec. = Total Sample Recovered / Total Interval Drilled % Rec. = Total Sample Recovered / Total Interval Sampled (Solid line indicates total interval drilled)				‡The drilling rate is expressed by a solid line and the weight on bit by a dashed line. No line is given for drilling rate when the core barrel spun through the formation.				

LOG AND TEST RESULTS
 BORING OKT-13, OAK CRATER
 ENEWETAK ATOLL, MARSHALL ISLANDS