

Stratum	PENETRATION BELOW SEAFLOOR IN FEET	SAMPLER* TYPE	BLOW COUNT [†]				PERCENT RECOVERY (See note below)				DRILLING RATE † MINUTES PER FOOT					REVES. PER MINUTE	
			● WATER CONTENT, %								WEIGHT ON BIT, KIPS						
			20	40	60	80	20	40	60	80	5	10	15	20	25	100	200
	600																
	610																
	620																
	630																
	640																
	650																
	660																
	670																
	680																
	690																
	700																
	710																
	720																
	730																
	740																
	750																
	760																
	770																
	780																
	790																
	800																
Job No. : 0185-1032 Final Penetration : 721.6' Date Completed : July 6, 1985 †Water Depth Measured : at 1705 hrs on June 29, 1985		*SAMPLER TYPE SS - 3.00-in. split-barrel TW - 3.00-in. thick-wall TT - 2.25-in. thin-wall TS - 3.00-in. thin-wall LY - Longyear system CD - Chiselens system	†Number of blows of a 300-lb weight dropped approx. 5-ft required to produce a 12-in. penetration, except where noted, of a 3.00-in.-OD, 2.50-in.-ID lapar tube sampler.	$\% \text{ Rec.} = \frac{\text{Total Sample Recovered}}{\text{Total Interval Drilled}}$ $\% \text{ Rec.} = \frac{\text{Total Sample Recovered}}{\text{Total Interval Sampled}}$ (Solid line indicates total interval drilled)	†The drilling rate is expressed by a solid line and the weight on bit by a dashed line. No line is given for drilling rate when the core barrel spun through the formation.												

**LOG AND TEST RESULTS
BORING OPZ-18, OAK CRATER
ENEWETAK ATOLL, MARSHALL ISLANDS**