

United States Department of the Interior
Geological Survey

MULTICHANNEL SEISMIC-REFLECTION PROFILES
FROM VANUATU COLLECTED IN 1982

by

H. G. Greene,¹ A. Macfarlane,² G. L. Smith,¹ and E. L. Geist¹

OPEN-FILE REPORT 90-100

This report is preliminary and has not been reviewed
for conformity with U.S. Geological Survey editorial standards
or with the North American Stratigraphic Code.

Any use of trade, product, or firm names in this publication is for
descriptive purposes only and does not imply
endorsement by the U.S. Government.

¹ U.S. Geological Survey, Menlo Park, California

² Department of Geology, Mines and Rural Water Supply, Port Vila, Vanuatu

In 1982, a geophysical survey (USGS cruise identifier L6-SP-82) in the territorial waters of Vanuatu was conducted by the U.S. Geological Survey aboard the R/V S. P. Lee (Plates 1 and 2). This survey yielded approximately 2400 km of 24-fold multichannel seismic reflection data, 2400 km of single channel seismic reflection data, and other geophysical profile data including gravity, magnetic gradiometer, 3.5 and 12 kHz high-resolution echo-sounding, and sonobuoy refraction profiles. Greene et. al (1982) have summarized the scientific objectives and preliminary results of this survey. Complete descriptions of the geophysical data collection and interpretation are published in Greene and Wong (1988).

With the publication of this open-file report, the following data are being released:

1. Analog (variable area/wiggle trace) sections of the stacked, multichannel seismic reflection profiles at a horizontal scale of 1 km/in and a two-way travel-time scale of 1.5 in/sec with stacking velocities displayed across the top of the section;
2. Magnetic tapes of digital multichannel seismic reflection data, unstacked (CDP sorted) and stacked, in SEG-Y format;
3. Trackline chart (Plates 1 and 2) with bathymetry and shotpoint locations.

Multichannel seismic reflection profiles

The multichannel seismic reflection data were collected along 41 lines (1 through 41, Plates 1 and 2). The survey conditions were excellent, and wave-induced noise was minimal.

The source and receiver equipment and recording parameters are shown in Table 1. The seismic source consisted of a tuned, 5 airgun array totaling 1311 cubic inches, pressurized to 2000 psi, towed at a depth of approximately 10.5 m. Individual gun volumes were usually 148, 194, 194, 309, and 466 cubic inches; the array was modified temporarily at times during the survey for repair. The receiver consisted of a 24 channel hydrophone streamer, with 100 meter group lengths containing 60 hydrophones in each group.

The near channel offset from the airguns was 297 m, and far channel offset 2611 m. The streamer was towed at a depth of approximately 12.5 m. The data were recorded with a GUS Model HDDR-4200 recording system. Recording problems contributing to skipped or unreadable records occurred at various times throughout the survey.

The basic processing steps are shown in Table 2. Particular attention was devoted to accurate velocity estimation, through the use

of standard semblance plots and constant velocity stacks. The semblance velocity analyses were performed every 2.5 km (50 CDP's) along each line, using a summation of 3 to 5 adjacent CDP gathers for each analysis.

Data availability

Analog reproductions of the stacked multichannel seismic records and shot point navigation data may be obtained from the National Geophysical Data Center (NGDC). Instructions for ordering data from these sources may be obtained by contacting:

National Geophysical Data Center
NOAA/EDIS/Code D64
325 Broadway
Boulder, Colorado 80302

The CDP sorted (unstacked) and stacked data can be obtained on SEG-Y format magnetic tapes at the requester's expense by contacting:

Data Curator
Branch of Pacific Marine Geology
345 Middlefield Rd. MS-999
Menlo Park, CA 94025

Additional copies of this report may be obtained by contacting:

Books and Open-File Reports Section
U.S. Geological Survey
P.O. Box 25425
Federal Center
Denver, Colorado 80225
Telephone: (303) 236-7476

References

- Greene, H. G., Wong, F. L., and Scientific Staff, 1982, Hydrocarbon resource studies in the southwest Pacific: U.S. Geological Survey open-file report 83-293.
- Greene, H.G. and Wong, F.L., eds., 1988, Geology and Offshore Resources of Pacific Island Arcs--Vanuatu Region: Circum-Pacific Council for Energy and Mineral Resources, Earth Science Series, Volume 8.

TABLE 1. RECORDING PARAMETERS AND EQUIPMENT USED
DURING CRUISE L6-82-SP

SOURCE:	BOLT AIR GUNS
AIR GUNS IN ARRAY:	5
NET VOLUME:	1311 CU. IN.
MANIFOLD PRESSURE:	2000 PSI
GUN DEPTH:	10.5 M
SHOT INTERVAL:	50 M
STREAMER:	SEI MULTIDYNE, CHARGE COUPLED
GROUP INTERVAL:	100 M
AVERAGE DEPTH:	12.5 M
GROUP LENGTH:	100 M
PHONES/GROUP:	60
DEPTH CONTROLLERS:	SEI VARIABLE WING BIRDS
RECORDING:	GUS HDDR 4200, BINARY GAIN
SAMPLE INTERVAL:	2 MS
RECORD LENGTH:	10 S
RECORDING FILTER:	5-110 HZ
NUMBER OF CHANNELS:	24
NAVIGATION:	MAGNAVOX SYSTEM
PRIMARY:	SATELLITE

TABLE 2. PROCESSING SEQUENCE

1. DEMULTIPLEX:	
DESAMPLE:	4 MS
GAIN RECOVERY:	
REFORMAT:	PHOENIX I
2. TRACE SHOT EDIT:	
3. STATIC CORRECTIONS:	
RECORDING STATICS:	256 MS
DATUM:	SEA LEVEL
4. CDP SORT:	
5. VELOCITY ANALYSIS:	
WINDOW LENGTH:	60 MS
WINDOW INTERVAL:	4 MS
BAND PASS FILTER:	3-6-40-50 HZ
VELOCITY RANGE:	1400-4900 M/S
6. NMO CORRECTION:	
7. 24-FOLD STACK:	
8. BANDPASS FILTER:	HANNING
FILTER POINTS:	64
TIME WINDOW:	0.0 - 10.0 S
FREQUENCY:	4-8-40-50 HZ
9. AGC:	350 MS WINDOW