

16—EOLIAN FEATURES

REF NO	DESCRIPTION	SYMBOL	CARTOGRAPHIC SPECIFICATIONS	NOTES ON USAGE
16.1	Dune crest		lineweight .25 mm dash .375 mm; space .3 mm	Dune forms shown by traces of dune crests.
16.2	Scarp on dune crest		hachure lineweight .2 mm; height 1.0 mm; spacing 4.75 mm	Add hachures to show scarp caused by slip; hachures point down slip face of dune.
16.3	Blowout rim around closed depression of eolian origin in dune field		all lineweights .15 mm hachure height .875 mm; spacing 3.5 mm long dash 1.4 mm; short dash .5 mm; space .375 mm	Hachures point into closed depression.
16.4	Blowout rim around closed depression of eolian origin in bedrock—Certain		all lineweights .2 mm hachure height .875 mm; spacing 2.5 mm	Hachures point into closed depression.
16.5	Blowout rim around closed depression of eolian origin in bedrock—Approximately located		2.5 mm .5 mm	Floor of closed depression, shown here as a dry lakebed, may be mapped as appropriate to individual feature.
16.6	Edge of dry lakebed within closed depression of eolian origin in bedrock		lineweight .15 mm; dash length 1.5 mm; space .375 mm	
16.7	Sediment transport direction—Determined from dune forms		all lineweights .15 mm 1.5 mm .875 mm radius .875 mm 5.0 mm 20° 1.375 mm 1.0 mm	
16.8	Sediment transport direction—Determined from dune bedding in horizontal section		1.25 mm .875 mm radius 1.0 mm all lineweights .15 mm	
16.9	Sediment transport direction—Determined from eolian crossbedding in vertical or near-vertical section		.5 mm 2.5 mm 1.0 mm dot diameter .3 mm; spacing .225 mm 40°	