



EMERGENCY ASSESSMENT OF DEBRIS-FLOW HAZARDS FROM BASINS BURNED BY THE 2007 WITCH FIRE, SAN DIEGO COUNTY, SOUTHERN CALIFORNIA

By

Susan H. Cannon,¹ Joseph E. Gartner, John A. Michael, Mark A. Bauer, Susan C. Stitt, Donna L. Knifong, Bernard J. McNamara, and Yvonne M. Roque

¹U.S. Geological Survey, Box 25046, DFC, MS 966, Denver CO 80225, (303) 273-8604, cannon@usgs.gov

2007

Introduction

The objective of this report is to present a preliminary emergency assessment of the potential for debris-flow generation from basins burned by the Witch Fire in San Diego County of southern California in 2007. Debris flows are among the most hazardous geologic phenomena (Turner and Schuster, 1996); debris flows that followed wildfires in southern California in 2003 killed 16 people and caused tens of millions of dollars of property damage (NOAA-USGS Debris Flow Task Force, 2005). A short period of even moderate rainfall on a burned watershed can lead to debris flows (Cannon and others, 2008). Rainfall that is normally absorbed into hillslope soils can run off almost instantly after vegetation has been removed by wildfire. This causes much greater and more rapid runoff than is normal from creeks and drainage areas. The highly erodible soils in a burn scar allow flood waters to entrain large amounts of ash, mud, boulders, and unburned vegetation. Within the burned area and downstream, the force of rushing water, soil, and rock can destroy culverts, bridges, roadways, and buildings, potentially causing injury or death.

This emergency debris-flow hazard assessment is presented as a relative ranking of the predicted median volume of debris flows that can issue from basin outlets in response to 2.25 inches (57.15 mm) of rainfall over a 3-hour period. Such a storm has a 10-year return period (Hershfield, 1961). The calculation of debris-flow volume is based on a multiple-regression statistical model that describes the median volume of material that can be expected from a recently burned basin as a function of the area burned at high and moderate severity, the basin area with slopes greater than or equal to 30 percent, and triggering storm rainfall (Gartner and others, 2008). Cannon and others (2007) describe the methods used to generate the hazard maps. Identification of potential debris-flow hazards from burned drainage basins is necessary to issue warnings for specific basins, to make effective and mitigation decisions, and to help plan evacuation timing and routes.

Results

Of the 473 basins evaluated in this assessment, 87 were identified as having the potential to produce debris flows with volumes less than 1,000 m³ in response to the 10-year recurrence, 3-hour rainstorm. Of the basins evaluated, 356 showed the potential to produce debris flows with volumes between 1,001 and 10,000 m³. These are the small (0.07 to 7.5 km²) basins that drain into the San Diego River and El Capitan Reservoir, Boulder Creek, and Cedar Creek on the east side of the burned area; into Lake Sutherland, Black Canyon, Temescal Creek, Rockwood Canyon, Santa Maria Creek, and Santa Ysabel Creek in the center of the burned area; and the San Dieguito River and Lake Hodges on the west side of the burned area. Thirty basins evaluated showed volume estimates between 10,001 and 100,000 m³. From west to east, these include an unnamed basin that drains into the San Dieguito River below Lake Hodges; Rattlesnake Creek, Warren Canyon, and an unnamed basin north of Warren Canyon that drains into Rancho Bernardo; an unnamed basin and the headwater basin to the San Dieguito River; three unnamed canyons west of Rockwood Canyon, Rockwood Canyon, and Boden Canyon; Bear Creek, Carney Canyon, Black Canyon, an unnamed basin south of Carney Canyon that drain into Temescal Creek, and the headwaters of Temescal Creek; two unnamed basins that drain into Santa Ysabel Creek; an unnamed basin that drains into Black Canyon; Bloomdale Creek which drains into Lake Sutherland; Witch Creek, Hatfield Creek, and Wash Hollow Creek; San Vicente Creek; Dye Canyon, Ritchie Creek, Kelly Creek, and Sand Creek, which drain into the San Diego River or El Capitan Reservoir; and Padre Barona Creek and Featherstone Canyon which drain into San Vicente Reservoir.

Debris flows issuing from these basins can impact highways and roads in the area. In addition, neighborhoods, buildings, roadways, and people within, or immediately below, any of the burned basins can be impacted by debris flows.

In response to a storm similar to that used in this assessment, Lake Sutherland, El Capitan Reservoir, San Vicente Reservoir, and Lake Hodges can expect large accumulations of sediment, and associated water quality issues.

Use and Limitations of the Map

This map shows potential hazards posed by debris flows as estimates of the median volumes of material that may issue from the outlets of basins burned by the Witch Fire of 2007 in southern California in response to a 10-year-recurrence, 3-hour-duration rainstorm. The maps identify the range of potential debris-flow volumes that can issue from individual basin outlets. This information can be used to issue warning for specific locations, to prioritize mitigation efforts, to aid in the design of mitigation structures, and to guide decisions for evacuation, shelter, and escape routes in the event that storms of similar magnitude to that evaluated here are forecast for the area.

In addition to the potential dangers within the basins, areas downstream from the basin outlets are also at risk. In some of these areas homes were destroyed by the fire, and workers and residents may be busy cleaning and rebuilding sites. The potential for debris flows during rainfall events places these people at high risk. In addition, if culverts are plugged or overwhelmed by flows, or if roads wash out, motorists may be stranded for long periods of time. In some cases, channels cross roads on blind curves where motorists could abruptly encounter debris-flow deposits on the road.

In addition to the colored drainage basins, small debris flows can be generated from non-colored areas within the burn perimeter. These areas were not included in the analysis because they are occupied by either planar hillslopes or basins that are smaller than those used in the model development (Cannon and others, 2007).

We expect that the maps presented here may be applicable for approximately three years after the fires for the storm conditions considered. The potential for debris-flow activity decreases with time following fire and the concurrent revegetation and stabilization of hillslopes. A compilation of information on post-fire runoff events from throughout the western U.S. indicates that under normal rainfall conditions most debris-flow activity occurs within about two years following a fire. If dry conditions slow re-growth of vegetation, this recovery period will be longer. Our assessment is specific to post-fire debris flows; significant hazards from flash flooding can remain for many years after a fire.

This assessment is based on the assumption that all basins are equally prone to debris flows. Recent work has indicated that in addition to the volume, the probability of debris flow will vary with burn severity, basin gradient, material properties, and storm rainfall. Unfortunately, a determination of debris-flow probability cannot yet be incorporated into this hazard assessment.

Basins on both sides of El Capitan Reservoir and along the San Diego River above the reservoir also burned in the 2003 Cedar Fire. The method used here does not incorporate the effects of multiple fires. We have not been able to take into account possible differences in the mapped burn severity or removal of stored sediment due to the previous fire.

Suggested Actions

People occupying businesses, homes, and recreational facilities downstream of the basins identified as the most hazardous must be informed of the potential dangers from debris flows and flooding. Warning must be given even for those basins with engineered mitigation structures at their mouths in the event that the structures are not adequate to contain potential debris flows. Site-specific debris-flow hazard assessments ought to be performed upslope from structures and facilities in areas identified as being at risk.

Because this assessment is specific to post-fire debris flows, further assessment of potential hazards posed by flash floods is needed. Continued operation of the early-warning system for both flash floods and debris flows established by NOAA's National Weather Service and the U.S. Geological Survey (http://www.wrh.noaa.gov/sgx/hydro/debris_flow.php; NOAA-USGS Debris Flow Task Force, 2005) would help local officials make decisions about evacuations and inform the public about potential dangers of debris flows in advance of rainfall events. The system consists of an extensive reporting rain-gage and stream-gage network coupled with National Weather Service weather forecasts and radar rainfall measurements. Any early-warning system should be coordinated with existing county and flood district facilities.

An evaluation of the effectiveness of hillslope and channel mitigation approaches focused on the ability of different treatment methods to decrease the potential volume of debris flows (deWolfe, 2006; deWolfe and others, 2008). This work found that extensive applications of treatments that promote rainfall infiltration into hillslopes combined with engineered works that control incision in low-gradient channel reaches can effectively mitigate debris-flow impacts in basins less than about two km² in area that are expected to produce debris-flow volumes of less than 10,000 m³. Large engineered check dams or collection basins are necessary to effectively mitigate hazards posed by events from basins larger than about two km² that are expected to produce debris-flow volumes greater than about 10,000 m³ (Hung and others, 1987; Fiebigler, 1997; Okubo and others, 1997; Heumader, 2000; deWolfe, 2006).

References Cited

- Cannon, S.H., Gartner, J.E., and Michael, J.A., 2007, Methods for the emergency assessment of debris-flow hazards from basins burned by the fires of 2007, southern California: U.S. Geological Survey Open-File Report 2007-1384, 10 p.
- Cannon, S.H., Gartner, J.E., Wilson, R.C., and Laber, J.L., 2008, Storm rainfall conditions for floods and debris flows from recently burned areas in southwestern Colorado and southern California: *Geomorphology*, doi:10.1019/j.geomorph.2008.03.019.
- deWolfe, V.G., 2006, An evaluation of erosion control methods after wildfire in debris-flow prone areas after wildfire: Golden, Colorado School of Mines, Department of Geology and Engineering Geology, M.S. thesis, 186 p.
- deWolfe, V.G., Santi, P.M., Ey, John, and Gartner, J.E., 2008, Effective mitigation of debris flows at Lemon dam, La Plata County, Colorado: *Geomorphology*, doi:10.1016/j.geomorph.2008.04.008.
- Fiebigler, G., 1997, Structures of debris-flow countermeasures, in Chen, C.I., ed., *Debris Flow Hazards Mitigation—Mechanics, Prediction, and Assessment*, Proceedings of First International Conference: New York, N.Y., American Society of Civil Engineers, p. 596–606.
- Gartner, J.E., Cannon, S.H., Santi, P.M., and deWolf, V.G., 2008, Empirical models to predict debris flow volumes generated from recently burned basins in the western U.S.: *Geomorphology*, doi:10.1016/j.geomorph.2008.02.033.
- Hershfield, D.M., 1961, Rainfall frequency atlas of the United States for durations from 30 minutes to 24 hours and return periods from 1 to 100 years: Technical Paper No. 40, U.S. Department of Commerce, Weather Bureau, 61 p.
- Heumader, J., 2000, Technical debris flow countermeasures in Austria—A review, in Wiczorek, G.F., and Naeser, N.D., eds., *Debris flow Hazards Mitigation—Mechanics, Prediction, and Assessment*, Proceedings of Second International Conference on Debris Flow Hazards Mitigation: Taipei, Taiwan August 16–18, 2000, A.A. Balkema, Brookfield, Vt., p. 553–564.
- Hung, Oldrich, Morgan, G.C., VanDine, D.F., and Lister, D.R., 1987, Debris flow defenses in British Columbia, in Costa, J.E., and Wiczorek, G.F., eds., *Debris Flows/Avalanches—Process, Recognition, and Mitigation: Reviews in Engineering Geology* vol. VII, The Geological Society of America, Boulder, Colo., p. 201–222.
- NOAA-USGS Debris Flow Task Force, 2005, NOAA-USGS debris-flow warning system—Final report: U.S. Geological Survey Circular 1283, 47 p.
- Okubo, S., Ikeya, H., Ishikawa, Y., and Yamada, T., 1997, Development of new methods for countermeasures against debris flows, in Armani, A., and Michiue, M., eds., *Recent Developments on Debris Flows*, Lecture Notes in Earth Sciences, vol. 64, Springer-Verlag, New York, N.Y., p. 166–185.
- Turner, A.K., and Schuster, R.L., eds, 1996, Landslides, investigation and mitigation, Transportation Research Board Special Report 247: Washington D.C., National Research Council, 673 p.