






TECHNICAL SUMMARY

Navigation	Differentially-corrected GPS
Data interval	70 metres
Terrain clearance	Helicopter 57 m
	Electromagnetic sensor 30 m
	Magnetometer 30 m
Data sampling interval	0.1 second
Magnetometer / sensitivity	Cesium / 0.01 nT
Electromagnetic system	MUGO RESOLVE
Regional field removed	International Geomagnetic Reference Field 2005
Date flown	March 26, 2007




Frequency	Sensitivity	Coil Orientation
3300 Hz	0.12 ppm	Vertical coaxial
400 Hz	0.12 ppm	Horizontal coplanar
1500 Hz	0.12 ppm	Horizontal coplanar
6200 Hz	0.24 ppm	Horizontal coplanar
25000 Hz	0.60 ppm	Horizontal coplanar
115000 Hz	0.60 ppm	Horizontal coplanar

FLIGHT LINES




RESIDUAL MAGNETIC FIELD CONTOURS



Magnetic inclination within the survey area: 69 degrees N
Magnetic declination within the survey area: 4 degrees E

LOCATION MAP




U.S. GEOLOGICAL SURVEY
ASHLAND AREA, NEBRASKA

RESIDUAL MAGNETIC FIELD
IGRF Removed

FUGRO RESOLVE SURVEY	REF: NK 14-9	GEOPHYSICIS
DATE: APRIL, 2007	JOB: 07026	SHEET: 1

Fugro Airborne Surveys



FUGRO AIRBORNE SURVEYS

