Qualitative Oil Yields by Test Tube Method

Drill-cutting samples from Colorado Interstate Gas Exploration Company's Well 3-13-94 drilled in CNW1/4 (1,343 feet FNL, 1,319 feet FWL) of sec 3, T 13 N, R 94 W, Sweetwater County, Wyoming

Surface elevation 6,366 feet

All samples were for 20 and 30-foot intervals

| Depth | Test result1/ | Depth | Test result ¹ / |
|-----------|---------------|-----------|----------------------------|
| 480- 510 | No oil | 2990-3020 | No oil |
| 510- 570 | Trace | 3020-3080 | c |
| 570- 630 | Ъ | 3090-3120 | Trace |
| 630- 660 | Trace | 3120-3170 | No oil |
| 660- 720 | Ъ | 3170-3200 | Trace |
| 720-1870 | No oil | 3200-3380 | No oil |
| 1900-2190 | No oil | 3380-3410 | Ъ |
| 2190-2280 | Trace | 3410-3440 | Trace |
| 2280-2400 | No oil | 3440-3470 | No oil |
| 2400-2430 | Trace | 3500-3590 | No oil |
| 2430-2610 | No oil | | |
| 2640-2820 | No oil | | |
| 2870-2900 | No oil | | |

Laramie Energy Research Center, Laramie, Wyoming, Illustration No. SBR-4674P

January 24, 1975

^{1/} "b"--less than 1.0 gallon of oil per ton, "c"--1.0 to 3.0 gallon per ton