PROFESSIONAL PAPER 305 PLATE 22

EXPLANATION

Gravel
Sandstone
Calcareous sandstone
Siltstone
Calcareous siltstone
Clay shale or claystone
Calcareous clay shale or claystone
Clay or claystone
Coal
Limestone
Cored interval
Not attempted or recovered

DRILL BIT
Cb — Cb
Ch — Ch

Oil show
Very fine grained
Fine grained
Medium grained
Coarse grained
Electrode spacing

BIT SYMBOLS

DRILL BITS

OWC
Crum Brailsford hole opener
Hughes OD
Hughes OSC1
Hughes OSC2
Hughes OSC3
Hughes OSC4
Hughes W7
Hughes W7R
Hughes W7R
IMO
Reed 1-RR-7
2T
Reed 4-OT
Security hole opener
S7
Security FB7R hole opener
S7R
Smith OWDJ1
K-2
Smith R2

CORE BITS

K-24
Reed 4-5/8 formation
K-25
Reed 4-3/4 soft formation

Location: Lat. 69°36' N., Long. 148°37' W.
Elevation: Kelly bushing 118 feet above sea level
Spudded: July 27, 1961
Completed: August 24, 1961
Total depth: 6002 feet
Status: Dry and abandoned

Drilling and engineering data supplied by Richfield Oil Corp.
Cores were determined by comparison of Electrical Log Characteristics with Core Laboratories, Inc., Core Analysis Reports.
Depths are measured from the top of the kelly bushing.

Logged by Florence R. Collins

INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D. C.—71168

TEST WELL 1, ALASKA

GRAPHIC LOG OF KAOLA

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY