

Abstract

The U.S. Geological Survey, in cooperation with the Iowa Department of Natural Resources, conducted bathymetric surveys on seven lakes in Iowa during 2005 (Arrowhead Pond, Central Park Lake, Lake Keomah, Manteno Park Pond, Lake Miami, Springbrook Lake, and Yellow Smoke Lake). The surveys were conducted to provide the Iowa Department of Natural Resources with information for the development of total maximum daily load limits, particularly for estimating sediment load and deposition rates. The bathymetric surveys provide a baseline for future work on sediment loads and deposition rates for these lakes. All of the lakes surveyed in 2005 are man-made lakes with fixed spillways.

Bathymetric data were collected using boat-mounted, differential global positioning system, echo depth-sounding equipment, and computer software. Data were processed with commercial hydrographic software and exported into a geographic information system for mapping and calculating area and volume. Lake volume estimates ranged from 47,784,000 cubic feet (1,100 acre-feet) at Lake Miami to 2,595,000 cubic feet (60 acre-feet) at Manteno Park Pond. Surface area estimates ranged from 5,454,000 square feet (125 acres) at Lake Miami to 558,000 square feet (13 acres) at Springbrook Lake.

Introduction

Bathymetric mapping can provide useful information for water-quality managers to address a variety of issues on Iowa's lakes and reservoirs. The Iowa Water Science Center of the United States Geological Survey (USGS) began a lake bathymetric mapping program in June 2001 on Lake Delhi in east central Iowa resulting in a published bathymetric map and report (Schoenbelen and others, 2003). The USGS, in cooperation with the Iowa Department of Natural Resources (IDNR), conducted a bathymetric survey of Lake Keomah in 2005 to provide the IDNR with information for the development of total maximum daily load limits (TMDLs), particularly for estimating sediment load and deposition rates. The bathymetric contours also can provide a baseline for future work on sediment load and deposition rates for Lake Keomah.

Lake Keomah was constructed in 1934 and is located in south-eastern Iowa about 5 miles (mi) east of Oskaloosa in Mahaska County, in the Lake Keomah State Park, and is used primarily for recreational activities. Lake Keomah receives flow from two unnamed creeks from the south. Discharge from Lake Keomah is over a fixed spillway to the east of the dam on the northern end of the lake into an unnamed tributary of the South Skunk River.

Methods

Bathymetry data were collected on June 20 and 21, 2005, and August 23 and 24, 2005. Bathymetric mapping was accomplished using boat-mounted global positioning system (GPS), echo depth-sounding equipment, and computer software. The GPS allowed for accuracies of about 3.28 feet (ft) (approximately 1 meter) in the horizontal direction. The echo sounder emits sound pulses that are reflected off the lake bottom and received by a transducer. The echo sounder transmitted at a frequency of 200 kilohertz; water depths were determined by the echo sounder based on the speed of sound in water compensated for temperature (Specialty Devices, Inc., 2003). In some areas of the lake, the depth limitations (less than 3.3 ft) of the echo-sounding equipment necessitated determining the depths manually at target points using a measuring device marked in 0.10-ft increments. These data were collected on June 20 and 21, 2005. Using the echo sounder, the bathymetry data were collected along planned transect lines spaced 100 ft apart. Individual data-collection locations along a transect line generally were 5 to 10 ft apart. These data were collected on August 23 and 24, 2005. The depth data later were converted to elevation, in the post-processing software (Coastal Oceanographics, Inc., 2002), by subtracting the depths at each location from the reference surface elevation of the lake. The reference surface elevation was determined on the days of bathymetric data collection by measuring from a reference point of known elevation on the spillway structure. The elevation of the reference point was determined using a combination of GPS and standard surveying techniques. The bathymetry data then were filtered (fig. 1) to reduce the density of data points and entered into geographic information system (GIS) software to produce a three-dimensional surface of the lake-bottom elevations. The three-dimensional surface was contoured, and the contours were adjusted manually to correct for interpretive errors. (See the Lake Keomah metadata at <http://water.usgs.gov/lookup/getlist> for a more detailed explanation of methods used to collect and process the bathymetric data.)

Quality Assurance

A bar check on the echo sounder was performed at the beginning of the day of data collection following established protocols (U.S. Army Corps of Engineers, 1994, Chapter 9). This was done to ensure that the echo sounder was calibrated correctly. The bar check involved suspending a 2-ft-diameter flat aluminum plate directly below the echo sounder. The suspension line was marked in 5-ft increments. An initial calibration was made at 5 ft by entering the speed of sound in water and adjusting the offset of the transducer in the computer software. The offset is the draft of the transducer below the lake surface. The aluminum plate was then lowered in 5-ft increments, depending on the range of depths expected to be encountered, and adjustments in the speed of sound were made until depth readings and the depth of the aluminum plate agreed to within approximately 0.1 ft.

A second independent bathymetry data set was collected for most of the area of Lake Keomah. The control data set was used to estimate the precision (repeatability) of the sounding data collected with the echo sounder, to estimate the accuracy of the interpolation in the three-dimensional surface, and to estimate the accuracy of the contours (Wilson and Richards, 2006). Within 1.5 ft of each other there were 13 paired data and control points with a calculated Root Mean Square Error (RMSE) of 0.13 ft. At corresponding locations were 1,276 paired three-dimensional surface elevations and control points with a calculated RMSE of 0.38 ft, and within 0.50 ft of each other there were 25 paired contours and control points with a calculated RMSE of 0.48 ft.

Bathymetric Contours

The water-surface elevation of Lake Keomah was 746.2 ft above North American Vertical Datum of 1988 (NAVD88) on June 20 and 21, 2005 and 745.8 ft above NAVD88 on August 23 and 24, 2005. Generally, the water depth increases toward the dam (fig. 2). The deepest part of the lake is located approximately 90 ft southwest of the dam and 300 ft west of the outflow, and the lowest elevation measured was 725.5 ft (20.7 ft deep). The average elevation of the lake bottom based on the three-dimensional surface was 737.0 ft (9.2 ft deep). The slope of the lake bottom generally is greatest along the dam. Data from this survey indicate that the total surface area of Lake Keomah, at a water-surface elevation of 746.2 ft, is approximately 3,423,000 square feet (ft²) (79 acres) and the total water volume of Lake Keomah is approximately 31,718,000 cubic feet (ft³) (728 acre-ft).

References

Coastal Oceanographics, Inc., 2002, HYPACK MAX[®], hydrographic survey software user's manual: Middlefield, Connecticut, Coastal Oceanographics, Inc. [variously paged].

Schoenbelen, D.J., Mcvay, J.C., Barnes, K.K., and Becher, K.D., 2003, Bathymetric mapping, sediment quality, and water quality of Lake Delhi, Iowa, 2001–02: U.S. Geological Survey Water-Resources Investigations Report 03–4085, 38 p.

Specialty Devices, Inc., 2003, Bathymetric Survey System BSS+5 with omnistar manual: Plano, Texas, Specialty Devices, Inc., 38 p.

U.S. Army Corps of Engineers, 1994, Engineering and design—Hydrographic surveying EM 1110-2-1003: Washington, DC, Department of the Army, chap. 9-3, p. 9-4 to 9-9; accessed January 2004 at <http://www.usace.army.mil/publications/eng-manuals/em1110-2-1003/c-9.pdf>.

Wilson, G.L., and Richards, J.M., 2006, Procedural documentation and accuracy assessment of bathymetric maps and area/capacity tables for small reservoirs: U.S. Geological Survey Scientific Investigations Report 06–5208, 24 p., CD-ROM.

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.



Lake Keomah in Mahaska County, Iowa (photograph by Clint Van Schepen, U.S. Geological Survey).





Figure 1. Data-collection points used to construct bathymetric contours.




EXPLANATION

— Lake boundary—Edge of water at lake-surface elevation, 746.2 feet above North American Vertical Datum of 1988

--- 744 Bathymetric contour—Line of equal lake-bottom elevation, in feet above North American Vertical Datum of 1988. Interval is 3 feet. Hachures indicate closed low

Figure 2. Bathymetric contours of Lake Keomah, 2005 (not for navigational use).



Location of Lake Keomah in Mahaska County, Iowa

Bathymetric Contours for Lake Keomah, Mahaska County, Iowa

By
S.M. Linhart and K.D. Lund
2008

Suggested citation:
Linhart, S.M., and Lund, K.D., 2008, Bathymetric contour maps of lakes surveyed in Iowa in 2005: U.S. Geological Survey Scientific Investigations Map 3037, 7 sheets.
For more information about USGS and its products:
Telephone: 1-888-ASK-USGS
World Wide Web: <http://www.usgs.gov>

Publishing support provided by:
Rolla Publishing Service Center
For additional information concerning this publication, contact:
Director, USGS Iowa Water Science Center
400 South Clinton Street, Room 269
Iowa City, IA 52240
(319) 337-4191
Or visit the Iowa Water Science Center Web Site at:
<http://iwa.water.usgs.gov>