



EXPLANATION					
21	Drill hole number		Coarse gravel and sand		Sand and trace of gravel
	Water table		Fine gravel and sand		Sand
	Soil		Sand and cobbles		Clay

- The locations of profiles  $LL'$  and  $MM'$  are shown on plate 1.
- Because the elevations of the tops of the drill holes were not measured, the logs are plotted with approximate elevations, which are extrapolated from the elevations measured during the geophysical surveys. The maximum error in the approximate elevation is estimated to be 2 meters.
- For drill holes 12, 14, 59, and 64 the field logs end at depths that are less than 30.5 meters and thus do not record the clay layer. Consequently, the clay layer is not shown.
- The terms "clay," "sand," "gravel," and "cobbles" are taken from the driller's logs. These logs also indicate the sizes of the gravel clasts. In this report, gravel clasts with diameters of about 1 centimeter (3/8 inch) are termed "fine gravel;" gravel clasts with diameters of about 1-1/4 centimeter (1/2 inch) and greater are termed "coarse gravel."

### Selected drill-hole logs

By  
K.J. Ellefsen, B.L. Burton, J.E. Lucius, S.S. Haines, D.V. Fitterman,  
J.A. Witty, D. Carlson, B. Milburn and, W.H. Langer  
2007

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.