Prepared in cooperation with the Santa Ana Watershed Project Authority

Application of a Watershed Model (HSPF) for Evaluating Sources and Transport of Pathogen Indicators in the Chino Basin Drainage Area, San Bernardino County, California

Scientific Investigations Report 2009-5219

Application of a Watershed Model (HSPF) for Evaluating Sources and Transport of Pathogen Indicators in the Chino Basin Drainage Area, San Bernardino County, California

By Joseph A. Hevesi, Lorraine E. Flint, Clinton D. Church, and Gregory O. Mendez

In cooperation with Santa Ana Watershed Project Authority

Scientific Investigations Report 2009–5219

**U.S. Department of the Interior
U.S. Geological Survey**

U.S. Department of the Interior
KEN SALAZAR, Secretary

U.S. Geological Survey
Marcia K. McNutt, Director

U.S. Geological Survey, Reston, Virginia: 2011

For more information on the USGS—the Federal source for science about the Earth, its natural and living resources, natural hazards, and the environment, visit <http://www.usgs.gov> or call 1-888-ASK-USGS

For an overview of USGS information products, including maps, imagery, and publications, visit <http://www.usgs.gov/pubprod>

To order this and other USGS information products, visit <http://store.usgs.gov>

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Although this report is in the public domain, permission must be secured from the individual copyright owners to reproduce any copyrighted materials contained within this report.

Suggested citation:

Hevesi, J.A., Flint, L.E., Church, C.D., and Mendez, G.O., 2011, Using a watershed model (HSPF) to evaluate sources and transport of pathogen indicator bacteria in the Chino Basin, San Bernardino County, California: U.S. Geological Survey Scientific Investigations Report 2009–5219, 148 p.

Contents

Abstract.....	1
Introduction.....	2
Background.....	2
Purpose and Scope	5
Characteristics of the Chino Basin	5
Topography and Geology.....	5
Climate	7
Surface Water and Drainage Network	7
Land Cover and Use	9
Water Quality.....	9
Water-Quality-Data Sources and Methods of Collection and Analysis	9
Pathogen Indicator Bacteria	9
Field Data Collection	11
Supplemental Water-Quality Data	14
Analysis of Water-Quality Data	19
Data Limitations.....	20
Simulation of Streamflow and Bacteria Transport.....	20
Description of Model.....	20
Subwatershed Delineation.....	25
Input Data.....	25
Channel Reach Data.....	25
Meteorological and Streamflow Data	28
Surface Properties and Land Use	28
Model Calibration	32
Results from the Streamflow and the Fecal Coliform Models.....	37
Streamflow-Model Calibration and Verification Results.....	37
Chino Creek Subbasin	42
Mill Creek Subbasin	42
San Antonio Creek Subbasin	42
West Branch Cucamonga Creek Subbasin	42
San Antonio Dam inflow	43
Transport Model Calibration and Verification Results.....	43
Analyses of Storm-Targeted Samples for Storms in Water-Year 2004	43
Comparisons of Model Simulations with Supplemental Data from other Studies.....	54
Uncertainties in Modeling a System with Changing Conditions.....	63

Model Application: Evaluation of Contribution to Bacteria Contamination on the Basis of Flow Process and Land Use	66
1988–2005 Simulation Results: Summary of Base Case	66
Flow-Process Contributions to Bacteria Contamination.....	72
Contribution of Flow Processes for Selected Storms	73
Concentration Duration Analysis for Flow-Process Contributions	75
Flow Processes Contributions to Average Bacteria Concentrations	77
Evaluation of Source Area Contribution on the Basis of Land Use	80
Land-Use Contributions to Bacteria Concentrations for Selected Storms.....	81
Model Application: Analysis of Basin Response to Possible Climate and Land-Use Changes.....	94
Climate Scenarios.....	94
Development.....	94
Results of Air Temperature Scenarios	94
Results of Precipitation Scenarios	115
Land-Use Scenarios	119
Development.....	119
Results of Land-Use Scenarios	122
Applying Results to Develop TMDLs	136
Summary and Conclusions.....	138
Acknowledgments	141
References Cited.....	141
Appendix 1. Water-Quality Data Collected by the USGS in Water-Year 2004 in the Chino Basin.....	143

Figures

1. Regional map of study area and other basins used to study indicator bacteria in and near the Chino Basin, California.....	3
2. Location of study area, model boundary, water bodies, and drains in the Chino Basin, California.....	4
3. Maps of geology and soil units used to develop the HSPF model for the Chino Basin, California.....	6
4. Average monthly precipitation from PRISM for November and January for the Chino Basin, California	8
5. Map of land-use and vegetation categories for the Chino Basin, California	10
6. Measured hourly stream discharge at gage 11073495 and measured bacteria concentrations at sample site MC for the 11/12/2003–11/13/2003 storm, the 2/2/2004–2/3/2004 storm, and the 2/22/2004–2/23/2004 storm in the Chino Basin, California	13
7. Measured fecal coliform data and measured <i>E. coli</i> , enterococci, and total coliforms for all storm sampling events in the Chino Basin, California	16
8. Streamflow hydrographs of and measured fecal coliform bacteria concentrations for water-years 1996–2005 in daily streamflow at gage 11073495 and daily fecal coliform concentrations at site MC, and monthly streamflow at gage 11073360 and daily fecal coliform concentrations at sample site CHIS in the Chino Basin, California	18
9. Routing processes represented by the Hydrological Simulation Program—FORTRAN code for the simulation of fecal coliform bacteria transport and storage parameters	24
10. Base model segmented by average precipitation in January, and delineated hydrologic response units for each reach in the Chino Basin, California	26
11. Submodels of basin area upstream of each calibration gage used for hydrologic calibration of the Chino Basin model	29
12. Subbasins used in applications of calibrated model in the Chino Basin	30
13. Map showing percentage of imperviousness of the Chino Basin, California	33
14. Simulated and measured hourly streamflow for February 2004 for the calibration period for Chino Creek gage 11073360 and San Antonio Creek gage 11073300 in the Chino Basin, California	38
15. Flow duration curves for simulated and measured streamflow for calibration and verification periods for Chino Creek, Mill Creek, San Antonio Creek, West Branch Cucamonga Creek, and San Antonio Canyon reach in the Chino Basin, California	41
16. Simulated and measured storm-flow bacteria concentrations for storm of 11/12/2003–11/13/2003 at site MC, and for storms of 2/2/2004 and 2/22/2004 at sample site INDND, sample site INDD, sample site RECND, sample site RECGC, sample site RECD, sample site RESD, sample site SC, sample site D, and sample site MC reach in the Chino Basin, California	45
17. Simulated and measured average bacteria concentrations in the Chino Basin, California, for the water-year 2004 storm and land-use targeted sampling sites used for model calibration	55

18.	Simulated streamflow and simulated and measured bacteria concentrations at sample site D, 1996–1998, sample site MC, 2002–2004, sample site CCM2, 2002–2004, sample site CHIS, 2002–2005, sample site IHC, 2002–2005, sample site BVAM, 2002–2004, and sample site PPOC, 2002–2004 in the Chino Basin, California	56
19.	Simulated and measured average bacteria concentrations in the Chino Basin for all sampling sites used for model calibration and verification	63
20.	Simulated hourly bacteria concentrations affected by different flow processes during storms in February 2004 at sample site D in the Chino Basin, California.....	73
21.	Simulated daily bacteria concentrations affected by different flow processes for storms during December–March, water-year 2004, at Mill Creek outflow, and storms during December–March, water-year 2005, at Mill Creek outflow in the Chino Basin, California	74
22.	Concentration durations for simulated hourly bacteria concentrations affected by different flow processes at San Antonio Dam outflow, sample site D, sample site PPOC (Prado Park Lake outflow), Chino Creek outflow, sample site CCM1, sample site CCM2, and Mill Creek outflow for water-years 1988–2005 in the Chino Basin, California	76
23.	Land-use contributions to simulated bacteria concentrations at Chino Creek outflow for storms in February 2004, Mill Creek outflow for storms in February 2004, Chino Creek outflow for storms in February 2005, and Mill Creek outflow for storms in February 2005 in the Chino Basin, California	83
24.	Concentration durations for simulated hourly bacteria concentrations affected by different land uses at San Antonio Dam outflow, sample site D, sample site PPOC, Chino Creek outflow, sample site CCM1, sample site CCM2, and Mill Creek outflow for water-years 1988–2005 in the Chino Basin, California	87
25.	Simulated air temperature scenarios for water-years 1988–2005 at upper San Antonio Canyon in the Chino Basin: monthly snow pack, monthly streamflow, and monthly bacteria concentration	111
26.	Simulated air-temperature scenarios at San Antonio Dam outflow in the Chino Basin during water-years 1988–2005: flow duration for hourly streamflow and concentration duration for hourly bacteria concentrations	114
27.	Flow duration of simulated hourly streamflow for precipitation scenarios for water-years 1988–2005 at San Antonio Dam outflow, Prado Park Lake outflow (sample site PPOC), and Chino Creek outflow in the Chino Basin, California	116
28.	Concentration duration of simulated hourly bacteria concentration for precipitation scenarios for water-years 1988–2005 at San Antonio Dam outflow, Prado Park Lake outflow (sample site PPOC), and Chino Creek outflow in the Chino Basin, California	120
29.	Simulated daily bacteria concentrations sampled during storms in water-year 2005 for 6 land-use scenarios at Prado Park Lake outflow, Chino Creek outflow, and Mill Creek outflow in the Chino Basin, California	132
30.	Concentration duration for simulated hourly bacteria concentrations for 6 land-use scenarios during water-year 1988–2005 at Prado Park Lake outflow, Chino Creek outflow, and Mill Creek outflow in the Chino Basin, California	135

Tables

1.	Storm sampling locations and results for fecal coliforms in samples collected November 2003 and February 2004 in the Chino Basin, California	12
2.	Variability in fecal coliform densities from replicate samples collected on February 22–23, 2004, at various sites in the Chino Basin, California	12
3.	Supplemental water quality data and primary land uses input for model calibration, from water samples collected during 1993–2004 in the Chino Basin, California	17
4.	Hydrological Simulation Program—FORTRAN (HSPF) model calibration parameters for hydrologic and transport simulations of fecal coliforms used in several regional models and the Chino Basin model, as well as default HSPF parameters.....	21
5.	Average values for precipitation and air temperature for 46 model segments used for the Chino Basin model, 1970–2005.....	27
6.	Meteorological and streamflow data sources, number of stations or station identification, and years with available data used for the Chino Basin model.....	31
7.	Average State Soil Geographic Database (STATSGO) soil properties for the Chino Basin model	31
8.	Initial and adjusted pervious and impervious areas for each land use defined in the Chino Basin model	34
9.	Land-use acreages for impervious and pervious land unit types for upstream subbasin areas contributing to sampling locations in the Chino Basin, California	35
10.	Measured and simulated streamflow values for highest and lowest flows and regression results for U.S. Geological Survey and San Antonio Dam sites in the Chino Basin, California	39
11.	Values for transport parameters SQO, ACCUM, SQOLIM, and WSQOP for 12 land uses and impervious and pervious land units in the Chino Basin, California	44
12.	Calibration summary of simulated fecal coliform concentrations and measured indicator bacteria concentrations for 18 sampling sites in the Chino Basin, California	64
13A.	Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations for the Chino Creek and San Antonio Canyon subbasins in the Chino Basin, California	67
13B.	Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations in the Mill Creek submodel in the Chino Basin, California	70
14A.	Summary of 1988–2005 simulation results for air temperature scenarios at sample site IHC and San Antonio Dam outflow in the Chino Creek subbasin, California	95
14B.	Summary of 1988–2005 simulation results for air temperature scenarios at sample site CCM1 and Mill Creek outflow in the Mill Creek subbasin, California.....	96
15A.	Summary of 1988–2005 simulation results for precipitation scenarios at San Antonio Dam outflow in the Chino Basin, California.....	97
15B.	Summary of 1988–2005 simulation results for precipitation scenarios at storm sample site D in the Chino Basin, California	99

15C.	Summary of 1988–2005 simulation results for precipitation scenarios at Prado Lake outflow in the Chino Basin, California	101
15D.	Summary of 1988–2005 simulation results for precipitation scenarios at Chino Creek outflow in the Chino Basin, California	103
15E.	Summary of 1988–2005 simulation results for precipitation scenarios at sample site CCM1 in the Chino Basin, California	105
15F.	Summary of 1988–2005 simulation results for precipitation scenarios at sample site CCM2 in the Chino Basin, California	107
15G.	Summary of 1988–2005 simulation results for precipitation scenarios at Mill Creek outflow in the Chino Basin, California	109
16A.	Summary of 1988–2005 simulation results for six land use scenarios for sample site D in the Chino Basin, California	123
16B.	Summary of 1988–2005 simulation results for six land use scenarios at Prado Park Lake outflow in the Chino Basin, California	125
16C.	Summary of 1988–2005 simulation results for six land use scenarios at Chino Creek outflow in the Chino Basin, California	127
16D.	Summary of 1988–2005 simulation results for six land use scenarios at Mill Creek outflow in the Chino Basin, California	129
Appendix 1.	Water quality data for bacteriological samples collected by U.S. Geological Survey during storms in 2003 and 2004 in the Chino Basin, California	143

CONVERSION FACTORS, DATUM, AND ABBREVIATED WATER-QUALITY UNITS

Multiply	By	To obtain
Length		
inch (in.)	2.54	centimeter (cm)
foot (ft)	0.3048	meter (m)
mile (mi)	1.609	kilometer (km)
Area		
acre	4,047	square meter (m ²)
acre	0.4047	hectare
square mile (mi ²)	259.0	hectare
Volume		
gallon (gal)	3.785	liter (L)
gallon (gal)	0.003785	cubic meter (m ³)
million gallons (Mgal)	3,785	cubic meter (m ³)
cubic foot (ft ³)	0.028317	cubic meter (m ³)
acre-foot (acre-ft)	1,233	cubic meter (m ³)
Flow		
cubic foot per second (ft ³ /s)	0.02832	cubic meter per second (m ³ /s)
million gallons per day (Mgal/d)	0.04381	cubic meter per second (m ³ /s)
inch per hour (in./hr)	0.0254	meter per hour (m/hr)
inch per year (in./yr)	2.54	centimeter per year (cm/yr)
Mass		
ounce, avoirdupois (oz)	28.35	gram (g)
pound, avoirdupois (lb)	0.4536	kilogram (kg)
pound per acre (lb/acre)	1.121	kilogram per hectare (kg/ha)

Temperature is reported in degrees Celsius (°C) which can be converted to degrees Fahrenheit (°F) as follows:

$$^{\circ}\text{F} = 1.8 (^{\circ}\text{C}) + 32^{\circ}$$

Temperature in degrees Fahrenheit (°F) may be converted to degrees Celsius (°C) as follows:

$$^{\circ}\text{C} = (^{\circ}\text{F} - 32) / 1.8$$

Horizontal coordinate information is referenced to the North American Datum of 1927 (NAD27).

Abbreviated water-quality units: Bacteria concentrations are reported in units of colony forming units per 100 milliliters (cfu/100 mL).

Acronyms and Abbreviations

ACCUM	parameter defining non-point source daily land-surface loading rate for bacteria
ADAPS	USGS automated data processing system for streamflow data
AFO	animal feeding operations
AOQUAL	algorithm representing transport processes with baseflow
CIMIS	California Irrigation Management information System
cfu	colony forming units
DEM	digital elevation model
DEQ	Department of Environmental Quality
FSTDEC	first-order exponential decay coefficient in channels
FTABLE	function table in HSPF describing the relation between discharge and stage
GIS	geographic information system

Hydrologic parameters

CEPSC	parameter defining interception of rainfall
HRU	hydrologic response unit
HSPF	Hydrological Simulation Program-FORTRAN
IEUA	Inland Empire Utilities Agency
IHC	Ice House Canyon
IMPLND	impervious land units in HSPF
IOQUAL	algorithm representing transport processes with interflow
IQUAL	water quality module in HSPF for impervious land units
IWATER	hydrologic water-budget module for impervious land units
LAC	Los Angeles County
MF	membrane-filtration
MPN	most probable number
MUID	map unit identifier for STATSGO database
NCDC	National Climatic Data Center
NHD	National Hydrography Dataset
NWIS	National Water Information System
OCPHL	Orange County Public Health Laboratory
OCWD	Orange County Water District
PERLND	pervious land units in HSPF
PET	potential evapotranspiration
PPOC	Prado Park Lake outflow
PQUAL	water quality module in HSPF for pervious land units
PWATER	hydrologic water-budget module for pervious lands
r^2	regression coefficient
RAWS	Remote Automated Weather Stations
REMQOP	parameter defining the constant die-off rate for bacteria
RETS	parameter defining the retention-storage
RP-1	Inland Empire Utilities Agency Carbon Canyon Regional Plant 1

RWQCB	Regional Water Quality Control Board
SAWPA	Santa Ana Watershed Project Authority
SBC	San Bernardino County
SCCWRP	Southern California Coastal Water Research Project Authority
SOQUAL	algorithm representing surface flow processes
SHADE	parameter defining shading on snow
SQO	initial loading on land surfaces
SQQLIM	parameter defining the storage limit of loading by estimating the die-off on the land surface between runoff events
STATSGO	State Soil Geographic Database
SSURGO	Soil Survey Geographic Database
TDS	total dissolved solids
TMDL	Total Maximum Daily Load (a pollution control plan)
USACE	U.S. Army Corps of Engineers
USEPA	U.S. Environmental Protection Agency
USGS	U.S. Geological Survey
WRCC	Western Regional Climate Center
WSQOP	parameter defining the rainfall needed to remove 90 percent of accumulated pollutant on land
WY	water year, October 1 through September 31

This page intentionally left blank.

Application of a Watershed Model (HSPF) for Evaluating Sources and Transport of Pathogen Indicators in the Chino Basin Drainage Area, San Bernardino County, California

By Joseph A. Hevesi, Lorraine E. Flint, Clinton D. Church, and Gregory O. Mendez

Abstract

A watershed model using Hydrologic Simulation Program—FORTRAN (HSPF) was developed for the urbanized Chino Basin in southern California to simulate the transport of pathogen indicator bacteria, evaluate the flow-component and land-use contributions to bacteria contamination and water-quality degradation throughout the basin, and develop a better understanding of the potential effects of climate and land-use change on water quality. The calibration of the model for indicator bacteria was supported by historical data collected before this study and by samples collected by the U.S. Geological Survey from targeted land-use areas during storms in water-year 2004. The model was successfully calibrated for streamflow at 5 gage locations representing the Chino Creek and Mill Creek drainages. Although representing pathogens as dissolved constituents limits the model's ability to simulate the transport of pathogen indicator bacteria, the bacteria concentrations measured over the period 1998-2004 were well represented by the simulated concentrations for most locations. Hourly concentrations were more difficult to predict because of high variability in measured bacteria concentrations. In general, model simulations indicated that the residential and commercial land uses were the dominant sources for most of the pathogen indicator bacteria during low streamflows. However, simulations indicated that land used for intensive livestock (dairies and feedlots) and mixed agriculture contributed the most bacteria during storms.

The calibrated model was used to evaluate how various land use, air temperature, and precipitation scenarios would affect flow and transport of bacteria. Results indicated that snow pack formation and melt were sensitive to changes in air temperature in the northern, mountainous part of the Chino Basin, causing the timing and magnitude of streamflow to shift

in the natural drainages and impact the urbanized areas of the central Chino Basin. The relation between bacteria concentrations and air temperature was more complicated, and did not substantially affect the quality of water discharging from the Chino Basin into the Santa Ana River. Changes in precipitation had a greater basin-wide affect on bacteria concentrations than changes in air temperature, and varied according to location. Drainages representing natural conditions had a decrease in bacteria concentrations in correlation with an increase in precipitation, whereas drainages in the central and southern part of the Chino Basin had an increase in bacteria concentrations. Drier climate conditions tended to result in higher sensitivity of simulated bacteria concentrations to changes in precipitation. Simulated bacteria concentrations in wetter climates were usually less sensitive to changes in precipitation because bacteria transport becomes more dependent on the land-use specified bacteria loading rates and the storage limits. Bacteria contamination from impervious-area runoff is affected to a greater degree by drier climates, whereas contamination from pervious-area runoff is affected to a greater degree by wetter climates. Model results indicated that the relation between precipitation, runoff, and bacteria contamination is complicated because after the initial bacteria washoff and transport from the land surfaces during the beginning of a storm period, subsequent runoff has fewer bacteria available for washoff, which then dilutes the concentrations of bacteria in the downstream reach. It was illustrated that pathogen indicator bacteria transport depends most significantly on the relation of imperviousness to runoff, which controls the frequency, and often the magnitude, of transport, and on the contribution of higher bacteria loading rates used for pervious land areas, especially intensive feedlots, to the infrequent, but very high, peaks of bacteria contamination.

The indicator bacteria transport model for the Chino Basin was based on the assumption that non-point bacteria loading rates can be defined according to 12 different land use categories. Results from water-quality sampling, model calibration, and model application indicated that important differences exist for loading rates and parameters controlling bacteria washoff between natural land use, urban land use, and agricultural land use. In addition, the fraction of impervious area for a given land use is a critical factor in determining the effect of storm runoff on downstream water quality. Increasing the impervious area usually increases the frequency of impaired water quality caused by bacteria that are washed off during smaller storms. An increase in the fraction of pervious area having higher non-point bacteria loading rates and wash-off limits does not necessarily cause the frequency of impaired water quality to increase, and may even cause the frequency of impaired water quality to decrease, but the maximum for bacteria concentrations during the largest storms will likely be much higher. Additional sampling during large storms would likely provide a better assessment of non-point-source loading rates and washoff limits for pervious areas with agricultural and recreational land use that are likely sources of bacteria contamination.

Introduction

Background

The Santa Ana River, the largest stream system in southern California, is the primary water supply for approximately 2 million people ([fig. 1](#)). The Santa Ana Regional Water Quality Control Board (RWQCB) has listed the Santa Ana River and its tributaries in the Chino Basin as impaired water bodies on the RWQCB 303(d) list from the Clean Water Act. The main constituent of regulatory concern is pathogens that have impaired the waters for the beneficial uses of warm freshwater habitat and non-contact water recreation. Baseflow in the Chino Basin streams consist primarily of secondary treated wastewater. Periodic storm events during the rainy season (December through March) supply water to the streams that consist primarily of urban runoff. In addition to urban runoff,

there is considerable runoff from the concentrated dairy operations in the southern part of the Chino Basin. Wastes in runoff from animal feeding operations (AFO) in the Chino Basin may adversely affect water quality in Chino Creek, Mill Creek, and the Santa Ana River ([fig. 2](#)). As of 1995 the Chino Basin had one of the highest concentrations of dairy animals in the world, with 279 facilities and more than 250,000 cows (Rice, 2005) within an area less than 50 square miles (30,000 acres). Applying manure to the ground in the Chino Basin ([fig. 1](#)) has resulted in significant ground-water pollution, specifically total dissolved solids (TDS) and nitrate (shipping solid wastes out of the basin and to bio-recycling facilities has reduced pollution). Contamination of ground water in the Chino Basin affects the quality of water in the Santa Ana River where ground water from the Chino Basin contributes to the surface flow of the Santa Ana River during the wetter winter months, especially during wetter than normal seasons.

Reaches in Chino Creek and two tributaries, Mill Creek and Prado Park Lake (in Prado Basin), together with reaches of the Santa Ana River ([fig. 2](#)), were included on the 1998 Clean Water Act Section 303(d) list of impaired water bodies for pathogens, thus triggering action for developing a pollution control plan, the Total Maximum Daily Load (TMDL) for pathogens. The TMDL process has begun for these Chino Basin water bodies, and the Santa Ana Watershed Project Authority (SAWPA) is currently assisting the Santa Ana RWQCB in collecting data from the Chino Basin to develop TMDLs.

Developing TMDLs typically requires using numerical or analytical models to evaluate the transport and storage of water and water-quality constituents (Moyer and Hyer, 2003). Calibrated models can be used to help develop a better understanding of the likely affect of climate change, land-use change, or changes in management practices on water quality. For this study, the Hydrological Simulation Program-FORTRAN (HSPF) was used to simulate the transport of water and pathogen indicator bacteria in the Chino Basin. Pathogen indicator bacteria include fecal coliform, *Escherichia coli* (*E. coli*), and enterococci. Indicator bacteria are typically used to develop pathogen TMDLs because the presence of indicator bacteria is correlated to the presence of pathogens, which are difficult to measure directly.

Figure 1. Study area and other basins used to study indicator bacteria in and near the Chino Basin, California. Meteorologic data stations used to develop upper boundary conditions for the Chino Basin are included. CIMIS, California Irrigation Management information System; LAC, Los Angeles County; NCDC, National Climatic Data Center; RAWS, Remote Automated Weather Stations; SBC, San Bernardino County.

Figure 2. Study area, model boundary, water bodies, and drains in the Chino Basin, California.

RWQCB, [Santa Ana] Regional Water Quality Control Board; TMDL, Total Maximum Daily Load; USGS, U.S. Geological Survey.

Purpose and Scope

This report describes the collection and analysis of pathogen indicator bacteria (total coliform, fecal coliform, *E. coli*, and enterococci), and the development, calibration, and application of the HSPF model to the Chino Basin. Land-use, meteorological, topographical, and water-quality and streamflow data for the Chino Basin were compiled to develop the necessary input parameters for the HSPF model. The U.S. Geological Survey (USGS) collected water-quality samples at 9 sites ([fig. 2](#)) throughout the basin during 3 storm periods in 2004. Indicator bacteria concentrations in these samples were plotted on storm hydrographs and analyzed to determine pathogen indicator bacteria concentrations in storm runoff from urbanized and agricultural areas. Sampling sites were selected primarily to represent bacteria loadings from specific land uses. The model was calibrated for streamflow simulation using streamflow data for the 1990–2001 water years and the 2004 water year from 4 USGS gaging stations and 1 U.S. Army Corps of Engineers (USACE) gage. Streamflow simulated by the model was verified using data from water-years 2002–03 and 2005. Calibration of the model for the simulation of bacteria concentrations during storm runoff was limited because of the small number of bacteria samples coincident with storm hydrographs. Supplementary data from other investigations were included in this study to improve the transport-model calibration and allow limited verification of the transport model. The transport model was applied using various climate and land-use scenarios to improve understanding of processes controlling indicator bacteria concentrations (and thus potential pathogen contamination) at locations throughout the Chino Basin. The findings from the water-quality sampling, analysis, and transport-model application will be used to support the development and implementation of the pathogen TMDL.

Characteristics of the Chino Basin

Topography and Geology

The topography in the Santa Ana River watershed ranges from steep, rugged mountains with peaks as high as 10,700 ft above sea level, to a broad alluvial-filled valley, bordered by the San Gabriel/San Bernardino Mountains to the northeast and the elevated Perris Block/San Jacinto Mountains to the south ([fig. 1](#)). The Santa Ana River is the main tributary draining the valley. The Chino Basin study area, located in the northwestern part of this watershed, was formed as a result of tectonic activity along major fault zones (Wildermuth

Environmental, Inc., 2003). The bottom of the basin—the effective base of the freshwater aquifer—consists of relatively impermeable sedimentary and igneous bedrock formations that are exposed at the surface in the surrounding mountains and hills. Sediments eroded from the surrounding mountains have filled the Chino Basin, providing reservoirs for ground water. In the deepest portions of the basin, these sediments are greater than 1,000 ft thick. The sediments consist of geologically old and young alluvium. The thickness of the older alluvium varies from about 200 ft near the southwestern end of the Chino Basin to over 1,100 ft in the eastern parts of the valley and averages about 500 ft throughout the basin. The surface outcrop is commonly distinguishable by its red-brown or brick-red color and is generally more weathered than the overlying younger alluvium. The younger alluvium occupies streambeds, washes, and other areas having recent sedimentation. The thickness of the younger alluvium varies from over 100 ft near the mountains to just a few feet in the center of the valley. The younger alluvium generally covers most of the northern half of the Chino Basin in undisturbed areas (Wildermuth Environmental, Inc., 2003).

The stratigraphy of the Chino Basin can be described by two natural divisions: (1) the pervious formations that comprise the ground-water reservoirs are termed the water-bearing sediments and (2) the less pervious formations that enclose the ground-water reservoirs are termed the consolidated bedrock. The consolidated bedrock is further differentiated as metamorphic and igneous rocks of the basement complex partially overlain by consolidated sedimentary rocks. The water-bearing sediments overlie the consolidated bedrock, with the bedrock formations coming to the surface in the surrounding hills and highlands. The general geology of the Chino Basin and the distribution of sediments and soils are shown in [figures 3A,B](#).

Most recharge to the ground-water reservoirs of the Chino Basin is from percolation of direct precipitation and infiltration of streamflow within tributaries exiting the surrounding mountains and hills and within the Santa Ana River. Potential sources of recharge in the Chino Basin include the following: (1) infiltration of flow (and, locally, imported water) within unlined stream channels overlying the basin, (2) infiltration of stormwater flow and municipal wastewater discharges within the channel of the Santa Ana River, (3) underflow from the saturated sediments and fractures within the bounding mountains and hills, (4) artificial recharge at spreading grounds of storm water, imported water, and recycled water, (5) underflow from seepage across the bounding faults, (6) intermittent underflow from adjacent basins, and (7) deep percolation of precipitation and returns from use (Wildermuth Environmental, Inc., 2003).

EXPLANATION

Figure 3. A. Geology and B. soil units used to develop the HSPF model for the Chino Basin, California. STATSGO, State Soil Geographic Database; MUID, Map Unit Identifier.

Climate

Warm, dry summers and cool, moist winters characterize the climate of the study area. Average annual precipitation ranges from about 18 in. in the lower part of the Chino Basin to about 40 in. in the San Gabriel Mountains. Most precipitation occurs during the winter rainy season between November and March. Average precipitation for January ranges from about 3 in. in the southern valley ([fig. 4A](#)) to more than 10 in the mountains, whereas average precipitation for July is less than 0.1 in. across the whole basin (Daly and others, 2004). The spatial distribution of average monthly precipitation is similar for most months and is characterized by the orographic effect of the San Gabriel Mountains. For example, although average November precipitation has a spatial distribution that is similar to the January pattern, the average January precipitation is over 30% greater than that for all other months ([fig. 4A,B](#)). Air temperatures across the basin in the winter are cool, with average daily temperatures in degrees Fahrenheit in January ranging from the 30s in the north, resulting in persistent mountain snowpack at the higher altitudes, to as high as 60 in the southern valley. Average daily air temperatures for July can be quite warm, ranging from 65 to 80 degrees.

Surface Water and Drainage Network

Chino Creek is a tributary of the Santa Ana River. It extends upstream to the northwest from its confluence with the Santa Ana River ([fig. 2](#)). Chino Creek is divided into two reaches. Reach 1 extends from the confluence with the Santa Ana River and flows from north to south. Except for a short segment in the upper part of the reach, Reach 1 has a semi-natural, unlined channel bed and banks that have been straightened by engineering. Chino Creek Reach 1 was added to the 303(d) pathogen-impaired-water list in 1994. Chino Creek Reach 2 extends north of its confluence with San Antonio Creek, a major tributary draining the northwestern part of the Chino Basin. Chino Creek Reach 2 flows from northwest to southeast and is concrete-lined along its channel bed and banks throughout its length. San Antonio Creek, an important drainage feature in the western Chino Basin, is a tributary to Chino Creek, Reach 2. Reach 2 was added to the 303(d) list in 1998.

Baseflow in Chino Creek consists primarily of wastewater effluent discharges from Inland Empire Utilities Agency's (IEUA) Carbon Canyon publicly owned treatment works (POTW) Regional Plant 5 (RP-5), RP-1 (from discharge into Prado Park Lake), and nuisance runoff (dry season urban runoff from excessive watering of lawns, washing cars and streets, and over-using water for other residential and commercial activities). Chino Creek received wastewater effluent discharge from RP-2 also from 1970 to 2004, but this treatment plant was discontinued (treatment operations were relocated to RP-5).

Mill Creek is a tributary to Chino Creek Reach 2 in the southeastern part of the Chino Basin ([fig. 2](#)). Most of Mill Creek is within the Prado flood control basin behind Prado Dam. Mill Creek extends from its confluence with Chino Creek to a location near the San Bernardino/Riverside County border, where its name changes to Cucamonga Creek and it is concrete-lined. Mill Creek generally flows in a northeast to southwest direction and has a natural, semi-meandering channel with an unlined channel bed and banks. Baseflow in Mill Creek consists primarily of wastewater effluent from IEUA's RP-1 and nuisance runoff. Mill Creek and Prado Basin were added to the 303(d) list in 1994.

Cucamonga Creek Reach 1 ([fig. 2](#)) flows from north to south across the central part of the Chino Basin and is concrete-lined along its channel bed and banks throughout its length. Reach 2 is upstream of Reach 1. As with Mill Creek, baseflow in Cucamonga Creek consists primarily of effluent from IEUA RP-1 and nuisance runoff. Cucamonga Creek, Reach 1, was added to the 303(d) list in 1998.

Prado Park Lake (in Prado Basin) is a 60-acre man-made lake located in the southern part of the Chino Basin at the confluence of two natural drainage channels. The lake collects runoff from both urban and agricultural areas. During low-flow conditions, urban runoff from these two channels flows under the lake through pipes, and discharges into the lake's outlet structure. The capacity of the pipes is exceeded during large storms, and the excess storm runoff is discharged directly into the lake. Water levels in Prado Park Lake are maintained by discharge of approximately 8 million gallons per day (Mgal/d) of recycled water from IEUA RP-1. Excess water flows out of the lake into Chino Creek Reach 1. Prado Park Lake was placed on the 303(d) list in 1994 as a result of a fish kill incident in 1991. Elevated nutrient and bacteria levels were identified as sources of impairment in the 303(d) listing.

With the exception of runoff from extreme storms, stormwater runoff and snow melt from the northern mountainous areas of the Chino Basin usually is diverted or lost to infiltration into ground-water storage before it reaches the major channels in the central and southern parts of the basin. San Antonio Dam is a large flood-control structure that captures most of the snow melt and storm flow from San Antonio Canyon, greatly reducing streamflow in San Antonio Creek. During extreme storms and wetter than average years, some flow is released from San Antonio Dam, but much of this flow is diverted to retention basins and spreading grounds to enhance ground-water recharge (Wildermuth Environmental, Inc., 2003). Numerous other retention basins along the base of the San Gabriel Mountains capture runoff for flood control, debris-flow control, and recharge enhancement. This greatly reduces streamflow in the major channels, such as Cucamonga and Deer Creeks.

Figure 4. Average monthly precipitation from PRISM for A. November and B. January for the Chino Basin, California.

In contrast, peak flows and total discharge volumes of storm runoff from the urbanized central and lower portions of the basin are more frequent and can be much greater than streamflow from the mountainous areas. The urbanized areas have a high percentage of impervious surfaces (roads, parking lots, rooftops), which can rapidly generate large volumes of runoff during storms. Some of this storm runoff is diverted to retention basins for flood control and recharge enhancement. However, much of the runoff during the larger storms reaches the Santa Ana River and the Prado flood control basin. Storm runoff from the central and lower parts of the Chino Basin tends to have poor water quality because of washoff of contaminants, including bacteria and associated pathogens, from urbanized and agricultural areas (including dairies).

Compared to storm runoff, wastewater discharges, and Orange County water transfers into San Antonio Creek, nuisance flow (flow originating as small inflow from urbanized areas) is only a small fraction of the total discharge from the Chino Basin into the Santa Ana River. However, data collected from previous studies (Rice, 2005) indicates that nuisance runoff may contain high densities of indicator bacteria and thus may significantly affect the overall water quality in the Chino Basin during low-flow conditions ([Appendix 1](#)).

Land Cover and Use

The central part of the Chino Basin (south of the San Gabriel Mountain front and north of USGS stream gage 11073495) is heavily urbanized with extensive areas of high-density residential development interspersed with areas of commercial and industrial development ([fig. 5](#)). As a result of the urbanization, much of the land surface is impervious, and runoff is channelized. The urban features result in non-point sources also, as well as concentrated sources, of water-quality contaminants, including bacteria and associated pathogens. Specific sources of bacteria contamination in the urban areas of the Chino Basin are not well understood or identified, and are currently being evaluated, but general sources likely include both domesticated animals (pets) and wildlife (birds, rodents).

In contrast to the central part of the basin, most of the land area in the southern part of the Chino Basin is agricultural; about one-half of the agricultural area is used for intensive livestock operations (dairies). The dairies are likely sources of significant concentrations of pathogens. The remaining agricultural areas are also potential sources because these areas include horse ranches, poultry and hog operations, and crops using manure fertilizer.

Water Quality

Four existing point sources and 1 discontinued point source (RP2) discharge wastewater effluent into the waterways of the Chino Basin ([fig. 2](#)). Fecal coliform bacteria concentrations must be less than 200 cfu/100 mL before DEQ allows treated wastewater to be released. Most wastewater released contained concentrations far below that; data from the Inland Empire Utility Agency, which operates all treatment plants, indicated that total coliform concentrations in effluent do not exceed 2 cfu/100 mL. In addition to wastewater effluent, the Orange County water deliveries to San Antonio Creek below San Antonio Dam are significant point-source discharges into the Chino Basin. These discharges are generally pristine water and not a significant source of bacteria contamination.

Most of the bacteria in the Chino Basin were derived from, and were represented in the model as, nonpoint sources. These bacteria are deposited on the land surface by many different sources (people, pets, livestock, and wildlife), and subsequently are transported to the stream network in runoff from rainfall. Primary sources are the dairies, followed by high-to-medium density residential areas, and commercial/services, and utilities/transport. Private septic systems are few in the Chino Basin and are not a significant source of bacteria contamination.

Water-Quality-Data Sources and Methods of Collection and Analysis

Pathogen Indicator Bacteria

Pathogen indicator bacteria, which typically do not cause disease, are used to assess the microbiological quality of water because they are correlated with the presence of several waterborne disease-causing organisms. The concentration of indicator bacteria is a measure of water safety for body-contact recreation or for consumption. Wastes from warm-blooded animals contribute a variety of intestinal bacteria that are disease causing, or pathogenic, to humans. Body contact with, and consumption of water that contains, pathogens of the genera *Salmonella*, *Shigella*, and *Vibrio*, for example, can result in several types of disease in humans, including gastroenteritis and bacillary dysentery, typhoid fever, and cholera. Indicator bacteria, such as *Escherichia coli* (*E. coli*), in water is direct evidence of fecal contamination from warm-blooded animals, and may indicate the presence of pathogens, but cannot definitively prove or disprove the presence of human pathogenic bacteria, viruses, or protozoans.

Figure 5. Land-use and vegetation categories for the Chino Basin, California.

Water-quality criteria were developed by the U.S. Environmental Protection Agency (USEPA) in 1986 for concentrations of indicator bacteria in recreational waters, shellfish-growing waters, and ambient waters (U.S. Environmental Protection Agency, 1986). *E. coli* and enterococci bacteria became the recommended indicator bacteria for recreational waters, replacing fecal coliform and fecal streptococci bacteria (U.S. Environmental Protection Agency, 1986, 2000). However, concentrations of fecal coliforms measured in the basin in 2004 were highly correlated with concentrations of measured *E. coli* and, although data and model parameters are included for all bacteria, fecal coliform data are used for most graphical displays and analyses in this report because fecal coliform data from other studies are available for comparison.

Field Data Collection

Samples of indicator bacteria to be analyzed were collected at the nine USGS sites in the Chino Basin ([fig. 2](#); [table 1](#)). Indicator bacteria analyzed in this study included total coliforms, fecal coliforms, *E. coli*, and enterococci ([Appendix 1](#)). Membrane-filtration (MF) and most probable number (MPN) methods indicate colony forming units per 100 milliliters (cfu/100 mL), and were used to presumptively identify, confirm, and enumerate indicator bacteria. Additional analysis included colilert and enterolert microbial counting, but these methods were less reliable and were not as consistent as MF and MPN methods used in other studies of indicator bacteria concentrations in the Chino Basin and other nearby basins. The data obtained using the MF and MPN methods were used to calibrate the model.

To maintain consistency between the samples collected for this study and other samples of bacteria collected in the Chino Basin by the RWQCB, the samples for this study were analyzed by Orange County Public Health Lab (OCPHL). Approximately 10 percent of the samples were replicated to test the variability of field sampling by collecting duplicate samples in the field. Duplicate rather than split samples were collected, as required for consistency with the Orange County Health Laboratory sample processing procedures. Analyses of samples collected during the 2/22/2004, storm indicated a difference from the mean ranging from 8 percent to 70 percent, with no apparent correlation with high- or low-density samples ([table 2](#)). This range indicates error in representative sampling rather than laboratory processing. Six

of the eight land-use categories have errors less than or equal to 22 percent. Sixty-two duplicate lab samples were collected and tested by OCPHL during their 2002–2003 sampling, and an average of 2.5 percent difference from the mean was calculated between duplicates, indicating a variability ranging from zero to 86 percent. Additional samples were collected for total suspended sediment as a potential surrogate for indicator bacteria. Samples were also collected for turbidity, and water surface elevation (stage) measurements were made. The stage data provided qualitative information about relative discharge magnitude associated with the bacteria samples, and this was useful for model calibration. All USGS data are available in the National Water information System (NWIS) database (<http://nwis.waterdata.usgs.gov/nwis>).

The storm-targeted and land-use-targeted sampling locations were selected primarily to support the investigation of indicator bacteria concentrations in storm runoff from urban land and intensive feedlots (dairies). The sample locations selected for the urban land uses were also chosen according to their proximity to dairies: locations close to dairies, but not directly affected by storm runoff from dairies, and locations far from dairies. The urban land-use sites located close to dairies are RecD and RecGC (recreational land use possibly affected by dairies), ResD (residential land use potentially affected by dairies), and IndD (industrial land use potentially affected by dairies). The urban land-use sites located far from dairies are IndND (industrial land use), RecND (recreational land use), and SC (commercial and services land use).

The two sample sites representing recreational land use close to dairies were also used to investigate potential differences between different recreational land uses; the RecD site was located within a park and the RecGC was located within the area of a golf course. Four sample sites (SC, RecGC, ResD, and IndD) were located where at least 80 percent of the upstream catchment areas were covered by single land-use types. However, four other samples sites (IndND, RecND, RecD, and D) had catchments with multiple land uses, because of the difficulty in finding good sampling locations having sufficient storm-flows and representing a single land use. The catchment for site IndND was included in the residential and commercial land-use categories in addition to the industrial land-use category. The catchment for site D included mixed agriculture, transportation, and utilities categories in addition to dairies.

12 Application of HSPF for Evaluating Pathogen Indicators, Chino Basin Drainage Area, San Bernardino Co., California

Table 1. Storm sampling locations and results for fecal coliforms in samples collected November 2003 and February 2004 in the Chino Basin, California.

[Densities measured in colony forming units per 100 milliliters (cfu/100 mL); %, percent; —, no calculation]

Station identifi- cation	Location	Targeted land use	Features of catchment	Date sampled water-year 2004	Fecal coliforms (cfu/100 mL)		Number of samples
					Geometric mean	Maximum	
MC	Mill Creek at Chino Corona Road near Norco	Integrated sample	Large, heteroge- neous basin with all land uses	11/12–11/13	30,047	150,000	20
				2/2–2/3	2,820	7,100	6
				2/21–2/23	3,394	9,400	5
IndND	Storm drain at Francis and Grove near Ontario	Industrial	30% residential, 60% industry, 10% other	2/2–2/3	—	4,000	1
				2/22–2/23	4,736	9,000	5
RecND	Storm drain near Cypress and Philadelphia near Chino	Recreational park	60% park, 40% high school field	2/2–2/3	—	7,400	1
				2/22–2/23	3,455	6,000	5
SC	Town Square shopping center storm drain at Chino	Shopping center	Shopping center and parking lot only	2/2–2/3	—	1,500	1
				2/22–2/23	1,063	2,900	5
RecD	Westwind park storm drain near Ontario	Park, potential dairy impact	70% park down- stream of 30% residential	2/2–2/3	—	400	1
				2/22–2/23	1,064	10,000	5
RecGC	Whispering Lakes golf course parking lot storm drain near Ontario	Golf course	100% golf course	2/2–2/3	—	280	1
				2/22–2/23	233	830	5
ResD	Storm drain near Parco and Riverside at Ontario	Residential, potential dairy impact	80% residential, 20% school	2/2–2/3	—	6,000	1
				2/22–2/23	6,844	18,000	5
IndD	Industrial park storm drain near Kimball near Chino	Industrial, dairy	80% dairy, 20% industry	2/2–2/3	—	200	1
				2/22–2/23	89	320	5
D	Pine Avenue drainage ditch near Chino	Dairy	30% dairy, 40% irrigated crop and pasture, 20% airport, 10% other	2/2–2/3	—	6,000	1
				2/22–2/23	66,250	250,000	5

Table 2. Variability in fecal coliform densities from replicate samples collected on February 22–23, 2004, at various sites in the Chino Basin, California.

[Densities measured in colony forming units per 100 milliliters (cfu/100 mL)]

Land use category and site (in parentheses)	Date	Sample location	Densities		Percent error
			Sample	Replicate	
Industrial non-dairy (IndND)	2/22/04	Storm drain	3,400	3,000	11.8
Recreational non-dairy (RecND)	2/22/04	Storm drain	3,800	6,500	–71.1
Recreational non-dairy (RecND)	2/23/04	Storm drain	4,200	3,400	19.0
Recreational non-dairy (RecND)	2/23/04	Storm drain	5,800	6,300	–8.6
Recreational golf course (RecGC)	2/22/04	Storm drain	70	80	–14.3
Residential dairy (ResD)	2/22/04	Storm drain	2,900	6,000	–106.9
Industrial dairy (IndD)	2/23/04	Storm drain	50	40	20.0
Dairy (D)	2/22/04	Freshwater	37,000	40,000	–8.1

One storm was sampled intensively (20 samples) on 11/12/2003–11/13/2003, at the Mill Creek sampling site (site MC), which was a location integrating the streamflow from all the other sampling sites. It was located downstream of the USGS stream gage 11073495 ([table 1](#)). Storms on 2/2/2004–2/3/2004, and 2/22/2004–2/23/2004 also were sampled less intensively at this site (6 and 5 samples, respectively). The storm on 2/2/2004, was sampled once at the other 8 sampling sites, and the storm of 2/22/2004–2/23/2004 was sampled 5 times at the other 8 sampling sites. The relation between sampled bacteria concentrations at site MC (including total coliform, fecal coliforms, *E. coli*, and enterococci) and measured stream discharge at gage 11073495 for the 3 storms is shown in [figures 6A–C](#). The results indicate a wide

range in measured bacteria concentrations for total coliform and the three indicator bacteria types. For example, measured fecal coliform indicates a range of fecal coliform densities of 370 to 150,000 cfu/100 mL ([Appendix 1](#)). Graphs showing bacteria concentrations compared to stream discharge indicate a complicated relation for the 11/12/2003–11/13/2003 and the 2/22/2004–2/23/2004 storms, whereas the graph for the 2/2/2004–2/3/2004 storm indicates a more direct relation. However, the correlation between hourly stream discharge and bacteria concentrations, using the bacteria data for all storms and all sample sites, was weak. The correlation between turbidity and bacteria concentrations from all sample sites and during all storms was also weak.

Figure 6. Measured hourly stream discharge at gage 11073495 and measured bacteria concentrations at sample site MC for *A*, the 11/12/2003–11/13/2003 storm, *B*, the 2/2/2004–2/3/2004 storm, and *C*, the 2/22/2004–2/23/2004 storm in the Chino Basin, California.

Although all 4 indicator bacteria constituents were collected and used in the transport modeling analysis, only fecal coliform concentrations are given throughout the report, for simplicity and consistency with previous studies by other agencies. The relation between the measured fecal coliforms and the other three indicator bacteria constituents is shown in [figure 7](#). As indicated, the regression lines and equations indicate strong linear relations (r^2 between 0.71 and 0.89) between the fecal coliform concentrations and the *E. coli* concentrations, a subset of fecal coliforms, enterococci, and total coliforms. The deviation around the regression lines indicates sampling and measurement uncertainties.

Supplemental Water-Quality Data

High concentrations of bacteria contributed to fish kills in Prado Park Lake in 1979, 1983, and 1989 and to discharge of waste-laden agricultural stormwater runoff. To investigate possible sources of these bacteria, RWQCB collected stormwater samples at 14 locations in Chino Creek and Cucamonga Creek/Mill Creek on 2/23/1993 ([table 3](#)). The data derived from this sampling indicated levels of bacteria concentration determined to be unhealthy by USEPA standards (U.S. Environmental Protection Agency, 1986). However, the 1993 storm sampling data has had a limited utility because the techniques

Figure 6. Continued.

used to detect bacteria concentrations in the water samples were reliable only for indicating a lower limit to concentrations (in terms of cfu/100 mL). Samples were also collected during the winters of water-years 1997 and 1998 at 15 locations to confirm the 1993 data and evaluate bacteria densities after storm events. The 1997–98 data have higher resolution and quality than the 1993 data, having followed more rigorous analysis procedures, and provide a more quantitative dataset of bacteria concentrations for subwatersheds feeding directly

into Prado Park Lake. The 1997–98 data represent runoff from agricultural areas, including dairies, downstream of the highly urbanized areas in the Chino Basin. Water samples were analyzed for total coliform and fecal coliforms only. Results indicated that stormwater runoff contained concentrations of fecal coliforms that exceeded water-quality objectives by several orders of magnitude. Locations, associated land use, and sampling dates are shown in [table 3](#).

C

Figure 6 Continued.

Figure 7. Measured fecal coliform data and measured *E. coli*, enterococci, and total coliforms for all storm sampling events in the Chino Basin, California.

To represent conditions during seasons other than those represented by samples collected during the storm events in 2003 and 2004, RWQCB established an extensive monitoring program in February 2002; water samples were collected weekly at 10 to 13 locations during nine 30-day sampling periods (table 3). Only one sample per day was collected (sampling times were usually between 10 am and 2 pm), but samples were collected on multiple days during each 30-day sampling period, and represented both wet-season and dry-season flows. There were 5 sites on Mill Creek and its tributaries and 6 sites on Chino Creek and its tributaries. Land uses included agriculture, urban activities, dairies, and open space. Samples were analyzed for bacteria indicators, including fecal coliform, total coliform, *E. coli*, and enterococcus. The results from the analyses of these samples were used to define natural background conditions and calibrate the transport model to time-averaged bacteria concentrations and to conditions before WY2004 storm targeted sampling. In addition, the RWQCB samples were useful for increasing the number of samples representing the integrated, downstream response to non-point source loading from land used for multiple purposes. Orange County Water District (OCWD) collected indicator bacteria samples during water-year 2005 at 14 sites (table 3), many of which coincided with RWQCB sites (but none of which coincided with the storm-and-land-use targeted sample sites). Concentrations of total coliform, fecal coliform, *E. coli*, and

enterococcus in the OCWD samples were measured; the resulting OCWD data were compared with data from fecal coliform measured and simulated for water 2005, and were used to verify the calibrated bacteria transport model.

Comparison of the RWQCB fecal coliform data (including both the earlier and more recent sampling) with the data for the water-year 2004 storm-targeted samples collected for this study (plotted as daily averages) indicated a similarity in the relative magnitude and variability in measured concentrations (figure 8A). In particular, the water-year 2004 storm-targeted data is comparable to the range and variability of the 1996–98 RWQCB data, which is also representative of storm-flow conditions, whereas the water-years 2003–2004 RWQCB data includes sampling from low-flow conditions. A maximum fecal coliform concentration of approximately 100,000 cfu/100 mL is comparable to the maximum daily-average obtained for the 11/12/2003–11/13/2003 storm at the MC sampling site. Most of the storm samples fall in the range of 1,000–100,000 cfu/100 mL (or mpn/100 mL) for the two groups of storm-affected samples. Most of the 2003–2004 RWQCB data, however, ranges between 100 to 1,000 cfu/100 mL (or mpn/100 mL). The measured daily mean streamflow data for the upstream gaging site also falls within this range, approximately 1,000 to less than 10 ft³/s.

Table 3. Supplemental water quality data and primary land uses input for model calibration, from water samples collected during 1993–2004 in the Chino Basin, California.

[TMDL, total maximum daily load (a pollution control plan); data was collected by the Regional Water Quality Control Board (RWQCB) and Orange County Water District (OCWD). CCWD, Cucamonga Creek Water District; IEUA, Inland Empire Utilities Agency; —, no data or information available]

Location	Site identifier	TMDL 1993 storm sampling	TMDL 1996–1998 storm sampling	TMDL 2002–2004 seasonal sampling	OCWD	Primary land use	Sampling years
Archibald Avenue at Cloverdale Avenue	—	—	—	M4	—	Agriculture	2002–2004
Big League Dreams storm drain	BLD	—	—	—	S9	Urban/agriculture	—
Bon View Ave at Merrill (northwest corner)	BVAM	—	—	M3	—	Agriculture	2002–2004
Chino Creek at Central Avenue	CHIC	—	—	C7	S2	Urban	2002–2004
Chino Creek at Chino Avenue	—	—	5	—	—	—	1996–1998
Chino Creek at Mill Creek confluence	—	—	—	C4	—	Agriculture/urban/effluent	2002–2004
Chino Creek at Pine Avenue	CHIP	11	12	—	S12	Urban/wastewater	1993, 1996–1998
Chino Creek at Prado Golf Course	—	—	—	C8	—	Impairment status	2002–2004
Chino Creek at Prado Wetlands	—	—	—	—	—	Impairment status	2002–2004
Chino Creek at Riverside	CHIR	—	—	—	S5	Urban	1996–1998
Chino Creek at Schaeffer	CHIS	6	—	C2	S3	Urban	1993, 2002–2004
Chino Creek downstream of Wetlands	—	—	—	C6	—	Impairment status	2002–2004
Cucamonga Creek at Baseline	—	1	—	—	—	—	1993
Cucamonga Creek at CCWD Ponds	CCM1	—	—	M1	—	Open space	2002–2004
Cucamonga Creek at IEUA RP-1	CCM2	—	—	M2	—	Urban	2002–2004
Cucamonga Creek at Philadelphia	—	2	—	—	—	—	1993
Cucamonga Creek at Riverside Drive	CUCR	3	2	—	—	—	1993
Cypress Channel at Edison Avenue	—	7	6	—	—	—	1993, 1996–1998
Cypress Channel at Golf Course	CYP3	—	—	—	S8	Urban	—
Cypress Channel at Kimball Avenue	CYP2	8	11	—	S7	Urban/agriculture	1993, 1996–1998
Cypress Channel at Pine Avenue	—	12	13	—	—	—	1993
Cypress Channel at Riverside	—	—	4	—	—	—	1996–1998
Cypress Channel at Shaeffer Avenue	CYP1	—	—	—	S6	Urban	—
Dirt channel on Kimball Avenue	KIM	—	—	—	S10	Urban/agriculture	—
Euclid Channel at Pine Avenue	E1	—	10	—	—	—	1996–1998
Grove Channel at Merrill Avenue	—	9	7	—	—	—	1993, 1996–1998
Grove Channel at Pine Avenue	G1	13	9	—	—	—	1993, 1996–1998
Grove Channel at Prado Park	—	15	14	—	—	—	1993, 1996–1998
Grove Channel at Riverside Drive	—	4	3	—	—	—	1993, 1996–1998
Icehouse Canyon Creek	IHC	—	—	C1	S1	Open space	2002–2004
IEUA Carbon Canyon waste reclamation facility	CCWRF	—	—	—	S14	Effluent	—
IEUA RP-1 effluent at Riverside Drive	RP1	—	2a	—	—	Effluent	1996–1998
IEUA RP-5 effluent	RP5	—	—	—	S13	Effluent	—
Mill Creek at Chino-Corona Road	MC	14	15	M5	—	Impairment status	1993, 1996–1998, 2002–2004
Prado Park Outlet at Chino Creek confluence	PPOC	—	—	C3	—	Agriculture/dairies	2002–2004
Prado Wetlands effluent	—	—	—	C5	—	—	2002–2004
San Antonio Wash at County Drive	SAW	—	—	—	S4	Urban/commercial	—

Figure 8. Streamflow hydrographs of and measured fecal coliform bacteria concentrations for water-years 1996–2005 in *A*, daily streamflow at gage 11073495 and daily fecal coliform concentrations at site MC, and *B*, monthly streamflow at gage 11073360 and daily fecal coliform concentrations at sample site CHIS in the Chino Basin, California. USGS, U.S. Geological Survey; TMDL, Total Maximum Daily Load; RWQCB, Regional Water Quality Control Board; OCWD, Orange County Water Agency.

Orange County Water District (OCWD) collected indicator bacteria samples during water-year 2005 at 14 sites (table 3), many of which coincided with RWQCB sites (but none of which coincided with the storm-and-land-use targeted sample sites). The OCWD samples were measured for total coliform, fecal coliform, *E. coli*, and enterococcus, the OCWD data were used to verify the calibrated bacteria transport model based on a comparison of measured and simulated fecal coliform for water 2005. Comparison of the water-years 1996–1998 and water-years 2002–2004 RWQCB fecal coliform samples with the OCWD 2005 fecal coliform samples indicates the range and variability in measured bacteria concentrations between the 3 sample groups

(fig. 8B). Like the historical data collected at the MC site, the RWQCB data indicates that the bacteria concentrations were higher in 1996–1998 than in 2002–2004; bacteria concentrations for the earlier group ranged from 200 cfu/100 mL to more than 100,000 cfu/100 mL, whereas concentrations for the later group ranged from about 10 cfu/100 mL to about 20,000 cfu/100 mL. The OCWD 2005 data, which includes samples collected during low-flow conditions, indicates a range of values more consistent with the 1996–1998 RWQCB data. No strong correlations between bacteria concentrations and streamflow magnitude were observed for the supplemental bacteria data. The lack of significant correlation is consistent with results obtained from previous studies.

B **Figure 8.** Continued.

Correlations between total coliform, fecal coliform, *E. coli*, and enterococcus were generally consistent with the correlations observed for the water-year 2004 storm-targeted sampling. Correlations with turbidity were not analyzed ([fig. 8B](#)).

Analysis of Water-Quality Data

The bacteria samples collected for this study and the supplemental data from other studies were generally consistent in indicating (1) highly variable concentrations of pathogen indicator bacteria in storm runoff from urban and agricultural

areas; (2) indicator bacteria concentrations frequently exceeding 200 cfu/100 mL for both urban and agricultural runoff; (3) indicator bacteria concentrations less frequently exceeding 200 cfu/100 mL for runoff representing natural or background conditions; (4) high bacteria concentrations in nuisance flow; (5) average bacteria concentrations higher during storm-flow conditions than during low-flow conditions; (6) maximum bacteria concentrations (>1,000,000 cfu/100 mL) in runoff from agricultural areas (including mixed agriculture and dairies); and (7) no significant correlation between bacteria concentration and hourly streamflow at nearby gages.

The variability and magnitude of fecal coliform concentrations in the storm-flow-targeted samples collected specifically for this study were generally consistent with those in the RWQCB 1996–1998 storm flow samples. Although there was no significant correlation between bacteria concentration and hourly streamflow, storm-flow concentrations were on average higher than the low flow and seasonal concentrations in samples collected by the RWQCB during 2002–2004. Bacteria levels usually reached a maximum during storm flows. The data collected for this study did not indicate a relation between bacteria contamination and proximity to dairies for a given land use (for locations not affected by runoff from dairies). Results from multiple sampling sites having a single land use (recreation and open space, industrial) indicated high variability in bacteria concentrations, suggesting that (1) non-point bacteria loading may not be consistent or uniform for a given land use, and, (2) more frequent sampling may be needed during storm runoff to establish correlations between storm-flow water quality and land use. The most conclusive results provided by the combined set of storm-flow and non-storm-flow water-quality samples are that (1) bacteria concentrations in storm runoff and nuisance flow are on average much higher than natural background levels in the Chino Basin, and, (2) there is a higher frequency of bacteria concentrations greater than 200 cfu/100 mL in runoff from both urban and agricultural land uses than for other land uses.

Data Limitations

Model development and simulation relies on a calibration that is based on field observations of the parameters of interest; in this case, streamflow and concentrations of indicator bacteria. Except for data for storm water sampled during storms in 1992–1993 and 1996–1998, available historical data did not represent the higher flow periods during and immediately after storms. In addition, many of the historical sampling sites were not selected to target runoff from specific land uses; most of the sampling sites were located too far downstream and therefore represent an integrated response to multiple land uses.

Storm-water data collected by the USGS for this study were incorporated into the model calibration process to provide information on the response of indicator bacteria concentrations (fecal coliforms, *E. coli*, total coliforms, and enterococci) during stormflows. Most of the data were for storm runoff from relatively small catchments (as small as 3 acres) that represented specific urban land uses. Uncertainties in collecting the water-year 2004 storm samples include lack of laboratory duplicates, and collecting single samples at each field location may not reflect cross-sectional averages in a stream. The size of the sample of indicator bacteria data was too small to enable relative land-use contributions for all

land uses defined in the model to be assessed. The data did not provide a direct measure of land-use-specific bacteria loading rates, storage capacities, and washoff limits, but model calibration was required to define the parameters controlling bacteria accumulation and transport, and relied on default and historical model parameters as initial estimates, such as those indicated in [table 4](#).

Bacteria sampling techniques, including both field methods and laboratory analysis, have evolved throughout the period during which the data used in the study were collected. A direct comparison of bacteria concentrations obtained using different sampling techniques is not always possible. For example, data obtained for the 1993 and 1996–1998 storm-water study has lower resolution than data obtained during 2004 and 2005 because of improvements in sampling techniques. Data indicated that bacteria concentrations collected by OCWD at the same sites appeared to be higher in WY2005 than in earlier years, but this may be caused by differences and improvements in sampling techniques as opposed to actual trends.

Simulation of Streamflow and Bacteria Transport

Description of Model

The computer code Hydrologic Simulation Program – FORTRAN (HSPF) version 12 (Bicknell and others, 1997)—a lumped-parameter, continuous-simulation watershed model—was chosen to simulate the streamflow and the indicator bacteria transport in the Chino Basin. HSPF simulates the transport and storage of water and associated water-quality constituents by routing observed precipitation by way of watershed surface, soil, and instream processes (Donigan and others, 1995). HSPF represents the mechanisms of transport and storage within distinct modules for three unique model elements: pervious land segments (PERLND), impervious land segments (IMPLND), and stream channels (RCHRES). These hydrologic transport mechanisms vary naturally because of spatial changes in watershed characteristics such as topography, land use, and soil properties; HSPF accounts for this variability by simulating runoff from smaller, more homogeneous parts of the watershed that are linked by interconnected channel segments. Thus, for modeling purposes, the watershed was disaggregated into segments having similar climatic and topographical characteristics. Each subwatershed was refined further into hydrologic response units (HRU) that represent areas, within each land segment, with similar watershed characteristics, such as land use.

Table 4. Hydrological Simulation Program—FORTRAN (HSPF) model calibration parameters for hydrologic and transport simulations of fecal coliforms used in several regional models and the Chino Basin model, as well as default HSPF parameters.

[Modules: PWATER, IWATER, PQUAL, IQUAL. Min, minimum; Max, maximum; unk, unknown, value not available; in/hr, inch per hour; deg F, degree Fahrenheit; cfu/d, colony forming units per day; cfu/ft³, colony forming units per cubic foot; n/a, not applicable]

Parameter	Description	Units	Model									
			HSPF		Santa Monica Bay ¹		Cottonwood Creek, Idaho ²		San Jacinto Basin ³		Chino Basin ⁴	
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
PWATER Module												
AGWETP	Fraction of remaining evapotranspiration from active groundwater	none	0	0.2	0.05	0.05	0.01	0.01	0.15	0.25	0.05	0.22
AGWRC	Base groundwater recession	1/day	0.85	0.999	0.92	0.92	0.98	0.98	0.7	0.995	0.01	0.85
BASETP	Fraction of remaining evapotranspiration from baseflow	none	0	0.2	0.05	0.05	0.05	0.05	0.2	0.2	0.02	0.34
CEPSC	Interception storage capacity	inch	0.01	0.4	0.1	0.1	0.1	0.1	0.1	0.15	0.1	0.2
DEEPR	Fraction of groundwater inflow to deep recharge	none	0	0.5	0.4	0.4	0.6	0.6	0.2	0.2	0.05	0.99
INFEXP	Exponent in infiltration equation	none	1	3	2	2	2	2	unk	unk	2	2
INFILD	Ratio of maximum to mean infiltration capacities	none	1	3	2	2	2	2	unk	unk	2	2
INFILT	Index to infiltration capacity	in/hr	0.001	0.5	0.03	0.03	0.05	0.05	0.08	1.5	0.11	0.44
INTFW	Interflow inflow parameter	none	1	10	1.5	1.5	0.1	0.1	3	10	0.15	2.55
IRC	Interflow recession parameter	none	0.3	0.85	0.7	0.7	0.7	0.7	0.3	0.8	0.05	0.75
KVARY	Variable groundwater recession	1/inch	0	5	2.3	2.3	0	0	unk	unk	0.01	0.999
LSUR	Length of overland flow	feet	100	700	155	155	500	500	unk	unk	100	1,000
LZETP	Lower zone evapotranspiration parameter	none	0.1	0.9	0.7	0.7	0.1	0.1	0.8	0.9	0.1	0.9
LZSN	Lower zone nominal soil moisture storage	inch	2	15	7.6	7.6	7	7	2	8	6.5	9.5
NSUR	Manning's n (roughness) for overland flow	none	0.05	0.5	0.2	0.2	0.25	0.35	unk	unk	0.02	0.35
PETMAX	Temperature below which evapotranspiration is reduced	deg F	32	48	33.4	33.4	32	32	unk	unk	35	40
PETMIN	Temperature below which evapotranspiration is set to 0	deg F	30	40	31	31	30	30	unk	unk	30	35
UZSN	Upper zone nominal soil moisture storage	inch	0.05	2	0.9	0.9	0.5	0.5	0.3	1	0.117	2.128
IWATER Module												
LSUR	Length of overland flow	feet	50	250	155	155	300	300	unk	unk	150	150
NSUR	Manning's n (roughness) for overland flow	none	0.01	0.15	0.025	0.025	0.2	0.2	unk	unk	0.05	0.05
PETMAX	Temperature below which evapotranspiration is reduced	deg F	32	48	35	35	40	40	unk	unk	35	35
PETMIN	Temperature below which evapotranspiration is set to 0	deg F	30	40	30	30	35	35	unk	unk	30	30
RETSC	Retention storage capacity	inches	0.01	0.3	0.05	0.05	0.65	0.65	unk	unk	0.02	0.02

Table 4. Hydrological Simulation Program—FORTRAN (HSPF) model calibration parameters for hydrologic and transport simulations of fecal coliforms used in several regional models and the Chino Basin model, as well as default HSPF parameters.—Continued

[Modules: PWATER, IWATER, PQUAL, IQUAL. Min, minimum; Max, maximum; unk, unknown, value not available; in/hr, inch per hour; deg F, degree Fahrenheit; cfu/d, colony forming units per day; cfu/ft³, colony forming units per cubic foot; n/a, not applicable]

Parameter	Description	Units	HSPF	Model							
				Santa Monica Bay ¹		Cottonwood Creek, Idaho ²		San Jacinto Basin ³		Chino Basin ⁴	
				Min	Max	Min	Max	Min	Max	Min	Max
PQUAL and IQUAL Modules											
ACCUM	Daily loading onto the land surface	cfu/d	0	1.0E+10	1.0E+11	4.4E+06	1.8E+07	n/a	n/a	1.6E+03	1.5E+11
AQO	Storage in active groundwater	cfu/ft ³	n/a	n/a	n/a	n/a	n/a	n/a	n/a	0	600
IQO	Storage in interflow	cfu/ft ³	n/a	n/a	n/a	n/a	n/a	n/a	n/a	0	600
FSTDEC	First-order exponential decay coefficient in reach	1/day	0.0001	0.8	1.8	0.6	0.6	n/a	n/a	0.33	0.83
SQO	Initial loading on land surface	cfu/d	0	0	1.2E+08	4.4E+06	1.8E+07	n/a	n/a	1.0E+02	1.2E+07
SQOLIM	Die-off on the land surface in between runoff (loading) events	cfu/d	0.000001	0	1.0E+11	4.0E+07	1.6E+08	n/a	n/a	3.6E+04	1.5E+13
WSQOP	Rainfall needed to remove 90% of accumulated pollutant on land	in/hr	0.01	0.01	0.5	0	0.5	n/a	n/a	8.8E-02	0.44

¹ Ackerman and Weisberg, 2003.

² U.S. Environmental Protection Agency, 2000.

³ Guay, 2002.

⁴ This report.

In each stream reach in the model, water from PERLNDs was supplied to the reach as overland flow, interflow (shallow subsurface flow), or baseflow (ground-water discharge); from IMPLNDs as overland flow; from point sources as sewage-treatment plant effluent or dam releases and from upstream channel reaches as streamflow. All water was assumed to enter the separate stream reaches at a single, upstream point. The impervious fraction was broken into two categories: “hydrologically effective” and “hydrologically ineffective” (Zarriello, 1999). Hydrologically effective areas drain directly to stream channels and were represented by the IMPLND (impervious lands) module. Hydrologically ineffective areas drain onto pervious land types, such as grassland or forest, and were better represented by the PERLND module.

The hydrologic processes acting on a PERLND are considerably more complex than those acting on an IMPLND and were represented by a hydrologic water-budget module (PWATER) that included model parameters for water storage and transport along both surface- and subsurface flow paths. The hydrologic water-budget module for processes affecting an IMPLND (IWATER) is much simpler than the PWATER module because there are no subsurface flow paths. Precipitation interception by features that extend above the IMPLND (urban vegetation and rooftops for example) is described by an impervious retention-storage parameter (RETS). Other hydrologic parameters for surface runoff are the same in IWATER and PWATER. Many of the hydrologic parameters for both PWATER and IWATER were adjusted during calibration to simulate the hydrologic routing through each HRU that was determined from GIS analysis using ArcGIS. These are defined in [table 4](#). More detailed descriptions of the modules, pathways, and parameters are given by Moyer and Hyer (2003).

Although bacteria transport in a watershed is closely tied to hydrologic processes, the concentrations at any location also depend heavily upon the initial supply from land-surface and point sources and the rate of die-off. The HSPF model simulates the transport of indicator bacteria from pervious land surfaces using a PQUAL (water quality on pervious land units) module similar to the hydrologic PWATER module. Thus, PQUAL simulates the storage and transport of bacteria along surface and subsurface flow paths. Seven bacteria-transport parameters are used in the PQUAL and IQUAL (water quality on impervious land units) modules for simulation ([fig. 9](#); [table 4](#)) and are run through 3 algorithms representing surface flow (SOQUAL), interflow (IOQUAL), and baseflow (AOQUAL) processes. Bacteria transport from impervious surfaces is simulated using an IQUAL module. The processes and routing parameters in IQUAL are identical to those in PQUAL for the surface-transport component.

Water that enters each reach was assumed to flow downstream as a kinematic wave (Martin and McCutcheon, 1999). Flow characteristics are governed by such channel morphological parameters as cross-sectional area, roughness, and slope. These parameters were measured in the field or estimated from aerial photos and used to develop a function table (FTABLE)

module that related stage to discharge at each end of the reach and provided reach values for channel water-surface area and volume. Except for a portion that dies off over time, bacteria that enter a stream reach were presumed to travel downstream with the water to the next reach. The die-off rate (parameter REMQOP) was a fixed first-order decay rate of 1.1 day^{-1} (U.S. Environmental Protection Agency, 1985). Every source represented in the model had a specific fecal coliform accumulation rate (represented by the ACCUM parameter). The total accumulation rate of fecal coliform bacteria on the land surface was bounded by a storage limit that enabled the model to account for the natural die-off of bacteria stored on the land surface. For this study, the storage limit (SQOLIM) was set to 1.8 times the accumulation rate, which represents a decay rate of 0.55 day^{-1} (U.S. Environmental Protection Agency, 1985).

The most critical limitation associated with the HSPF bacteria-transport model developed for this study was that pathogen indicator bacteria were simulated as a dissolved constituent. Bacteria, however, are particulate constituents and are deposited and re-suspended once delivered to the active stream channel. The transport mechanisms associated with deposition and resuspension were not simulated explicitly. Although HSPF can simulate bacteria as particulate constituents using a combination of sediment transport and water-quality modules, these methods were not applied in this study because of the need for additional model parameters for sediment transport and a lack of available data to support the parameterization. Other studies simulating bacterial transport using HSPF have had successful results despite this limitation (Moyer and Hyer, 2003; Yagow and others, 2001), and have suggested addressing bacteria as dissolved constituents. In the advective transport model used for this study, the resuspension of bacteria was implicitly represented by interflow and baseflow transport used primarily in the northern mountainous parts of the Chino Basin. For this study, interflow and baseflow transport were used in order to also provide at least some representation of point sources affecting baseflow in the mountainous drainages.

Interflow and baseflow in the central and southern parts of the Chino Basin were not included in the model, except for a small amount of throughflow in the southernmost part. Instead, an assumed nuisance flow (flow originating as small inflow from urbanized areas) was added to each reach having urban or agricultural land use in the land segment contributing runoff to that reach. The nuisance flow was modeled as a specified point-source inflow (to the upstream node of the reach) rather than as a specified overland flow component, because of a lack of data specifying nuisance flow for the 12 PERLNDs and IMPLNDs. The specified nuisance flow was used to implicitly represent contaminated runoff from the land units during the dry periods between storms, as well as point sources and re-suspension or regrowth of bacteria in reaches. Although this method likely over-simplifies processes controlling bacteria loading and transport in the reaches, the inclusion of contaminated nuisance flow was supported by the field data and thus was preferred to assuming nuisance flow was pristine.

Figure 9. Routing processes represented by the Hydrological Simulation Program—FORTRAN code for the simulation of fecal coliform bacteria transport and storage parameters. SQO, initial loading on land surface; IQO, storage in interflow; AQO, storage in active ground water; SOQUAL, algorithm representing surface flow processes; IOQUAL, algorithm representing interflow processes; AOQUAL, algorithm representing baseflow processes.

Subwatershed Delineation

The topography and drainages of the Chino Basin were determined from a 10-m digital elevation model into which the urban drainage features were incorporated. Topographic features contributing to basin drainage were defined using the ARC/GIS module Arc/Hydro. To simulate streamflow and bacteria transport, the basin was delineated into 229 small single-reach, interconnected hydrologic response units. Although this degree of watershed disaggregation was greater than that used in similar HSPF modeling studies, the delineation of so many channel reaches enabled the simulation of runoff and transport through a complex network of urban drainage features, such as constructed channels and storm drains, and natural channels. Once the 229 channel reaches and the associated hydrologic response units had been determined, they were recombined into 46 larger base model segments ([fig. 10](#)), each of which had relatively uniform upper boundary conditions for input of air temperature and precipitation. These distributions represent the spatial variability of climatic conditions in the basin ([figs. 4A,B](#)). Average annual precipitation and air temperature for each of the 46 segments indicate the variability of upper boundary conditions in the Chino Basin ([table 5](#)). The data presented in the table are the averages for 1970–2005. The 46 model segments were further recombined into 5 subbasins that were represented by 5 separate submodels. These were intended to optimize hydrologic model calibration and verification at the 4 USGS streamflow gaging stations and 2 sampling sites at the San Antonio dam and provide simulated flow and transport characteristics at the mouths of the 4 streams in the Chino Basin ([fig. 11](#)). The San Antonio Canyon subbasin is characterized by natural (background) conditions for bacteria generation; two sampling sites, Ice House Canyon (IHC) and Cucamonga Canyon M1 (CCM1) ([table 3](#)) were used to calibrate the model for land uses representing natural-background conditions (shrubs/grasslands, woodlands, and barren/vacant).

Once model calibration was complete, the model was applied for the entire Chino basin to test various scenarios. To simplify discussion on the basis of hydrologic boundaries, the model segments were recombined into four hydrologic subbasins: San Antonio Canyon subbasin, Chino Creek subbasin, Mill Creek subbasin, and Prado Basin subbasin ([fig. 12](#)).

The Chino Creek subbasin has several characteristics that distinguish it from the Mill Creek subbasin. The Chino Creek drainage includes several less-engineered drainages along the northeastern slope of the Chino Hills, and the lower reaches of Chino Creek are more characteristic of natural stream channels than concrete lined channels. The Mill Creek subbasin contains a higher percentage of concrete-lined engineered channels in the central and southern part of the Chino Basin

than the Chino Creek subbasin. Streamflow from the mountain drainages in the northern part is captured in numerous retention basins and spreading grounds. Downstream of the mountain front, retention basins capture streamflow from the main channels. The Prado Basin subbasin is within the Prado Dam storage basin and is subject to flooding. In addition, the subbasin contains the Orange County engineered wetlands, which includes inflows from the Santa Ana River. The complex hydrology of the subbasin was not explicitly represented by the HSPF bacteria-transport model. Rather, the subbasin was defined only to integrate the outflows from Chino Creek and Mill Creek subbasins into a single pour point simulating inflow from the Chino Basin to the Santa Ana River. Because of the greater uncertainty associated with simulating the Prado Basin subbasin, model results presented in this report are limited to the San Antonio, Chino Creek, and Mill Creek subbasins.

Input Data

Channel Reach Data

Channel properties were defined using a combination of data sources. Descriptive information for the San Antonio Creek, Chino Creek, Cucamonga Creek, and Mill Creek channels was obtained from previous reports (U.S. Army Corps of Engineers, 1991; Wildermuth Environmental, Inc., 2003; Belitz and others, 2004; Izbicki and others, 2004; Rice, 2005). A detailed drainage network map for the Chino Basin was provided by the San Bernardino County Flood Control District, including geometry and channel type attributes for all channels. A storm drain map for the southeastern section of the Chino Basin within Riverside County was provided by the Riverside County Flood Control District. Photographs, field visits, and digital orthophotos were also used to help determine channel properties for all reach segments represented in the HSPF model. Estimates of channel roughness (Manning's n) were made on the basis of published data for concrete channels, and channel median grain size, irregularity (width to depth ratios), alignment (abrupt changes in channel width), obstructions (debris), and vegetation (instream and bank vegetation) for natural channels. Channel slope was estimated by dividing the change in elevation from the upstream to the downstream ends of a reach by the reach length determined using hydrography and elevation data in GIS. Cross-section measurements, estimates of channel roughness, and slope calculations were used in WinHSPF (the Windows-based pre-processor for HSPF) to generate FTABLEs. Modeled streams are shown in [figures 11](#) and [12](#).

Figure 10. Base model segmented by average precipitation in January, and delineated hydrologic response units for each reach in the Chino Basin, California.

Table 5. Average values for precipitation and air temperature for 46 model segments used for the Chino Basin model, 1970–2005.[For locations, see [fig. 10](#)]

Model segment number	Precipitation (in inches)				Precipitation (in inches)		
	Average annual	Maximum annual	Minimum annual	Maximum daily	Average daily	Maximum monthly	Minimum monthly
1	37.8	86.4	11.4	9.3	42.1	63.0	24.9
2	36.0	83.5	9.8	8.9	45.3	66.3	27.8
3	43.3	99.3	12.0	10.7	42.3	62.9	25.4
4	38.8	89.8	10.0	9.7	45.1	65.9	27.9
5	34.5	79.8	9.1	8.8	49.1	70.0	31.6
6	42.5	97.3	11.9	10.8	45.8	66.2	28.9
7	29.1	66.8	8.3	7.5	54.1	74.6	36.3
8	41.6	94.5	12.4	10.7	49.3	69.4	32.6
9	36.3	82.9	10.5	9.3	50.2	70.3	33.2
10	31.8	72.9	9.1	8.2	51.1	71.3	33.7
11	25.3	57.2	7.1	6.7	59.0	78.9	41.3
12	24.8	56.6	7.0	6.4	55.6	75.4	38.3
13	28.5	64.6	8.7	7.5	54.7	74.5	37.8
14	31.4	70.5	9.8	8.4	54.4	74.1	37.7
15	22.0	50.1	6.8	5.8	56.7	76.2	39.7
16	19.6	44.1	6.1	4.9	57.6	76.9	40.6
17	19.3	43.3	6.4	5.5	61.3	80.4	44.9
18	18.3	40.5	2.3	5.6	61.0	79.9	44.3
19	18.2	41.4	5.9	4.9	61.3	80.4	44.8
20	14.7	34.2	4.2	4.6	63.2	81.7	47.5
21	16.5	39.0	5.6	4.3	61.7	80.3	45.3
22	16.5	37.4	5.6	4.1	61.8	80.6	45.4
23	14.3	35.7	4.1	4.0	62.3	80.0	46.7
24	14.0	32.7	4.7	4.0	62.9	80.7	47.3
25	14.8	34.7	4.1	4.6	62.9	81.2	47.1
26	14.6	33.4	4.8	3.9	62.3	78.9	47.4
27	13.0	31.0	3.6	3.8	63.7	81.2	48.7
28	12.8	30.1	3.0	4.2	64.2	82.1	49.2
29	14.7	32.9	4.8	3.9	62.2	78.3	47.4
30	13.8	32.8	4.7	4.0	62.8	79.6	47.9
31	12.2	28.7	3.4	3.4	64.2	81.6	49.8
32	13.2	31.7	4.3	3.7	63.2	80.4	48.4
33	12.3	29.0	3.4	3.3	63.9	80.8	49.7
34	14.9	32.9	4.9	4.0	62.4	78.0	48.3
35	14.2	33.0	4.7	4.7	63.0	79.3	48.9
36	13.0	31.1	3.9	4.5	63.4	80.0	49.4
37	14.9	32.9	4.8	4.3	62.6	78.7	49.0
38	11.7	27.3	3.6	3.0	64.5	81.9	50.3
39	11.5	26.7	3.1	2.9	64.1	81.1	50.4
40	12.5	28.7	2.6	3.5	63.7	80.3	50.0

Table 5. Average values for precipitation and air temperature for 46 model segments used for the Chino Basin model, 1970–2005.—Continued

[For locations, see fig. 10]

Model segment number	Precipitation (in inches)				Precipitation (in inches)		
	Average annual	Maximum annual	Minimum annual	Maximum daily	Average daily	Maximum monthly	Minimum monthly
41	11.8	27.3	2.9	3.1	63.8	80.5	50.3
42	13.1	30.1	4.1	3.8	63.3	79.7	49.9
43	14.1	31.4	4.6	4.1	62.9	79.3	49.7
44	12.5	28.7	3.7	3.3	63.4	80.0	50.3
45	11.2	26.0	3.2	3.0	63.7	80.7	50.2
46	12.3	28.4	3.6	3.6	63.4	80.4	50.1
Average	20.5	47.2	6.0	5.5	58.7	77.0	43.2
Maximum	43.3	99.3	12.4	10.8	64.5	82.1	50.4
Minimum	11.2	26.0	2.3	2.9	42.1	62.9	24.9

Meteorological and Streamflow Data

Precipitation data were obtained from the National Climatic Data Center (NCDC), San Bernardino County (SBC), and Los Angeles County (LAC) ([table 6](#)). Precipitation data were also obtained from the Western Regional Climate Center (WRCC) website from the network of Remote Automated Weather Stations (RAWS) and include hourly measurements of air temperature, dew point temperature (relative humidity), barometric pressure, precipitation, wind speed, and wind direction. Meteorological data were obtained from California Department of Water Resources and University of California at Davis, through the California Irrigation Management Information System (CIMIS). These data included hourly measurements of potential evapotranspiration, precipitation, solar radiation, vapor pressure, air temperature, wind speed and direction and daily measurements of potential evapotranspiration, solar radiation, minimum and maximum air temperature, and average vapor pressure. Precipitation data sources, number of stations and dates for which data were available for each source are shown in [table 6](#). Station locations are shown on [figure 1](#).

Streamflow data were available from USGS streamflow gaging stations for Chino Creek (gage 11073360, Chino Creek at Schaefer Avenue near Chino, California), San Antonio Creek River (gage 11073300, San Antonio Creek at Riverside Drive near Chino, California), West Branch Cucamonga Creek (gage 11073493, West Branch Cucamonga Channel above Ely Percolation Basin at Ontario), and Mill Creek (gage 11073495, Cucamonga Creek near Mira Loma, California) for various

time periods ([table 6](#)). Daily data were obtained from NWIS, and 15-minute data were obtained directly from the USGS Automated Data Processing System (ADAPS) and processed to produce a mean hourly record. Daily outflow data for San Antonio Dam were available from the Army Corps of Engineers (2005) ([table 6](#)).

Surface Properties and Land Use

Surface properties were estimated from a combination of soils, vegetation, and land-use data. Vegetation is a dominant land cover in some areas of the Chino Basin, particularly in the northern mountainous region. Vegetation type was converted to percent cover ([fig. 5](#)) and used in several of the hydrologic parameters, such as shading on snow (SHADE) and interception of rainfall (CEPSC) ([table 4](#)). Soils data were available from the State Soil Geographic Database (STATSGO), a state-compiled geospatial database of soil properties that generally are consistent across state boundaries (U.S. Dept. of Agriculture-National Resource Conservation Service, 1994) ([table 7](#); [fig. 3B](#)). More detailed information was available from the local and refined database Soil Survey Geographic Database (SSURGO) that is archived by the National Cartography and Geospatial Center and the Natural Resource Conservation Service (Soil Survey Staff, 2007). Soils information, such as particle size, permeability, and depth, are used extensively in the hydrologic parameters for PERLNDs.

Figure 11. Submodels of basin area upstream of each calibration gage used for hydrologic calibration of the Chino Basin model.

Figure 12. Subbasins used in applications of calibrated model in the Chino Basin.

Table 6. Meteorological and streamflow data sources, number of stations or station identification, and years with available data used for the Chino Basin model.

[NCDC, National Climatic Data Center; SBC, San Bernardino County; LAC, Los Angeles County; RAWS, Remote Automated Weather Stations; CIMIS, California Irrigation Management Information System]

Meteorological data			
Parameter	Data source	Number of stations	Available years
Precipitation	NCDC hourly	49	1970–2004
	NCDC daily	39	1970–2004
	SBC	56	1970–2005
	LAC	7	1970–2005
	RAWS	27	2005
Air temperature	NCDC surface airways	5	1970–2004
Dew-point temperature	CIMIS	13	1980–2005
Percent cloud cover	CIMIS	13	1980–2005
Potential evapotranspiration	CIMIS	13	1980–2005
Wind	CIMIS	13	1980–2005
Streamflow data			
Parameter	Data source	Station ID or description	Available years
Streamflow—daily	USGS	11073360	1988–2005
	USGS	11073300	1999–2005
	USGS	11073493	1996–2005
	USGS	11073495	1970–2005
	Army Corps of Engineers	San Antonio reservoir inflows	1956–2005
	Army Corps of Engineers	San Antonio Dam outflow	1956–2005
Streamflow—15-minute	USGS	11073360	1988–2005
	USGS	11073300	1998–2005
	USGS	11073493	1996–2005
	USGS	11073495	1980–2005

Table 7. Average State Soil Geographic Database (STATSGO) soil properties for the Chino Basin model.

[ft, foot; in³/in³, cubic inch per cubic inch; in/in, inch per inch; in/hr, inch per hour]

STATSGO map unit identifier	Area (acre)	Soil thickness (ft)	Coarse fragments (percent)	Porosity (in ³ /in ³)	Clay (percent)	Field capacity (in/in)	Saturated hydraulic conductivity (in/hr)
CA676	3,005	1.5	73.0	0.42	10.69	0.26	4.88
CA672	3,935	1.2	44.5	0.40	19.09	0.32	1.49
CA665	1,499	4.9	36.1	0.38	9.45	0.21	8.57
CA671	9,515	1.4	73.5	0.43	6.94	0.22	7.84
CA670	11,259	1.3	56.9	0.40	14.33	0.28	2.57
CA639	78,986	4.2	22.7	0.36	7.86	0.19	8.24
CA645	373	3.3	19.3	0.37	18.55	0.28	1.38
CA614	10,137	4.9	20.0	0.36	12.89	0.24	3.92
CA642	13,398	2.3	32.8	0.42	27.52	0.36	0.65
CA613	6,873	3.7	14.6	0.37	16.89	0.26	1.39

GIS data for land use in 2000 in the Chino Basin were available from the Southern California Association of Governments. The land-use coverage identifies 83 possible land-use types, which were combined into 12 general types using general similarities of types that contribute to hydrological routing similarities and density of water-quality contaminants. All urban agricultural land uses, including all animal production land uses, were lumped, with the exception of the dairies, which were a separate land use for this model. Areas indicated as “vacant” were evaluated on the basis of orthophotos from the USGS seamless website (<http://seamless.usgs.gov/>) to determine if they were natural wildland, wetland, or urban lots. The combined land uses are Shrubs/Grassland, Forest, Barren/Vacant, Mixed Urban, Utilities/Transport, Residential, Mixed Agriculture, Recreation/Open, Commercial/Services, Industrial, Wetlands, Dairies/Feedlots. These general land-use types are used to represent the land uses within each HRU in a subwatershed. The aggregated land-use map is shown in [figure 5](#).

The degree of imperviousness for any given land use was based on a 2001 map from the National Land Cover Data database (U.S. Geological Survey, 2001). This map was used to define the relative acreages of PERLND and IMPLND for each HRU to assign appropriate hydrologic and transport parameters ([fig. 13](#)). The land-use map was evaluated for imperviousness for all the PERLNDs and IMPLNDs and adjusted by a factor related to how effectively the area mapped as impervious facilitated runoff. The initial impervious area was adjusted using aerial photos and orthophotos during calibration to account for hydrologically effective and ineffective areas, and the effective impervious area was adjusted for each land-use type ([table 8](#)).

The land-use types for the upstream areas contributing to sampling locations are given in [table 9](#), which illustrates which land use dominates the impervious and pervious land-unit types, as well as the dominant land-use or land-unit type contributing to the sampled bacteria concentrations from the different sampling locations.

Model Calibration

The HSPF model was first calibrated to simulate streamflow, with a particular emphasis on accurately simulating storm runoff. For all calibration and verification model simulations, a three-year model initialization period was used to minimize uncertainty associated with the estimated initial conditions. The initial streamflow calibrations indicated a poor match between simulated and measured flows during low flow

conditions. To improve model calibration for the low flows, an assumed nuisance flow component was added to the model by specifying a constant point-source inflow to all reaches receiving surface runoff from urban or agricultural land. The magnitude of the nuisance flow was scaled on the basis of the absolute area of the urban and agricultural land uses within the land area supplying surface runoff to the reach. The scaling was applied consistently to all affected reaches in the Chino Basin model.

The model was calibrated for streamflow by iteratively adjusting hydrologic parameters ([table 4](#)) until simulated streamflow closely matched measured streamflow at the five streamflow gaging stations in the study area (four USGS streamflow gages and USACE streamflow data from below San Antonio Dam). The simulation period for calibration was on the basis of available hourly and daily streamflow records from water-year 1990 through water-year 2001, as well as water-year 2004. The calibrated model was verified using hourly and daily streamflow records for water-years 2002–2003 and 2005. In addition, hourly streamflow data for one selected winter (November–February) storm month for each year of the calibration period was used to calibrate storm runoff. Hourly streamflow data for January 2005 were used to verify model simulations of storm flow.

Two general criteria were used for deciding when simulated daily streamflow adequately represented measured daily streamflow: (1) the average difference between simulated and measured daily streamflow during the complete calibration period needed to be less than 20-percent and (2) the average difference between simulated and recorded values of an annual high-flow statistic (daily discharge exceeded 10 percent of the time) also needed to be less than 20 percent for the calibration period. The calibration goals for simulating hourly discharge for high-flow periods were similar to those for simulating daily discharge: (1) during the calibration period, the average difference between simulated and measured hourly discharge that was exceeded 50-percent of the time needed to be less than 20 percent; and (2) during the calibration period, the average difference between the simulated and recorded hourly peak discharge computed as the hourly discharge that was exceeded 10 percent of the time needed to be less than 20 percent. In addition to the numerical goals for calibration and verification, graphical comparisons of simulated and measured discharges were used to judge the effectiveness of the calibrated hydrologic model. The calibration and verification results for hydrologic modeling are described in the following section.

Figure 13. Percentage of imperviousness of the Chino Basin, California.

Table 8. Initial and adjusted pervious and impervious areas for each land use defined in the Chino Basin model.[See [figure 5](#) for location. PERLND, pervious land unit; IMPLND, impervious land unit; —, no adjustment]

Land use	Total area (acre)	Initial impervious area (percent)	Effective impervious area factor	Adjusted impervious area (percent)	Adjusted PERLND area (acre)	Adjusted IMPLND area (acre)
Barren or vacant	11,921	8.6	0.5	4.3	11,410	512
Commercial and services	8,922	45.0	0.8	36.0	5,708	3,214
Forest	11,693	0.3	0.0	0.0	11,693	—
High density residential	35,952	41.3	0.7	28.9	25,563	10,389
Industrial	9,404	52.3	0.9	47.1	4,978	4,427
Intensive livestock (dairies)	6,891	4.1	0.5	2.1	6,749	142
Mixed agriculture	12,205	4.8	0.5	2.4	11,912	293
Mixed urban	6,692	21.4	0.7	15.0	5,689	1,003
Recreation and open space	3,964	6.6	0.5	3.3	3,833	131
Shrubs and grassland	24,200	0.6	0.0	0.0	24,200	—
Transportation and utilities	6,357	33.7	0.7	23.6	4,858	1,499
Wetland or water	777	3.9	0.0	0.0	777	—
Total	138,978				117,369	21,609

On the basis of available measured bacteria data of <2 cfu/100 mL from the six permitted point sources (Carbon Canyon POTW discharge to Chino Creek, RP-1 discharge to Cucamonga channel, RP-1 discharge to Prado Park Lake, RP-2 discharge to Chino Creek, RP-5 discharge to Chino Creek, and Orange County water transfers to San Antonio Channel below San Antonio Dam), which is insignificant in comparison with other point source loadings, the permitted point sources were represented in the model as pristine (bacteria-free) inflows. Monthly and daily discharge data for wastewater effluent were obtained from the inland Empire Utility Agency and Wildermuth Environmental, Inc. (Wildermuth Environmental, Inc., 2003). Monthly and daily discharge data for the Orange County water transfers were obtained from the Orange County Water District and Wildermuth Environmental, Inc. (Gwen Sharp, Orange County Water District, Fountain Valley, California, Wildermuth Environmental, Inc., unpub. data, 2003). The monthly and daily time-series data were converted to hourly time-series data that assumed uniform daily or monthly discharge rates, and the hourly data were incorporated into the model as point sources.

Bacteria were measured at six permitted point sources: Carbon Canyon POTW discharge to Chino Creek, RP-1 discharge to Cucamonga channel, RP-1 discharge to Prado Park Lake, RP-2 discharge to Chino Creek, RP-5 discharge

to Chino Creek, and Orange County water transfers to San Antonio Channel below San Antonio Dam. The available data show that bacteria concentrations at these point sources were <2 cfu/100 mL, which was insignificant compared with other point source loadings and therefore the inflows at these point sources were represented in the model as being pristine (bacteria-free).

Daily and hourly mean discharge data were available for San Antonio Dam outflow (R.M. Kuboshige, U.S. Army Corps of Engineers, Los Angeles, California, unpub. data, 2006). These data were combined to develop an hourly time series representing the surface-water inflows from the San Antonio Canyon subbasin to the Chino Creek subbasin. The hourly time-series was incorporated into the model as a pristine point-source discharge at the headwaters of San Antonio Creek (at San Antonio Dam outflow) in the Chino Creek subbasin. The pristine point-source discharge was used only for calibrating the model to streamflow. Transport-model calibration, as well as model applications, incorporated the simulated outflow from San Antonio Dam, and included both simulated hourly discharge and simulated bacteria concentration rather than the measured records used for flow calibration and verification.

Table 9. Land-use acreages for impervious and pervious land unit types for upstream subbasin areas contributing to sampling locations in the Chino Basin, California.

Modeled subdrainage	Location (site or gage in parentheses)	Land unit type	Land use, in acres						
			Shrubs and grasslands	Forests	Barren or vacant	Mixed urban	Recreation or open space	Commercial and services	Transportation and utilities
San Antonio Canyon (Ice House Canyon)	site IHC	Impervious	0	0	6	4	0	0	0
		Pervious	788	1,690	132	21	1	0	0
		Total	788	1,690	138	25	1	0	0
San Antonio Canyon (San Antonio Dam)	San Antonio Dam inflow	Impervious	0	0	30	24	5	3	8
		Pervious	8,871	7,123	674	139	133	4	25
		Total	8,871	7,123	704	163	137	7	32
Chino Creek (San Antonio Channel)	Stream gage 11073300	Impervious	0	0	34	201	13	841	177
		Pervious	712	0	763	1,138	369	1,493	576
		Total	712	0	797	1,339	382	2,333	753
Chino Creek (Upper Chino Creek)	Stream gage 11073360 (site CHIS)	Impervious	0	0	86	229	21	1,274	288
		Pervious	868	2	1,904	1,300	620	2,262	933
		Total	868	2	1,989	1,529	641	3,536	1,221
Chino Creek (Lower Chino Creek)	Chino Creek outflow	Impervious	0	0	246	462	68	1,949	619
		Pervious	4,883	717	5,481	2,621	1,986	3,462	2,008
		Total	4,883	717	5,726	3,083	2,054	5,412	2,628
Chino Creek (Lower Chino Creek)	Chino Creek at Central Ave. (site CHIC)	Impervious	0	0	195	399	40	1,753	396
		Pervious	2,670	409	4,339	2,260	1,164	3,113	1,284
		Total	2,670	409	4,534	2,659	1,204	4,866	1,680
Chino Creek (Prado Park Lake)	Euclid Ave. drainage (site D)	Impervious	0	0	1	11	0	57	121
		Pervious	0	0	25	63	0	101	391
		Total	0	0	26	74	0	157	512
Chino Creek (Prado Park Lake)	Prado Park Lake outflow (site PPOC)	Impervious	0	0	10	26	6	124	176
		Pervious	14	4	217	148	169	220	570
		Total	14	4	226	174	175	343	746
Chino Creek (Prado Park Lake)	Bon View & Merrill drainage (site BVAM)	Impervious	0	0	0	1	0	2	0
		Pervious	0	0	5	7	0	4	0
		Total	0	0	5	8	0	6	0
Mill Creek (Lower Mill Creek)	Mill Creek outflow	Impervious	0	0	225	519	836	4,679	110
		Pervious	9,446	3,443	5,016	2,778	2,711	11,512	4,483
		Total	9,446	3,443	5,240	3,297	3,548	16,190	4,593
Mill Creek (Upper Mill Creek)	Mill Creek (site MC)	Impervious	0	0	218	513	32	1,183	827
		Pervious	9,426	3,283	4,855	2,745	910	2,100	2,680
		Total	9,426	3,283	5,073	3,258	942	3,284	3,506
Mill Creek (Cucamonga Creek)	Cucamonga Creek (gage 11073495)	Impervious	0	0	201	421	32	1,173	773
		Pervious	9,401	3,269	4,487	2,221	910	2,082	2,504
		Total	9,401	3,269	4,688	2,642	942	3,255	3,277
Mill Creek (West Branch Cucamonga Creek)	West Branch Cucamonga (gage 11073493)	Impervious	0	0	14	29	10	350	96
		Pervious	27	0	304	164	287	622	312
		Total	27	0	317	193	297	972	408
Mill Creek (Cucamonga Canyon)	Cucamonga Creek (site CCM1)	Impervious	0	0	5	0	0	0	0
		Pervious	3,374	2,674	105	0	0	0	0
		Total	3,374	2,674	110	0	0	0	0
Mill Creek (Cucamonga Creek)	Cucamonga Creek (site CCM2)	Impervious	0	0	148	381	27	1,033	569
		Pervious	9,192	3,269	3,298	1,999	764	1,834	1,844
		Total	9,192	3,269	3,446	2,380	791	2,867	2,412

Table 9. Land-use acreages for impervious and pervious land unit types for upstream subbasin areas contributing to sampling locations in the Chino Basin, California.—Continued

Modeled subdrainage	Location (site or gage in parentheses)	Land unit type	Land use, in acres					Total, in acres
			Residential	Mixed agriculture	Industrial	Water and wetlands	Intensive livestock	
San Antonio Canyon (Ice House Canyon)	site IHC	Impervious	0	0	0	0	0	10
		Pervious	0	0	0	0	0	2,631
		Total	0	0	0	0	0	2,641
San Antonio Canyon (San Antonio Dam)	San Antonio Dam inflow	Impervious	20	0	55	0	0	145
		Pervious	50	2	62	0	0	17,083
		Total	70	2	117	0	0	17,228
Chino Creek (San Antonio Channel)	Stream gage 11073300	Impervious	1,707	13	959	0	0	3,946
		Pervious	4,201	536	1,078	0	15	10,881
		Total	5,909	549	2,037	0	16	14,827
Chino Creek (Upper Chino Creek)	Stream gage 11073360 (site CHIS)	Impervious	2,974	15	1,219	0	0	6,104
		Pervious	7,317	592	1,371	0	15	17,184
		Total	10,290	606	2,589	0	16	23,288
Chino Creek (Lower Chino Creek)	Chino Creek outflow	Impervious	5,294	161	2,099	0	56	10,955
		Pervious	13,027	6,559	2,360	167	2,694	45,965
		Total	18,321	6,720	4,459	167	2,750	56,919
Chino Creek (Lower Chino Creek)	Chino Creek at Central Ave. (site CHIC)	Impervious	4,526	55	1,996	0	7	9,366
		Pervious	11,136	2,228	2,245	19	340	31,206
		Total	15,662	2,282	4,241	19	347	40,572
Chino Creek (Prado Park Lake)	Euclid Ave. drainage (site D)	Impervious	144	31	14	0	18	394
		Pervious	353	1,239	15	0	838	3,025
		Total	497	1,270	29	0	856	3,420
Chino Creek (Prado Park Lake)	Prado Park Lake outflow (site PPOC)	Impervious	345	66	49	0	43	844
		Pervious	850	2,680	55	55	2,072	7,051
		Total	1,195	2,746	104	55	2,115	7,896
Chino Creek (Prado Park Lake)	Bon View & Merrill drainage (site BVAM)	Impervious	0	6	0	0	7	17
		Pervious	1	255	0	0	350	620
		Total	1	261	0	0	357	638
Mill Creek (Lower Mill Creek)	Mill Creek outflow	Impervious	37	1,189	2,112	0	73	9,780
		Pervious	1,048	2,111	2,375	198	3,485	48,605
		Total	1,085	3,300	4,486	198	3,558	58,385
Mill Creek (Upper Mill Creek)	Mill Creek (site MC)	Impervious	4,679	86	2,106	0	60	9,703
		Pervious	11,512	3,507	2,368	26	2,820	46,231
		Total	16,190	3,593	4,475	26	2,879	55,934
Mill Creek (Cucamonga Creek)	Cucamonga Creek (gage 11073495)	Impervious	4,660	22	1,987	0	6	9,275
		Pervious	11,465	914	2,235	15	267	39,769
		Total	16,125	937	4,222	15	273	49,044
Mill Creek (West Branch Cucamonga Creek)	West Branch Cucamonga (gage 11073493)	Impervious	3	1,394	346	0	0	2,240
		Pervious	116	3,429	389	0	0	5,648
		Total	119	4,822	734	0	0	7,888
Mill Creek (Cucamonga Canyon)	Cucamonga Creek (site CCM1)	Impervious	0	0	0	0	0	5
		Pervious	0	0	0	0	0	6,153
		Total	0	0	0	0	0	6,158
Mill Creek (Cucamonga Creek)	Cucamonga Creek (site CCM2)	Impervious	4,264	10	1,368	0	0	7,800
		Pervious	10,492	387	1,538	8	0	34,624
		Total	14,757	397	2,906	8	0	42,424

After the model was calibrated and verified for simulation of streamflow, it was calibrated for simulation of indicator bacteria concentrations. Initial estimates of the total amount of bacteria deposited by each of the dominant sources of fecal coliform bacteria were based on literature values taken from the BASINS software default parameters that are based on a case study by the U.S. Environmental Protection Agency in Cottonwood Creek, Idaho (U.S. Environmental Protection Agency, 2000; [table 4](#)). Parameter estimates from other HSPF modeling studies conducted in the region (Ackerman and Weisberg, 2003; Guay, 2002; U.S. Environmental Protection Agency, 2000; [table 4](#)), were used for comparison with the calibrated parameters developed for this study and to help develop initial estimates for land uses not represented by the storm sampling. Few data were available to calculate specific deposition or accumulation rates for indicator bacteria. Land-surface processes were represented by parameters shown in [table 4](#): ACCUM, SQOLIM, SQO, and WSQOP, which were assigned according to land use; REMQOP, a constant die-off rate described in the model description section; IQO and AQO ([fig. 9](#)) were assigned to land surfaces in San Antonio Canyon to represent interflow and baseflow transport, respectively. An assumed bacteria concentration for nuisance flow was represented as a uniform value proportional to the absolute area of the urban and agricultural land uses connected to each reach (and thus supplying overland flow to that reach). The proportionality constants were then adjusted such that simulated concentrations matched observed data.

The bacteria transport model was first calibrated to the storm samples collected during water-year 2004 (storms of 11/11/2003, 2/2/2004, and 2/22/2004) that provided information on loadings for targeted land-use areas. These usually consisted of runoff from small areas (or catchments; a few acres to several tens of acres) that represented specific land uses. These small catchments were included in the model as separate RCHRES segments (each sample site was included as a RCHRES). Stormflows and bacteria concentrations were simulated for these RCHRES segments and compared with concentrations measured in the field. The primary parameters that were iteratively changed to match simulated concentrations with measured concentrations were the 7 parameters listed in the PQUAL module section of [table 4](#). Final transport model calibration incorporated all available bacteria data for the Chino Basin, including the storm- and land-use-targeted

samples collected as part of this study and the supplemental data available from previous and ongoing studies of pathogen indicator bacteria in the Chino Basin.

Results from the Streamflow and the Fecal Coliform Models

Streamflow-Model Calibration and Verification Results

Streamflow-model calibration, during which model parameters were changed to improve the predictive capability of the model, was based on the comparison of simulated and measured hourly and daily streamflow at the four USGS gaged sites and on the comparison of simulated and measured daily streamflow at San Antonio Dam. All calibrations were for WY1990–WY2001 and WY2004. The streamflow model was verified to illustrate its predictive capability for WY2002–WY2003 and WY2005 using the calibrated model and comparisons of simulated and measured streamflow at the sites used for model calibration. Records for a period which had variations in climate but no major changes in land use were chosen to calibrate the model. Water-year 2004 was used for calibration, but not verification, to reduce uncertainty of simulated streamflow for the storms sampled as part of this study. Land use was represented as constant over the model period on the basis of maps available in 2000.

Examples of simulated and measured storm flows for February 2004 for the gage locations on Chino Creek (gage 11073360) and San Antonio Creek (gage 11073300) ([fig. 2](#)) shown in [figure 14](#) illustrate good matches in peak flows for both locations for the series of five runoff events. Measured and simulated streamflow values for the 1, 10, 25, and 50 percent highest flows and the 1, 10, 25, and 50 percent lowest flows were compared for the entire calibration period. These results of the comparisons and the regression results are given in [table 10](#) for mean hourly streamflow at all USGS sites and for daily inflow to San Antonio Dam; the results include comparisons for average flows during winter and summer. Calibration and verification results, based on graphical comparison of simulated and measured hourly and daily flow-duration curves, are shown for the USGS gages and for measured daily inflow to San Antonio Dam in [figure 15](#).

Figure 14. Simulated and measured hourly streamflow for February 2004 for the calibration period for A, Chino Creek gage 11073360 and B, San Antonio Creek gage 11073300 in the Chino Basin, California.

The model was calibrated by changing parameters consistently over all basins, rather than changing parameters within each subbasin. Having a consistently calibrated parameter set for all gaged subbasins improved the overall robustness of the model when applied to the ungaged areas of the Chino Basin, which included a substantial area in the southern part of the basin. This calibration approach required compromises between matching high flows in some subbasins and low flows in other subbasins. In addition, as there were no data to support variable nuisance flows in the different subbasins, a uniform nuisance inflow rate was added to all affected reaches

and was scaled uniformly using the absolute area of the combined urban and agricultural land uses contributing runoff to the affected reach. The scaling factor was adjusted during calibration to better match the lower flows. The uniform scaling caused the similarity between simulated lower flows and measured lower flows in some basins to decrease. This is illustrated for both Chino Creek, for which nuisance flows were underestimated, and San Antonio Creek, for which nuisance flows were overestimated ([fig. 14](#)).

Table 10. Measured and simulated streamflow values for highest and lowest flows and regression results for U.S. Geological Survey and San Antonio Dam sites in the Chino Basin, California.

[Streamflow is in cubic feet per second and percent (%) difference. Regression coefficients (r^2) compare simulated streamflow for the total simulation period with measured streamflow. Winter is October through March; summer is April through September]

Sites	Model run type	Regression analysis	Hourly streamflow												Average
			Highest				Lowest				1				
			1	10	25	50	50	25	10						
Chino Creek (11073360)	Calibration	slope	0.80	Measured	711	174	67	40	1.0	0.8	0.7	0.5	22.6	18.5	
		intercept	5.9	Simulated	662	182	85	42	1.4	1.3	1.2	1.1	26.0	18.9	
	Verification	r ²	0.81	% difference	0.07	-0.04	-0.28	-0.06	-0.40	-0.64	-0.74	-1.18	-0.15	-0.02	
		slope	0.66	Measured	1,211	193	78	42	1.6	1.3	1.1	0.8	33.1	11.6	
Mill Creek (11073495)	Calibration	intercept	4.0	Simulated	887	164	70	35	1.4	1.3	1.2	1.1	27.7	9.8	
		r ²	0.80	% difference	0.27	0.15	0.10	0.15	0.15	0.00	-0.06	-0.36	0.16	0.16	
	Verification	slope	1.16	Measured	1,410	245	131	86	28.6	23.4	18.8	10.7	76.0	38.0	
		intercept	-9.4	Simulated	2,144	341	157	94	21.5	19.0	16.5	12.6	86.6	26.7	
West Branch Cucamonga Creek (11073493)	Calibration	r ²	0.65	% difference	-0.52	-0.40	-0.20	-0.08	0.25	0.19	0.12	-0.18	-0.14	0.30	
		slope	0.75	Measured	2,518	420	201	130	41.5	36.7	31.5	19.4	115.3	58.9	
	Verification	intercept	1.1	Simulated	2,259	353	167	102	29.9	27.0	23.7	18.9	88.8	43.6	
		r ²	0.71	% difference	0.10	0.16	0.17	0.22	0.28	0.26	0.25	0.03	0.23	0.26	
San Antonio Creek (11073300)	Calibration	slope	0.86	Measured	164	23	11	7	0.6	0.2	0.1	0.0	5.8	1.3	
		intercept	0.4	Simulated	192	30	12	7	0.5	0.5	0.4	0.4	6.1	0.9	
	Verification	r ²	0.70	% difference	-0.17	-0.28	-0.10	0.02	0.20	-1.31	-4.22	-12.77	-0.06	0.31	
		slope	0.90	Measured	262	41	16	10	0.9	0.2	0.1	0.0	8.5	2.5	
	Calibration	intercept	0.1	Simulated	291	45	18	9	0.5	0.5	0.4	0.4	8.1	2.0	
		r ²	0.79	% difference	-0.11	-0.10	-0.17	0.01	0.47	-0.90	-3.60	-12.90	0.05	0.20	
	Verification	slope	1.01	Measured	218	75	32	16	1.4	0.2	0.1	0.1	10.3	6.0	
		intercept	1.5	Simulated	249	82	36	18	0.8	0.8	0.7	0.7	12.9	6.5	
	Calibration	r ²	0.86	% difference	-0.14	-0.09	-0.13	-0.14	0.41	-2.40	-4.67	-11.70	-0.25	-0.10	
		slope	0.71	Measured	796	124	51	26	0.3	0.2	0.2	0.0	20.5	5.8	
	Verification	intercept	3.1	Simulated	640	115	47	24	0.8	0.8	0.8	0.7	18.8	5.9	
		r ²	0.77	% difference	0.20	0.07	0.08	0.08	-1.48	-2.48	-3.31	-13.68	0.08	-0.02	

Table 10. Measured and simulated streamflow values for highest and lowest flows and regression results for U.S. Geological Survey and San Antonio Dam sites in the Chino Basin, California.—Continued

[Streamflow is in cubic feet per second and percent (%) difference. Regression coefficients (r^2) compare simulated streamflow for the total simulation period with measured streamflow. Winter is October through March; summer is April through September]

Sites	Model run type	Regression analysis	Daily streamflow									
			1	10	25	50	50	25	10	1		
Chino Creek (11073360)	Calibration	slope	472	159	78	40	40	1.1	0.8	0.7	0.5	
		intercept	489	168	85	42	42	1.4	1.3	1.3	1.3	
	Verification	r^2		-0.04	-0.06	-0.09	-0.05	-0.29	-0.57	-0.85	-1.34	
		slope	840	182	82	39	35	1.7	1.5	1.3	1.0	
Mill Creek (11073495)	Calibration	intercept	699	159	70	35	35	1.4	1.3	1.3	1.3	
		r^2		0.17	0.12	0.14	0.10	0.19	0.10	0.01	-0.32	
	Verification	slope	920	199	109	75	75	29.6	25.7	22.0	17.1	
		intercept	1,499	286	135	82	82	20.8	18.1	16.0	12.3	
West Branch Cucamonga Creek (11073493)	Calibration	r^2		-0.63	-0.44	-0.24	-0.08	0.30	0.30	0.27	0.28	
		slope	2,094	414	204	128	128	44.2	40.9	38.3	34.9	
	Verification	intercept	1,955	375	175	106	106	30.0	27.1	23.9	19.0	
		r^2		0.07	0.09	0.14	0.17	0.32	0.34	0.38	0.45	
San Antonio Creek (11073300)	Calibration	slope	122	26	12	7	7	0.4	0.1	0.0	0.0	
		intercept	133	31	13	7	7	0.5	0.5	0.5	0.4	
	Verification	r^2		-0.08	-0.20	-0.05	0.07	-0.32	-3.69	-10.93	none	
		slope	188	40	18	10	10	0.7	0.1	0.0	0.0	
San Antonio Dam	Calibration	intercept	196	45	17	9	9	0.5	0.5	0.5	0.4	
		r^2		-0.04	-0.10	0.05	0.04	0.23	-2.63	-10.77	none	
	Verification	slope	212	100	53	27	27	0.1	0.0	0.0	0.0	
		intercept	219	104	57	27	27	0.8	0.8	0.8	0.8	
San Antonio Creek (11073300)	Calibration	r^2		-0.03	-0.05	-0.08	-0.02	-7.59	-95.88	none	none	
		slope	608	126	55	28	28	0.4	0.3	0.2	0.1	
	Verification	intercept	523	114	50	23	23	0.8	0.8	0.8	0.8	
		r^2		0.14	0.09	0.10	0.18	-1.12	-1.99	-3.25	-8.51	
San Antonio Dam	Calibration	slope	392	129	16	16	16	0.0	0.0	0.0	0.0	
		intercept	306	117	59	33	33	0.0	0.0	0.0	0.0	
	Verification	r^2		0.22	0.09	-2.78	-1.07	none	none	none	none	
		slope	731	192	26	26	26	0.0	0.0	0.0	0.0	
San Antonio Dam	Verification	intercept	548	165	79	20	20	0.0	0.0	0.0	0.0	
		r^2		0.25	0.14	-2.08	0.22	none	none	none	none

Figure 15. Flow duration curves for simulated and measured streamflow for calibration and verification periods for A, Chino Creek, B, Mill Creek, C, San Antonio Creek, D, West Branch Cucamonga Creek, and E, San Antonio Canyon reach in the Chino Basin, California.

The lack of specific data for flow diversions caused estimations of low flows to be particularly uncertain in some locations, especially in San Antonio Canyon (fig. 15E). For the urbanized subbasins upstream of the four USGS gages, specific data for transfers to recharge spreading basins, and minor inflows from local point sources, were not readily available and were not incorporated into this study. More generalized data, such as estimated annual recharge at several of the main spreading basins (Wildermuth Environmental, Inc., 2002), were incorporated into model development and calibration.

Verification results illustrate that the model generally agreed with most measured streamflows. However, the simulated streamflows for WY2005, a year characterized by large storm flows, did not agree with the measured streamflows. These flows were greater than those used for calibration, which suggests that the model was extrapolated beyond the range of streamflows used for calibration. This resulted in differences between measured and simulated results for verification periods for Chino Creek and San Antonio Creek that were somewhat high (table 10). Another condition not incorporated into the model was the increase in imperviousness during the study period, including the addition of concrete-lined channels, all of which contributed to a general underestimation of peaks, particularly in Mill Creek (table 10). In general, the comparison of simulated streamflow with measured streamflow met the criteria for acceptable calibration, with the exception of the highest flows in Mill Creek, which simulation results overestimated. Applying the calibrated model to the verification period was quite successful and met the criteria in all cases. Specific details regarding the calibration of each basin follow.

Chino Creek Subbasin

The model for the Chino Creek subbasin was calibrated and verified using measured streamflow data from USGS gage 11073360 for both daily and hourly time steps. This subbasin, which is significantly influenced by the San Antonio Dam releases and Orange County water transfers, provides a good representation of urban runoff that includes variable nuisance flow. There was very little area upstream of gage 11073360 that is agricultural or has dairies; therefore, their input was insignificant. The gage is the main flow calibration point for Chino Creek subbasin, which includes San Antonio Creek and eastern Chino Creek. The location of the streamgage coincides with the RWQCB sampling site identified as site CHIS in this report.

A comparison of simulated and measured hourly flow duration curves indicating the percentage of time hourly streamflows were exceeded for during the calibration and verification periods is shown in figure 15A and illustrates a slight under-simulation of peaks and a slight under-simulation of very low flows. Regression results comparing simulated and measured hourly streamflow indicate r^2 values were about 0.80 for both calibration and verification periods (table 10).

Mill Creek Subbasin

The Mill Creek subbasin is represented by USGS gage 11073495. This watershed provides a good representation of an integrated response to urban runoff with some natural runoff and a minor amount of agricultural runoff. There is a high baseflow caused by large releases of effluent at RP-1 and a significant nuisance flow.

A comparison of hourly simulated and measured streamflow related to the percentage of time the flow was exceeded is shown in Figure 15B and illustrates peak flows higher than those in all other subbasins. The r^2 values are lower than those for other subbasins because this subbasin is larger and more heterogeneous spatially (table 10). More land in the Mill Creek subbasin than in other areas was affected by changes in land use (primarily residential and commercial development) and by channel engineering (development of new retention basins, emplacement of concrete lined channels).

San Antonio Creek Subbasin

San Antonio Channel drains the outflow from San Antonio Dam and the drainage area between the dam and USGS gage 11073300 that is located just upstream of the confluence of San Antonio Creek and Chino Creek. The area between the gage and the dam comprises the San Antonio Creek subbasin, which represents urban runoff, with significant influence from San Antonio Dam and the Orange County water transfers just downstream of the dam. There is also variable nuisance flow in this subbasin. Calibrating this gage is important for checking the upstream response to the main calibration gage at Chino Creek and for representing recharge in spreading and retention basins (a significant part of the outflow from San Antonio Dam as well as the Orange County water transfer is recharged upstream of the San Antonio Channel stream gage).

Simulated streamflows at the San Antonio Channel gage compare well with measured streamflow for both high and low flows (fig. 15C) for both hourly and daily timesteps (table 10), and r^2 values are high (table 10). The simulated hourly flows are slightly less than those measured at the highest peak flows, and slightly lower than those measured at the very lowest flows.

West Branch Cucamonga Creek Subbasin

The West Branch Cucamonga Creek and USGS gage 11073493 is upstream of and flows into Mill Creek. This subbasin is smaller than Chino Creek and Mill Creek watersheds and provides a good representation of urban runoff with variable nuisance flow and no additional inflows from water diversions or wastewater effluent.

Simulated flows at the West Branch Cucamonga Creek gage were generally slightly higher than the highest measured flows during the calibration period, whereas simulated low flows were generally lower (table 10; fig. 15D). The regression analysis indicates better correlations between daily simulated and measured values than for hourly values (table 10). Simulated nuisance flows underestimate measured flows for both calibration and verification periods (fig. 15D).

San Antonio Dam inflow

San Antonio Creek, which drains San Antonio Canyon, provides the surface water inflow into the storage basin behind San Antonio Dam. The USACE has maintained a record of daily inflows that was used to calibrate the model. The hydrology of this mountainous subbasin is strongly controlled by the formation and melting of a winter snowpack. Nuisance flows and urban runoff are generally nonexistent, but some baseflow in San Antonio Creek may occur in response to ground-water discharge from springs or as delayed release from streambed storage. Baseflow in the upper sections of San Antonio Creek may not reach the San Antonio Dam storage basin because of flow diversions and channel losses (recharge).

Calibration results using the daily streamflow record representing the inflow to San Antonio Dam indicate a reasonable fit between simulated and measured streamflow for medium to high streamflow magnitudes (table 10), with a poor fit for flows less than 10 ft³/s (fig. 15E). Simulating low flows was particularly difficult because channel losses and diversions upstream of the dam were not known exactly.

Transport Model Calibration and Verification Results

Transport simulations were done for total coliforms, fecal coliforms, *E. coli*, and enterococci, but for simplicity, most results are represented by results from the transport of fecal coliforms. Comparisons of simulated and measured fecal coliform concentrations were done on results obtained using the advective (dissolved constituent) transport parameters developed for previous studies in nearby coastal watersheds (Stein and others, 2003). These parameters were used successfully in the San Jacinto basin water-quality modeling study (Tetra Tech Inc., 2003), and were applied in this study as a reference for a set of regionally calibrated transport parameters. They were also used to help develop initial estimates of parameter values for land uses (such as natural land uses) not represented explicitly in the storm-water samples collected for the study. The purpose of the comparison was to help evaluate conditions in the Chino Basin study area relative to average conditions in nearby watersheds, and to provide a reference to a parameter set not calibrated specifically to the Chino Basin bacteria data. The regional parameters do not necessarily define a final set of calibrated parameters, and are referred to in this study as the uncalibrated parameter set.

The average calibrated HSPF transport parameters defining non-point source loading for bacteria, ACCUM and SQOLIM, are shown in table 11 for the 12 land-use categories for both IMPLNDs and PERLNDs. The calibrated bacteria loading parameters (ACCUM and SQOLIM) for the urban and agricultural land uses were generally higher than the initial uncalibrated parameter values that were based on literature values and examples from other studies. Bacteria loading rates and limits calibrated for PERLNDs were higher (by a factor of 5) compared to IMPLND loading rates and limits for a given land use. The washoff limits for all PERLND land uses were higher than the limits for corresponding IMPLND land uses, representing an increase in surface roughness for the pervious land areas. The calibrated bacteria loading rates were much higher for urban land than for grasslands or forests, which is consistent with other studies. Highest loadings were for intensive livestock land-use for both impervious and pervious land units, and the second highest loadings were for mixed agriculture.

Analyses of Storm-Targeted Samples for Storms in Water-Year 2004

The transport model was calibrated for land-use-specific storm sampling sites (water-year 2004 storm samples) by qualitatively comparing simulated and measured hourly bacteria concentrations at the specific location of sample collection, included in the model as a separate reach (RCHRES) for each sampling site. Trial and error adjustments of transport parameters were used to optimize the fit of model simulations to measured data. In addition to bacteria concentrations, the field data included measurements of stage (water-surface elevation), and these were used as a relative measure of stream flow. The upstream catchments for most of the specific land-use sampling sites were generally small (from 3 to approximately 100 acres). Stream flow and bacteria transport at these sites were simulated using a single land-use segment (apportioned into impervious and pervious areas) connected to a single reach segment representing the flow conduit sampled in the field. With the exception of the Mill Creek integrated sample site (site MC), these flow conduits were street gutters, parking lot drains, and small drainage features or storm drains. Although model parameters defining these small catchment areas and flow conduits were adjusted to provide an improved fit between simulated and measured stage, there were no flow measurements available for model calibration. As part of the model calibration process, simulated hourly bacteria concentrations were excluded from the analysis if the hourly simulated streamflow was less than 0.0005 ft³/s. The screening was done to avoid potential problems with model simulations that tend to occur in connection with extremely low flows. For example, concentrations for dry reaches are undefined, and thus zero-discharge conditions were excluded from the analysis.

Table 11. Values for transport parameters SQO, ACCUM, SQOLIM, and WSQOP for 12 land uses and impervious and pervious land units in the Chino Basin, California.

[SQO (initial loading on land), ACCUM (daily loading on land), and SQOLIM (die-off on land in between runoff events) are given in organisms per acre; WSQOP (rainfall needed to remove 90 percent of accumulated pollutant on land) is in inches per hour]

Land use	Transport parameters			
	SQO	ACCUM	SQOLIM	WSQOP
Impervious land units				
Barren or vacant	9.10E+07	9.10E+07	1.60E+08	2.30E-01
Commercial and services	5.00E+09	5.00E+09	9.00E+09	9.00E-02
Forest	1.30E+07	1.30E+07	2.30E+07	5.10E-01
Industrial	5.00E+08	5.00E+08	9.00E+08	7.00E-02
Intensive livestock	1.30E+11	1.30E+11	2.30E+11	3.10E-01
Mixed agriculture	2.60E+10	2.60E+10	4.70E+10	3.50E-01
Mixed urban	3.70E+09	3.70E+09	6.60E+09	1.90E-01
Recreation and open space	1.40E+09	1.40E+09	2.50E+09	2.70E-01
Residential	4.30E+09	4.30E+09	7.80E+09	1.50E-01
Shrubs and grassland	3.80E+07	3.80E+07	6.80E+07	3.90E-01
Transportation and utilities	1.20E+09	1.20E+09	2.10E+09	1.10E-01
Wetland or water	0.00E+00	0.00E+00	0.00E+00	9.90E-01
Pervious land units				
Barren or vacant	9.10E+07	9.10E+07	1.60E+08	3.50E-01
Commercial and services	4.50E+10	4.50E+10	8.10E+10	1.40E-01
Forest	1.30E+07	1.30E+07	2.30E+07	7.70E-01
Industrial	4.50E+09	4.50E+09	8.10E+09	1.10E-01
Intensive livestock	1.10E+12	1.10E+12	2.10E+12	4.70E-01
Mixed agriculture	2.40E+11	2.40E+11	4.30E+11	5.30E-01
Mixed urban	3.30E+10	3.30E+10	5.90E+10	2.90E-01
Recreation and open space	1.30E+10	1.30E+10	2.30E+10	4.10E-01
Residential	3.90E+10	3.90E+10	7.00E+10	2.30E-01
Shrubs and grassland	3.80E+07	3.80E+07	6.80E+07	5.90E-01
Transportation and utilities	1.10E+10	1.10E+10	1.90E+10	1.70E-01
Wetland or water	0.00E+00	0.00E+00	0.00E+00	1.50E+00

Figure 16A shows the comparison between simulated and measured hourly bacteria concentrations at sample site MC for the 11/12/2003–11/13/2003 storm. The MC site is in the main channel of Mill Creek, a more natural, unlined channel about 0.5 mi downstream of the terminus of the Cucamonga Creek concrete-lined channel. Discharge at this site can be high, and represented an integrated response of runoff to many upstream land uses. The hourly bacteria concentrations simulated for MC included results obtained using the uncalibrated (regional) parameters and the calibrated parameters. All results indicated a rapid increase in bacteria concentration (above the baseflow concentration of about 30 cfu/100 mL) during the rising limb of the hydrograph. The peak bacteria concentration occurs between the two streamflow peaks of the hydrograph that occurred for this storm. The second hydrograph peak is much

higher than the first peak, and resulted in dilution of the simulated bacteria concentration due to depletion of the bacteria stored (as a non-point source term) on the upstream IMPLNDs and PERLNDs. Although the simulated bacteria concentrations for the calibrated model reasonably matched the measured concentrations associated with the first hydrograph peak, concentrations associated with the second, higher hydrograph peak were underestimated. The measured concentrations did not indicate dilution during flow represented by the second peak. Results using the uncalibrated parameters showed a response to streamflow similar to that using the calibrated parameters, but the resulting concentrations were about 5 to 8 times lower than the concentrations in the calibrated model, whereby the model greatly underestimated the measured concentrations.

Figure 16. Simulated and measured storm-flow bacteria concentrations for *A*, storm of 11/12/2003–11/13/2003 at site MC, and for storms of 2/2/2004 and 2/22/2004 at *B*, sample site INDND, *C*, sample site INDD, *D*, sample site RECND, *E*, sample site RECGC, *F*, sample site RECD, *G*, sample site RESD, *H*, sample site SC, *I*, sample site D, and *J*, sample site MC reach in the Chino Basin, California. USGS, U.S. Geological Survey.

[Figure 16B](#) compares simulated and measured bacteria concentrations for the IndND site (industrial land use, not near intensive livestock land use; [table 2](#)) during the February 2004 storm period. This sample site is a street gutter having a relatively large upstream area (approximately 118 acres) that causes the street to be prone to flooding. The flow conduit is represented in the model as a first order stream. Values for the simulated bacteria concentrations from the calibrated model reasonably matched the measured values, although the time of the simulated peak concentrations did not match the measured

peak concentration for the 2/22/2004 storm, again because of the dilution effect simulated by the model. The results for the uncalibrated model indicated under-simulation of the measured concentrations, with more dilution in response to the higher discharges. Nuisance flow between storms causes a uniform flow of about 0.01 ft³/s and a uniform bacteria concentration of about 600 to 700 cfu/100 mL for both calibrated and uncalibrated models (nuisance flow is represented the same way for both models).

B **Figure 16.** Continued

The relation between simulated streamflow and simulated bacteria concentration is complex because the peak bacteria concentration increases rapidly during the rising limb of the hydrograph, and the magnitude of the peak bacteria concentration depends on preceding conditions (washoff from preceding storms diminishes the available supply) and on the amount of dilution following the initial washoff. In addition, high bacteria concentrations are often simulated for very low flows. For these reasons, there was no direct correlation between simulated stream flow and simulated bacteria concentrations for the small catchment areas represented by a single land (PERLND and IMPLND) or reach (RCHRES) segment. In some cases, there appeared to be an inverse correlation between the peak of the streamflow hydrograph and the peak bacteria concentration (as in the case of the 2/22/2004 storm) because a previous storm had depleted the bacteria storage component for the land

surface and, following the initial washoff, continued runoff generated by the storm diluted the bacteria concentration in the reach.

Figures 16C (sample site IndD) and 16D (sample site RecND) show calibration results obtained for sites having very low simulated flows because of the very small upstream areas contributing runoff to these sites. Simulated bacteria concentrations in simulated flows of 0.0005 ft³/s and less were excluded from the analysis because of the high uncertainty associated with such low flows. However, this did not affect the comparison with the measured bacteria concentrations because simulated flows during the sampled 2/2/2004 and 2/22/2004–2/23/2004 storms, though still relatively low, were well above the 0.0005 ft³/s screening threshold that was chosen for evaluation of model results.

Figure 16. Continued

Results for sample site IndD ([fig. 16D](#)) indicate that the calibrated model provides a better fit than the uncalibrated model to the measured concentrations for the 2/2/2004 storm and the latter part of the 2/23/2004 storm; the uncalibrated model underestimated concentrations. Comparison with the results obtained for sample site IndND indicates the difficulty in providing a good fit to both sites representing the industrial land use; a good fit to one site caused concentrations to be overestimated or underestimated at the second site. For example, the measured concentrations for sample site IndND indicated no dilution during the peak storm flows of 2/22/2004–2/23/2004 storm, whereas the measured concentrations for sample site IndD indicated a strong dilution in response to the peak storm flows.

[Figure 16D](#) indicates that the bacteria concentrations simulated by the calibrated model are similar to the measured concentrations. Simulation results match the measured concentration results for the 2/2/2004 storm, but the model underestimates concentrations at the hydrograph peak during the 2/23/2004 storm because of dilution. The uncalibrated model underestimates concentrations more than the calibrated model. Simulated flows at the RecND site are very low (less than 0.1 ft³/s for the peak flow 2/26/2004), and the 0.0005 ft³/s screening limit was applied to the nuisance flows between storms (the nuisance flows were as low as 0.0001 ft³/s). For such low flows, the diurnal pattern of evaporation of water in the reach was pronounced.

D **Figure 16.** Continued

Simulation results at the RecGC sampling site did not match measured bacteria concentrations during the 2/2/2004 storm, but matched the data for the 2/23/2004 storm reasonably well ([fig. 16E](#)). The measured concentrations for the 2/23/2004 storm are well represented by the simulated dilution process occurring during the peak flow, and are very similar to the measured and simulated response to peak flow at sample site IndD ([fig. 16C](#)). The values simulated for the 2/2/2004 storm by the uncalibrated model are closer to the measured value than those simulated by the calibrated model. The reverse is true for the 2/23/2004 storm, although the calibrated model values are only slightly closer to the measured value than the uncalibrated. Simulated nuisance flow at site RecGC is about 0.007 ft³/s, well above the 0.0005 ft³/s screening limit,

and the corresponding bacteria concentrations simulated for nuisance flow are about 1,000 cfu/100 mL.

Simulation results for both the RecND and RecGC sites indicate that bacteria concentrations during nuisance flow may be overestimated by the model. However, because a uniform bacteria concentration is assumed for all nuisance inflows according to the total acreage of urban land uses contributing to each model reach section, it is expected that the nuisance flow concentrations are overestimated at some locations and underestimated at other locations. Varying the estimated nuisance flow concentrations according to contributing areas of separate land uses would likely improve model calibration, but this would also require additional field sampling of various nuisance flows based on land use.

E **Figure 16.** Continued

Simulation results for the RecD site ([fig. 16F](#)) are similar to the results for the RecGC site in terms of the comparison between measured and simulated bacteria concentrations. The calibrated model provides a poor fit to the single sample for the 2/2/2004 storm, whereas the uncalibrated model provides an excellent fit. However, the calibrated model provides a good fit to the multiple samples for the 2/23/2004 storm, whereas the uncalibrated model underestimates the measured concentrations. The measured and simulated concentrations indicate dilution associated with the second hydrograph peak simulated for the 2/23/2004 storm. The simulated nuisance

flow at this site is very low (about 0.002 ft³/s), but remains above the 0.0005 ft³/s screening limit for all hourly time steps. The diurnal effect on the simulated flow and the bacteria concentration indicates the very high sensitivity to evaporation at such low flow rates and also indicates an inverse relation between flow and concentration. During low flows, the affect of evaporation is much greater than bacteria die-off (as defined by the RCHRES decay coefficient).

Figure 16. Continued

Simulation results for ResD ([fig. 16G](#)) and SC ([fig. 16H](#)) are also consistent with results obtained at the other sites—a poor match to the single measured sample by using the uncalibrated model for the 2/2/2004 storm, but a closer match using the calibrated model for the 2/23/2004 storm. At these sites, the simulated nuisance flows are less sensitive to hourly evaporation because the estimated reach area is much smaller. The simulated nuisance flow concentration is about 1,500 cfu/100 mL at both sites. Concentrations simulated by the calibrated model matched the measured concentrations at both sites better than those simulated by the uncalibrated model for the February 23 storm.

Results indicate higher measured bacteria concentrations at site D ([fig. 16I](#)) than at the other sites, exceeding 100,000 cfu/100 mL during the February 23 storm. This site is in the channel of a well-defined natural drainage having a fairly large upstream area with most of the other land-use targeted sampling sites. Simulated stormflows were nearly 100 ft³/s for the February 26 storm. The site is primarily affected by runoff from pervious mixed agricultural areas and dairies, and results indicate a better correlation between streamflow and bacteria concentration than at other sites. Simulated nuisance flows were approximately 0.09 ft³/s, and simulated nuisance-flow bacteria concentrations were close

Figure 16. Continued

to 1,000 cfu/100 mL. Fluctuations in simulated bacteria concentrations were diminished by the higher simulated flows. As with many of the other sites, simulation by the uncalibrated model matched the single measured concentration for the February 2 storm more closely than the calibrated model, but the calibrated model more closely matched the multiple samples for the February 23 storm. Both models underestimated the peak bacteria concentrations during the February 23 storm. However, the calibrated model was able to simulate the higher peak concentrations (>100,000 cfu/100 mL) during the following storm of February 26, whereas the uncalibrated model cannot simulate concentrations greater than 15,000 cfu/100 mL. [Figure 16J](#) shows calibration results for the February 2004

storms at sample site MC and includes fecal coliform bacteria concentrations obtained from the monthly samples collected for the RWQCB study. The results indicate a good match between simulated and most measured storm-flow bacteria concentrations in the USGS storm flow samples. A generally good match was also observed for simulated and measured concentrations using the RWQCB data, especially for the flows associated with the February 2, February 18, February 26, and March 2 storms. A slightly better match was observed for the uncalibrated model and the RWQCB data. The concentrations simulated by the uncalibrated model reasonably match the USGS measured storm-targeted concentrations, but this model underestimated concentrations during the peak flows

Figure 16. Continued

more than the calibrated model. Figure 16J includes simulated hourly bacteria concentrations also that are based on modeled nuisance flows (all land area bacteria loading for PERLNDs and IMPLNDs was set to zero). The simulated nuisance flow concentrations of approximately 15 cfu/100 mL underestimated the measured concentrations of 100 to 200 cfu/100 mL. However, the measured and simulated concentrations illustrate the importance of representing contaminated nuisance flow in the model, as opposed to assuming pristine (uncontaminated) nuisance flow.

Measured bacteria concentrations in the peak flows of November 12 and 13 (fig. 16A) were relatively high for this storm (up to 100,000 cfu/100 mL). The simulation results correlated with the rapid increase in concentrations occurring during the rising limb of the first hydrograph peak and with

dilution during peak flow. This effect is also indicated during the second peak of the storm hydrograph; however, the simulated results are lower than the measured concentrations for the second hydrograph peak.

Improving the match between the simulated and the measured values for the second hydrograph peak would require an increase in the land-use loading rates, and this in turn would result in overestimation of bacteria concentrations measured for other storms and at other locations. The bacteria concentrations measured during the November 12–13 storm at the Mill Creek site may be high because of conditions unique to this storm, such as a flushing of sediments in retention basins and channels (this storm may represent unique conditions that would usually occur during the early part of the wet season).

Figure 16. Continued

Quantifying the transport-model calibration results on the basis of simulated versus measured hourly bacteria concentration was difficult because the measured and the simulated concentrations varied greatly from hour-to-hour. To better quantify the transport model calibration results, the simulated average fecal coliform concentration was compared with the measured average concentration for each sampling time for storm-targeted sites (fig. 17). The r^2 value of the exponential regression line for simulated versus measured average bacteria concentrations was 0.58, which was slightly higher than the r^2 values for simulated versus measured geometric mean concentrations and simulated versus measured maximum concentrations. The exponential regression line indicates

a tendency of the model to overestimate bacteria concentrations for the sites having low bacteria levels (industrial and recreation and open space land uses), while those same land uses in the higher range of concentrations are underestimated. The regression line also indicates the tendency of the model to underestimate bacteria concentrations for most sites having high bacteria levels (intensive livestock and commercial and services land uses). Overall, the calibration was satisfactory given the variability observed between sites having the same land use (industrial, recreation and open space). The calibrated model provided a better overall match with the average bacteria concentrations than the uncalibrated model, which underestimated the average measured concentrations.

Figure 16. Continued

Comparisons of Model Simulations with Supplemental Data from other Studies

The water-quality data collected as part of this study was supplemented with water-quality data collected by the RWQCB Task Force and the OCWD. The supplemental data were used to improve the transport-model calibration and allow for model verification. The RWQCB supplemental data were available for multiple sampling sites in the Chino Basin study area and was helpful for developing an improved calibration because of the longer sampling time periods. Additional sampling representing the integrated response in the main stream channels and additional sampling representing specific land uses is not represented by the data collected as part of this study.

[Figure 18A](#) shows the comparison of simulated daily and monthly bacteria concentrations and measured concentrations in samples collected by RWQCB at site D during the storms of 1996–1998. The daily simulations reasonably match the general range, magnitude, and temporal distribution of the measured concentrations. The daily results were used for comparison because the exact time of measurement for the RWQCB samples is not known. The monthly results are included to better illustrate the average temporal distribution of the simulated concentrations. The simulation results are consistent with the measured concentrations in indicating the maximum concentrations (exceeding 100,000 cfu/100 mL) resulting from the storm flows.

Figure 17. Simulated and measured average bacteria concentrations in the Chino Basin, California, for the water-year 2004 storm and land-use targeted sampling sites used for model calibration.

The graph of the Mill Creek sampling site (MC) includes both storm-targeted bacteria data collected during the 2003–2004 winter season and supplemental data collected by the RWQCB (fig. 18B). The 2003–2004 storm-targeted data (USGS storm samples) are from the daily averages for the sampling dates. The storm-targeted data for samples collected during the storms of 2004 show higher bacteria concentrations than the data for the concentrations from the lower-flow samples collected during 2004 and most of the RWQCB samples collected before water-year 2004, because these samples better represent non-storm-flow conditions. Although nuisance flow is a significant part of the total base flow at the Mill Creek sampling site, wastewater effluent is a larger part of the base-flow component and helps dilute the higher concentrations usually associated with nuisance flow. Simulated nuisance flow concentrations of 20 to 30 cfu/100 mL

compare well with the minimum concentrations represented by the RWQCB data. However, the RWQCB samples for the dry period in water-year 2002 indicate elevated concentrations in nuisance flow (between 800 and 3,000 cfu/100 mL), and these are not well represented by the model. It is likely that the low-flow sampling is sensitive to localized point sources of contamination which are not explicitly included in the model. In addition, the elevated concentrations for the low flows may indicate bacteria regrowth in the Cucamonga Creek channel, which is not represented by the model. Comparison of the monthly results for the calibrated and uncalibrated models indicates the higher average concentrations simulated by the calibrated model, which better matches the higher storm flow concentrations and the overall average concentration measured at this site. However, for certain periods, the uncalibrated model better matches the data.

Figure 18. Simulated streamflow and simulated and measured bacteria concentrations at *A*, sample site D, 1996–1998, *B*, sample site MC, 2002–2004, *C*, sample site CCM2, 2002–2004, *D*, sample site CHIS, 2002–2005, *E*, sample site IHC, 2002–2005, *F*, sample site BVAM, 2002–2004, and *G*, sample site PPOC, 2002–2004 in the Chino Basin, California. RWQCB, Regional Water Quality Control Board; USGS, U.S. Geological Survey; OCWD, Orange County Water District.

Measured fecal coliform concentrations for Cucamonga Creek at sample site CCM2 (upstream of the location of RP-1 effluent discharge into Cucamonga Creek channel) indicate that the maximum measured bacteria concentration occurred between storm events during water-year 2002 instead of during storms ([fig. 18C](#)). The higher concentrations measured during the low-flow conditions in water-year 2002 were consistent with the data for sample site MC. The data indicate that the nuisance flows are likely to have relatively high bacteria concentrations (in some cases even higher than concentrations during storm flows) at some locations. This location is upstream of areas used for the mixed agriculture and intensive

livestock, and is somewhat comparable to land used similarly that affect the Chino Creek at Schaeffer Ave. sampling site ([fig. 18D](#), sample site CHIS).

The data collected at the Chino Creek at Schaeffer Ave (CHIS) sampling site ([fig. 18D](#)), which was coincident with the location of the USGS stream gage 11073360 used for calibrating the stream flow component of the model, provided data for characterizing the integrated response in the main Chino Creek channel for 2002 through 2005. This location illustrates the effect of the OCWD water transfers that result in diluting the bacteria concentrations and lowering level of bacteria in nuisance flows.

B **Figure 18.** Continued

Measured concentrations at both the CHIS and CCM2 sites indicated that high bacteria loads were likely in the main stream channels because of nuisance flows and storm runoff from urban areas upstream of the mixed agriculture and intensive livestock land-use areas. The simulated bacteria concentrations in nuisance flow at the two locations ranged from 1,000 to 1,500 cfu/100 mL, and this provided a better match with the available data than the simulation results based on a model that assumed pristine nuisance flow. However, the data indicated high variability in bacteria concentrations during low flow conditions, and this was not well represented by the

uniform nuisance flow concentration assumed for the model. For some of the storm periods, the lower (<100 cfu/100 mL) measured concentrations suggested that some storm flows diluted the bacteria concentrations, and this was well represented by the model. Comparing the monthly results for the calibrated and the uncalibrated models indicated the higher average concentrations obtained using the calibrated model best represented the actual concentrations. At sample site CHIS, the calibrated model more closely matched the OCWD samples used for model verification.

C

Figure 18. Continued

Natural background conditions were represented by the IHC site in San Antonio Canyon and illustrate the relatively low bacteria concentrations in the upland areas representative of natural, or background, conditions (fig. 18E). Simulated average monthly bacteria concentrations obtained using the calibrated parameters were compared with results obtained using the uncalibrated parameters; the uncalibrated parameters yielded higher concentrations because of higher loads for the natural land uses. However, neither the calibrated nor the uncalibrated model accurately simulated the peak bacteria concentration of 9,000 cfu/100 mL measured during the

beginning of water-year 2003. This sample may represent point, rather than nonpoint, bacteria loading in the stream channel and thus was not represented by the model. The other samples, all of which had concentrations less than about 300 cfu/100 mL, were more closely represented by the models. The OCWD samples were also included in the comparison and indicated very low bacteria concentrations for water-year 2005. The calibrated model simulated the OCWD samples used for model verification more accurately than the uncalibrated model.

D **Figure 18.** Continued

The data collected at the Bon View and Merrill Ave. sampling site (BVAM) confirmed the bounds for the combined mixed agriculture and intensive livestock land uses and indicated the condition under which pervious land requires very high flows to effectively transport bacteria, as shown by the very high bacteria concentrations measured during March, 2003 ([fig. 18F](#)). The calibrated daily model indicated peak daily concentrations consistently exceeding 100,000 cfu/100 mL in response to storm runoff, and this was supported by the

field data. The uncalibrated model, in comparison, generally underestimated the measured bacteria concentrations at this site. The simulated nuisance flow of about 1,000 cfu/100 mL provided a good fit to the measured minimum concentration of about 900 cfu/100 mL obtained during water-year 2002. In general, the calibrated model provided a good fit to the range and temporal distribution of the water-year 2002 data.

The integrated site at Prado Park Lake outflow (PPOC) generally matches the daily and monthly bacteria

E **Figure 18.** Continued

concentrations during storm-flow and higher flow conditions ([fig. 18G](#)). The calibrated model provides a good match to the timing and general magnitude of the measured peak concentration during the March 2003 storm flow conditions. The average monthly concentrations obtained using the calibrated model provide a good general fit to the measured concentrations, whereas results obtained using the uncalibrated model consistently underestimates the concentrations. For low-flow conditions, the calibrated model usually underestimates bacteria concentrations. However, increasing the simulated low-flow concentrations was difficult because (1) the inflows into Prado Park Lake from RP-1 were assumed to be pristine and

this greatly diluted bacteria levels during low-flow conditions, (2) the residence time for water stored in Prado Park Lake caused most of the bacteria transported into the lake from upstream areas to decay, and (3) the bypass pipe underlying the lake and diverting low-flows directly into the lake outflow was not explicitly defined in the model. The bacteria in the diverted low flows would not undergo the dilution and die-off that would occur if discharged into the upstream part of the lake, as represented by the model.

For this study, the decay coefficients were kept consistent throughout the modeling domain for all RCHRES segments.

F **Figure 18.** Continued

In some cases, such as Prado Park Lake, a different decay coefficient may improve model calibration. In many cases, the supplemental data were interpreted as representing base flow only (wastewater effluent, water transfers, and nuisance flow). However, in some cases, such as the Prado Park Lake outflow, the supplemental data represented, at least in part, the effect of storm runoff alone or the combined effect of storm-runoff and base-flow components.

Final model calibration included a comparison of simulated and measured average bacteria concentrations using all RWQCB monthly samples and all USGS storm-targeted

samples (fig. 19). The calibrated transport model was verified by comparing simulated bacteria concentrations with the measured average bacteria concentrations in the OCWD WY2005 samples. The OCWD samples were available for multiple sites for water-year 2005. Figure 19 and table 12 show the calibration and verification analysis. The r^2 value for both the calibration and the verification exponential regression lines is 0.78. The slope of the calibration line is similar to that of the 1-to-1 line, whereas the slope of the verification

G

Figure 18. Continued

line is less similar, overestimating bacteria levels for the cleanest sites and underestimating bacteria levels for the most contaminated sites. Calibration results were improved by including (1) sample sites representing natural or background conditions (IHC and CCM1), (2) RWQCB storm-flow samples for 1996–1998 (labeled CBSW sites in [figure 19](#)), and (3) the most contaminated sample site, BVAM, which provided the most direct sampling of the intensive livestock land use. The OCWD samples indicated a slight bias towards higher measured bacteria levels relative to the other sample groups, causing the calibrated model to underestimate bacteria levels for the verification. The bias in the OCWD data may in part be due to improved sampling techniques.

Results in [table 12](#) show summary statistics for measured and simulated fecal coliform concentrations for all samples collected in 1997–1998 and 2002–2004, including winter and

summer flows, and storm flows. The statistics for the simulated concentrations were calculated using only the hourly simulations that corresponded to the time and date a measurement was made. For RWQCB and OCWD data, 12:00 pm (noon) was used as the sampling time (most samples were collected between 10 am and 2 pm). Statistics compared include average, geometric mean, maximum, and minimum bacteria concentrations. The highest average measured bacteria concentration of 452,931 cfu/100 mL was obtained at sample site BVAM from 13 samples collected for the RWQCB study (the 1997–98 storm flow samples and the 2003–2004 monthly samples were combined for the analysis). The highest average simulated bacteria concentration (based on the hourly simulations for 6 sampling dates and times) was 19,230 cfu/100 mL for the ResD storm sampling (and winter) site.

Figure 19. Simulated and measured average bacteria concentrations in the Chino Basin for all sampling sites used for model calibration and verification. TMDL, Total Maximum Daily Load; USGS, U.S. Geological Survey.

Uncertainties in Modeling a System with Changing Conditions

Critical model datasets used to develop parameters representing the hydrologic characteristics of the study area included the stream-channel and storm-drain network, the location and storage capacity of the larger retention basins, the land-use map, and the imperviousness map. These datasets were mostly based on features that existed during 1999–2000 and likely do not accurately represent past or future basin characteristics (the data is most accurate for the 1999–2000 time frame). In general, the trend of increasing population and urbanization has resulted in a decrease in pervious areas and natural drainages with time.

Additional uncertainties and limitations included the many simplifying assumptions used to define the hydrologic behavior of the basin and the processes controlling bacteria development and transport. Irrigation of pervious landscapes was not represented directly by the model. Increased soil moisture resulting from irrigation would likely generate more runoff relative to that generated on non-irrigated landscapes. Such characteristics were indirectly incorporated into the model by adjusting parameters during the model calibration process (the increased runoff should be accounted for by the stream flow record).

Table 12. Calibration summary of simulated fecal coliform concentrations and measured indicator bacteria concentrations for 18 sampling sites in the Chino Basin, California.

[Location of some sites on [figure 2](#) (green). Measured values are indicator bacteria concentrations and simulated values are fecal bacteria concentrations, all in colony forming units per 100 milliliters. USGS, U.S. Geological Survey; RWQCB, Regional Water Quality Control Board; OCWD, Orange County Water District. N/A, not applicable]

Sample site ID	Mill Creek drainage					
	RecD	IndND	RecGD	MC	CCM1	CCM2
Collecting agency	USGS	USGS	USGS	USGS/RWQCB	RWQCB	RWQCB
All recorded concentrations						
Measured						
Number of measured values	6	6	6	85	36	45
Average	2,603	4,967	393	15,240	12	6,558
Geometric mean	904	4,604	240	1,836	11	2,040
Maximum	10,000	9,000	830	150,000	60	50,000
Minimum	140	3,200	40	9	9	9
Standard deviation	3,919	2,289	338	30,798	10	9,419
Simulated						
Average	2,114	1,476	2,688	4,098	5	5,114
Geometric mean	507	62	683	405	3	2,063
Maximum	9,696	7,691	11,833	32,853	32	41,220
Minimum	32	2	44	17	0	615
Standard deviation	3,746	3,075	4,532	6,622	7	9,527
Concentrations categorized by season						
Measured						
Summer (May–October)						
Number of measured values	0	0	0	12	3	10
Average	N/A	N/A	N/A	1,408	37	16,730
Geometric mean	N/A	N/A	N/A	1,327	29	12,891
Winter (November–April)						
Number of measured values	6	6	6	73	33	35
Average	2,603	4,967	393	17,514	10	3,651
Geometric mean	904	4,604	240	1,937	10	1,204
Simulated						
Summer (May–October)						
Average	N/A	N/A	N/A	463	0	1,220
Geometric mean	N/A	N/A	N/A	35	0	1,219
Winter (November–April)						
Average	2,114	1,476	2,688	4,695	6	6,227
Geometric mean	507	62	683	607	3	2,398
Concentrations collected from stormflow						
Measured						
Number of measured values	6	6	6	25	1	2
Average	2,603	4,967	393	36,712	20	510
Geometric mean	904	4,604	240	16,660	20	473
Simulated						
Average	2,114	1,476	2,688	7,822	2	1,945
Geometric mean	507	62	683	5,304	2	1,918

Table 12. Calibration summary of simulated fecal coliform concentrations and measured indicator bacteria concentrations for 18 sampling sites in the Chino Basin, California.—Continued

[Location of some sites on [figure 2](#) (green). Measured values are indicator bacteria concentrations and simulated values are fecal bacteria concentrations, all in colony forming units per 100 milliliters. USGS, U.S. Geological Survey; RWQCB, Regional Water Quality Control Board; OCWD, Orange County Water District. N/A, not applicable]

Sample site ID Collecting agency	Chino Creek drainage											
	D USGS	SC USGS	ResD USGS	IndD USGS	RecND USGS	CHIC RWQCB	CHIS RWQCB	BVAM RWQCB	IHC RWQCB	PPOC RWQCB	S6 OCWD	S8 OCWD
All recorded concentrations												
Measured												
Number of measured values	6	6	6	6	6	4	50	13	48	42	4	5
Average	84,083	27,050	7,875	131	5,517	17,775	8,655	452,931	219	404	3,004	26,423
Geometric mean	44,397	17,108	6,696	102	5,397	9,431	826	31,026	15	152	1,467	4,883
Maximum	250,000	60,000	18,000	320	7,400	46,000	160,000	5,200,000	9,400	8,200	6,750	117,000
Minimum	6,000	2,400	3,200	45	3,800	2,550	9	900	2	9	230	595
Standard deviation	95,844	22,955	5,369	108	1,250	20,267	25,968	1,427,487	1,354	1,250	3,105	50,730
Simulated												
Average	18,901	11,585	19,230	1,379	2,585	5,689	2,775	12,713	87	534	1,446	15,624
Geometric mean	12,928	1,907	328	442	1,998	1,193	1,859	3,962	20	3	1,118	5,400
Maximum	40,276	59,629	114,158	6,128	6,754	16,950	13,557	59,736	736	16,530	3,020	32,753
Minimum	1,811	91	36	45	884	147	30	699	3	0	543	543
Standard deviation	14,228	23,594	46,506	2,360	2,206	7,922	2,973	19,738	146	2,586	1,167	15,154
Concentrations categorized by season												
Measured												
Summer (May–October)												
Number of measured values	0	0	0	0	0	3	13	0	12	7	2	3
Average	N/A	N/A	N/A	N/A	N/A	17,367	21,106	N/A	837	257	458	39,488
Geometric mean	N/A	N/A	N/A	N/A	N/A	7,468	1,620	N/A	47	166	397	3,927
Winter (November–April)												
Number of measured values	6	6		6	6	1	37	13	36	35	2	2
Average	84,083	27,050	7,875	131	5,517	19,000	4,281	452,931	13	434	5,550	6,825
Geometric mean	44,397	17,108	6,696	102	5,397	19,000	652	31,026	10	150	5,419	6,769
Simulated												
Summer (May–October)												
Average	N/A	N/A	N/A	N/A	N/A	1,936	1,515	N/A	4	0	562	5,551
Geometric mean	N/A	N/A	N/A	N/A	N/A	493	936	N/A	3	0	561	1,697
Winter (November–April)												
Average	18,901	11,585	19,230	1,379	2,585	16,950	3,218	12,713	115	641	2,331	30,733
Geometric mean	12,928	1,907	328	442	1,998	16,950	2,366	3,962	35	7	2,227	30,667
Concentrations collected from stormflow												
Measured												
Number of measured values	6	6	6	6	6	2	2	1	2	0	2	3
Average	84,083	27,050	7,875	131	5,517	32,500	42,500	5,200,000	10	N/A	5,550	43,550
Geometric mean	44,397	17,108	6,696	102	5,397	29,563	42,453	5,200,000	9	N/A	5,419	17,501
Simulated												
Average	18,901	11,585	19,230	1,379	2,585	11,231	2,517	845	464	N/A	2,331	25,666
Geometric mean	12,928	1,907	328	442	1,998	9,666	2,324	845	376	N/A	2,227	24,444

Model Application: Evaluation of Contribution to Bacteria Contamination on the Basis of Flow Process and Land Use

The calibrated HSPF transport model was applied to evaluate the relative contributions to bacteria loading in streamflow from the various flow processes represented in the model and from the various land uses ([table 13](#)). The relative contributions were compared to the average bacteria loads for the calibrated model: the comparison was referred to as the base-case result. The objective of this application was to improve understanding of the potential downstream affects on water quality of the different non-point bacteria loading rates, washoff limits, decay coefficients, and the areas of the different land uses. The results were also used to evaluate differences between the effects of PERLND (pervious area) and IMPLND (impervious area) on flow and transport, as well as differences between storm flow and low flow conditions and between summer and winter flow conditions.

The simulation period for model application was calendar year 1985–2005. The period analyzed was 1988–2005, allowing for a 3-year model initialization period to minimize the effect of initial conditions on the analysis. As in the case of model calibration, the analysis excluded results for time steps for which the simulated hourly streamflow was less than 0.0005 ft³/s because of the high uncertainty associated with HSPF transport results for the very low flows.

1988–2005 Simulation Results: Summary of Base Case

[Table 13](#) provides a summary of the 1988–2005 simulation results for 6 sites in the Chino Creek subbasin ([table 13A](#)) and 6 sites in the Mill Creek subbasin ([table 13B](#)). The simulation results were compiled for the base-case, and for all flow-process and land-use test cases, using (1) all simulated flows, (2) winter and (3) summer flows, (4) storm flows, and (5) low flows. Winter flows were defined by results for November through April for a given water year, and summer flows were defined by results for May through October. The flow limit used for separating low flows from storm flows was based on visual inspection of the flow hydrograph at each site. The results for all flows, storm flows, and low flows include the average, geometric mean, maximum, and minimum bacteria concentrations. The results for winter and summer flows include the average, maximum and geometric mean for bacteria concentrations.

The maximum hourly bacteria concentration for all 12 sites was about 2.7 million cfu/100 mL for sample site D ([table 13A](#)). Sample site D, which primarily represents storm runoff from the mixed agricultural and intensive livestock land

uses, had the highest simulated average bacteria concentration of 8,551 cfu/100 mL also. Other sites having relatively high simulated average bacteria levels (greater than 2,000 cfu/100 mL) were USGS stream gage 11073360 (sample site CHIS), CCM2 ([table 13B](#)), and USGS stream gage 11073493. Simulated average bacteria concentration exceeded 200 cfu/100 mL at all sites in the central and southern parts of the Chino Basin. Average bacteria concentrations were less than 200 cfu/100 mL at the 3 sites representing natural drainages: CCM1 (average of 6 cfu/100 mL), IHC (average of 46 cfu/100 mL), and San Antonio Dam outflow (average of 121 cfu/100 mL). For all sites, the simulated geometric mean bacteria concentration was much lower than the simulated average concentration (by as much as 1 to 2 orders of magnitude). Minimum concentrations were also relatively low; from 0 at CCM1 and PPOC to 37 at sample site D. In general, the simulation results at all sites were characterized by high variances and highly skewed distributions.

Average winter bacteria concentrations were much higher than average summer bacteria concentrations at all sites, and average simulated streamflow was also higher in the winter at all sites. The greatest absolute difference between average winter and summer bacteria levels occurred at site D (winter average of 15,203 cfu/100 mL versus summer average of 1,997 cfu/100 mL). The highest relative differences tended to occur at sites in the Chino Creek subbasin (Chino Creek outflow, PPOC, and IHC). Maximum hourly bacteria concentrations were highest during the winter at all sites except San Antonio Dam outflow, CCM2, and stream gage 11073495.

Average bacteria concentrations for storm flows were higher than average concentrations for low flows at all sites except stream gage 11073360 (sample site CHIS). Sample sites PPOC and D, downstream of the mixed agriculture and dairies land uses, had the highest storm flow average bacteria concentrations (73,321 cfu/100 mL for PPOC and 49,524 for D). The storm flow average and the maximum hourly bacteria concentrations in the Chino Creek outflow and the Mill Creek outflow were similar, but the storm flow geometric mean concentration of 280 cfu/100 mL in the Chino Creek outflow was much lower than the geometric mean of 3,531 cfu/100 mL for the Mill Creek outflow. This difference is due in part to the Orange County water transfers that affected the Chino Creek drainage but not the Mill Creek drainage. The Orange County water transfer inflows, which in this study were modeled as pristine water, have a much higher flow volume than the wastewater effluent inflows and are included in the storm flow results. These inflows cause a lot of dilution of contaminated water in Chino Creek.

Table 13A. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations for the Chino Creek and San Antonio Canyon subbasins in the Chino Basin, California..

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Chino Creek and San Antonio Canyon subbasins					
		Chino Creek outflow	Sample site PPOC	Sample site D	Stream gage 11073360	San Antonio Dam outflow	Sample site IHC
Simulation results for all flows							
Average streamflow	ft³/s	68.7	22.7	0.8	19.7	25.9	10.3
Maximum streamflow	ft³/s	12,538	781	1,139	4,101	1,314	1,355
Minimum streamflow	ft³/s	16.6	2.2	0	0.3	0	1.4
Average bacteria concentration	cfu/100 mL	1,397	1,397	8,551	5,125	121	46
Maximum bacteria concentration	cfu/100 mL	235,198	255,855	2,698,312	123,553	2,385	3,045
Minimum bacteria concentration	cfu/100 mL	8	0	37	7	1	2
Geometric mean bacteria concentration	cfu/100 mL	93	1	1,687	1,694	31	9
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	48	4	47	75	55	55
Pervious area runoff	% of average	50	96	45	2	43	39
Nuisance flow	% of average	2	0	9	23	0	0
Groundwater	% of average	0	0	0	0	2	6
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	1	3
Forest	% of average	0	0	0	0	1	5
Barren and vacant	% of average	0	0	0	0	2	3
Mixed urban	% of average	3	0	0	3	52	89
Recreation and open space	% of average	0	0	0	0	15	1
Commercial and services	% of average	14	0	3	28	4	0
Utilities and transportation	% of average	1	0	2	1	2	0
Residential	% of average	30	0	0	40	19	0
Mixed agriculture	% of average	15	21	19	1	0	0
Industrial	% of average	2	0	0	3	4	0
Intensive livestock (dairies)	% of average	33	78	66	0	0	0
Simulation results for winter (November through April) flows							
Average streamflow	ft³/s	83.4	25.2	1.5	23.3	33.9	12.2
Average bacteria concentration	cfu/100 mL	2,592	2,793	15,203	7,458	160	83
Maximum bacteria concentration	cfu/100 mL	235,198	255,855	2,698,312	123,553	1,693	3,045
Geometric mean bacteria concentration	cfu/100 mL	213	10	2,724	2,900	72	23
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	45	3	47	82	58	57
Pervious area runoff	% of average	54	97	49	3	41	40
Nuisance flow	% of average	1	0	4	15	0	0
Groundwater	% of average	0	0	0	0	1	4
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	1	2
Forest	% of average	0	0	0	0	1	3
Barren and vacant	% of average	0	0	0	0	2	3
Mixed urban	% of average	3	0	0	3	52	92
Recreation and open space	% of average	0	0	0	0	14	1
Commercial and services	% of average	13	0	3	31	4	0
Utilities and transportation	% of average	1	0	3	1	2	0
Residential	% of average	29	0	0	45	20	0
Mixed agriculture	% of average	16	21	20	1	0	0
Industrial	% of average	1	0	0	3	4	0
Intensive livestock (dairies)	% of average	35	78	69	0	0	0

Table 13A. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations for the Chino Creek and San Antonio Canyon subbasins in the Chino Basin, California.—Continued

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Chino Creek and San Antonio Canyon subbasins					
		Chino Creek outflow	Sample site PPOC	Sample site D	Stream gage 11073360	San Antonio Dam outflow	Sample site IHC
Simulation results for summer (May through October) flows							
Average streamflow	ft³/s	54	20	0	16	10	8
Average bacteria concentration	cfu/100 mL	220	22	1,997	2,827	45	9
Maximum bacteria concentration	cfu/100 mL	30,736	16,377	787,116	95,826	2,385	2,891
Geometric mean bacteria concentration	cfu/100 mL	42	0	1,052	997	6	4
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	80	36	46	54	39	38
Pervious area runoff	% of average	6	64	11	1	56	29
Nuisance flow	% of average	14	0	43	45	0	0
Groundwater	% of average	0	0	0	0	6	33
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	2	11
Forest	% of average	0	0	0	0	3	21
Barren and vacant	% of average	0	0	0	0	2	3
Mixed urban	% of average	3	0	0	2	50	64
Recreation and open space	% of average	0	0	0	0	22	1
Commercial and services	% of average	25	2	3	22	3	0
Utilities and transportation	% of average	1	1	2	1	1	0
Residential	% of average	44	0	0	28	12	0
Mixed agriculture	% of average	4	21	11	0	0	0
Industrial	% of average	3	0	0	2	3	0
Intensive livestock (dairies)	% of average	4	74	40	0	0	0
Simulation results for storm flows							
Frequency (percentage of all flows)	% of time	11	1	13	15	25	6
Average streamflow	ft³/s	286.5	104.3	5.9	126.7	98.3	40.7
Maximum streamflow	ft³/s	12,538	781	1,139	4,101	1,314	1,355
Minimum streamflow	ft³/s	100	50	0.2	20	20	20
Average bacteria concentration	cfu/100 mL	7,306	73,321	49,524	4,354	152	225
Maximum bacteria concentration	cfu/100 mL	235,198	255,855	2,698,312	123,553	1,186	3,045
Minimum bacteria concentration	cfu/100 mL	9	368	37	7	1	3
Geometric mean bacteria concentration	cfu/100 mL	280	34,659	9,877	141	93	80
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	38	1	39	89	11	10
Pervious area runoff	% of average	62	99	61	10	88	89
Nuisance flow	% of average	0	0	0	1	0	0
Groundwater	% of average	0	0	0	0	1	1

Table 13A. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations for the Chino Creek and San Antonio Canyon subbasins in the Chino Basin, California.—Continued

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Chino Creek and San Antonio Canyon subbasins					
		Chino Creek outflow	Sample site PPOC	Sample site D	Stream gage 11073360	San Antonio Dam outflow	Sample site IHC
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	2	3
Forest	% of average	0	0	0	0	1	2
Barren and vacant	% of average	0	0	0	0	1	2
Mixed urban	% of average	3	0	0	4	52	92
Recreation and open space	% of average	0	0	0	0	27	1
Commercial and services	% of average	11	0	3	30	3	0
Utilities and transportation	% of average	1	0	2	2	1	0
Residential	% of average	27	0	0	56	12	0
Mixed agriculture	% of average	20	21	22	3	1	0
Industrial	% of average	1	0	0	3	2	0
Intensive livestock (dairies)	% of average	36	78	72	0	0	0
Simulation results for low flows							
Frequency (percentage of all flows)	% of time	89	99	87	85	75	94
Average streamflow	ft³/s	42.3	21.6	0.1	1	2.1	8.4
Maximum streamflow	ft³/s	100	50	0.2	20	20	20
Minimum streamflow	ft³/s	16.6	2.2	0	0.3	0	1.4
Average bacteria concentration	cfu/100 mL	680	465	2,625	5,260	111	35
Maximum bacteria concentration	cfu/100 mL	70,926	120,073	74,825	101,893	2,385	1,937
Minimum bacteria concentration	cfu/100 mL	8	0	447	64	1	2
Geometric mean bacteria concentration	cfu/100 mL	82	1	1,306	2,611	21	8
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	61	10	68	73	75	72
Pervious area runoff	% of average	34	90	1	1	22	19
Nuisance flow	% of average	5	0	31	26	0	0
Groundwater	% of average	0	0	0	0	3	9
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	1	3
Forest	% of average	0	0	0	0	1	6
Barren and vacant	% of average	0	0	0	0	2	3
Mixed urban	% of average	2	0	1	3	51	88
Recreation and open space	% of average	0	0	0	0	10	0
Commercial and services	% of average	18	1	4	28	5	0
Utilities and transportation	% of average	1	1	3	1	2	0
Residential	% of average	33	0	0	38	22	0
Mixed agriculture	% of average	10	21	12	1	0	0
Industrial	% of average	2	0	0	3	5	0
Intensive livestock (dairies)	% of average	29	77	49	0	0	0

Table 13B. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for locations in the Mill Creek submodel in the Chino Basin, California.

[ft³/s, cubic foot per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Mill Creek subbasins					
		Mill Creek outflow	Sample site MC	Stream gage 11073495	Sample site CCM2	Stream gage 11073493	Sample site CCM1
Simulation results for all flows							
Average streamflow	ft³/s	51.7	51.8	51.1	24	4.3	10.3
Maximum streamflow	ft³/s	13,896	14,469	13,513	12,211	1,671	5,094
Minimum streamflow	ft³/s	8.5	8	7.8	0.2	0.4	0
Average bacteria concentration	cfu/100 mL	1,111	1,223	1,015	7,713	2,517	6
Maximum bacteria concentration	cfu/100 mL	333,188	227,032	65,496	195,891	91,456	421
Minimum bacteria concentration	cfu/100 mL	13	13	16	17	3	0
Geometric mean bacteria concentration	cfu/100 mL	77	93	96	2,185	684	3
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	85	87	93	87	87	28
Pervious area runoff	% of average	13	10	4	0	1	43
Nuisance flow	% of average	2	3	4	12	12	0
Groundwater	% of average	0	0	0	0	0	29
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	0	42
Forest	% of average	0	0	0	0	0	23
Barren and vacant	% of average	0	0	0	0	0	34
Mixed urban	% of average	5	5	6	6	1	0
Recreation and open space	% of average	0	0	0	0	0	0
Commercial and services	% of average	14	14	18	16	22	0
Utilities and transportation	% of average	2	2	3	2	1	0
Residential	% of average	46	47	60	61	61	0
Mixed agriculture	% of average	6	6	2	1	1	0
Industrial	% of average	3	3	3	2	2	0
Intensive livestock (dairies)	% of average	22	21	4	0	0	0
Simulation results for winter (November through April) flows							
Average streamflow	ft³/s	76.3	76	74.3	45.1	7.5	18.6
Average bacteria concentration	cfu/100 mL	1,948	2,113	1,703	10,783	3,823	10
Maximum bacteria concentration	cfu/100 mL	333,188	227,032	51,717	148,239	91,456	421
Geometric mean bacteria concentration	cfu/100 mL	178	195	186	2,848	1,010	4
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	84	87	94	93	92	30
Pervious area runoff	% of average	14	12	4	1	2	52
Nuisance flow	% of average	1	2	2	7	7	0
Groundwater	% of average	0	0	0	0	0	18
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	0	44
Forest	% of average	0	0	0	0	0	19
Barren and vacant	% of average	0	0	0	0	0	37
Mixed urban	% of average	5	6	6	6	1	0
Recreation and open space	% of average	0	0	0	0	0	0
Commercial and services	% of average	13	13	18	17	23	0
Utilities and transportation	% of average	2	2	3	2	1	0
Residential	% of average	45	46	61	64	65	0
Mixed agriculture	% of average	7	6	2	1	1	0
Industrial	% of average	3	3	3	3	2	0
Intensive livestock (dairies)	% of average	23	23	4	0	0	0

Table 13B. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for (B) locations in the Mill Creek submode in the Chino Basin, California.—Continued

[ft³/s, cubic foot per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Mill Creek subbasins					
		Mill Creek outflow	Sample site MC	Stream gage 11073495	Sample site CCM2	Stream gage 11073493	Sample site CCM1
Simulation results for summer (May through October) flows							
Average streamflow	ft³/s	27.5	27.9	28.3	3.3	1.1	1.8
Average bacteria concentration	cfu/100 mL	287	346	338	4,688	1,230	2
Maximum bacteria concentration	cfu/100 mL	26,269	46,300	65,496	195,891	69,501	281
Geometric mean bacteria concentration	cfu/100 mL	34	45	50	1,682	466	2
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	92	90	89	75	71	20
Pervious area runoff	% of average	1	0	0	0	0	6
Nuisance flow	% of average	8	9	11	25	29	0
Groundwater	% of average	0	0	0	0	0	75
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	0	37
Forest	% of average	0	0	0	0	0	41
Barren and vacant	% of average	0	0	0	0	0	22
Mixed urban	% of average	5	5	5	4	1	0
Recreation and open space	% of average	0	0	0	0	0	0
Commercial and services	% of average	15	15	17	15	19	0
Utilities and transportation	% of average	2	2	2	1	1	0
Residential	% of average	52	52	58	52	49	0
Mixed agriculture	% of average	4	3	1	0	0	0
Industrial	% of average	3	3	3	2	1	0
Intensive livestock (dairies)	% of average	11	11	2	0	0	0
Simulation results for storm flows							
Frequency (percentage of all flows)	% of time	5	4	5	7	15	6
Average streamflow	ft³/s	536	618	530	322	25	139
Maximum streamflow	ft³/s	13,896	14,469	13,513	12,211	1,671	5,094
Minimum streamflow	ft³/s	70	80	60	10	0.9	15
Average bacteria concentration	cfu/100 mL	8,326	8,776	7,158	12,596	11,765	23
Maximum bacteria concentration	cfu/100 mL	333,188	227,032	51,166	128,988	91,456	241
Minimum bacteria concentration	cfu/100 mL	17	16	22	17	3	0
Geometric mean bacteria concentration	cfu/100 mL	3,531	3,760	2,754	3,082	5,322	9
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	69	70	91	97	98	1
Pervious area runoff	% of average	31	30	9	3	2	91
Nuisance flow	% of average	0	0	0	0	1	0
Groundwater	% of average	0	0	0	0	0	7
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	0	67
Forest	% of average	0	0	0	0	0	22
Barren and vacant	% of average	0	0	0	0	0	11
Mixed urban	% of average	5	5	6	6	1	0
Recreation and open space	% of average	0	0	0	0	0	0
Commercial and services	% of average	10	11	18	19	24	0
Utilities and transportation	% of average	2	2	3	3	1	0
Residential	% of average	36	39	62	67	69	0
Mixed agriculture	% of average	9	8	3	1	1	0
Industrial	% of average	2	2	3	3	3	0
Intensive livestock (dairies)	% of average	35	32	4	0	0	0

Table 13B. Summary of 1988–2005 simulation results and percent contribution to bacteria loading by flow process and land use for (B) locations in the Mill Creek submode in the Chino Basin, California.—Continued

[ft³/s, cubic foot per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Locations in Mill Creek subbasins					
		Mill Creek outflow	Sample site MC	Stream gage 11073495	Sample site CCM2	Stream gage 11073493	Sample site CCM1
Simulation results for low flows							
Frequency (percentage of all flows)	% of time	94.9	95.7	95	92.7	84.7	93.7
Average streamflow	ft ³ /s	25.9	26.3	26.1	0.7	0.5	1.6
Maximum streamflow	ft ³ /s	70	80	60	10	0.9	15
Minimum streamflow	ft ³ /s	8.5	8	7.8	0.2	0.4	0
Average bacteria concentration	cfu/100 mL	726	884	695	7,331	845	5
Maximum bacteria concentration	cfu/100 mL	25,368	66,086	65,496	195,891	29,176	421
Minimum bacteria concentration	cfu/100 mL	13	13	16	106	243	0
Geometric mean bacteria concentration	cfu/100 mL	63	79	81	2,127	472	3
Percent contribution to average bacteria concentration by flow process							
Impervious area runoff	% of average	96	95	94	86	59	36
Pervious area runoff	% of average	1	1	1	0	0	29
Nuisance flow	% of average	3	4	6	14	41	0
Groundwater	% of average	0	0	0	0	0	35
Percent contribution to average bacteria concentration by land use							
Shrubs and grasses	% of average	0	0	0	0	0	35
Forest	% of average	0	0	0	0	0	24
Barren and vacant	% of average	0	0	0	0	0	41
Mixed urban	% of average	5	6	5	6	0	0
Recreation and open space	% of average	0	0	0	0	0	0
Commercial and services	% of average	16	15	18	16	16	0
Utilities and transportation	% of average	2	2	3	2	1	0
Residential	% of average	52	50	60	60	41	0
Mixed agriculture	% of average	4	4	2	1	0	0
Industrial	% of average	3	3	3	2	1	0
Intensive livestock (dairies)	% of average	14	16	4	0	0	0

Flow-Process Contributions to Bacteria Contamination

The relative contribution to bacteria contamination was evaluated for 4 different flow processes represented by the HSPF transport model: (1) impervious-area runoff, (2) pervious-area runoff, (3) groundwater discharge, and (4) nuisance flow. The relative contribution by a given flow process was simulated by setting the parameters defining transport and bacteria loading for the other three processes to zero. For example, to simulate the relative contribution from impervious-area runoff, SQO, ACQOP, and SQOLIM were set to zero for all PERLNDs, and bacteria loading for nuisance inflow was set to zero (nuisance inflows were modeled as uncontaminated). To simulate the effect of pervious-area runoff, bacteria loading for nuisance inflow was set to zero, SQO, ACQOP, and SQOLIM

were set to zero for all IMPLNDs, and the SQO, ACQOP, and SQOLIM for PERLNDs were left unchanged (equal to the calibrated base-case parameter values). Parameters controlling ground-water bacteria loading (throughflow and deep ground-water discharge) for PERLNDs were also set to zero for evaluating pervious-area runoff. To evaluate ground-water contributions, bacteria loading for nuisance flow was set to zero, SQO, ACQOP, and SQOLIM for both IMPLNDs and PERLNDs were set to zero (eliminating bacteria loading for overland flow), and the parameters defining bacteria loading for throughflow and deep ground-water discharge were left unchanged. To evaluate nuisance flow contributions, SQO, ACQOP, and SQOLIM for IMPLNDs and PERLNDs were set to zero, and ground-water bacteria loading was set to zero. In all cases, the decay coefficients in RCHRES were left unchanged.

Contribution of Flow Processes for Selected Storms

Simulation results from the modified model were used to compare bacteria concentrations in terms of the four flow-process contributions for the February 2004 storms sampled at site D (fig. 20) and for the winter storms in 2004 and 2005 sampled at the Mill Creek outflow (fig. 21). The simulated hourly bacteria concentrations for the two storms sampled at site D (February 2 and February 22–23) were primarily affected by impervious area runoff (fig. 20). Ground water did not contribute to bacteria contamination at this site; nuisance flow contributions were diluted during the storm flows, but substantial during low flow conditions. Nuisance

flow contributions between storm flows were approximately 1,000 cfu/100 mL. Runoff from pervious areas made no contribution to the February 2 storm because pervious areas were not generating runoff, and only minor amounts came from pervious areas during the February 22–23 storm. However, during the next storm on February 26 (not sampled for bacteria), runoff from pervious areas contributed much more than runoff from impervious areas to the simulated bacteria concentrations (by approximately 2 orders of magnitude). Runoff from the next smaller storm on March 2 also included substantial bacteria loading from pervious area runoff, but slightly less than from the impervious areas.

Figure 20. Simulated hourly bacteria concentrations affected by different flow processes during storms in February 2004 at sample site D in the Chino Basin, California.

Figure 21. Simulated daily bacteria concentrations affected by different flow processes for *A*, storms during December–March, water-year 2004, at Mill Creek outflow, and *B*, storms during December–March, water-year 2005, at Mill Creek outflow in the Chino Basin, California.

Simulated daily bacteria concentrations at Mill Creek outflow were mostly from impervious area runoff for the 12/6/2003 to 3/9/2004 storm period ([fig. 21A](#)). Only a small amount of bacteria loading from pervious-area runoff occurred during the 2/26/2004 and 3/2/2004 storms. In contrast, the contribution to bacteria loading from pervious-area runoff was much greater than the impervious area contribution for the larger storms of 2005 ([fig. 21B](#)). Bacteria concentrations from

impervious area runoff were usually elevated during earlier storms in a storm sequence and during the time represented by the rising limb of the storm hydrograph. Bacteria concentrations from pervious-area runoff were usually elevated during the latter part of a storm sequence, after the ground had become saturated. Bacteria concentration from pervious runoff reached a peak during or after the hydrograph peak for the Mill Creek outflow.

B **Figure 21.** Continued.

Concentration Duration Analysis for Flow-Process Contributions

Results for the flow processes were compared using concentration-duration curves indicating the percentage of time bacteria concentrations were exceeded for simulated 1988–2005 hourly fecal coliform concentrations at 7 sites: San Antonio Dam outflow, sample site D, sample site PPOC, Chino Creek outflow, site CCM1, sample site CCM2, and Mill Creek outflow (fig. 22). For most locations within and downstream of the urbanized areas in the Chino Basin, maximum bacteria levels were simulated in response to runoff from pervious areas, but the percentage of time that pervious area runoff was the dominant bacteria source was relatively low. Pervious-area runoff was the dominant source of maximum

simulated bacteria concentrations at San Antonio Dam outflow (fig. 22A), sample site D (fig. 22B), sample site PPOC (fig. 22C), Chino Creek outflow (fig. 22D), and Mill Creek outflow (fig. 22G). However, the percentage of time during which pervious-area runoff was the dominant bacteria source was less than about 4 percent at site PPOC, less than about 1 percent at site D and Chino Creek outflow, and less than about 0.15 percent at Mill Creek outflow. For the two sites representing natural conditions, CCM1 (fig. 22E) and San Antonio Dam outflow (fig. 22A), pervious-area runoff was an important source to the total bacteria load much more often than for the locations within and downstream of the urban areas.

A

Figure 22. Concentration durations for simulated hourly bacteria concentrations affected by different flow processes at A, San Antonio Dam outflow, B, sample site D, C, sample site PPOC (Prado Park Lake outflow), D, Chino Creek outflow, E, sample site CCM1, (F) sample site CCM2, and G, Mill Creek outflow for water-years 1988–2005 in the Chino Basin, California.

The concentration-duration analysis for CCM2 indicates that pervious area runoff is a minor to insignificant source of bacteria loading at all times compared to loading from impervious areas and nuisance flows (fig. 22F). Nuisance-flow contributions downstream of urban areas but upstream of wastewater treatment facilities significantly affected water quality; bacteria concentrations from nuisance flow were greater than 1,000 cfu/100 mL about 60 percent of the time and greater than 200 cfu/100 mL about 90 percent of the time. Although the model incorporated a very simplified representation of nuisance flow using an assumed inflow concentration, the general concept of contaminated nuisance flow is consistent with the measured bacteria data. Results for sample site D (fig. 22B) also indicate important contributions to total bacteria loading

from nuisance flow; bacteria concentrations from nuisance flow was greater than 900 cfu/100 mL for about 70 percent of the time, and greater than 200 cfu/100 mL for about 90 percent of the time. However, the model may not represent the flow volume component of the nuisance flow accurately at this site because an assumed inflow rate per unit area of urban and agricultural land uses in the entire model area was used to determine the magnitude of the nuisance inflow.

Nuisance-flow contributions to bacteria contamination was significant for sites located within urbanized areas (where the nuisance flow was generated) and upstream of inflows from the wastewater treatment facilities. This was especially true for low flow conditions when stream flow was essentially equivalent to the nuisance inflows.

B **Figure 22.** Continued.

Flow Processes Contributions to Average Bacteria Concentrations

The average simulated bacteria concentrations for all flows at the 12 sites used to summarize model results (table 13) indicates that impervious-area runoff was the dominant bacteria source for the central and lower parts of the Mill Creek subbasin (from 85 to 93 percent of the average bacteria loading for the base-case simulation). In contrast, results for the Chino Creek subbasin indicate higher site-to-site variation in the dominant flow process contributing to bacteria contamination. Pervious-area runoff is responsible for 96 percent of the average bacteria loading at site PPOC,

but only 45 percent at site D. This difference occurs because the flows having a high percentage of impervious area bacteria loading tend to be low flows that are easily diluted by the RP-1 discharges into Prado Park Lake, upstream of PPOC. In addition, bacteria decay (die-off) is maximized in Prado Park Lake because of the average residence time of water in the lake (as opposed to the shorter residence time of water stored in the main channels). Only the larger storms result in high bacteria concentrations in Prado Park Lake outflow, and these storms tend to be dominated by bacteria loading from pervious-area runoff.

C

Figure 22. Continued.

Overall, pervious area runoff resulted in the highest peak concentrations because pervious areas account for a larger percentage of total upstream land area and because loading rates were estimated to be higher for pervious areas than for the urban and agricultural (including dairy) land uses. The overall comparison of simulation results indicates that impervious area runoff was the main source of the storm runoff and subsequent bacteria washoff in the Chino Basin because impervious area runoff occurs much more often than pervious area runoff. Runoff from pervious areas is generated only during the larger storms when the precipitation intensity exceeds the soil infiltration capacity or during storm periods characterized by a high frequency of storms that saturate soils.

Impervious-area runoff contributions were slightly higher than pervious-area contributions for the IHC and San Antonio Canyon outflow sites, even though these sites are fed by drainages that represent mostly natural conditions. The land-use map identified a small fraction of the total area within the San Antonio Canyon drainage, including the area directly upstream of the IHC site, as urban land (for example, the road in San Antonio Canyon, low density residential, and campground or picnic areas are included as urban land). In contrast, the drainage upstream of the CCM1 site contained only the 3 natural land-use categories; shrubs and grasses, forests, and barren areas. Simulation results at CCM1 indicated that pervious area runoff was the dominant contributor to the average bacteria loading.

D **Figure 22.** Continued.

Sites indicating a substantial (greater than 10 percent) contribution to average bacteria concentrations from nuisance flow were stream gage 11073493 and CCM2 in the Mill Creek subbasin and stream gage 11073360 (sample site CHIS) in the Chino Creek subbasin ([table 13](#)). All sites were strongly affected by runoff from the highly urbanized central part of the Chino Basin and were upstream of the wastewater effluent inflows that dilute the high concentrations of the nuisance flows. Nuisance flow contributions were highest during summer flows and low flows at most sites. The highest nuisance flow contribution during summer was 45 percent at stream gage 11073360 (sample site CHIS), and the highest low flow contribution was 41 percent at stream gage 11073493.

Only the CCM1 site indicated a substantial groundwater contribution (29 percent) to average bacteria concentrations based on all flows combined. There was also some small ground-water contribution to the sites in San Antonio Canyon: 6 percent at IHC and 2 percent at San Antonio Dam outflow. Groundwater contribution to average bacteria concentrations at all other sites was zero. Ground-water contributions were much higher during summer flows; 75 percent at CCM1, 33 percent at site IHC, and 6 percent at San Antonio Canyon outflow. Groundwater contributions were only slightly higher during low flows; 35 percent at CCM1, 9 percent at IHC, and 3 percent at San Antonio Dam outflow.

E

Figure 22. Continued.

Evaluation of Source Area Contribution on the Basis of Land Use

Bacteria loading from a single land-use area was simulated by setting the SGO, ACQOP, and SQOLIM parameters to zero for all other land uses except for the land use being simulated (the calibrated base line parameters were left unchanged for this land use). In addition, nuisance flow was simulated as pristine water (nuisance inflows did not include bacteria) in order to fully isolate the effect of a single land use on the average bacteria loading. The parameters defining bacteria loading for ground water for a given PERLND were

left unchanged for the PERLND being simulated. These simulations were repeated for all land-use types except for water and wetlands (water and wetlands is a significant land use only for the Prado Dam subbasin), and the results from all simulations, including the base-case (baseline) simulation for all land uses, were compared. The evaluations were based on the simulation results for calendar years 1988–2005, allowing for a 3 year model ramp up (simulations were started on 1/1/1985) to mitigate the effects of uncertainty in initial conditions.

F **Figure 22.** Continued.

Land-Use Contributions to Bacteria Concentrations for Selected Storms

Simulated hourly bacteria concentrations affected by various land uses and by storms during 2/21/2004–2/28/2004 and 2/17/2005–2/25/2005 at Mill Creek and Chino Creek outflow were compared (fig. 23). Runoff from residential land use contributed the most to the total bacteria loading at both locations during the 2/22/2004–2/23/2004 storm (fig. 23A). Runoff from commercial and services land use also contributed substantially to the downstream bacteria concentrations at Chino Creek outflow. Impervious-area runoff from dairies

contributed the most to bacteria concentrations at the Mill Creek site, but only a minor amount to the Chino Creek outflow site. In both cases, the bacteria contamination was caused by impervious-area runoff. Most of the bacteria were washed off of the impervious surfaces during the first hydrograph peak on 2/22/2004. Runoff during the second hydrograph peak had much less bacteria to washoff and diluted bacteria concentration in downstream reaches. Bacteria concentration increased during the falling limb of the hydrograph because the delayed inflows from the upstream reaches were not diluted.

G

Figure 22. Continued.

Contaminated runoff from mixed agriculture and intensive livestock was a much higher amount of total bacteria loading for the 2/26/2004 storm than for the 2/22/2004 storm at Chino Creek outflow (fig. 23A). The maximum bacteria concentration for both was about 10,000 cfu/100 mL, only slightly more than that for residential land use. Results for the 2/26/2004 storm at Mill Creek were different because the contamination was caused by impervious area runoff (fig. 23B), whereas the high bacteria concentrations simulated for Chino Creek included a substantial contribution from pervious area runoff.

The results for the wetter 2/17/2005–2/25/2005 storms show a much higher contribution from the mixed agriculture and intensive livestock land uses because pervious-area runoff was the dominant runoff source during these storms and the modeled non-point source area loading was much higher for mixed agriculture and intensive livestock than for all other land uses. At Chino Creek outflow, mixed agriculture runoff caused the highest peak bacteria concentrations, about 38,000 cfu/100 mL, and residential runoff also contributed substantially to the total bacteria loading (fig. 23C). In contrast, mixed agriculture and residential runoff provided only

A

Figure 23. Land-use contributions to simulated bacteria concentrations at *A*, Chino Creek outflow for storms in February 2004, *B*, Mill Creek outflow for storms in February 2004, *C*, Chino Creek outflow for storms in February 2005, and *D*, Mill Creek outflow for storms in February 2005 in the Chino Basin, California.

minor contributions to the bacteria loading compared with runoff from dairies at the Mill Creek site ([fig. 23D](#)). Previous-area runoff from intensive livestock land use areas upstream of Mill Creek outflow caused peak hourly bacteria concentrations of about 140,000 cfu/100 mL during the end of the storm sequence in response to saturated soil conditions. In general, the primary sources of bacteria contamination at Chino Creek and Mill Creek outflow were areas used for residential, mixed agriculture, and intensive livestock land-use areas that produced runoff during the storm periods.

Hourly concentration-duration (or exceedance) curves for land-use sources were analyzed using simulation results for 7 sites: San Antonio Dam outflow, sample site D, sample site PPOC (Prado Park Lake outflow), Chino Creek outflow, sample site CCM1, sample site CCM2, and Mill Creek outflow ([fig. 24](#)). The concentration-duration curve shows the proportion of all hourly fecal coliform concentrations exceeding a given value. Simulation results for each separate land use were compared to the base case concentration-duration curves (upper black line) at all sites to evaluate the relative

B **Figure 23.** Continued.

contributions to bacteria contamination. At San Antonio Dam outflow, the primary sources of bacteria contamination were the mixed-urban, residential, and recreational and open-space land uses ([fig. 24A](#)). The natural land uses at San Antonio Dam outflow provided only minor contributions to total bacteria loading relative to those provided by the urban land uses, even though the natural areas were a much greater fraction of the total upstream area. At sample site D, intensive livestock, mixed agriculture, and transportation and utilities provided the greatest contribution to bacteria contamination; the concentrations from intensive livestock land-use areas are above

2,000 cfu/100 mL ([fig. 24B](#)) approximately 22 percent of the time. Most of the time, nuisance flow was the primary source of bacteria levels higher than 200 cfu/100 mL at site D. At Prado Park Lake outflow, contamination was primarily caused by runoff from intensive livestock and mixed agriculture land-use areas ([fig. 24C](#)), but concentrations from intensive livestock exceeded the 200 cfu/100 mL limit only about 12 percent of the time because of dilution from RP-1 discharges into Prado Park Lake and the longer residence time of water in Prado Park Lake. In contrast to results for the Prado

Figure 23. Continued.

Park Lake drainage, results for Chino Creek outflow indicate that runoff from residential land use contributes a higher relative amount to the total bacteria load than intensive livestock and mixed agriculture for most flows ([fig. 24D](#)). Concentrations exceeding 200 cfu/100 mL are caused by residential runoff about 15 percent of the time, whereas concentrations exceeding 200 cfu/100 mL due to runoff from intensive livestock occur about 9 percent of the time. The bacteria concentration of runoff from intensive livestock is higher than runoff from residential areas for only about 1.5 percent of the time at Chino Creek outflow.

Simulation results for the CCM1 site indicated the lowest bacteria concentrations compared with results for all other sites ([fig. 24E](#)). Bacteria concentrations exceeded the 200 cfu/100 mL limit only 0.03 percent of the time. Runoff from the barren and vacant land use caused the maximum bacteria concentration. At CCM2, runoff from the residential and the commercial and services land uses was the primary source of bacteria concentration above 2,000 cfu/100 mL ([fig. 24F](#)). Runoff from mixed urban areas also provided substantial bacteria loading at this location. The relative contributions from the different land uses at Mill Creek outflow ([fig. 24G](#)) were

D

Figure 23. Continued.

similar to those at Chino Creek outflow (fig. 24D). Residential land use was the primary source of bacteria contamination exceeding 200 cfu/100 mL for most storm flows at both locations. However, runoff from intensive livestock had a greater average affect on Chino Creek outflow. At Mill Creek, runoff from intensive livestock exceeds 10,000 cfu/100 mL for only about 0.2 percent of the time, compared with about 1.2 percent of the time at Chino Creek.

The highest relative contribution to the average bacteria concentration was provided by runoff from residential areas at six of the twelve sites analyzed for land use contributions to bacteria contamination (table 13). Five of these sites were in the Mill Creek subbasin (Mill Creek outflow, sample site MC, stream gage 11073495, CCM2, and stream gage 1073493),

Figure 24. Concentration durations for simulated hourly bacteria concentrations affected by different land uses at *A*, San Antonio Dam outflow, *B*, sample site D, *C*, sample site PPOC, *D*, Chino Creek outflow, *E*, sample site CCM1, *F*, sample site CCM2, and *G*, Mill Creek outflow for water-years 1988–2005 in the Chino Basin, California.

whereas only one was in the Chino Creek subbasin. The maximum percentage of contributions to bacteria loading from residential areas ranged from 61 percent at the CCM2 and stream gage 11073493 sites to 40 percent at stream gage 11073360 (sample site CHIS). Runoff from intensive livestock was the dominant bacteria source for three of the twelve sites: Chino Creek outflow, sample site D, and sample site PPOC.

The highest percentage contribution to the average base-case bacteria concentration from a single land use in the central and southern parts of the Chino Basin was 78 percent for runoff from intensive livestock upstream of PPOC. The bacteria contribution from intensive livestock was also relatively high (66 percent) for sample site D, which was also the location where the maximum bacteria concentrations were simulated

Figure 24. Continued.

(about 2.7 million cfu/100 mL). Commercial and services and mixed agriculture were also important bacteria sources for the central and southern parts of the Chino Basin. A maximum relative contribution to bacteria loading for commercial and services land use was 28 percent at stream gage 11073360 (sample site CHIS). A maximum contribution for the mixed agricultural land use was 21 percent at the PPOC site. The

highest contribution from a single land-use area within the Chino Basin was for the mixed urban land use at sample site IHC. Model results indicated that industrial, utilities and transportation and recreation and open space land uses were not important sources of bacteria contamination, in terms of average concentration, for the Chino Basin.

Figure 24. Continued.

Figure 24. Continued.

E **Figure 24.** Continued.

Figure 24. Continued.

Figure 24. Continued.

Model Application: Analysis of Basin Response to Possible Climate and Land-Use Changes

Climate Scenarios

Model simulations were made of various climate scenarios to test the hydrologic and transport sensitivity of the Chino Basin model simulations to possible changes in precipitation and air temperature.

Development

Climate scenarios were developed to represent possible conditions and do not represent predictions or indications of potential future conditions. The scenarios were used to indicate watershed responses to changes in climate. The results provide an indication of the sensitivity of simulated flow and bacteria concentrations to changes in precipitation and air temperature while model parameters remained the same. The model results were evaluated for the 1988-2005 simulation period. Simulations were started on 1/1/1985 to allow for a 3-year model ramp up to 1988 and ran continuously through 12/31/2005.

Two different air temperature scenarios were defined as (1) a constant 5°F increase in hourly air temperature and (2) a 5°F decrease in hourly air temperature. The air temperature scenarios were used primarily to evaluate watershed responses and model sensitivity to changes in snow fall, snowpack storage, and snowmelt in the higher altitude subwatersheds. In general, the development and persistence of a snow pack and the timing of snow melt can be sensitive to small changes in air temperature. Although changes in air temperature can change the estimates of hourly PET (a decrease in air temperature decreases PET and an increase in air temperature increases PET), these changes were not applied to the PET estimates because this effect was assumed to be small relative to the effect of air temperature on snowmelt.

Eight different precipitation scenarios were developed. Seven scenarios were developed using a simple scaling of the hourly precipitation inputs, with scaling factors of 0, 0.1, 0.5, 0.8, 1.2, 1.5, and 2.0. The scaling factor 0 was used to evaluate results based only on the inflows from wastewater effluent, water deliveries, and nuisance flow. The eighth precipitation scenario was developed using a scaling factor of 0.2 for calendar years 1988–1996 and a scaling factor of 1.8 for calendar years 1997–2005. The eighth scenario was used to evaluate the effect of increased precipitation variability on simulated flow and bacteria transport (a dry period followed by a wet period).

Results of Air Temperature Scenarios

Simulated 1988-2005 streamflow and bacteria concentration for the two air temperature scenarios were compared with the results obtained for the base case (current climate) simulation. Two air temperature scenarios—one assuming a 5°F decrease in air temperature and one assuming a 5°F increase—were simulated for five locations ([tables 14](#) and [15](#)). The results for the San Antonio Canyon submodel using the 5°F decrease indicated a significant increase in the simulated monthly snow pack for upper San Antonio Canyon ([fig. 25A](#)), upstream of sample site IHC. Simulations of water years having the greatest snow accumulations (1993, 1995, 1998, and 2005) showed a maximum monthly snow pack depth approximately 30 percent greater than that for the base case simulation. Results for upper San Antonio Canyon using the 5°F increase indicated an even greater relative change in monthly snow pack depth; for most years, the snow pack depth was approximately 70 to 80 percent less than that for the base-case simulation.

Simulation results for monthly streamflow indicate changes in the magnitude and the timing of streamflow for upper San Antonio Canyon in response to the changes in air temperature. The 5°F decrease in air temperature caused maximum monthly streamflow to shift into later spring ([fig. 25B](#)). The 5°F increase in air temperature caused a significant (about 30 to 50 percent) increase in maximum monthly streamflow during some winters, especially for the wetter than average years, and minimal to zero flows during summer.

Simulated monthly bacteria concentrations indicated a complex response to the changes in streamflow caused by the differences in snow accumulation and melt as a result of the decrease and increase in air temperature in upper San Antonio Canyon ([fig. 25C](#)). During most months and water years, the decrease in air temperature caused an increase in bacteria concentrations, whereas the increase in air temperature usually caused a decrease in monthly bacteria concentrations. Two exceptions to this pattern were the dry water-years 1994 and 1999, when the increased air temperature scenario caused the maximum monthly bacteria concentration to be about 30 percent higher than that for the base case and the decreased air temperature scenario caused the maximum monthly concentrations to be slightly less than that for the base case. The complex response is due to the interplay between (1) bacteria washoff during overland flow, which tends to increase as temperature increases because less precipitation occurs as snow, and (2) baseflow concentrations, which for this study were represented as including point sources along stream channels. Baseflow concentrations tend to increase as flows decrease, and flows decrease as temperature decreases.

Table 14A. Summary of 1988–2005 simulation results for air temperature scenarios at sample site IHC and San Antonio Dam outflow in the Chino Creek subbasin, California.

[Temperature in degrees Fahrenheit. ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Parameter	Units	Sample site IHC			San Antonio Dam outflow		
		Base case	Air temperature		Base case	Air temperature	
			– 5 degrees	+ 5 degrees		– 5 degrees	+ 5 degrees
Simulation results for all flows							
Number of simulated values	hours	157,800	157,800	157,800	72,944	93,084	40,562
Percentage of time flow occurred	%	100	100	100	46	59	26
Average simulated streamflow	ft³/s	10.3	11.4	8.9	25.9	22.1	49.4
Maximum streamflow	ft³/s	1,355	191	1,849	1,314	445	2,055
Minimum streamflow	ft³/s	1.4	1.6	0.9	0.0	0.0	0.0
Average bacteria concentration	cfu/100 mL	46	46	40	121	89	183
Geometric mean bacteria concentration	cfu/100 mL	9	9	8	31	22	37
Maximum bacteria concentration	cfu/100 mL	3,045	2,387	3,057	2,385	2,020	3,666
Minimum bacteria concentration	cfu/100 mL	2	2	2	1	1	0
Percentage of base case concentration	%		101	88		73	151
Simulation results for winter flows							
Number of winter values	hours	78,312	78,312	78,312	48,459	54,397	32,365
Percentage of time flow occurred	%	50	50	50	31	34	21
Average streamflow	ft³/s	12.2	11.1	12.5	33.9	23.5	60.7
Average bacteria concentration	cfu/100 mL	83	73	71	160	113	210
Geometric mean bacteria concentration	cfu/100 mL	23	20	18	72	51	58
Maximum bacteria concentration	cfu/100 mL	3,045	2,185	3,057	1,693	1,389	3,666
Percentage of base case concentration	%		88	86		71	131
Simulation results for summer flows							
Number of summer values	hours	79,488	79,488	79,488	24,485	38,689	8,199
Percentage of time flow occurred	%	50	50	50	16	25	5
Average streamflow	ft³/s	8.4	11.8	5.4	9.9	20.2	4.5
Average bacteria concentration	cfu/100 mL	9	20	10	45	55	78
Geometric mean bacteria concentration	cfu/100 mL	4	5	4	6	6	6
Maximum bacteria concentration	cfu/100 mL	2,891	2,387	2,466	2,385	2,020	2,516
Percentage of base case concentration	%		220	105		124	174
Simulation results for stormflows							
Number of stormflow values	hours	9,113	9,525	8,437	18,025	22,222	13,550
Percentage of time flow occurred	%	6	6	5	11	14	9
Average streamflow	ft³/s	40.7	43.7	58.2	98.3	83.7	142.0
Maximum streamflow	ft³/s	1,355	191	1,849	1,314	445	2,055
Minimum streamflow	ft³/s	20.0	20.0	20.0	20.0	20.0	20.0
Average bacteria concentration	cfu/100 mL	225	234	173	152	151	141
Geometric mean bacteria concentration	cfu/100 mL	80	77	65	93	77	60
Maximum bacteria concentration	cfu/100 mL	3,045	2,387	3,057	1,186	722	1,520
Minimum bacteria concentration	cfu/100 mL	3	3	5	1	3	1
Percentage of base case concentration	%		104	77		99	93
Simulation results for low flows							
Number of lowflow values	hours	148,687	148,275	149,363	54,919	70,864	27,014
Percentage of time flow occurred	%	94	94	95	35	45	17
Average streamflow	ft³/s	8.4	9.4	6.1	2.1	2.8	2.9
Maximum streamflow	ft³/s	20.0	20.0	20.0	20.0	20.0	20.0
Minimum streamflow	ft³/s	1.4	1.6	0.9	0.0	0.0	0.0
Average bacteria concentration	cfu/100 mL	35	34	32	111	70	204
Geometric mean bacteria concentration	cfu/100 mL	8	8	7	21	15	29
Maximum bacteria concentration	cfu/100 mL	1,937	1,815	1,849	2,385	2,020	3,666
Minimum bacteria concentration	cfu/100 mL	2	2	2	1	1	0
Percentage of base case concentration	%		98	94		63	184

Table 14B. Summary of 1988–2005 simulation results for air temperature scenarios at sample site CCM1 and Mill Creek outflow in the Mill Creek subbasin, California.

[Temperature in degrees Fahrenheit. ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results.]

Parameter	Units	Sample site CCM1			Mill Creek outflow		
		Base case	Air temperature		Base case	Air temperature	
			– 5 degrees	+ 5 degrees		– 5 degrees	+ 5 degrees
Simulation results for all flows							
Number of simulated values	hours	152,971	157,800	141,685	157,800	157,800	157,800
Percentage of time flow occurred	%	97	100	90	100	100	100
Average simulated streamflow	ft³/s	10.3	9.5	11.6	51.7	49	52.7
Maximum streamflow	ft³/s	5,094	4,172	4,883	13,896	12,541	13,778
Minimum streamflow	ft³/s	0	0	0	8.5	8.5	8.5
Average bacteria concentration	cfu/100 mL	6	7	9	1,111	1,184	1,093
Geometric mean bacteria concentration	cfu/100 mL	3	3	2	77	82	76
Maximum bacteria concentration	cfu/100 mL	421	244	7,828	333,188	332,079	327,200
Minimum bacteria concentration	cfu/100 mL	0	0	0	13	13	13
Percentage of base case concentration	%		115	140		107	98
Simulation results for winter flows							
Number of winter values	hours	77,563	78,312	75,346	78,312	78,312	78,312
Percentage of time flow occurred	%	49	50	48	50	50	50
Average streamflow	ft³/s	18.6	16.1	20.3	76.3	70.5	78.3
Average bacteria concentration	cfu/100 mL	10	12	12	1,948	2,097	1,909
Geometric mean bacteria concentration	cfu/100 mL	4	6	4	178	199	174
Maximum bacteria concentration	cfu/100 mL	421	244	906	333,188	332,079	327,200
Percentage of base case concentration	%		119	125		108	98
Simulation results for summer flows							
Number of summer values	hours	75,411	79,488	66,387	79,488	79,488	79,488
Percentage of time flow occurred	%	48	50	42	50	50	50
Average streamflow	ft³/s	1.8	2.9	1.7	27.5	27.8	27.5
Average bacteria concentration	cfu/100 mL	2	3	4	287	286	288
Geometric mean bacteria concentration	cfu/100 mL	2	2	2	34	34	34
Maximum bacteria concentration	cfu/100 mL	281	178	7,828	26,269	26,089	26,269
Percentage of base case concentration	%		106	186		99	100
Simulation results for stormflows							
Number of stormflow values	hours	9,693	15,434	8,496	8,002	8,863	8,063
Percentage of time flow occurred	%	6	10	5	5	6	5
Average streamflow	ft³/s	139.2	77.1	172.2	535.8	424.7	551.7
Maximum streamflow	ft³/s	5,094	4,172	4,883	13,896	12,541	13,778
Minimum streamflow	ft³/s	15	15	15	70	70	70
Average bacteria concentration	cfu/100 mL	23	25	18	8,326	8,172	8,091
Geometric mean bacteria concentration	cfu/100 mL	9	12	6	3,531	2,316	3,398
Maximum bacteria concentration	cfu/100 mL	241	244	224	333,188	332,079	327,200
Minimum bacteria concentration	cfu/100 mL	0	0	0	17	13	16
Percentage of base case concentration	%		111	80		98	97
Simulation results for low flows							
Number of lowflow values	hours	143,281	142,366	133,237	149,798	148,937	149,737
Percentage of time flow occurred	%	91	90	84	95	94	95
Average streamflow	ft³/s	1.6	2.1	1.4	25.9	26.6	25.8
Maximum streamflow	ft³/s	15	15	15	70	70	70
Minimum streamflow	ft³/s	0	0	0	8.5	8.5	8.5
Average bacteria concentration	cfu/100 mL	5	5	8	726	768	716
Geometric mean bacteria concentration	cfu/100 mL	3	3	2	63	67	62
Maximum bacteria concentration	cfu/100 mL	421	198	7,828	25,368	25,342	25,368
Minimum bacteria concentration	cfu/100 mL	0	1	0	13	13	13
Percentage of base case concentration	%		102	159		106	99

Table 15A. Summary of 1988–2005 simulation results for precipitation scenarios at San Antonio Dam outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for all flows								
Number of simulated values	hours	0	0	8,657	72,944	145,064	157,800	74,953
Percentage of time flow occurred	%	0	0	5	46	92	100	47
Average streamflow	ft³/s	0	0	5.6	25.9	46.5	86.4	46.3
Maximum streamflow	ft³/s	0	0	52.7	1,313.9	4,119.6	7,243.2	5,906.1
Minimum streamflow	ft³/s	0	0	0.0	0.0	0.0	0.5	0.0
Average bacteria concentration	cfu/100 mL	0	0	267	121	56	54	78
Geometric mean bacteria concentration	cfu/100 mL	0	0	106	31	10	8	18
Maximum bacteria concentration	cfu/100 mL	0	0	2,786	2,385	1,775	833	3,119
Minimum bacteria concentration	cfu/100 mL	0	0	1	1	1	1	1
Percentage of base case average concentration	%	0	0	220	100	46	44	65
Simulation results for winter flows								
Number of winter values	hours	0	0	8,107	48,459	77,531	78,312	42,922
Percentage of time flow occurred	%	0	0	5	31	49	50	27
Average streamflow	ft³/s	0.0	0.0	5.9	33.9	66.8	123.9	58.1
Average bacteria concentration	cfu/100 mL	0	0	277	160	80	76	106
Geometric mean bacteria concentration	cfu/100 mL	0	0	125	72	31	26	40
Maximum bacteria concentration	cfu/100 mL	0	0	2,786	1,693	1,775	833	3,119
Percentage of base case average concentration	%	0	0	173	100	50	47	66
Simulation results for summer flows								
Number of summer values	hours	0	0	550	24,485	67,533	79,488	32,031
Percentage of time flow occurred	%	0	0	0	16	43	50	20
Average streamflow	ft³/s	0.0	0.0	0.2	9.9	23.1	49.5	30.6
Average bacteria concentration	cfu/100 mL	0	0	117	45	28	32	42
Geometric mean bacteria concentration	cfu/100 mL	0	0	8	6	3	2	6
Maximum bacteria concentration	cfu/100 mL	0	0	1,406	2,385	1,065	726	725
Percentage of base case average concentration	%	0	0	263	100	63	72	93

Table 15A. Summary of 1988–2005 simulation results for precipitation scenarios at San Antonio Dam outflow in the Chino Basin, California.—Continued

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	Variable dry-wet
Simulation results for storm flows								
Number of stormflow values	hours	0	0	416	18,025	54,354	107,061	21,208
Percentage of time flow occurred	%	0	0	0	11	34	68	13
Average streamflow	ft ³ /s	0.0	0.0	37.8	98.3	113.7	122.8	155.0
Maximum streamflow	ft ³ /s	0.0	0.0	52.7	1,313.9	4,119.6	7,243.2	5,906.1
Minimum streamflow	ft ³ /s	0.0	0.0	20.0	20.0	20.0	20.0	20.0
Average bacteria concentration	cfu/100 mL	0	0	84	152	106	77	147
Geometric mean bacteria concentration	cfu/100 mL	0	0	57	93	42	15	67
Maximum bacteria concentration	cfu/100 mL	0	0	342	1,186	1,099	833	1,039
Minimum bacteria concentration	cfu/100 mL	0	0	19	1	1	1	1
Percentage of base case average concentration	%	0	0	55	100	70	50	96
Simulation results for low flows								
Number of lowflow values	hours	0	0	8,241	54,919	90,710	50,739	53,745
Percentage of time flow occurred	%	0	0	5	35	57	32	34
Average streamflow	ft ³ /s	0.0	0.0	4.0	2.1	6.1	9.8	3.4
Maximum streamflow	ft ³ /s	0.0	0.0	19.9	20.0	20.0	20.0	20.0
Minimum streamflow	ft ³ /s	0.0	0.0	0.0	0.0	0.0	0.5	0.0
Average bacteria concentration	cfu/100 mL	0	0	276	111	26	6	51
Geometric mean bacteria concentration	cfu/100 mL	0	0	109	21	5	2	10
Maximum bacteria concentration	cfu/100 mL	0	0	2,786	2,385	1,775	249	3,119
Minimum bacteria concentration	cfu/100 mL	0	0	1	1	1	1	1
Percentage of base case average concentration	%	0	0	248	100	23	5	46

Table 15B. Summary of 1988–2005 simulation results for precipitation scenarios at storm sample site D in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	Variable dry-wet
Simulation results for all flows								
Number of simulated values	hours	157,800	157,800	157,800	157,800	157,800	157,800	157,800
Percentage of time flow occurred	%	100	100	100	100	100	100	100
Average streamflow	ft³/s	0.1	0.1	0.2	0.8	1.9	3.2	1.2
Maximum streamflow	ft³/s	0.1	2.5	243.5	1,139.0	1,967.3	2,788.7	1,961.1
Minimum streamflow	ft³/s	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Average bacteria concentration	cfu/100 mL	844	2,636	5,476	8,551	11,205	13,957	8,569
Geometric mean bacteria concentration	cfu/100 mL	844	1,199	1,682	1,687	1,590	1,493	1,547
Maximum bacteria concentration	cfu/100 mL	922	93,410	2,170,030	2,698,312	2,591,125	3,558,091	3,321,682
Minimum bacteria concentration	cfu/100 mL	755	766	172	37	26	13	23
Percentage of base case average concentration	%	10	31	64	100	131	163	100
Simulation results for winter flows								
Number of winter values	hours	78,312	78,312	78,312	78,312	78,312	78,312	78,312
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	0.1	0.1	0.3	1.5	3.6	6.2	2.2
Average bacteria concentration	cfu/100 mL	818	4,242	9,278	15,203	19,890	25,378	15,039
Geometric mean bacteria concentration	cfu/100 mL	817	1,580	2,796	2,724	2,386	2,082	2,377
Maximum bacteria concentration	cfu/100 mL	910	93,410	2,170,030	2,698,312	2,591,125	3,558,091	3,321,682
Percentage of base case average concentration	%	5	28	61	100	131	167	99
Simulation results for summer flows								
Number of summer values	hours	79,488	79,488	79,488	79,488	79,488	79,488	79,488
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	0.1	0.1	0.1	0.1	0.2	0.3	0.2
Average bacteria concentration	cfu/100 mL	870	1,055	1,730	1,997	2,648	2,705	2,195
Geometric mean bacteria concentration	cfu/100 mL	870	914	1,019	1,052	1,066	1,076	1,013
Maximum bacteria concentration	cfu/100 mL	922	80,909	86,299	787,116	2,396,785	1,908,209	2,133,113
Percentage of base case average concentration	%	44	53	87	100	133	135	110

Table 15B. Summary of 1988–2005 simulation results for precipitation scenarios at storm sample site D in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for storm flows								
Number of stormflow values	hours	0	2,024	11,283	19,939	26,809	31,731	17,503
Percentage of time flow occurred	%	0	1	7	13	17	20	11
Average streamflow	ft ³ /s	0.0	0.6	2.0	5.9	10.7	15.7	10.5
Maximum streamflow	ft ³ /s	0.0	2.5	243.5	1,139.0	1,967.3	2,788.7	1,961.1
Minimum streamflow	ft ³ /s	0.0	0.2	0.2	0.2	0.2	0.2	0.2
Average bacteria concentration	cfu/100 mL	0	55,213	39,279	49,524	54,601	60,846	56,746
Geometric mean bacteria concentration	cfu/100 mL	0	52,142	22,401	9,877	5,460	3,598	6,659
Maximum bacteria concentration	cfu/100 mL	0	93,410	2,170,030	2,698,312	2,591,125	3,558,091	3,321,682
Minimum bacteria concentration	cfu/100 mL	0	3,065	172	37	26	13	23
Percentage of base case average concentration	%	0	111	79	100	110	123	115
Simulation results for low flows								
Number of lowflow values	hours	157,800	155,776	146,516	137,861	130,991	126,068	140,297
Percentage of time flow occurred	%	100	99	93	87	83	80	89
Average streamflow	ft ³ /s	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Maximum streamflow	ft ³ /s	0.1	0.2	0.2	0.2	0.2	0.2	0.2
Minimum streamflow	ft ³ /s	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Average bacteria concentration	cfu/100 mL	844	1,953	2,873	2,625	2,323	2,155	2,559
Geometric mean bacteria concentration	cfu/100 mL	844	1,142	1,378	1,306	1,235	1,196	1,289
Maximum bacteria concentration	cfu/100 mL	922	58,477	62,581	74,825	67,289	67,603	61,104
Minimum bacteria concentration	cfu/100 mL	755	766	449	447	491	481	497
Percentage of base case average concentration	%	32	74	109	100	89	82	97

Table 15C. Summary of 1988–2005 simulation results for precipitation scenarios at Prado Lake outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for all flows								
Number of simulated values	hours	157,800	157,800	157,800	157,800	157,800	157,800	157,800
Percentage of time flow occurred	%	100	100	100	100	100	100	100
Average streamflow	ft³/s	21.1	21.1	21.4	22.7	25.0	27.9	23.6
Maximum streamflow	ft³/s	48.0	48.0	138.9	781.0	1,929.1	3,608.9	2,899.3
Minimum streamflow	ft³/s	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Average bacteria concentration	cfu/100 mL	0	5	78	1,397	3,230	5,004	2,033
Geometric mean bacteria concentration	cfu/100 mL	0	0	1	1	2	3	1
Maximum bacteria concentration	cfu/100 mL	0	499	73,118	255,855	281,167	273,166	269,068
Minimum bacteria concentration	cfu/100 mL	0	0	0	0	0	0	0
Percentage of base case average concentration	%	0	0	6	100	231	358	145
Simulation results for winter flows								
Number of winter values	hours	78,312	78,312	78,312	78,312	78,312	78,312	78,312
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	22.2	22.2	22.7	25.2	29.7	35.3	26.8
Average bacteria concentration	cfu/100 mL	0	9	152	2,793	6,119	9,534	3,601
Geometric mean bacteria concentration	cfu/100 mL	0	0	3	10	22	42	6
Maximum bacteria concentration	cfu/100 mL	0	499	73,118	255,855	281,167	273,166	269,068
Percentage of base case average concentration	%	0	0	5	100	219	341	129
Simulation results for summer flows								
Number of summer values	hours	79,488	79,488	79,488	79,488	79,488	79,488	79,488
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	20.1	20.1	20.1	20.2	20.4	20.7	20.5
Average bacteria concentration	cfu/100 mL	0	0	5	22	384	542	488
Geometric mean bacteria concentration	cfu/100 mL	0	0	0	0	0	0	0
Maximum bacteria concentration	cfu/100 mL	0	261	884	16,377	229,083	244,558	243,628
Percentage of base case average concentration	%	0	2	22	100	1,762	2,487	2,238

Table 15C. Summary of 1988–2005 simulation results for precipitation scenarios at Prado Lake outflow, in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	Variable dry-wet
Simulation results for storm flows								
Number of stormflow values	hours	0	0	219	2,020	3,967	6,036	2,283
Percentage of time flow occurred	%	0	0	0	1	3	4	1
Average streamflow	ft ³ /s	0.0	0.0	60.6	104.3	146.4	176.7	162.8
Maximum streamflow	ft ³ /s	0.0	0.0	138.9	781.0	1,929.1	3,608.9	2,899.3
Minimum streamflow	ft ³ /s	0.0	0.0	50.1	50.0	50.0	50.0	50.0
Average bacteria concentration	cfu/100 mL	0	0	12,156	73,321	89,553	90,720	94,018
Geometric mean bacteria concentration	cfu/100 mL	0	0	3,328	34,659	50,388	57,592	61,098
Maximum bacteria concentration	cfu/100 mL	0	0	73,118	255,855	281,167	273,166	269,068
Minimum bacteria concentration	cfu/100 mL	0	0	443	368	320	367	525
Percentage of base case average concentration	%	0	0	17	100	122	124	128
Simulation results for low flows								
Number of lowflow values	hours	157,800	157,800	157,581	155,780	153,833	151,764	155,517
Percentage of time flow occurred	%	100	100	100	99	97	96	99
Average streamflow	ft ³ /s	21.1	21.1	21.4	21.6	21.8	22.0	21.6
Maximum streamflow	ft ³ /s	48.0	48.0	50.0	50.0	50.0	50.0	50.0
Minimum streamflow	ft ³ /s	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Average bacteria concentration	cfu/100 mL	0	5	61	465	1,004	1,595	682
Geometric mean bacteria concentration	cfu/100 mL	0	0	1	1	2	2	1
Maximum bacteria concentration	cfu/100 mL	0	499	47,364	120,073	147,960	126,917	130,260
Minimum bacteria concentration	cfu/100 mL	0	0	0	0	0	0	0
Percentage of base case average concentration	%	0	1	13	100	216	343	147

Table 15D. Summary of 1988–2005 simulation results for precipitation scenarios at Chino Creek outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	Variable dry-wet
Simulation results for all flows								
Number of simulated values	hours	157,800	157,800	157,800	157,800	157,800	157,800	157,800
Percentage of time flow occurred	%	100	100	100	100	100	100	100
Average streamflow	ft³/s	48.0	48.9	55.3	68.7	94.2	131.3	79.9
Maximum streamflow	ft³/s	358.7	363.0	2,507.5	12,537.8	29,889.5	47,657.3	32,370.5
Minimum streamflow	ft³/s	16.6	16.6	16.6	16.6	16.7	16.7	16.7
Average bacteria concentration	cfu/100 mL	31	496	775	1,397	2,117	2,747	1,572
Geometric mean bacteria concentration	cfu/100 mL	30	55	74	93	120	159	94
Maximum bacteria concentration	cfu/100 mL	205	28,693	153,011	235,198	231,578	410,850	248,115
Minimum bacteria concentration	cfu/100 mL	7	7	8	8	8	9	8
Percentage of base case average concentration %	%	2	35	55	100	152	197	113
Simulation results for winter flows								
Number of winter values	hours	78,312	78,312	78,312	78,312	78,312	78,312	78,312
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	44.3	46.1	57.9	83.4	132.3	200.7	102.2
Average bacteria concentration	cfu/100 mL	32	891	1,381	2,592	3,851	5,048	2,767
Geometric mean bacteria concentration	cfu/100 mL	31	93	147	213	293	412	205
Maximum bacteria concentration	cfu/100 mL	190	28,693	153,011	235,198	231,578	410,850	248,115
Percentage of base case average concentration %	%	1	34	53	100	149	195	107
Simulation results for summer flows								
Number of summer values	hours	79,488	79,488	79,488	79,488	79,488	79,488	79,488
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft³/s	51.7	51.8	52.8	54.2	56.7	63.0	58.0
Average bacteria concentration	cfu/100 mL	30	107	178	220	409	480	394
Geometric mean bacteria concentration	cfu/100 mL	29	33	37	42	50	62	44
Maximum bacteria concentration	cfu/100 mL	205	26,883	26,645	30,736	135,433	167,523	135,406
Percentage of base case average concentration %	%	14	49	81	100	186	219	179

Table 15D. Summary of 1988–2005 simulation results for precipitation scenarios at Chino Creek outflow in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for storm flows								
Number of stormflow values	hours	10,114	10,769	14,473	17,066	19,645	22,745	16,335
Percentage of time flow occurred	%	6	7	9	11	12	14	10
Average streamflow	ft³/s	151.8	150.8	187.7	286.5	457.5	654.8	406.7
Maximum streamflow	ft³/s	358.7	363.0	2,507.5	12,537.8	29,889.5	47,657.3	32,370.5
Minimum streamflow	ft³/s	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Average bacteria concentration	cfu/100 mL	16	1,003	3,280	7,306	10,855	12,536	8,548
Geometric mean bacteria concentration	cfu/100 mL	16	26	118	280	559	899	254
Maximum bacteria concentration	cfu/100 mL	170	28,693	153,011	235,198	231,578	410,850	248,115
Minimum bacteria concentration	cfu/100 mL	7	7	9	9	9	9	9
Percentage of base case average concentration %	%	0	14	45	100	149	172	117
Simulation results for low flows								
Number of lowflow values	hours	147,686	47,031	143,327	140,734	138,155	135,055	141,465
Percentage of time flow occurred	%	94	93	91	89	88	86	90
Average streamflow	ft³/s	40.9	41.5	41.9	42.3	42.6	43.2	42.2
Maximum streamflow	ft³/s	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Minimum streamflow	ft³/s	16.6	16.6	16.6	16.6	16.7	16.7	16.7
Average bacteria concentration	cfu/100 mL	32	459	522	680	875	1,099	766
Geometric mean bacteria concentration	cfu/100 mL	32	58	70	82	97	119	84
Maximum bacteria concentration	cfu/100 mL	205	27,143	29,572	70,926	66,793	71,450	70,199
Minimum bacteria concentration	cfu/100 mL	8	8	8	8	8	9	8
Percentage of base case average concentration %	%	5	67	77	100	129	161	113

Table 15E. Summary of 1988–2005 simulation results for precipitation scenarios at sample site CCM1 in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation					Variable dry-wet	
		X 0.	X 0.1	X 0.5	Base case	X 1.5		X 2.0
Simulation results for all flows								
Number of simulated values	hours	0	30,463	106,352	152,974	157,800	157,800	114,465
Percentage of time flow occurred	%	0	19	67	97	100	100	73
Average streamflow	ft ³ /s	0.0	0.0	2.8	10.3	21.2	33.4	15.3
Maximum streamflow	ft ³ /s	0.0	0.3	1,844.8	5,094.0	8,320.7	11,642.6	9,488.9
Minimum streamflow	ft ³ /s	0.0	0.0	0.0	0.0	0.0	0.3	0.0
Average bacteria concentration	cfu/100 mL	0	119	23	6	6	6	14
Geometric mean bacteria concentration	cfu/100 mL	0	41	4	3	3	3	4
Maximum bacteria concentration	cfu/100 mL	0	3,057	13,442	421	321	303	6,168
Minimum bacteria concentration	cfu/100 mL	0	0	0	0	0	0	0
Percentage of base case average concentration	%	0	1,924	380	100	90	93	222
Simulation results for winter flows								
Number of winter values	hours	0	29,359	68,704	77,563	78,312	78,312	64,859
Percentage of time flow occurred	%	0	19	44	49	50	50	41
Average streamflow	ft ³ /s	0.0	0.0	4.0	18.6	38.5	60.4	23.1
Average bacteria concentration	cfu/100 mL	0	110	31	10	9	9	20
Geometric mean bacteria concentration	cfu/100 mL	0	38	7	4	4	4	6
Maximum bacteria concentration	cfu/100 mL	0	2,927	1,720	421	321	303	1,305
Percentage of base case average concentration	%	0	1,115	313	100	88	91	205
Simulation results for summer flows								
Number of summer values	hours	0	1,104	37,648	75,411	79,488	79,488	49,606
Percentage of time flow occurred	%	0	1	24	48	50	50	31
Average streamflow	ft ³ /s	0.0	0.0	0.5	1.8	4.1	6.7	5.1
Average bacteria concentration	cfu/100 mL	0	358	10	2	2	3	5
Geometric mean bacteria concentration	cfu/100 mL	0	222	1	2	2	2	2
Maximum bacteria concentration	cfu/100 mL	0	3,057	13,442	281	168	173	6,168
Percentage of base case average concentration	%	0	14,928	422	100	103	107	221

Table 15E. Summary of 1988–2005 simulation results for precipitation scenarios at sample site CCM1 in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation					Variable dry-wet	
		X 0.	X 0.1	X 0.5	Base case	X 1.5		X 2.0
Simulation results for storm flows								
Number of stormflow values	hours	0	0	2,470	9,693	18,123	25,914	9,320
Percentage of time flow occurred	%	0	0	2	6	11	16	6
Average streamflow	ft³/s	0.0	0.0	89.3	139.2	162.4	183.0	168.5
Maximum streamflow	ft³/s	0.0	0.0	1,844.8	5,094.0	8,320.7	11,642.6	9,488.9
Minimum streamflow	ft³/s	0.0	0.0	15.0	15.0	15.0	15.0	15.0
Average bacteria concentration	cfu/100 mL	0	0	34	23	20	18	21
Geometric mean bacteria concentration	cfu/100 mL	0	0	14	9	8	8	9
Maximum bacteria concentration	cfu/100 mL	0	0	199	241	321	303	317
Minimum bacteria concentration	cfu/100 mL	0	0	2	0	0	0	0
Percentage of base case average concentration	%	0	0	148	100	86	78	90
Simulation results for low flows								
Number of lowflow values	hours	0	30,463	103,882	143,281	139,677	131,886	105,145
Percentage of time flow occurred	%	0	19	66	91	89	84	67
Average streamflow	ft³/s	0.0	0.0	0.7	1.6	2.9	4.0	1.7
Maximum streamflow	ft³/s	0.0	0.3	15.0	15.0	15.0	15.0	15.0
Minimum streamflow	ft³/s	0.0	0.0	0.0	0.0	0.0	0.3	0.0
Average bacteria concentration	cfu/100 mL	0	119	23	5	4	3	13
Geometric mean bacteria concentration	cfu/100 mL	0	41	4	3	3	3	3
Maximum bacteria concentration	cfu/100 mL	0	3,057	13,442	421	170	148	6,168
Minimum bacteria concentration	cfu/100 mL	0	0	0	0	1	1	0
Percentage of base case average concentration	%	0	2,350	459	100	73	67	260

Table 15F: Summary of 1988–2005 simulation results for precipitation scenarios at sample site CCM2 in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for all flows								
Number of simulated values	hours	157,800	157,800	157,800	157,800	157,800	157,800	157,800
Percentage of time flow occurred	%	100	100	100	100	100	100	100
Average streamflow	ft ³ /s	0.4	0.8	6.8	24.0	49.7	82.2	29.6
Maximum streamflow	ft ³ /s	0.5	225.0	3,635.1	12,211.3	26,260.8	34,070.4	23,739.7
Minimum streamflow	ft ³ /s	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Average bacteria concentration	cfu/100 mL	1,159	10,545	9,516	7,713	6,795	6,471	9,212
Geometric mean bacteria concentration	cfu/100 mL	1,156	2,345	2,546	2,185	1,943	1,778	2,325
Maximum bacteria concentration	cfu/100 mL	1,392	163,519	156,489	195,891	176,667	185,158	182,654
Minimum bacteria concentration	cfu/100 mL	1,019	1,023	30	17	11	1	8
Percentage of base case average concentration	%	15	137	123	100	88	84	119
Simulation results for winter flows								
Number of winter values	hours	78,312	78,312	78,312	78,312	78,312	78,312	78,312
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft ³ /s	0.4	1.2	12.5	45.1	93.8	155.4	53.0
Average bacteria concentration	cfu/100 mL	1,106	17,988	14,949	10,783	8,726	7,700	14,314
Geometric mean bacteria concentration	cfu/100 mL	1,105	3,938	4,044	2,848	2,140	1,681	3,318
Maximum bacteria concentration	cfu/100 mL	1,329	163,519	156,489	148,239	148,955	146,042	166,648
Percentage of base case average concentration	%	10	167	139	100	81	71	133
Simulation results for summer flows								
Number of summer values	hours	79,488	79,488	79,488	79,488	79,488	79,488	79,488
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft ³ /s	0.3	0.4	1.2	3.3	6.3	10.2	6.6
Average bacteria concentration	cfu/100 mL	1,211	3,212	4,164	4,688	4,892	5,260	4,185
Geometric mean bacteria concentration	cfu/100 mL	1,210	1,407	1,614	1,682	1,766	1,879	1,637
Maximum bacteria concentration	cfu/100 mL	1,392	155,663	148,223	195,891	176,667	185,158	182,654
Percentage of base case average concentration	%	26	69	89	100	104	112	89

Table 15F. Summary of 1988-2005 simulation results for precipitation scenarios at sample site CCM2 in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Precipitation						
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	Variable dry-wet
Simulation results for storm flows								
Number of stormflow values	hours	0	1,564	6,685	11,445	16,891	22,627	11,087
Percentage of time flow occurred	%	0	1	4	7	11	14	7
Average streamflow	ft ³ /s	0.0	28.4	147.1	322.3	457.5	568.3	412.7
Maximum streamflow	ft ³ /s	0.0	225.0	3,635.1	12,211.3	26,260.8	34,070.4	23,739.7
Minimum streamflow	ft ³ /s	0.0	10.0	10.0	10.0	10.0	10.0	10.0
Average bacteria concentration	cfu/100 mL	0	61,582	23,893	12,596	8,089	5,866	13,781
Geometric mean bacteria concentration	cfu/100 mL	0	52,257	10,292	3,082	1,483	878	2,369
Maximum bacteria concentration	cfu/100 mL	0	139,745	138,868	128,988	128,642	123,943	150,865
Minimum bacteria concentration	cfu/100 mL	0	5,763	30	17	11	1	8
Percentage of base case average concentration	%	0	489	190	100	64	47	109
Simulation results for low flows								
Number of lowflow values	hours	157,800	156,236	151,115	146,355	140,909	135,173	146,713
Percentage of time flow occurred	%	100	99	96	93	89	86	93
Average streamflow	ft ³ /s	0.4	0.5	0.6	0.7	0.8	0.9	0.7
Maximum streamflow	ft ³ /s	0.5	10.0	10.0	10.0	10.0	10.0	10.0
Minimum streamflow	ft ³ /s	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Average bacteria concentration	cfu/100 mL	1,159	10,034	8,880	7,331	6,639	6,572	8,867
Geometric mean bacteria concentration	cfu/100 mL	1,156	2,273	2,393	2,127	2,007	2,001	2,321
Maximum bacteria concentration	cfu/100 mL	1,392	163,519	156,489	195,891	176,667	185,158	182,654
Minimum bacteria concentration	cfu/100 mL	1,019	1,023	159	106	97	95	95
Percentage of base case average concentration	%	16	137	121	100	91	90	121

Table 15G. Summary of 1988–2005 simulation results for precipitation scenarios at Mill Creek outflow in the Chino Basin, California.

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for all flows								
Number of simulated values	hours	157,800	157,800	157,800	157,800	157,800	157,800	157,800
Percentage of time flow occurred	%	100	100	100	100	100	100	100
Average streamflow	ft ³ /s	24.7	25.3	32.3	51.7	81.3	119.4	58.6
Maximum streamflow	ft ³ /s	55.7	238.8	3,904.4	13,896.2	22,711.6	38,264.4	21,132.3
Minimum streamflow	ft ³ /s	8.0	8.0	8.4	8.5	8.7	9.0	8.0
Average bacteria concentration	cfu/100 mL	22	685	1,100	1,111	1,286	1,518	1,280
Geometric mean bacteria concentration	cfu/100 mL	22	52	73	77	81	85	77
Maximum bacteria concentration	cfu/100 mL	41	31,649	31,758	333,188	1,056,093	923,047	1,218,728
Minimum bacteria concentration	cfu/100 mL	13	13	13	13	13	4	11
Percentage of base case average concentration	%	2	62	99	100	116	137	115
Simulation results for winter flows								
Number of winter values	hours	78,312	78,312	78,312	78,312	78,312	78,312	78,312
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft ³ /s	25.3	26.2	39.6	76.3	132.6	204.9	86.6
Average bacteria concentration	cfu/100 mL	23	1,259	1,965	1,948	2,261	2,682	2,306
Geometric mean bacteria concentration	cfu/100 mL	22	106	174	178	182	185	184
Maximum bacteria concentration	cfu/100 mL	39	31,649	31,758	333,188	1,056,093	923,047	1,218,728
Percentage of base case average concentration	%	1	65	101	100	116	138	118
Simulation results for summer flows								
Number of summer values	hours	79,488	79,488	79,488	79,488	79,488	79,488	79,488
Percentage of time flow occurred	%	50	50	50	50	50	50	50
Average streamflow	ft ³ /s	24.2	24.3	25.2	27.5	30.8	35.1	31.1
Average bacteria concentration	cfu/100 mL	22	120	248	287	325	371	268
Geometric mean bacteria concentration	cfu/100 mL	22	26	31	34	36	40	33
Maximum bacteria concentration	cfu/100 mL	41	22,290	23,167	26,269	27,609	133,493	127,602
Percentage of base case average concentration	%	8	42	86	100	113	129	93

Table 156. Summary of 1988–2005 simulation results for precipitation scenarios at Mill Creek outflow in the Chino Basin, California.—Continued

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Simulated parameter	Units	Precipitation						Variable dry-wet
		X 0.	X 0.1	X 0.5	Base case	X 1.5	X 2.0	
Simulation results for storm flows								
Number of stormflow values	hours	0	424	4,510	8,002	10,966	13,897	6,980
Percentage of time flow occurred	%	0	0	3	5	7	9	4
Average streamflow	ft³/s	0.0	97.3	263.4	535.8	816.9	1,076.6	771.1
Maximum streamflow	ft³/s	0.0	238.8	3,904.4	13,896.2	22,711.6	38,264.4	21,132.3
Minimum streamflow	ft³/s	0.0	70.0	70.0	70.0	70.0	70.0	70.0
Average bacteria concentration	cfu/100 mL	0	16,321	9,458	8,326	10,102	11,354	11,750
Geometric mean bacteria concentration	cfu/100 mL	0	15,520	6,275	3,531	2,992	2,194	3,332
Maximum bacteria concentration	cfu/100 mL	0	25,516	31,758	333,188	1,056,093	923,047	1,218,728
Minimum bacteria concentration	cfu/100 mL	0	6,983	71	17	14	4	11
Percentage of base case average concentration	%	0	196	114	100	121	136	141
Simulation results for low flows								
Number of lowflow values	hours	157,800	157,376	153,290	149,798	146,834	143,903	150,820
Percentage of time flow occurred	%	100	100	97	95	93	91	96
Average streamflow	ft³/s	24.7	25.1	25.5	25.9	26.4	26.9	25.7
Maximum streamflow	ft³/s	55.7	70.0	70.0	70.0	70.0	70.0	70.0
Minimum streamflow	ft³/s	8.0	8.0	8.4	8.5	8.7	9.0	8.0
Average bacteria concentration	cfu/100 mL	22	643	854	726	627	568	795
Geometric mean bacteria concentration	cfu/100 mL	22	51	64	63	62	62	65
Maximum bacteria concentration	cfu/100 mL	41	31,649	30,059	25,368	26,153	35,958	29,917
Minimum bacteria concentration	cfu/100 mL	13	13	13	13	13	13	13
Percentage of base case average concentration	%	3	89	118	100	86	78	110

Figure 25. Simulated air temperature scenarios for water-years 1988–2005 at upper San Antonio Canyon in the Chino Basin: *A*, monthly snow pack, *B*, monthly streamflow, and *C*, monthly bacteria concentration.

Simulation results obtained for the outflow at San Antonio Dam indicated a different relationship between air temperature, streamflow, and bacteria concentrations. The increased air temperature scenario resulted in higher peak flows, higher average flows, and higher bacteria concentrations, whereas the lower air temperature scenario resulted in lower peak flows, lower average flows, and lower bacteria concentrations (table 14). The results for the 1988–2005 base case simulation included an average simulated streamflow of 25.9 ft³/s, a maximum streamflow of 1,314 ft³/s, an average bacteria concentration of 121 cfu/100 mL, and a maximum bacteria

concentration of 2,385 cfu/100 mL. In comparison, results for the increased air temperature scenario included an average streamflow of 49.4 ft³/s, a maximum streamflow of 2,055 ft³/s, an average bacteria concentration of 183 cfu/100 mL, and a maximum bacteria concentration of 3,666 cfu/100 mL. Results for the decreased air temperature scenario included an average streamflow of 22.1 ft³/s, a maximum streamflow of 445 ft³/s, an average bacteria concentration of 89 cfu/100 mL, and a maximum bacteria concentration of 2,020 cfu/100 mL.

B **Figure 25.** Continued.

The flow duration curves for simulated hourly outflow from San Antonio Dam (based on hourly results for the 1988–2005 simulation period) at temperatures 5 degrees above and below a baseline air temperature—the two air temperature scenarios—were plotted and compared with the baseline curve. The flow duration analysis indicated that increasing air temperature increased the percentage of time that flows were approximately 100 ft^3/s and greater (fig. 26A) and decreased the percentage of time that smaller flows were less than about 100 ft^3/s . Analysis of the decreased air temperature scenario

indicated the opposite results: a decrease in the percentage of time that flows were greater than about 200 ft^3/s and an increase in the percentage of time (or number of hours) that flows were 60 ft^3/s or less. The maximum streamflow simulated for the base case was approximately 1,000 ft^3/s ; increasing the air temperature increased the maximum streamflow to about 1,800 ft^3/s and decreasing the air temperature decreased maximum streamflow to only 400 ft^3/s .

Figure 25. Continued.

The concentration duration analysis of simulated hourly fecal coliform concentrations indicated variations caused by changes in air temperature similar to those of simulated streamflow ([fig. 26B](#)). Comparison of concentration durations (percentage of time hourly bacteria concentrations were exceeded) for the increased air temperature scenario and the base case simulation showed a relative difference similar to those for streamflow. Concentration durations for bacteria concentrations of about 200 cfu/100 mL and higher were increased relative to the base case, whereas concentration durations for the low concentrations (about 100 cfu/100 mL

and less) were decreased relative to the base case. The results for the decreased air temperature scenario were more similar to the base-case results, with a small decrease in the percentage of time bacteria concentrations were exceeded for concentrations of about 400 cfu/100 mL and higher. The increased air temperature scenario indicated that bacteria concentrations of 200 cfu/100 mL and higher occurred about 3 percent of the time, compared with about 2 percent of the time for the base case and decreased air temperature simulations.

Figure 26. Simulated air-temperature scenarios at San Antonio Dam outflow in the Chino Basin during water-years 1988–2005: *A*, flow duration for hourly streamflow and *B*, concentration duration for hourly bacteria concentrations.

The effects of temperature change on Mill Creek outflow were also analyzed. Although changing the air temperature scenarios significantly affected the results obtained for the San Antonio Canyon subbasin and in the northern part of the Mill Creek subbasin (sample site CCM1), only a small effect was observed in simulation results for Mill Creek outflow ([table 14B](#)). The increased air temperature scenario caused

a slight increase in average and maximum streamflow, but a slight decrease in average and maximum bacteria concentrations. The decrease in bacteria concentrations was caused by a shift in the timing of peak bacteria concentrations in the outflow from upstream drainages in the San Gabriel Mountains.

Figure 26. Continued.

Results of Precipitation Scenarios

Simulated hourly streamflow flow-duration curves for all precipitation scenarios at San Antonio Dam outflow, Chino Creek outflow, and Prado Park Lake outflow are shown in [figure 27](#). Flow duration curves representing the eight precipitation scenarios for the simulated 1988–2005 hourly outflow at San Antonio Dam were compared with the base case (current climate) results ([fig. 27A](#)). As expected, changes in precipitation caused significant changes in simulated outflow. Doubling precipitation increased the maximum mean hourly outflow by four times at San Antonio Dam; halving precipitation reduced the outflow to about one-tenth the rate of the base outflow.

Results for Chino Creek outflow indicated similar results in terms of sensitivity to precipitation ([fig. 27B](#)). However, flow-duration analysis indicated that the peak flows for Chino Creek outflow were the most sensitive to changes in precipitation; flows less than about 300 ft³/s were less sensitive because these flows were strongly controlled by wastewater effluent and OCWD water deliveries in Chino Creek. For example, the percent exceedance for zero precipitation closely matches the percent exceedance for the 0.1 × precipitation scenario because these simulations are dominated by the inflows of wastewater effluent and water deliveries.

Figure 27. Flow duration of simulated hourly streamflow for precipitation scenarios for water-years 1988–2005 at *A*, San Antonio Dam outflow, *B*, Prado Park Lake outflow (sample site PPOC), and *C*, Chino Creek outflow in the Chino Basin, California.

A summary of results for precipitation scenarios at 7 locations is provided in [table 15](#). The simulation results are summarized for all flows, winter flows, summer flows, storm flows, and low flows. At San Antonio Dam outflow, there is no outflow from the Dam and thus no bacteria transport for the 0 scale factor and the $0.1 \times$ precipitation scenarios ([table 15A](#)). The $0.5 \times$ precipitation scenario resulted in an average outflow of 5.6 ft³/s, with outflow from the dam occurring 5 percent of time. The base case simulation yielded an average outflow of 25.9 ft³/s, with outflow occurring 46 percent of the time. Maximum outflow for the $2.0 \times$ precipitation scenario was

7,243 ft³/s, compared with a maximum outflow of 1,314 ft³/s for the base case. The maximum simulated bacteria concentration was 3,119 cfu/100 mL for the variable dry/wet precipitation scenario. With the exception of the $2.0 \times$ precipitation scenario, maximum bacteria concentrations occurred during low flow conditions for all other scenarios.

Results for sample site D indicate low sensitivity of maximum simulated bacteria concentration to the various precipitation scenarios ([table 15B](#)). The maximum concentrations occur during storm and winter flow conditions in all

Figure 27. Continued.

cases. Average bacteria concentrations show higher sensitivity and increase from a minimum of 844 cfu/100 mL for the 0 x precipitation scenario (representing only nuisance flow) to a maximum of 13,597 cfu/100 mL for the 2.0 x precipitation scenario. Simulated average streamflow ranges from a minimum of 0.1 ft³/s (nuisance flow only) to a maximum of 3.2 ft³/s for the 2.0 x precipitation scenario. The maximum simulated bacteria concentrations at this site are higher than at all other locations simulated for the Chino Basin. The maximum bacteria concentration of 3,559,091 cfu/100 mL was simulated for the 2.0 x precipitation scenario, higher than the maximums of 2,698,312 cfu/100 mL for the base case and 922 cfu/100 mL for nuisance flow.

Relative differences and responses to increased and decreased precipitation for Prado Park Lake outflow were similar to those for sample site D, but the average and maximum concentrations were much lower than site D because of dilution and die-off processes affecting Prado Park Lake (table 15C). Results of the simulations for this site indicated a strong positive correlation between simulated bacteria concentrations and simulated streamflow (not included in table), and average bacteria concentrations for storm flows were much higher than those for low flows.

Figure 27. Continued.

Results for Chino Creek outflow also indicated a consistent trend of increasing streamflow and increasing average bacteria concentration with increased precipitation (table 15D). However, results for sites CCM1, CCM2, and Mill Creek outflow indicated a more complex response to the various precipitation scenarios. Sample site CCM1 indicated the expected increase in average and maximum streamflow with increasing precipitation, but the average bacteria concentration was highest for the 0.1 x precipitation climate scenario, and the maximum hourly concentration was highest for the 0.5 x precipitation scenario (table 15E). At CCM2, the average bacteria concentration of 10,545 cfu/100 mL was also highest for the 0.1 x precipitation scenario, and the maximum hourly concentration of 195,891 cfu/100 mL was highest for the base

case scenario (prec. x 1.0; table 15F). At Mill Creek outflow, the variation in average bacteria concentrations in response to the different precipitation scenarios was low relative to the other sites, especially for 0.5 x precipitation and wetter scenarios (table 15G).

For most locations and for most scenarios that receive precipitation greater than zero, average simulated bacteria concentrations for winter were greater than average concentrations for summer. Maximum concentrations tended to occur during winter and during storm flows. Average hourly simulated bacteria concentrations during storm flows tended to be greater than average concentrations during low flows. The geometric mean of the hourly concentration was considerably

less than the average concentration by as much as an order of magnitude or greater. For all flows at most sites, the average simulated concentration exceeded 200 cfu/100 mL, whereas the geometric mean concentration was less than 200 cfu/100 mL. The highest geometric mean concentrations occurred at sites where nuisance flow is the dominant component of low flow.

Simulated bacteria concentrations tended to increase with increasing precipitation at most sites. Maximum hourly bacteria concentrations often occurred for the variable dry/wet precipitation scenario. Exceptions to these patterns are results for San Antonio Dam outflow, CCM1, and CCM2, where maximum concentrations occur for the 0.1 $\times$ precipitation and the 0.5 $\times$ precipitation scenarios and increasing precipitation resulted in decreasing concentrations. The overall results illustrate the importance of location and upstream land use on the bacteria transport response to the various climate scenarios.

The concentration duration curves for the various precipitation scenarios at San Antonio Dam outflow indicate a complex relation between precipitation and the distribution of bacteria concentration (fig. 28A). Most of the scenarios resulted in a decrease in the frequency of maximum concentrations relative to the base case simulation. The 0.5 $\times$ precipitation scenario produced higher concentrations than the base case at exceedances of 0.1 and less (0.1 percent of the time the base case bacteria concentration was exceeded). The 200 cfu/100 mL concentration was exceeded only 2 percent of the time for the 0.5 $\times$ precipitation scenario, compared with about 9 percent for the base case model. The greatest increase in maximum bacteria concentrations resulted from the variable precipitation scenario; maximum concentrations were higher than those for the base case about 0.2 percent of the time and less.

Simulated bacteria concentrations were highly sensitive to the various precipitation scenarios at Prado Park Lake outflow (fig. 28B), but less sensitive at Chino Creek outflow (fig. 28C). At Prado Park Lake outflow, simulated bacteria concentrations affected by 2.0 times the base case precipitation were 3,000 cfu/100 mL or higher 10 percent of the time, compared with about 3 percent of the time for the base case. The 200 cfu/100 mL concentration was exceeded about 0.7 percent of the time for the 0.1 $\times$ precipitation scenario, 7 percent of the time for the 0.5 $\times$ precipitation scenario, about 12 percent of the time for the base case simulation, and about 20 percent of the time for the 2.0 $\times$ precipitation scenario. The relatively high sensitivity of bacteria concentrations to all precipitation scenarios for recurrence probabilities greater than 1 percent was caused by the response of pervious areas in the agricultural land uses. The higher fraction of pervious areas resulted in a higher fraction of upstream area with high loading rates and washoff limits.

Results for the precipitation scenarios at Chino Creek outflow indicated high sensitivity to scenarios drier than that for the base case, but low sensitivity (compared with that for Prado Park Lake outflow) to the scenarios wetter (fig. 28C).

Maximum bacteria concentrations were similar for the 0.8 $\times$ precipitation and wetter scenarios relative to the base case simulation at exceedances of about 0.4 percent and less. To compare the effects of precipitation and stormflow with baseflow only (nuisance flow, wastewater effluent, and Orange County water deliveries), the 0 $\times$ precipitation scenario (zero precipitation) was included in the concentration-duration analysis. Hourly bacteria concentrations derived from the no precipitation (baseflow only) scenario did not exceed the 200 cfu/100 mL level because the wastewater discharges and Orange County water deliveries dilute the contaminated nuisance flows. The 0.1 $\times$ precipitation scenario, which represents extremely dry conditions, caused a very large increase in the maximum simulated concentrations compared to the base case; the 200 cfu/100 mL level was exceeded 15 percent of the time, compared to about 25 percent of the time for the base case. Maximum concentrations were about 30,000 cfu/100 mL for both the 0.1 and 0.5 $\times$ precipitation scenarios. Maximum concentration increased to about 120,000 cfu/100 mL for the 0.8 $\times$ precipitation scenario. The simulated bacteria concentrations for the drier precipitation scenarios were very sensitive because impervious areas respond quickly to small changes in precipitation during drier conditions; bacteria washoff is initiated in response to small amounts of precipitation because of the lower washoff limits calibrated for the impervious areas. Under the wetter scenarios, the bacteria loading rates for the various land uses limited maximum concentrations, and this reduced sensitivity to the higher precipitation amounts.

Land-Use Scenarios

Land-use scenarios were used to evaluate the potential effect of land-use changes on basin hydrology and bacteria loading and transport.

Development

Six different land-use scenarios were developed for comparison with the base case condition. The first land-use scenario (identified as land use scenario 0) was defined by setting the bacteria loading for nuisance flows to zero (nuisance flow was simulated as pristine water). The remaining five land-use scenarios were defined by modifying the areas (in acres) of specific land uses contributing to each model reach segment, in addition to setting bacteria loading for nuisance flows to zero. Using uncontaminated nuisance flow allowed a more direct comparison of the effects of the five different land-use changes for all flows because contaminated nuisance flow tended to dominate concentrations simulated for the lower flows.

Figure 28. Concentration duration of simulated hourly bacteria concentration for precipitation scenarios for water-years 1988–2005 at *A*, San Antonio Dam outflow, *B*, Prado Park Lake outflow (sample site PPOC), and *C*, Chino Creek outflow in the Chino Basin, California.

The land-use modifications were based on the assumptions that residential and recreation and open space land uses would likely increase as mixed agriculture land use (including intensive livestock) and barren or vacant areas decrease. The assumption of increased residential land use was based on recent and projected trends in population growth (Rice, 2005). The assumption of a decrease in mixed agriculture land use, particularly intensive livestock, is supported by recent changes in land use observed in the Chino Basin. Although some increases in commercial and services, industrial, and transportation and utilities land uses are likely with increased population, these changes were not considered in this study. The estimated bacteria loading rate for residential land use was higher than those for all of the other urban land uses and

represented an upper bound for the effect of expanding urban areas. The estimated bacteria loading rate for recreation and open-space land use was lower than those for the other urban land uses and represented a lower bound for the effect of increased urbanization at the expense of barren or vacant and mixed agriculture land uses.

Land-use scenario 1 was defined by converting the areas of the barren or vacant land use to the residential land use for each model reach segment (barren or vacant areas in mountainous terrain were not converted to residential). The barren or vacant land-use areas were set to zero. Land-use scenario 2 was defined by converting the intensive livestock land-use area to the residential areas for each model reach segment and setting the area of intensive livestock to zero. All

Figure 28. Continued.

land-use areas designated as intensive livestock were set to zero. Land-use scenario 3 was defined by converting all mixed agriculture land-use areas to residential and setting the area of mixed agricultural land use to zero. Land-use scenario 4 was defined by converting barren or vacant areas (excluding barren mountainous areas), intensive livestock, and mixed agriculture land uses to residential. Thus, land-use scenario 4 was defined by combining modifications of land-use scenarios 1 through 3. Land-use scenario 4 represents the full expansion of the residential land use into the likely areas for population growth in the Chino Basin area. Land-use scenario 5 was defined by converting barren or vacant areas (excluding barren mountainous areas), intensive livestock, and mixed agriculture land uses to recreation and open space land uses.

By converting the various land-use areas to residential or recreation and open space land use, the balance between pervious and impervious areas was also modified to preserve the ratio of pervious to impervious areas defined for the different land uses. This resulted in a decrease in pervious area and an increase in impervious area for land-use scenarios 1 through 4. Land-use scenario 1 (converting barren or vacant to residential) resulted in an increase in the estimated non-point source bacteria accumulation and storage terms relative to the base case, whereas land-use scenarios 2, 3, 4, and 5 all resulted in a decrease in the estimated non-point source bacteria accumulation and storage terms relative to the base case.

Figure 28. Continued.

Results of Land-Use Scenarios

Simulation results for the various land-use scenarios were evaluated and compared to the base case result for four locations throughout the Chino Basin study area: (1) sample site D, (2) Prado Park Lake outflow, (3) Chino Creek outflow, and (4) Mill Creek outflow ([table 16](#)). The greatest differences between the various land-use scenarios resulted from simulating sample site D ([table 16A](#)) and Prado Park Lake outflow

([table 16B](#)); the smallest differences occurred at Mill Creek outflow ([table 16D](#)). Sample site D and Prado Park Lake outflow were the most sensitive because the amount of upstream land area affected by the land-use changes was greatest for the Prado Basin subwatershed, which includes the Euclid Avenue subwatershed upstream of sample site D.

Table 16A. Summary of 1988–2005 simulation results for six land use scenarios for sample site D in the Chino Basin, California.

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Simulated parameter	Units	Base case	Land use scenarios				
			0	1	2	3	4
Simulation results for all flows							
Average streamflow	ft ³ /s	0.8	0.8	1.0	1.1	1.4	0.8
Maximum streamflow	ft ³ /s	1,139	1,139	1,140	1,126	1,126	1,139
Minimum streamflow	ft ³ /s	0.02	0.02	0.02	0.02	0.02	0.02
Average bacteria concentration	cfu/100 mL	8,551	7,807	2,677	5,418	2,302	708
Geometric mean bacteria concentration	cfu/100 mL	1,687	0.23	0.15	0.22	0.17	0.06
Maximum bacteria concentration	cfu/100 mL	2,698,312	2,686,745	579,616	1,853,706	144,945	100,569
Minimum bacteria concentration	cfu/100 mL	37	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	91	31	63	27	8
Simulation results for winter flows							
Average streamflow	ft ³ /s	1.5	1.5	2.0	2.1	2.6	1.6
Average bacteria concentration	cfu/100 mL	15,203	14,508	4,838	9,946	4,039	1,292
Geometric mean bacteria concentration	cfu/100 mL	2,724	67	37	63	44	10
Maximum bacteria concentration	cfu/100 mL	2,698,312	2,686,745	579,616	1,853,706	144,945	100,569
Percentage of base case average concentration	%	100	96	32	65	27	8
Simulation results for summer flows							
Average streamflow	ft ³ /s	0.1	0.1	0.1	0.1	0.2	0.1
Average bacteria concentration	cfu/100 mL	1,997	1,142	547	957	590	133
Geometric mean bacteria concentration	cfu/100 mL	1,052	0	0	0	0	0
Maximum bacteria concentration	cfu/100 mL	787,116	787,091	162,690	386,946	46,653	36,773
Percentage of base case average concentration	%	100	57	27	48	30	7

Table 16A. Summary of 1988–2005 simulation results for six land use scenarios for sample site D in the Chino Basin, California.—Continued

[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent; bacteria refers to fecal bacteria. The reported significant figures do not imply a level of accuracy attributed to the simulation results]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for storm flows								
Number of stormflow values	hours	19,939	19,939	19,988	22,172	21,958	22,924	20,191
Percentage of time flow occurred	%	13	13	13	14	14	15	13
Average streamflow	ft³/s	5.9	5.9	5.9	7.1	7.8	9.2	6.0
Maximum streamflow	ft³/s	1,139.0	1,139.0	1,139.1	1,140.3	1,125.8	1,126.4	1,138.8
Minimum streamflow	ft³/s	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Average bacteria concentration	cfu/100 mL	49,524	49,334	49,035	14,470	30,767	11,006	3,960
Geometric mean bacteria concentration	cfu/100 mL	9,877	7,707	7,710	3,989	7,449	4,303	1,074
Maximum bacteria concentration	cfu/100 mL	2,698,312	2,698,306	2,686,745	579,616	1,853,706	144,945	100,569
Minimum bacteria concentration	cfu/100 mL	37	2	2	2	1	1	1
Percentage of base case average concentration	%	100	100	99	29	62	22	8
Simulation results for low flows								
Number of lowflow values	hours	137,861	137,861	137,812	135,628	135,842	134,875	137,609
Percentage of time flow occurred	%	87	87	87	86	86	85	87
Average streamflow	ft³/s	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Maximum streamflow	ft³/s	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Minimum streamflow	ft³/s	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Average bacteria concentration	cfu/100 mL	2,625	1,801	1,791	749	1,321	822	231
Geometric mean bacteria concentration	cfu/100 mL	1,306	0	0	0	0	0	0
Maximum bacteria concentration	cfu/100 mL	74,825	74,247	74,328	27,509	46,975	25,819	10,100
Minimum bacteria concentration	cfu/100 mL	447	0	0	0	0	0	0
Percentage of base case average concentration	%	100	69	68	29	50	31	9

Table 16B. Summary of 1988–2005 simulation results for six land use scenarios at Prado Park Lake outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios				
		0	1	2	3	4	5
Simulation results for all flows							
Average streamflow	ft ³ /s	22.7	22.7	23.3	23.4	24.1	22.7
Maximum streamflow	ft ³ /s	781	785	816	826	865	784
Minimum streamflow	ft ³ /s	2.19	2.19	2.20	2.21	2.22	2.19
Average bacteria concentration	cfu/100 mL	1,397	1,400	354	1,147	146	47
Geometric mean bacteria concentration	cfu/100 mL	1.24	0.03	0.02	0.04	0.03	0.01
Maximum bacteria concentration	cfu/100 mL	255,855	256,010	59,474	202,758	14,747	6,952
Minimum bacteria concentration	cfu/100 mL	0.02	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration %	%	100	100	25	82	10	3
Simulation results for winter flows							
Average streamflow	ft ³ /s	25.2	25.2	26.3	26.6	27.8	25.3
Average bacteria concentration	cfu/100 mL	2,793	2,798	703	2,287	283	92
Geometric mean bacteria concentration	cfu/100 mL	10.5	2.6	2.0	3.8	2.5	0.3
Maximum bacteria concentration	cfu/100 mL	255,855	256,010	59,474	202,758	14,747	6,952
Percentage of base case average concentration %	%	100	100	25	82	10	3
Simulation results for summer flows							
Average streamflow	ft ³ /s	20.2	20.2	20.3	20.3	20.4	20.2
Average bacteria concentration	cfu/100 mL	22	22	10	24	11	2
Geometric mean bacteria concentration	cfu/100 mL	0.15	0.00	0.00	0.00	0.00	0.00
Maximum bacteria concentration	cfu/100 mL	16,377	16,459	4,823	14,739	2,578	735
Percentage of base case average concentration %	%	100	100	46	108	51	7

Table 16B. Summary of 1988–2005 simulation results for six land use scenarios at Prado Park Lake outflow in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for storm flows								
Number of stormflow values	hours	2,020	2,020	2,116	3,149	3,335	4,108	2,117
Percentage of time flow occurred	%	1.3	1.3	1.3	2.0	2.1	2.6	1.3
Average streamflow	ft³/s	104.3	104.3	103.5	101.6	103.8	112.9	103.5
Maximum streamflow	ft³/s	781.0	781.0	784.6	816.1	826.5	865.0	784.1
Minimum streamflow	ft³/s	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Average bacteria concentration	cfu/100 mL	73,321	73,320	70,105	11,436	36,288	2,858	2,109
Geometric mean bacteria concentration	cfu/100 mL	34,659	34,655	30,347	3,511	8,331	1,521	1,166
Maximum bacteria concentration	cfu/100 mL	255,855	255,854	256,010	59,474	202,758	14,747	6,952
Minimum bacteria concentration	cfu/100 mL	368	368	321	154	270	179	47
Percentage of base case average concentration	%	100	100	96	16	49	4	3
Simulation results for low flows								
Number of lowflow values	hours	155,780	155,780	155,684	154,651	154,465	153,692	155,683
Percentage of time flow occurred	%	99	99	99	98	98	97	99
Average streamflow	ft³/s	21.6	21.6	21.6	21.7	21.7	21.7	21.6
Maximum streamflow	ft³/s	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Minimum streamflow	ft³/s	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Average bacteria concentration	cfu/100 mL	465	464	466	128	388	73	19
Geometric mean bacteria concentration	cfu/100 mL	1.09	0.02	0.02	0.02	0.03	0.02	0.00
Maximum bacteria concentration	cfu/100 mL	120,073	120,072	120,084	27,714	97,802	7,777	3,368
Minimum bacteria concentration	cfu/100 mL	0	0	0	0	0	0	0
Percentage of base case average concentration	%	100	100	100	28	84	16	4

Table 16C. Summary of 1988–2005 simulation results for six land use scenarios at Chino Creek outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for all flows								
Average streamflow	ft ³ /s	68.7	68.7	70.9	69.8	71.2	74.2	69.1
Maximum streamflow	ft ³ /s	12,538	12,538	12,956	12,820	12,894	13,336	12,784
Minimum streamflow	ft ³ /s	16.64	16.64	16.66	16.71	16.71	16.76	16.66
Average bacteria concentration	cfu/100 mL	1,397	1,366	1,441	926	1,218	872	729
Geometric mean bacteria concentration	cfu/100 mL	93.49	1.07	1.12	0.93	1.12	1.00	0.69
Maximum bacteria concentration	cfu/100 mL	235,198	235,192	248,161	155,979	150,068	89,807	75,284
Minimum bacteria concentration	cfu/100 mL	7.62	0.00	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	98	103	66	87	62	52
Simulation results for winter flows								
Average streamflow	ft ³ /s	83.4	83.4	87.4	85.5	88.0	93.5	84.1
Average bacteria concentration	cfu/100 mL	2,592	2,561	2,695	1,681	2,258	1,551	1,294
Geometric mean bacteria concentration	cfu/100 mL	212.6	30.6	32.5	24.7	32.3	26.3	16.7
Maximum bacteria concentration	cfu/100 mL	235,198	235,192	248,161	155,979	150,068	89,807	75,284
Percentage of base case average concentration	%	100	99	104	65	87	60	50
Simulation results for summer flows								
Average streamflow	ft ³ /s	54.2	54.2	54.6	54.4	54.6	55.1	54.3
Average bacteria concentration	cfu/100 mL	220	189	206	182	193	203	173
Geometric mean bacteria concentration	cfu/100 mL	41.61	0.04	0.04	0.04	0.04	0.04	0.03
Maximum bacteria concentration	cfu/100 mL	30,736	30,730	35,693	26,958	25,489	29,286	25,171
Percentage of base case average concentration	%	100	86	94	83	88	93	79

Table 16C. Summary of 1988–2005 simulation results for six land use scenarios at Chino Creek outflow in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for storm flows								
Number of stormflow values	hours	17,066	17,066	17,293	17,297	17,435	17,784	17,125
Percentage of time flow occurred	%	11	11	11	11	11	11	11
Average streamflow	ft³/s	286.5	286.5	302.8	293.5	303.8	325.0	288.8
Maximum streamflow	ft³/s	12,538	12,538	12,956	12,820	12,894	13,336	12,784
Minimum streamflow	ft³/s	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Average bacteria concentration	cfu/100 mL	7,306	7,285	7,657	4,747	6,159	4,192	3,470
Geometric mean bacteria concentration	cfu/100 mL	280	23	26	21	25	24	16
Maximum bacteria concentration	cfu/100 mL	235,198	235,192	248,161	155,979	150,068	89,807	75,284
Minimum bacteria concentration	cfu/100 mL	9.17	0.00	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	100	105	65	84	57	47
Simulation results for low flows								
Number of lowflow values	hours	140,734	140,734	140,507	140,503	140,365	140,016	140,675
Percentage of time flow occurred	%	89	89	89	89	89	89	89
Average streamflow	ft³/s	42.3	42.3	42.3	42.3	42.3	42.3	42.3
Maximum streamflow	ft³/s	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Minimum streamflow	ft³/s	16.6	16.6	16.7	16.7	16.7	16.8	16.7
Average bacteria concentration	cfu/100 mL	680	648	676	456	605	450	396
Geometric mean bacteria concentration	cfu/100 mL	81.8	0.7	0.8	0.6	0.8	0.7	0.5
Maximum bacteria concentration	cfu/100 mL	70,926	70,906	70,780	25,849	56,550	29,149	24,797
Minimum bacteria concentration	cfu/100 mL	7.62	0.00	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	95	99	67	89	66	58

Table 16D. Summary of 1988–2005 simulation results for six land use scenarios at Mill Creek outflow in the Chino Basin, California.[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for all flows								
Average streamflow	ft³/s	51.7	51.7	53.4	52.4	52.6	54.9	51.0
Maximum streamflow	ft³/s	13,896	13,896	14,269	13,981	14,036	14,499	13,392
Minimum streamflow	ft³/s	8.49	8.49	8.49	8.67	8.68	8.88	8.46
Average bacteria concentration	cfu/100 mL	1,111	1,089	1,154	905	1,094	1,004	795
Geometric mean bacteria concentration	cfu/100 mL	77.16	0.67	0.71	0.59	0.11	0.61	0.54
Maximum bacteria concentration	cfu/100 mL	333,188	333,158	350,650	103,482	307,000	83,182	33,866
Minimum bacteria concentration	cfu/100 mL	12.52	0.00	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	98	104	81	98	90	71
Simulation results for winter flows								
Average streamflow	ft³/s	76.3	76.3	79.4	77.5	78.0	82.2	75.0
Average bacteria concentration	cfu/100 mL	1,948	1,925	2,031	1,573	1,927	1,733	1,373
Geometric mean bacteria concentration	cfu/100 mL	178.0	22.9	24.7	19.7	12.7	20.7	17.0
Maximum bacteria concentration	cfu/100 mL	333,188	333,158	350,650	103,482	307,000	83,182	33,866
Percentage of base case average concentration	%	100	99	104	81	99	89	70
Simulation results for summer flows								
Average streamflow	ft³/s	27.5	27.5	27.8	27.6	27.7	28.0	27.5
Average bacteria concentration	cfu/100 mL	287	265	290	247	273	285	225
Geometric mean bacteria concentration	cfu/100 mL	33.86	0.02	0.02	0.02	0.00	0.02	0.02
Maximum bacteria concentration	cfu/100 mL	26,269	26,237	27,906	21,201	25,300	23,533	18,656
Percentage of base case average concentration	%	100	92	101	86	95	99	78

Table 16D. Summary of 1988–2005 simulation results for six land use scenarios at Mill Creek outflow in the Chino Basin, California.—Continued[ft³/s, cubic feet per second; cfu/100 mL, colony forming units per 100 milliliters; %, percent]

Simulated parameter	Units	Base case	Land use scenarios					
			0	1	2	3	4	5
Simulation results for storm flows								
Number of stormflow values	hours	8,002	8,002	8,213	8,140	8,170	8,483	7,920
Percentage of time flow occurred	%	4	4	4	4	4	4	4
Average streamflow	ft³/s	535.8	535.8	554.1	538.8	541.8	564.7	527.2
Maximum streamflow	ft³/s	13,896	13,896	14,269	13,981	14,036	14,499	13,392
Minimum streamflow	ft³/s	70.0	70.0	70.0	70.0	70.0	70.0	70.0
Average bacteria concentration	cfu/100 mL	8,326	8,314	8,601	5,766	8,037	6,087	4,820
Geometric mean bacteria concentration	cfu/100 mL	3,531	3,467	3,739	2,770	3,547	3,009	2,331
Maximum bacteria concentration	cfu/100 mL	333,188	333,158	350,650	103,482	307,000	83,182	33,866
Minimum bacteria concentration	cfu/100 mL	17.20	3.64	4.86	3.76	3.90	5.30	4.60
Percentage of base case average concentration	%	100	100	103	69	97	73	58
Simulation results for low flows								
Number of lowflow values	hours	149,798	149,798	149,587	149,660	149,630	149,317	149,880
Percentage of time flow occurred	%	95	95	95	95	95	95	95
Average streamflow	ft³/s	25.9	25.9	25.9	25.9	25.9	26.0	25.9
Maximum streamflow	ft³/s	70.0	70.0	70.0	70.0	70.0	70.0	70.0
Minimum streamflow	ft³/s	8.5	8.5	8.5	8.7	8.7	8.9	8.5
Average bacteria concentration	cfu/100 mL	726	703	745	641	715	715	582
Geometric mean bacteria concentration	cfu/100 mL	62.9	0.4	0.4	0.4	0.1	0.4	0.3
Maximum bacteria concentration	cfu/100 mL	25,368	25,330	26,396	22,840	24,800	25,534	21,900
Minimum bacteria concentration	cfu/100 mL	12.52	0.00	0.00	0.00	0.00	0.00	0.00
Percentage of base case average concentration	%	100	97	103	88	98	98	80

Changing from contaminated to pristine nuisance flow (scenario 0) reduced the average bacteria concentration (for all flows) at site D from 8,551 cfu/100 mL to 7,807 cfu/100 mL, a decrease of about 9 percent (table 16A). The geometric-mean bacteria concentration was reduced from 1,687 ft³/s /100 mL to about zero; however, there was no significant affect on the maximum bacteria concentration. Land-use scenario 4 reduced the average concentration substantially to 2,302 cfu/100 mL, a 73 percent reduction from the base case. The largest reduction (and thus improvement) was caused by land-use scenario 5, which reduced the average concentration to 708 cfu/100 mL, a 92 percent reduction. Relative changes in simulated maximum hourly concentrations were greater than relative changes in the average concentrations; the lowest maximum concentration at site D under land-use scenario 5 was 100,569, compared with the highest maximum concentration of about 2.7 million cfu/100 mL for the base case. The greatest improvement in water quality for a land-use scenario involving a change in only one land use (scenarios 1–3) was simulated for land-use scenario 2, which resulted in a 69 percent reduction in average concentration.

Results for Prado Park Lake outflow were similar to results obtained for site D, but indicated an even greater relative reduction in average and maximum bacteria concentrations (table 16B). The average bacteria concentration for land-use 5 was 47 cfu/100 mL compared with the average concentration of 1,397 cfu/100 mL for the base case, a reduction of 97 percent. The maximum concentration was reduced from 255,855 cfu/100 mL for the base case to 6,952 cfu/100 mL for land-use scenario 5. Stormflow bacteria concentrations for Prado Park Lake outflow were several orders of magnitude higher than low flow concentrations for all land-use scenarios.

Results for the various land-use scenarios at Chino Creek outflow indicated a diminished response to the land-use scenarios compared to the affect of the scenarios on the Prado Basin. Simulation of pristine nuisance flow (land-use scenario 0) resulted in only a 2-percent reduction in the average bacteria concentrations, and no reduction in the maximum hourly concentration. Results based on land-use scenario 2 indicated a 34-percent reduction in the average bacteria concentration. Land-use scenario 4 provided a 3-percent reduction in the average bacteria concentration, while results for land-use scenario 5 indicated a 48-percent reduction. As with the other sites, the greatest improvement in water quality was simulated using land-use scenario 5; the maximum hourly bacteria concentration of 235,198 cfu/100 mL obtained for the base case was reduced to 75,284 cfu/100 mL.

Land-use scenarios applied to the Mill Creek subbasin generally resulted in smaller changes in simulated bacteria

concentrations at Mill Creek outflow compared with those for the locations simulated for the Chino Creek subbasin (table 16D). Land-use scenario 4 resulted in a 4-percent decrease in average bacteria concentrations. Land-use scenario 5 resulted in only a 29-percent reduction in average bacteria concentration. A much greater relative reduction was obtained in the simulated maximum hourly concentrations. The maximum concentration obtained using land-use scenario 5 is 33,866 cfu/100 mL, about one-order of magnitude lower than the simulated maximum concentration of 333,188 cfu/100 mL for the base case.

Comparisons of simulated daily streamflow and bacteria concentrations during storms for the five land-use scenarios at Prado Park Lake outflow (sample site PPOC), Chino Creek outflow, and Mill Creek outflow during 12/24/2004–3/8/2005 are shown in figures 29A–C. The base case model with pristine nuisance flow is equivalent to land-use scenario 0 discussed previously. Results for Prado Park Lake outflow indicate a relatively simple relation between peak streamflow and peak bacteria concentration, although peak bacteria concentrations for land-use scenarios 4 and 5 are much lower than peak streamflow (fig. 29A). Results for Chino Creek outflow indicate a more complicated response; differences between land-use scenarios were relatively small for the smaller storm peaks, but much greater for the simulated stormflows greater than approximately 100 ft³/s (fig. 29B). The smaller stormflows were affected less by outflow from Prado Park Lake, and differences in concentrations represented the effect of changes in land use in other parts of the Chino Creek subbasin. The larger streamflows included a significant contribution from Prado Basin, and these flows reflect the much higher sensitivity to the changes in land use, as compared to runoff generated in other parts of the Chino Creek subbasin. Results for Mill Creek outflow indicated a more complicated and variable relation between bacteria concentration and streamflow compared to the results obtained for both the Chino Creek and Prado Park Lake outflows (fig. 29C). The results for Mill Creek outflow indicated much higher bacteria concentrations (greater than 45,000 cfu/100 mL) for the 2/26/2005 storm relative to concentrations for the other storms (less than 20,000 cfu/100 mL), including the 1/10/2005 storm with a higher peak flow compared to the 2/26/2005 storm. The earlier storms in the storm sequence, including the 1/10/2005 storm, created antecedent conditions that resulted in saturated soils and increased runoff generation from the mixed agriculture and intensive livestock PERLNDs that are affected by the land-use scenarios.

Figure 29. Simulated daily bacteria concentrations sampled during storms in water-year 2005 for 6 land-use scenarios at *A*, Prado Park Lake outflow, *B*, Chino Creek outflow, and *C*, Mill Creek outflow in the Chino Basin, California.

The concentration duration curves for the 1988–2005 simulated hourly bacteria concentrations (indicating the percentage of time bacteria concentrations are exceeded) using the six land-use scenarios is shown for the same three locations (figs. 30A–C). The concentration duration curves also indicated that Prado Park Lake outflow was the most affected by the land-use scenarios 2, 3, 4, and 5 because this subbasin had the greatest percentage of upstream land area affected by these land-use scenarios (fig. 30A). Land-use scenario 0 has little to no affect on Prado Park Lake outflow because nuisance flows were diluted by RP-1 discharge and the long residence time for water in Prado Park Lake maximizes bacteria die-off (the model does not account for possible bacteria re-growth and point source contamination at Prado Park Lake). Land-use

scenario 1 also has no affect because there is no barren and vacant land use upstream of Prado Park Lake. Land-use scenario 2 (conversion of intensive livestock to residential land use) had the greatest affect for changes to a single land use (intensive livestock). Land-use scenarios 2 and 4 significantly reduced maximum bacteria concentrations that occur 4 percent of the time or less (about 600 cfu/100 mL for both scenarios relative to 1,500 for the base case). However, only land-use scenario 5 greatly reduced the percentage of time that bacterial concentrations exceeded 200 cfu/100 mL—to about 3 percent of the time compared with about 12 percent for the base case. Results for Chino Creek outflow indicated a much lower affect on bacteria concentrations caused by the land-use scenarios because the mixed agriculture, intensive livestock, and vacant

B **Figure 29.** Continued.

or barren land uses do not comprise a large fraction of the total upstream area in the Chino Creek subbasin ([fig. 30B](#)). The percentage of time the 200 cfu/100 mL was exceeded is about 10 percent for land-use scenario 5, and about 12 percent for the base case. Results for Mill Creek outflow also indicate a diminished affect from the land-use scenarios relative to the results for Prado Park Lake outflow ([fig. 30C](#)). The primary affect of the land-use scenarios at Mill Creek outflow was on the maximum bacteria concentrations that occurred only about 0.1 percent of the time or less.

Location was an important consideration in the evaluation of land-use scenarios because land uses are not distributed uniformly throughout the study area ([fig. 6](#)). Upstream locations were likely to include only a subset of land uses in their

catchment areas—this is especially true for the mixed agriculture and intensive livestock land uses which are concentrated in the lower part of the Chino Basin. In addition, all locations are likely to be most affected by the nearest upstream land use because of bacteria die-off and dilution during transport.

Land-use scenario 0 (pristine nuisance flow) affected sample site D the most because nuisance flow is the dominant-to-sole contribution to low flows at this site. Sites in the lower reaches of Chino Creek (including Prado Park Lake outflow), Cucamonga Creek, and Mill Creek, which are downstream of discharges from wastewater treatment plants, were affected less by land-use scenario 0.

Figure 29. Continued.

Comparing hourly simulation results indicated that (1) the effect of land-use scenario 1 was minor to insignificant at all analyzed locations, (2) land-use scenario 5 had the greatest effect with the greatest reduction in peak concentrations, (3) of the scenarios having a single land use change, land-use scenario 2 (intensive livestock to residential) reduced peak concentrations the most, (4) the effect of land-use scenarios on bacteria concentrations depended mostly on location because land uses are not uniformly distributed throughout the Chino Basin, and (5) for the land-use scenarios considered, relative differences in bacteria concentrations may only be significant for the larger storms that cause runoff (and bacteria washoff) from pervious land areas.

Land-use scenario 5 (barren or vacant, mixed agriculture, and intensive livestock converted to recreation and open

space) decreased average and peak bacteria concentrations the most, followed by land-use scenarios 4 (barren or vacant, mixed agriculture, and intensive livestock converted to residential), land-use scenario 2 (intensive livestock converted to residential) and land-use scenario 3 (mixed agriculture converted to residential). This result was expected given that the estimated accumulation and storage of bacteria in intensive livestock and mixed agriculture areas is greater than that in residential areas and much greater than that in recreational and open space areas.

Conversion to residential (all scenarios except 5) increased the percentage of impervious area, which increased the frequency of hourly concentrations exceeding 200 cfu/100 mL. Conversion to recreation and open space (land-use

Figure 30. Concentration duration for simulated hourly bacteria concentrations for 6 land-use scenarios during water-year 1988–2005 at *A*, Prado Park Lake outflow, *B*, Chino Creek outflow, and *C*, Mill Creek outflow in the Chino Basin, California.

scenario 5) did not increase impervious area and thus did not increase the frequency of concentrations exceeding 200 cfu/100 mL.

For all scenarios where there were significant reductions in bacteria loading, the most significant were for the infrequent peak concentrations in response to the larger storms. The reduction in concentrations below the assumed 200 cfu/100 mL target concentration is much less substantial because this level of bacteria contamination is affected more by the more frequent, smaller storms that cause washoff from impervious areas only. For this reason, land-use scenario 4 caused a slightly higher proportion of hourly bacteria concentrations greater than 10 cfu/100 mL but less than approximately 300 cfu/100 mL at the Prado Park Lake outflow location because of a substantial increase in total upstream

impervious area. The increased impervious area resulted in increased bacteria loading for the more frequent, smaller storms.

The land-use scenarios considered in this study generally affected only the lower reaches of the Chino Creek and Mill Creek subbasins, because this is where the mixed agriculture and intensive livestock land uses are located. However, these lower reaches coincide with waterways targeted for multi-use (parks and recreation). In addition, the lower reaches downstream of the mixed agriculture and intensive livestock land uses are the most likely to be affected by extreme bacteria loading in response to large storms, and thus land-use changes are likely to reduce maximum bacteria concentrations the most in this area.

Figure 30. Continued.

Applying Results to Develop TMDLs

The results of this study indicated that the bacteria loading in the Chino Basin waterways depended more on impervious area bacteria sources and loading rates if the TMDL target concentration of fecal coliform and *E. coli* was in the range of 100–300 cfu/100 mL (for this study, a target concentration of 200 cfu/100 mL was used for the concentration-duration analysis). Peak concentrations depended more on larger storms and on pervious-area bacteria sources and loading rates. Only the larger storms generated runoff, and thus bacteria washoff, on the pervious areas in the Chino Basin (most precipitation falling on pervious areas enters the soil, and is then lost to evapotranspiration or percolates down below the zone of

evapotranspiration and becomes recharge). Land uses that were assigned the highest bacteria-loading (agriculture and feedlots) values affected the time-averaged bacteria loads and the frequency of concentrations exceeding 200 cfu/100 mL less because significant washoff occurred relatively infrequently from the pervious areas (during some years, there is no washoff from pervious areas). For this reason, the changing of areas of modeled land use from agriculture and feedlots to residential did not significantly improve the average water quality of the Chino Basin waterways (and in some cases resulted in a decrease in the time-averaged water quality), although peak bacteria loading was decreased. In contrast, modeling the conversion of vacant, mixed agriculture, and intensive livestock areas to recreation and open space land use

Figure 30. Continued.

areas resulted in a more significant reduction of the peak bacteria concentrations and the frequency of hourly concentrations exceeding 200 cfu/100 mL.

Analyses of field data indicated that (1) bacteria loading to nuisance flow (either as point or non-point sources) was significant to the overall bacteria loading, especially for locations where the nuisance flow was the dominant baseflow component, and should be considered as part of the TMDL development. It is hypothesized that the nuisance flow originated primarily as over-watering of irrigated landscapes, which in turn were likely sources of bacteria contamination. The nuisance flow component was included in the model as an estimated constant inflow with uniform bacteria concentration for each RCHRES segment on the basis of the total area of urban land uses contributing to the segment. The contaminated nuisance-flow component was generally supported by the available

field data, but was included in the model in a very simplified manner. To evaluate the contribution of nuisance flow relative to storm runoff and other sources of bacteria contamination (groundwater discharge, inflows), a land-use scenario using pristine (uncontaminated) nuisance flow was included in model application and analysis. The results from the evaluation suggested that both storm flow and nuisance flow need to be considered in the TMDL development (storm flow alone does not account for all of the water-quality degradation). Overall, residential land use contributed the greatest total bacteria loading (as indicated by comparing the relative average loading rates for individual land uses). Residential land use accounted for the greatest total area in the Chino Basin, and the field data and subsequent model calibration indicated a moderate to high land-surface accumulation rate. Results from land-use modeling scenarios indicated that an increase in

residential land use with a corresponding decrease in agriculture, intensive livestock (dairies), or barren or vacant land use did not cause a significant decrease in the frequency that bacteria concentrations in waterways exceeded 200 cfu/100 mL. A decrease in mixed agriculture and intensive livestock land use would likely result in a decrease in peak bacteria concentrations during the larger storms, as well as a decrease in total bacteria loading, but this may not change the level of compliance with the TMDL if the frequency or duration of exceeding 200 cfu/100 mL is used as the criterion. Reducing the effective impervious area would likely affect TMDL compliance more favorably.

Calibrating models contains uncertainties. In particular, the small sample size for storm runoff for specific land uses, such as recreation and open space, and a lack of samples for definitive pervious-area runoff from the urban and agricultural land uses (samples from large storms), increased uncertainties in the model. Results from the land-use scenario analysis suggest that commercial and services land use has the highest estimated loading rates (this is consistent with the relative loading rates of the regional parameters). The loading rates may be correlated to size and number of irrigated landscapes and the degree of over-watering, which would also explain the high degree of contamination in the nuisance flows. Domestic animals (pets) and wildlife (birds, rats) likely rely on the over-watering as a source of drinking water. Industrial land-use areas have a lower loading rate because of fewer over-watered landscapes (there are fewer animals because there is less available water).

The calibrated loading rates for fecal coliforms were higher than the regional fecal coliform loading rates developed by the Southern California Coastal Water Research Project Authority (SCCWRP) for the Los Angeles region for most (but not all) land uses. The calibrated loading rates for urban and agricultural land uses were mostly higher than the SCCWRP rates, while loading rates for natural areas were mostly lower. This may be related to climate: the drier climate of the Chino Basin study area (hotter conditions, lower humidity compared with that of the coastal watersheds) encourages less wildlife in the natural environments and increased irrigation (and thus overwatering) in the urban environment (which attracts more animals to the irrigated landscapes). Thus, a reduction of overwatering may lead to a reduction in bacteria loading for both nuisance flows (nuisance flows would decrease if overwatering decreased) and storm flows (bird and rodent populations would decrease). Using more retention basins to capture contaminated runoff and allow bacteria and pathogens to die off may also help improve downstream water quality.

Results of the modeling indicate that conversion of the mixed agriculture and intensive livestock land uses to the recreation and open-space land use would significantly improve water quality for the Prado Basin. Water quality in the lower sections of Chino Creek and Mill Creek would also improve, but the effect would be smaller because only a small fraction of the total area supplying runoff to these main

channels would be affected by the land use change. The recreation and open-space land use was calibrated to have bacteria loading rates lower than that for residential and commercial and services land uses and thus converting to this land use would improve water quality substantially more than converting to other land uses. Given the greater likelihood that the mixed agriculture and intensive livestock land uses will eventually be converted to residential land use, peak and total bacteria loading will still decrease substantially. However, the frequency at which bacteria concentrations exceed a given criterion level (for example, a limit of 200 cfu/100 mL for fecal coliform) may not change significantly. The results from this study suggest that if there are no changes in the existing conditions affecting the quality of urban runoff from impervious areas, water quality may even diminish in terms of the frequency of contamination, regardless of land-use changes, as the percentage of impervious area increases.

Summary and Conclusions

Pathogen indicator bacteria concentrations were measured during three storms in water-year 2004 at 9 locations in the Chino Basin to help evaluate water quality and to develop and calibrate a Hydrological Simulation Program-FORTRAN (HSPF) pathogen-indicator bacteria transport model for the Chino Basin. The data and transport model are being used for the Chino Basin study area as part of ongoing work to establish a pathogen-indicator bacteria Total Maximum Daily Load (TMDL) for a part of the Santa Ana River watershed that primarily includes the Chino Basin tributary.

The pathogen-indicator bacteria samples collected during the 3 storms in water-year 2004 included total coliform, fecal coliform, *E. coli*, and enterococci. The data set was supplemented by indicator bacteria samples available from previous and ongoing water-quality studies in the Chino Basin. The bacteria data indicated elevated bacteria concentrations high above limits considered as being potentially harmful to human health, downstream of the highly urbanized central part of the Chino Basin and downstream of the mixed agriculture and intensive livestock areas in the southern part of the basin.

The HSPF transport model area incorporated a relatively detailed representation of the urban area hydrography using 10- and 30-meter digital elevation models (DEM), available storm-drain maps, hydrography maps, detailed and fairly recent (2000) land-use maps, high-resolution orthophotos, and an available map of estimated 2001 imperviousness. The drainage system was defined using 229 reach and reservoir model segments that were grouped into 46 land area segments having consistent land-surface and climate properties. The land-use map was used to define 12 pervious-area land types and 9 impervious area land types that were superimposed onto the 46 land area segments, generating a total of 966 hydrologic response units. Parameters controlling streamflow and bacteria transport processes were defined for all hydrologic response

units, and these were distributed by contributing area over the 229 reach and reservoir segments.

National Land Cover Dataset (NLCD) impervious-area maps were used to better quantify differences between pervious and impervious land areas within the 12 land types that were identified on the basis of generalized land uses and vegetation groups. The 12 land types were (1) shrubs and grasses; (2) forest; (3) barren and vacant; (4) mixed urban; (5) recreation and open space; (6) commercial and services; (7) utilities and transportation; (8) medium to high density residential; (9) industrial; (10) mixed agriculture; (11) wetlands and water bodies; and (12) intensive livestock (dairies). Shrubs and grasses, forest, and wetlands and water did not have significant impervious areas and thus were defined only as pervious-area land types. Initial impervious-area percentages (as a percentage of total land-use area) were refined to improve model calibration. Identifying the relative pervious and impervious areas for the various land uses and land types for the Chino Basin was an important part of model development because storm runoff and streamflow were very sensitive to the impervious areas affecting the drainage system.

Developing spatially distributed hourly climate inputs using available data from a regionally distributed network of monitoring sites helped in calibrating the Chino Basin model to hydrographs that reflected complex hydrological processes. Areally-distributed recharge over pervious land units did not account for all recharge because of significant artificially-induced recharge throughout the basin. Adding representation of in-stream recharge processes (retention basins) helped improve model calibration.

Evaluation of simulated hourly fecal coliform bacteria concentrations in the Chino Basin study area indicated important differences in contributions to bacteria loading between impervious and pervious source areas. Impervious areas tended to cause bacteria loading to be much more frequent, particularly bacteria concentrations less than approximately 1,000 cfu/100 mL, because precipitation amounts from and intensities of most storms are not sufficient to generate significant runoff and bacteria washoff from pervious areas. Runoff usually comes from pervious areas when the soils become saturated, and in the central and southern parts of the Chino Basin, this only occurs in response to the larger storms during wetter than normal years. In contrast to pervious areas, runoff and subsequent bacteria washoff comes from impervious areas during all storms with precipitation exceeding the surface retention storage term, which was estimated to range from 0.08 to 0.15 in. for the Chino Basin study area. However, pervious-area washoff often results in more than 1 order of magnitude greater bacteria concentrations in downstream reaches, especially in locations where the upstream areas are used mostly for mixed agriculture and intensive livestock, uses which were calibrated as generating high bacteria accumulation rates per unit land area.

Analyses of simulated and measured bacteria concentrations at many different sampling sites in the Chino Basin indicated that storm flows (runoff in response to precipitation)

alone cannot account for all measured elevated bacteria concentrations. The field data and simulation results suggest that nuisance flows (flows originating as very small inflows from urbanized areas) likely contribute significantly to bacteria loading throughout the Chino Basin. The uncertainties encountered in model calibration with regard to estimates of nuisance flows indicated that they are an important data need and should be considered when interpreting the processes affecting water quality.

The correlation between storm flow and bacteria concentration was poor for most locations, and depended on location (upstream or downstream) along the drainage network and the ratio of pervious to impervious area. Small catchments with a high percentage of impervious area were characterized by rapid washoff of bacteria, even for relatively small runoff events. For most storms, the bacteria concentration peaked during the early (rising limb) stages, represented by the storm hydrograph, as increasing runoff diluted the initial bacteria loads. As runoff decreased, bacteria concentrations often increased because die-off is slow relative to the decrease in flow indicated by the falling limb of the hydrograph, and owing to delayed inflows of more contaminated runoff from upstream areas. For very low flows, bacteria concentrations could become very high because the evaporation rate exceeded the die-off rate. Small catchments with a high percentage of pervious area (agriculture, feedlot, open space land uses) were characterized by peak bacteria loads better correlated to the magnitude of streamflow because washoff from the pervious areas tended to occur only during the larger storms. During drier than normal periods, only the impervious areas contributed to bacteria loading and subsequent pathogenic degradation of downstream water quality.

Using different climate and land-use scenarios in the model helped improve understanding of processes affecting bacteria concentrations (and thus pathogen contamination) in the Chino Basin. Changing the average air temperature substantially affected simulated streamflow in the northern part of the Chino Basin because of the effect on snow pack formation and melting and the bacteria loading from mountain-front canyons (San Antonio Canyon, Cucamonga Canyon, and Deer Creek Canyon). In general, higher temperatures caused an increase in simulated bacteria concentrations. However, increased bacteria concentrations in streamflow discharging from the mountain-front canyons had very little effect on the downstream sections of the drainage system in the model simulations because this streamflow is a minor fraction of the total runoff generated in the Chino Basin.

Increased precipitation resulted in simulations having improved water quality for pristine areas (shrubs and grasslands, forests) in the northern, mountainous part of the basin, owing to dilution. In contrast, increased precipitation caused a simulated decrease in water quality for urban areas and downstream parts of the Chino Basin watershed because runoff from pervious areas for land uses with relatively high loading rates increased. A decrease in precipitation could also diminish water quality at locations in the drainage that are

strongly affected by nuisance flows, because of less dilution and higher constituent concentrations during low flow conditions. Locations downstream of wastewater inflows were usually less sensitive to nuisance flow contamination when the wastewater inflows were pristine (this was generally supported by the available data). Locations downstream of surface-water storage facilities also usually had lower simulated bacteria concentrations during low flows because bacteria die-off and dilution decreased concentrations in the stored water. However, the simplified advective transport model used in this study did not account for possible bacteria regrowth or resuspension as particulate matter. These processes might be better represented using a sediment transport model.

The primary conclusions regarding the relation of pathogen indicator bacteria to land use in the Chino Basin is that the urban land uses generate a higher frequency (owing to impervious areas), yet lower magnitude, bacteria load, whereas the intensive livestock and mixed agriculture land uses generate higher peak loads but less often. The simulated peak bacteria loads occurred infrequently because only the largest storms generated substantial runoff from the pervious areas.

Results from this study indicated that if management options or Total Maximum Daily Load (TMDL, a pollution control plan) requirements are to be based on how often certain thresholds (such as 200 cfu/100 mL) are exceeded, then it is probably more important to control bacteria buildup and washoff from impervious areas than from pervious areas. A shift from mixed agriculture and intensive livestock land uses to residential land use upstream of an impaired reach may not have the desired effect in terms of meeting a TMDL requirement, because the frequency that threshold concentrations are exceeded may not change very much. On the other hand, if criteria for management options or TMDL requirements are to be based on peak loads, then reducing buildup and washoff from the pervious areas of urban and agricultural land uses (including intensive livestock) would be more important. A change in land use from mixed agriculture and intensive livestock to residential may meet management or TMDL requirements if based on peak loads or total loads.

A change from mixed agriculture and intensive livestock (dairies/feedlots) to residential land use would most likely affect the Prado Basin, because a high percentage of the area upstream of this drainage is used for mixed agriculture and intensive livestock. Model results indicated that during wet years such as 2005, the effect of runoff from mixed agriculture and intensive livestock to Prado Park Lake is extreme. The effect in other areas depends on location, as most of the basin is upstream of the intensive livestock land use, but the lower part of the basin is influenced by dilution from the wastewater effluent. Streamflow upstream of the treatment plants is not diluted and the bacteria load coming directly from the urban areas, from both nuisance flow and storm runoff, appears to be significant.

The accuracy of model simulations of future climate and land-use scenarios cannot be quantified without additional field data consisting of both land-use-targeted sampling of small catchments in upstream areas and integrated response samples from the main channels, preferably from stream-gage locations. The results obtained in this study suggest an important distinction between impervious and pervious land area processes contributing to the total bacteria load. However, the most important pervious areas with potential bacteria loading are generally located in the lower part of the Chino Basin, downstream of the stream gages used to calibrate the stream flow component of the transport model. Therefore, since data could not be collected in one location for both streamflow and bacteria loading in pervious areas, the model calibration did not fully represent the pervious land-use areas (mixed agriculture and intensive livestock) and could not be sufficiently calibrated. Location of additional stream gages downstream of the mixed agriculture and intensive livestock land uses would greatly improve model accuracy in representing the pervious area contribution to bacteria loading.

Low soil infiltration rates assigned for the lower part of the Chino Basin were estimated on the basis of the high percentage of clays indicated in available STATSGO and SSURGO data. Simulated runoff and subsequent bacteria washoff for these areas is likely to be sensitive to these low infiltration rates, and as a result, indicates that soil properties should be more accurately defined. Runoff generation was also sensitive to precipitation intensity, which can vary greatly for the hourly time step used in this model. The hourly precipitation inputs are mostly based on the available 1-hour precipitation data but in some cases are based on 1-hour totals of higher resolution (15 or 5 minute) data. The higher resolution data more accurately represent maximum precipitation intensities occurring during shorter (less than 1 hour) time intervals, but the number of stations with higher resolution data is much less than stations with hourly data.

Nuisance flow was observed to be an important factor affecting overall water quality for the study area, especially in terms of the frequency or duration of impaired water quality. However, nuisance flow was also considered to be the least accurately represented component of the HSPF flow and transport model. In order to better characterize the nuisance-flow component, more streamflow and water-quality data are needed for channels affected only by urban runoff and nuisance flow (such as the drainage upstream of gage 11073493). To improve model accuracy the bacteria sampling must include more data collected during dry periods when only nuisance flow is occurring in the channel. In addition, sources of nuisance flow contamination would be better understood by monitoring discharges from various storm drains and land uses.

Acknowledgments

This study was supported by the Santa Ana Watershed Project Authority. Supporting and interested stakeholders included San Bernardino County, Los Angeles County, Orange County, Riverside County, Inland Empire Utilities Agency, Wildermuth Environmental Inc., U.S. Army Corps of Engineers, and the Regional Water Quality Control Board.

Funding for this project has been provided in part through an agreement with the State Water Resources Control Board (SWRCB) pursuant to the Costa-Machado Water Act of 2000 (Proposition 13) and any amendments thereto for the implementation of California's Nonpoint Source Pollution Control Program. The contents of this document do not necessarily reflect the views and policies of the SWRCB, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

References Cited

- Ackerman, Drew, and Weisberg, S.B., 2003, Relationship between rainfall and beach bacterial concentrations on Santa Monica Bay beaches: *Journal of Water and Health*, v. 1, no. 2, p. 85–89.
- Belitz, Kenneth, Hamlin, S.N., Burton, C.A., Kent, Robert, Fay, R.G., and Johnson, Tyler, 2004, Water quality in the Santa Ana basin, California, 1999–2001: U.S. Geological Survey Circular 1238, 47 p.
- Bicknell, B.R., Imhoff, J.C., Kittle, J.L., Jr., Donigian, A.S., Jr., and Johanson, R.C., 1997, Hydrological Simulation Program-FORTRAN, User's manual for Version 11: U.S. Environmental Protection Agency, National Exposure Research Laboratory, Athens, Ga., EPA/600/R-97/080, 775 p.
- California Irrigation Management information System (CIMIS), 2005, Meteorological data: California Department of Water Resources and University of California at Davis. Available at <http://www.cimis.water.ca.gov/>
- Daly, C., Gibson, W.P., Doggett, M., Smith, J., and Taylor, G., 2004, Up-to-date monthly climate maps for the conterminous United States: Proceedings of the 14th Conference on Applied Climatology, 84th American Meteorological Society Annual Meeting, Seattle, Wash., January 13–16, 2004, Paper P5.1, CD-ROM.
- Donigian, A.S., Bicknell, B.R., and Imhoff, J.C., 1995, Hydrological Simulation Program-FORTRAN (HSPF), in Singh, V.P., ed., *Computer models of watershed hydrology*, chap. 12. p. 395–442.
- Guay, J.R., 2002, Rainfall-runoff characteristics and effects of increased urban density on streamflow and infiltration in the eastern part of San Jacinto River Basin, Riverside County, California: U.S. Geological Survey Water-Resources Investigations Report 02–4090, 60 p.
- Izbicki, J.A., Pimental, M.I., Leddy, M., and Bergamaschi, Brian, 2004, Microbial and dissolved organic carbon characterization of stormflow in the Santa Ana River at Imperial Highway, Southern California, 1999–2002: U.S. Geological Survey Scientific investigations Report 2004–5116, 80 p.
- Martin, J.L., and McCutcheon, S.C., 1999, *Hydrodynamics and transport for water quality modeling*: Boca Raton, Fla., Lewis Publishers, 794 p.
- Moyer, D.L., and Hyer, K.E., 2003, Use of the Hydrological Simulation Program-FORTRAN and bacterial source tracking for development of the fecal coliform Total Maximum Daily Load (TMDL) for Accotink Creek, Augusta County, Virginia: U.S. Geological Survey, Water-Resources Investigations Report 03–4160, 67 p.
- Rice, W.B., 2005, Staff report on bacterial indicator total maximum daily loadings in the middle Santa Ana River watershed: Report to California Regional Water Quality Control Board, Santa Ana Region, February 3, 2005, 144 p.
- Soil Survey Staff, 2007, Soil Survey Geographic (SSURGO) Database: Natural Resources Conservation Service, U.S. Department of Agriculture, accessed 3/31/04 at <http://soils.usda.gov/survey/geography/ssurgo/>
- Stein, E.D., Ackerman, Drew, and Schiff, Kenneth, 2003, Watershed-based sources of contaminants to San Pedro Bay and Marina del Rey—Patterns and trends, Southern California Coastal Water Research Project: Report prepared for the Los Angeles Contaminated Sediments Task Force.
- Tetra Tech, Inc., 2003, Lake Elsinore and Canyon Lake nutrient source assessment: Submitted to the Santa Ana Watershed Project Authority, 11615 Sterling Ave., Riverside, California, 149 p.
- U.S. Army Corps of Engineers, 1991, Water control manual, San Antonio Dam, Los Angeles County and San Bernardino County, San Antonio Creek, California: Los Angeles District, 128 p.
- U.S. Army Corps of Engineers, 2005, Daily outflow data for San Antonio Dam. Available at <http://www.spl.usace.army.mil/resreg/>
- U.S. Department of Agriculture, 1994, State Soil Geographic (STATSGO) Data Base—Data use information: Natural Resource Conservation Service, Misc. Pub. no. 1492, (<http://soils.usda.gov/survey/geography/statsgo/>).

- U.S. Environmental Protection Agency, 1985, Rates, constants, and kinetics formulations in surface water quality modeling (2d ed.): U.S. Environmental Protection Agency, EPA 600/3-85/040.
- U.S. Environmental Protection Agency, 1986, Ambient water quality criteria for bacteria: U.S. Environmental Protection Agency, EPA 440/5-84-002.
- U.S. Environmental Protection Agency, 2000, Basins case study 1: Cottonwood Creek Watershed, Idaho County, Idaho: U.S. Environmental Protection Agency, EPA 823-R-00-024, 12 p.
- U.S. Geological Survey, 2001, The national map seamless server database. Available at <http://seamless.usgs.gov/web-site/seamless>
- Wildermuth Environmental, Inc., 2003, Chino Basin optimum basin management program—Chino Basin dry-year yield program: Prepared for Chino Basin Watermaster, inland Empire Utilities Agency, Chino, Calif., 141 p.
- Yagow, G., Dillaha, T., Mostaghimi, S., Brannan, K., Heatwole, C., and Wolfe, M.L., 2001, TMDL modeling of fecal coliform bacteria with HSPF: Proceedings of the American Society of Agricultural Engineering International Meeting, Sacramento, Calif., Paper No. 01-2066, 20 p.
- Zarriello, P. J., 1999, A precipitation-runoff model for part of the Ninemile Creek watershed near Camillus, Onondaga County, New York: U.S. Geological Survey Water-Resources Investigations Report 98-4201, 60 p.

**Appendix 1. Water-Quality
Data Collected by the USGS in
Water-Year 2004 in the Chino Basin**

Appendix 1. Water quality data for bacteriological samples collected by U.S. Geological Survey during storms in 2003 and 2004 in the Chino Basin, California.—Continued[Samples analyzed by the Orange County Public Health Laboratory. Densities in colony forming units per milliliter. USGS, U.S. Geological Survey; in., inch; $\geq$, greater than or equal to]

Station identification	Sample identification	Date sampled	Time sampled	Stage when sampled (in.)	Sample type	Density of bacteria types			
						Total coliforms	Fecal coliforms	Enterococcus <i>E. coli</i>	
Storm 2—February 2–3, 2004—Continued									
MC	MC 2-1	2/2/2004	2120	34.8	STREAM	3,400	300	1,400	500
MC	MC 2-2	2/2/2004	2220	47.0	STREAM	240,000	4,200	18,000	5,000
MC	MC 2-3	2/2/2004	2330	35.6	STREAM	111,000	7,100	15,000	5,200
MC	MC 2-4	2/3/2004	130	29.6	STREAM	40,000	5,100	16,000	4,100
MC	MC 2-5	2/3/2004	230	27.5	STREAM	37,000	3,800	11,300	3,900
MC	MC 2-6	2/3/2004	900	25.3	STREAM	33,000	2,900	6,800	2,200
Storm 3—February 22–23, 2004									
IndND	IndND 3-1	2/22/2004	820	18	STORM DRAIN	83,000	3,800	26,000	4,100
IndND	IndND 3-2	2/22/2004	1300	24	STORM DRAIN	>93,000	6,400	60,000	5,900
IndND	IndND 3-3	2/22/2004	1950	26	STORM DRAIN	71,000	3,400	40,000	2,700
IndND	IndND 3-3 DUPL.	2/22/2004	1950	26	STORM DRAIN	63,000	3,000	35,000	2,300
IndND	IndND 3-4	2/23/2004	25	6	STORM DRAIN	82,000	3,400	32,000	2,900
IndND	IndND 3-5	2/23/2004	930	12	STORM DRAIN	790,000	9,000	69,000	8,000
RecND	RecND 3-1	2/22/2004	825	8	STORM DRAIN	>86,000	4,700	48,000	6,400
RecND	RecND 3-2	2/22/2004	1250	4	STORM DRAIN	>59,000	6,000	78,000	9,600
RecND	RecND 3-3	2/22/2004	1935	6	STORM DRAIN	>58,000	3,800	45,000	8,400
RecND	RecND 3-3 DUPL.	2/22/2004	1935	6	STORM DRAIN	>53,000	6,500	52,000	7,800
RecND	RecND 3-4	2/23/2004	10	4	STORM DRAIN	>35,000	4,200	44,000	6,200
RecND	RecND 3-4 DUPL.	2/23/2004	10	4	STORM DRAIN	>35,000	3,400	43,000	4,800
RecND	RecND 3-5	2/23/2004	945	8	STORM DRAIN	>56,000	5,800	32,000	6,400
RecND	RecND 3-5 DUPL.	2/23/2004	945	8	STORM DRAIN	>73,000	6,300	29,000	6,900
SC	SC 3-1	2/22/2004	845	0.5	STORM DRAIN	29,000	2,400	950	>490
SC	SC 3-2	2/22/2004	1240	0.25	STORM DRAIN	9,000	320	2,600	2,000
SC	SC 3-3	2/22/2004	1925	0.5	STORM DRAIN	13,900	2,900	14,200	190
SC	SC 3-4	2/22/2004	2357	0.5	STORM DRAIN	60,000	290	760	130
SC	SC 3-5	2/23/2004	955	0.5	STORM DRAIN	48,000	2,100	1,600	2,500
RecD	RecD 3-1	2/22/2004	810	1	STORM DRAIN	61,000	10,000	30,000	23,000
RecD	RecD 3-2	2/22/2004	1325	0.25	STORM DRAIN	>21,000	440	7,100	390
RecD	RecD 3-3	2/22/2004	1920	2.5	STORM DRAIN	>23,000	4,100	36,000	4,700
RecD	RecD 3-4	2/22/2004	2350	1	STORM DRAIN	>6,300	540	7,500	750
RecD	RecD 3-5	2/23/2004	920	1	STORM DRAIN	>2,800	140	1,270	130

Hevesi and others—Application of a Watershed Model (HSPF) for Evaluating Sources and Transport of Pathogen Indicators in the Chino Basin Drainage Area,
San Bernardino County, California—SIR 2009-5219