




UNCERTAINTIES AND LIMITATIONS FOR USE OF FLOOD-INUNDATION MAPS

Although the flood-inundation maps represent the boundaries of inundated areas with a distinct line, some uncertainty is associated with these maps. The flood boundaries shown were estimated based on water stages (water-surface elevations) and streamflows at selected USGS streamgages. Water-surface elevations along the stream reaches were estimated by steady-state hydraulic modeling, assuming unobstructed flow, and using streamflows and hydrologic conditions anticipated at the USGS streamgage(s). The hydraulic model reflects the land-cover characteristics and any bridge, dam, levee, or other hydraulic structures existing as of October, 2014. Unique meteorological factors (timing and distribution of precipitation) may cause actual streamflows along the modeled reach to vary from those assumed during a flood, which may lead to deviations in the water-surface elevations and inundation boundaries shown. Additional areas may be flooded due to unanticipated conditions such as: changes in the streambed elevation or roughness, backwater into major tributaries along a main stem river, or backwater from localized debris or ice jams. The accuracy of the floodwater extent portrayed on these maps will vary with the accuracy of the digital elevation model used to simulate the land surface. Additional uncertainties and limitations perioe (NWS) river forecasts, the user should be aware of flood inundation maps heets. If this series of flood-inundation maps will be aware of additional uncertainties that may be inherent or factored into NWS forecast procedures. The NWS uses forecast models (1) estimate the amount of runoff generated by precipitation) for the stream at given location (AHPS forecast point) throughout the forecast point) throughout the forecast point) throughout the forecast period (every 6 hours and 3 to 5 days out in many locations). For more information on AHPS forecasts, please see: http://water.weather.gov/ahps/pcpn_and_river_forecasting.pdf.

DISCLAIMER

Inundated areas shown should not be used for navigation, regulatory, permitting, or other legal purposes. The USGS provides these maps "as-is" for a quick reference, emergency planning tool but assumes no legal liability or responsibility resulting from the use of this information.



Transverse Mercator projection North American Datum of 1983 (NAD 83) Orthography from New York State Digital Orthoimagery Program, 2013

National Map available at http://viewer.nationalmap.gov/viewer. Position of boundary on this map is approximate and for informational purposes only.

Suggested citation: Nystrom, E.A., 2016, Flood-inundation maps for the Schoharie Creek at Prattsville, New York, 2014: U.S. Geological Survey Scientific Investigations Report 2015-5190, 12 p., 17 sheets, *http://dx.doi.org/10.3133/sir20155190*.

ISSN 2328-0328 (online) http://dx.doi.org/10.3133/sir20155190 Flood-Inundation Map for Prattsville, New York, Corresponding to a Stage of 15.0 Feet and Elevation of 1,145.96 Feet (NAVD 88) at U.S. Geological Survey Streamgage 01350000 on the Schoharie Creek By Elizabeth A. Nystrom

2016

Publishing support provided by: Pembroke Publishing Service Center Manuscript approved for publication December 29, 2015

For more information concerning this publication, contact: Director, New York Water Science Center U.S. Geological Survey 425 Jordan Road Troy, NY 12180 (518) 285–5600

Or visit the New York Water Science Center Web site at: http://ny.water.usgs.gov/

This report is available at: http://dx.doi.org/10.3133/sir20155190.

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

This and other USGS information products are available at: http://store.usgs.gov/ U.S. Geological Survey, Box 25286 Denver Federal Center, Denver, CO 80225

To learn about the USGS and its information products visit http://www.usgs.gov/ 1-888-ASK-USGS