

U.S. Department of the Interior

U.S. Geological Survey

Prepared in cooperation with the

Missouri Department of Natural Resources

Scientific Investigations Report 2023–5018
Plate 10 of 12

# **Table 1.** Surface area and capacity at specified water-surface elevations for Monroe Lake B (Monroe City South) near Monroe City, Missouri, April 27, 2021.

[Primary spillway elevation is about 712.8 feet; the mean water-surface elevation during the survey was about 712.8 feet (row shaded in the table)]

Water-surface elevation,¹ in feet	Surface area, in acres	Capacity, <sup>2</sup> in acre-feet
696.0	0.06	0.07
698.0	1.93	1.28
700.0	7.27	10.1
702.0	14.8	31.6
704.0	24.5	70.7
706.0	33.5	129
708.0	42.6	205
710.0	52.9	300
712.0	58.8	412
712.8	61.9	460

<sup>1</sup>Elevations are referenced to the North American Vertical Datum of 1988 using the geoid model GEOID18.

<sup>2</sup>Capacities were calculated from surface testing at 0.14-foot vertical accuracy at a 95-percent confidence level. An explanation of the vertical accuracy calculation can be found in the "Bathymetric Surface, Contour Map, and Bathymetric Change Quality Assurance" section of the report of which this plate is a part.

#### **EXPLANATION**

#### Area of multibeam survey data collection

## Boundary of resurvey for point-to-point quality-assurance data collection (cross-check line)

Water-surface elevation—Shows mean water-surface elevation (712.8 feet, refer to table 1). Datum is North American Vertical Datum of 1988 using the geoid model GEOID18

—— 700 — Bathymetric contour—Shows elevation of the lake bottom.

Index contour interval 10 feet. Intermediate contour

(gray) interval 2 feet. Datum is North American Vertical

Datum of 1988 using the geoid model GEOID18

# Locations of supplemental depth data collected with an acoustic Doppler current profiler (ADCP)

Reference mark and identifier—Shows location of survey control used in the survey. RM1 is the chiseled X on the crown of a rock downstream from the spillway, about 39 feet north from south road and about 66 feet from gate. Elevation 707.58 feet. RM2 is a chisel arrow in the middle of the southeastern wingwall of spillway, over the water. Elevation 716.98 feet. RM3 is the top of the concrete spillway lip on south end. Elevation 712.82 feet. Datum is North American Vertical Datum of 1988 using the geoid model GEOID18



Any use of trade, firm, or product names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

### Suggested citation:

Rivers, B.C., Huizinga, R.J., Richards, J.M., and Waite, G.J., 2023, Bathymetric contour maps, surface area and capacity tables, and bathymetric change maps for selected water-supply lakes in northeastern Missouri, 2021: U.S. Geological Survey Scientific Investigations Report 2023–5108, xx p., and 12 oversized plates,

ISSN 2328-0328 (online) //doi.org/10.3133/sir20235108

Bathymetric Contour Map and Surface Area and Capacity Table for Monroe Lake B (Monroe City South; lake 32) near Monroe City, Missouri, 2021