

May 31, 2019

Revision History for U.S. Geological Survey Techniques and Methods 4–B5

Guidelines for Determining Flood Flow Frequency—Bulletin 17C

By John F. England, Jr., Timothy A. Cohn, Beth A. Faber, Jery R. Stedinger,
Wilbert O. Thomas, Jr., Andrea G. Veilleux, Julie E. Kiang, and Robert R. Mason, Jr.

Posted online March 29, 2018

Revised and reposted May 31, 2019, Version 1.1

- On p. 3, in the first paragraph, right column, “(in press)” was changed to “(2019)”.
- On p. 39, left column, “(in press)” was changed to “2019”.
- On p. 97, in the paragraph above equation 8–25, “ $\hat{\mu}_y = 3.304$ and $\hat{\sigma}_y^2 = 0.081$ ” were changed to “ $\mu_y = 3.3024$ and $\sigma_y^2 = 0.08105$ ” and (2) equation 8–25 was changed from “ $y_i = 3.436 + 0.8478(x_i - 4.141)$ ” to “ $y_i = 3.4364 + 1.4416(x_i - 4.1414)$ ”.
- On p. 99, in table 8–2, each of the 13 values in the second column was revised as shown in the modified table below:

Table 8–2. MOVE extended record for 13 years
(1972 to 1984) for Suwanee Creek at Suwanee,
Georgia (station 02334885).

[ft³/s, cubic feet per second]

Water year	Annual peak streamflow (ft³/s)
1972	2,830
1973	2,010
1974	2,300
1975	2,200
1976	4,310
1977	4,150
1978	3,730
1979	5,180
1980	3,040
1981	722
1982	6,070
1983	1,460
1984	2,440