


Water Resources Data Pennsylvania Water Year 1999

Volume 1. Delaware River Basin

By R.R. Durlin and W.P. Schaffstall

Water-Data Report PA-99-1



Prepared in cooperation with the Pennsylvania Department of Environmental Protection, the Philadelphia District of the U.S. Army Corps of Engineers, the Chester County Water Resources Authority, and with other State, municipal, and Federal agencies.



PREFACE

This volume of the annual hydrologic data report of Pennsylvania is one of a series of annual reports that document hydrologic data gathered from the U.S. Geological Survey's surface- and ground-water data-collection networks in each State, Puerto Rico, and the Trust Territories. These records of streamflow, ground-water levels, and quality of water provide the hydrologic information needed by State, local, and Federal agencies, and the private sector for developing and managing our Nation's land and water resources. Hydrologic data for Pennsylvania are contained in 3 volumes.

- Volume 1. Delaware River Basin
- Volume 2. Susquehanna and Potomac River Basins
- Volume 3. Ohio and St. Lawrence River Basins

Volume 1 was prepared in cooperation with the Commonwealth of Pennsylvania and other agencies under the general supervision of William H. Werkheiser, District Chief, Pennsylvania District; Robert A. Hainly, Assistant District Chief for Hydrologic Surveillance and Data Management; Randall R. Durlin, Chief of the Hydrologic Surveillance Program, Lemoyne District Office, and William P. Schaffstall, Chief, Williamsport Project Office. It is the product of a team effort by dedicated personnel of the U.S. Geological Survey who collected, compiled, analyzed, verified, and organized these data, and who typed, edited, and assembled the report. In addition to the authors, who had primary responsibility for assuring that the information contained herein is accurate, complete, and adheres to Geological Survey policy and established guidelines, the following individuals contributed significantly to the collection, processing, and tabulation of these data:

M. R. Beaver	J. D. Hollenbach	C. J. Rowland
J. K. Bender	K. S. Housel	C. L. Schreffler
R. T. Campbell	J. V. Irvin	L. A. Senior
J. J. Chaplin	M. E. Jones	D. A. Town
C. A. Cravotta	D. G. Kelley	K. E. Tuers
J. T. Fisher	A. G. Reif	M. V. Truhlar
D. R. Galeone	J. D. Riggle	J. B. Weitzel
J. S. Grover	J. J. Rote	N. J. Weisbeker

CONTENTS

	Page
Preface	iii
List of surface-water stations, in downstream order, for which records are published in this volume	vii
List of ground-water wells, by county, for which records are published in this volume	x
List of discontinued continuous-record surface-water discharge stations	xii
List of discontinued continuous-record surface-water-quality stations	xv
Pennsylvania District office locations and addresses	xx
Introduction	1
Cooperation	1
Summary of hydrologic conditions	3
Surface water	3
Water quality	8
Ground water	9
References	9
Special networks and programs	11
Explanation of the records	11
Station identification numbers	12
Downstream-order system	12
Latitude-longitude system	12
Records of stage and water discharge	13
Data collection and computation	13
Data presentation	14
Station manuscript	14
Data table of daily mean values	15
Statistics of monthly mean data	15
Summary statistics	15
Identifying estimated daily discharge	17
Accuracy of the records	17
Other records available	17
Records of surface-water quality	17
Classification of records	17
Arrangement of records	18
On-site measurements and sample collection	18
Water temperature	18
Sediment	18
Laboratory measurements	19
Data presentation	19
Remark codes	20
Water quality-control data	20
Records of ground-water levels	21
Data collection and computation	21
Data presentation	21
Data table of water-levels	22
Records of ground-water quality	22
Data collection and computation	22
Data presentation	23
Access to USGS Water Data	23
Definition of terms	24
Publications on Techniques of Water-Resources Investigations	34
Special Notes, Remark Codes, and Selected Constituent Definitions	44

CONTENTS--Continued

	Page
Station records, surface water	
Continuous water-discharge and water-quality station records	46
Discharge at partial-record stations and miscellaneous sites	
Crest-stage partial-record stations	388
Miscellaneous sites	390
Analyses of samples collected at special-study stations	
Spectral reflectance project	392
Stream conditions of Chester County biological monitoring network	396
Source and extent of fecal coliform bacteria in the Brandywine Creek and its tributaries	422
Delaware River Basin NAWQA project	428
Special Notes, Remark Codes, and Selected Constituent Definitions	484
Station records, ground water	
Water-level and water-quality	486
Index	566

ILLUSTRATIONS

Figure 1.--Comparison of monthly precipitation in the Delaware River Basin at Pleasant Mount and Allentown, Pa. during the 1999 water year with mean monthly precipitation for the period 1961 through 1990	4
2.--Comparison of streamflow at two long-term streamflow-gaging stations during the 1999 water year with the median monthly and annual mean streamflow for the period 1961 through 1990	6
3.--Monthly mean specific conductance measured in the Delaware River at Reedy Island Jetty, De. for the 1999 water year and the mean monthly specific conductance for the period 1965 through 1998	8
4.--Relation between 1999 seasonal ground-water levels and long-term ground-water levels	10
5.--System for numbering wells and miscellaneous sites	12
6-14.--Maps showing:	
6.--Location of continuous-record data-collection stations in the upper Delaware River Basin	38
7.--Location of continuous-record data-collection stations in the lower Delaware River Basin	39
8.--Location of partial-record data-collection stations in the upper Delaware River Basin	40
9.--Location of partial-record data-collection stations in the lower Delaware River Basin	41
10.--Location of stations in the Delaware River Basin National Water-Quality Assessment Program surface-water fixed site network	42
11.--Location of Delaware River Basin National Water-Quality Assessment Program bed-sediment sampling sites	435
12.--Location of Delaware River Basin National Water-Quality Assessment Program fish-tissue sampling sites	455
13.--Location of Delaware River Basin National Water-Quality Assessment Program fish-community sampling sites	469
14.--Location of Delaware River Basin National Water-Quality Assessment Program synoptic sites	472

TABLES

Table 1. Spectral reflectance project station list	393
2. Stream conditions of Chester County biological monitoring network station list	396
3. Delaware River Basin NAWQA project site descriptions	433

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

[Letters after station name designate type of data: (d) discharge, (c) chemical, (sc) specific conductance, (pH), (t) water temperature, (do) dissolved oxygen, (s) sediment, (b) biological (e) elevation, gage heights, or contents.]

NORTH ATLANTIC SLOPE BASINS

	Station number	Page
DELAWARE RIVER BASIN		
West Branch Delaware River at Hancock, N.Y. (t)	01427000	46
Delaware River at Callicoon, N.Y. (d,t)	01427510	48
Delaware River above Lackawaxen River near Barryville, N.Y. (d,t)	01428500	52
LACKAWAXEN RIVER BASIN		
West Branch Lackawaxen River near Aldenville (d,t)	01428750	56
West Branch Lackawaxen River at Prompton (d,t)	01429000	60
Dyberry Creek near Honesdale (d)	01429500	64
Lackawaxen River near Honesdale (d)	01430000	66
Lackawaxen River at Hawley (d)	01431500	68
Wallenpaupack Creek:		
Wallenpaupack Creek at Wilsonville (d)	01432000	70
Lakes and Reservoirs in Lackawaxen River basin (e)		72
Delaware River at Barryville, N.Y. (t)	01432160	74
Delaware River at Pond Eddy, N.Y. (t)	01432805	76
Delaware River at Port Jervis, N.Y. (d,c,t)	01434000	78
Delaware River at Montague, N.J. (d)	01438500	86
BUSH KILL BASIN		
Bush Kill at Shoemakers (d)	01439500	88
BRODHEAD CREEK BASIN		
Brodhead Creek near Analomink (d)	01440400	90
Brodhead Creek at Minisink Hills (d)	01442500	92
Delaware River at Belvidere, N.J. (d)	01446500	94
LEHIGH RIVER BASIN		
Lehigh River at Stoddartsville (d,t)	01447500	96
Tobyhanna Creek:		
Tunkhannock Creek near Long Pond (d)	01447680	100
Tobyhanna Creek near Blakeslee (d,t)	01447720	102
Lehigh River below Francis E. Walter Reservoir near White Haven (d,t)	01447800	106
Lehigh River at Lehighton (d)	01449000	110
Pohopoco Creek at Kresgeville (d,t)	01449360	112
Pohopoco Creek below Beltzville Lake near Parryville (d,t)	01449800	116
Aquashicola Creek at Palmerton (d)	01450500	120
Lehigh River at Walnutport (d)	01451000	122
Little Lehigh Creek near Allentown (d)	01451500	124
Little Lehigh Creek at Tenth Street Bridge at Allentown (d)	01451650	126
Jordan Creek near Schnecksville (d,c,t)	01451800	128
Jordan Creek at Allentown (d)	01452000	136
Monocacy Creek at Bethlehem (d)	01452500	138
Lehigh River at Bethlehem (d)	01453000	140
Lehigh River at Glendon (d,c,t)	01454700	142
Lehigh River at Easton (sc,pH,t,do)	01454720	150
Lakes and Reservoirs in Lehigh River Basin (e)		158

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

NORTH ATLANTIC SLOPE BASINS--Continued

	Station number	Page
DELAWARE RIVER BASIN --Continued		
TOHICKON CREEK BASIN		
Nockamixon Reservoir near Ottsville (e)	01459350	160
Tohickon Creek Near Pipersville (d)	01459500	162
Delaware River at Trenton, N.J. (d)	01463500	164
NESHAMINY CREEK BASIN		
North Branch Neshaminy Creek below Lake Galena near New Britain (d)	01464645	166
North Branch Neshaminy Creek at Chalfont (d)	01464720	168
Little Neshaminy Creek at Valley Road near Neshaminy (d,c,t)	01464907	170
Neshaminy Creek near Langhorne (d)	01465500	180
POQUESSING CREEK BASIN		
Poquessing Creek at Grant Avenue, Philadelphia (d)	01465798	182
PENNYPACK CREEK BASIN		
Pennypack Creek at Lower Rhawn Street Bridge, Philadelphia (d)	01467048	184
FRANKFORD CREEK BASIN		
Frankford Creek at Castor Avenue, Philadelphia (d)	01467087	186
Delaware River at Benjamin Franklin Bridge at Philadelphia (sc,pH,t,do)	01467200	188
SCHUYLKILL RIVER BASIN		
Schuylkill River at Landingville (d)	01468500	198
Little Schuylkill River at Tamaqua (d)	01469500	200
Schuylkill River at Berne (d)	01470500	202
Tulpehocken Creek near Bernville (d,c,t)	01470779	204
Spring Creek:		
Furnace Creek at Robesonia (d)	01470853	216
Tulpehocken Creek at Blue Marsh damsite near Reading (d,t)	01470960	218
Blue Marsh Reservoir Intake (c)	01470962	222
Tulpehocken Creek near Reading (d)	01471000	224
Schuylkill River at Reading (d)	01471510	226
Manatawny Creek near Spangsville (d)	01471875	228
Manatawny Creek near Pottstown (d)	01471980	230
Schuylkill River at Pottstown (d)	01472000	232
Schuylkill River at Vincent Dam at Linfield (t,do)	01472104	234
French Creek near Phoenixville (d,c,b,t)	01472157	238
Perkiomen Creek at East Greenville (d)	01472198	250
West Branch Perkiomen Creek at Hillegass (d)	01472199	252
East Branch Perkiomen Creek near Dublin (d)	01472620	254
East Branch Perkiomen Creek near Schwenksville (d)	01472810	256
Perkiomen Creek at Graterford (d)	01473000	258
Valley Creek at Pennsylvania Turnpike Bridge near Valley Forge (d,c,b)	01473169	260
Wissahickon Creek at mouth, Philadelphia (d)	01474000	264
Schuylkill River at Philadelphia (d,c,sc,t)	01474500	266
Lakes and Reservoirs in Schuylkill River Basin (e)		278
Delaware River at Fort Mifflin at Philadelphia (sc,t)	01474703	280
CRUM CREEK BASIN		
Crum Creek near Newtown Square (d,c,b)	01475850	286
RIDLEY CREEK BASIN		
Ridley Creek at Media (d)	01476480	292
CHESTER CREEK BASIN		
Chester Creek near Chester (d)	01477000	294
Delaware River at Chester (sc,pH,t,do)	01477050	296

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

NORTH ATLANTIC SLOPE BASINS--Continued

	Station number	Page
DELAWARE RIVER BASIN --Continued		
CHRISTINA RIVER BASIN		
White Clay Creek:		
White Clay Creek near Strickersville (d)	01478245	306
Unnamed Pond above Unnamed Tributary to West Branch Red Clay Creek at Kennett Square (c)	01479677	308
Unnamed Tributary to West Branch Red Clay Creek at Kennett Square (d,c)	01479678	310
Red Clay Creek near Kennett Square (d)	01479820	314
Brandywine Creek:		
West Branch Brandywine Creek near Honey Brook (d,c,b)	01480300	316
Birch Run near Wagontown (d,c,b,t)	01480400	324
West Branch Brandywine Creek at Coatesville (d,c,b,t)	01480500	330
West Branch Brandywine Creek at Modena (d,c,b,sc,pH,t,do)	01480617	336
East Branch:		
Marsh Creek near Glenmoore (d,c,b)	01480675	347
Marsh Creek near Downingtown (d,c,b)	01480685	350
East Branch Brandywine Creek near Downingtown (d,c,b)	01480700	353
East Branch Brandywine Creek below Downingtown (d,c,b,sc,pH,t,do)	01480870	356
Brandywine Creek at Chadds Ford (d,c,b,sc,pH,t,do)	01481000	367
Lakes and Reservoirs in Christina River Basin (e)		376
Delaware River at Reedy Island Jetty, Del. (sc,pH,t,do)	01482800	378
Discharge at partial-record stations and miscellaneous sites		
Crest-stage partial-record stations		388
Miscellaneous sites		390
Analysis of samples collected at special-study sites		
Spectral reflectance project		392
Stream conditions of Chester County biological monitoring network		396
Source and extent of fecal coliform bacteria in the Brandywine Creek and its tributaries		422
Delaware River Basin NAWQA project		428

GROUND-WATER WELLS, BY COUNTY, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

[Letters after local well number designate type of data: (l) water level, (c) chemical.]

GROUND-WATER RECORDS

	Page
BERKS COUNTY	
Well 402615075530501 Local number BE 623 (l)	486
BUCKS COUNTY	
Well 402643075150501 Local number BK 929 (l)	487
Well 401157075032001 Local number BK 1020 (l)	488
CARBON COUNTY	
Well 410123075425401 Local number CB 104 (l)	489
CHESTER COUNTY	
Well 400650075514001 Local number CH 2 (l)	491
Well 395450075485401 Local number CH 10 (l)	490
Well 395717075392301 Local number CH 12 (l)	491
Well 395222075423201 Local number CH 28 (l)	491
Well 394846075444901 Local number CH 38 (l)	492
Well 400400075314401 Local number CH 89 (l)	492
Well 400453075255601 Local number CH 210 (l)	492
Well 400103075390101 Local number CH 249 (l)	493
Well 394457075581601 Local number CH 254 (l)	493
Well 395701075561601 Local number CH 1201 (l)	493
Well 400412075404301 Local number CH 1229 (l)	494
Well 400645075411501 Local number CH 1247 (l)	494
Well 395540075332601 Local number CH 1387 (l)	494
Well 400956075391501 Local number CH 1571 (l)	495
Well 394757075432101 Local number CH 1921 (l)	495
Well 400242075484301 Local number CH 2273 (l)	495
Well 400325075332501 Local number CH 2313 (l)	496
Well 400847075414701 Local number CH 2328 (l)	496
Well 400133075450001 Local number CH 2456 (l)	496
Well 400039075335201 Local number CH 2457 (l)	497
Well 400456075320301 Local number CH 2561 (l)	497
Well 394624075444001 Local number CH 2663 (l)	497
Well 400358075311301 Local number CH 3289 (l)	498
Well 395045075434701 Local number CH 5172 (l,c)	499
Well 395045075434702 Local number CH 5173 (l,c)	503
Well 395048075434701 Local number CH 5174 (l,c)	507
Well 395048075434702 Local number CH 5175 (l,c)	511
Well 395052075434501 Local number CH 5176 (l,c)	515
Well 395052075434502 Local number CH 5177 (l,c)	519
Well 395049075434301 Local number CH 5178 (l,c)	523
Well 395049075434302 Local number CH 5179 (l,c)	527
Well 395052075434201 Local number CH 5181 (l,c)	531
Well 395043075440701 Local number CH 5182 (l,c)	535
Well 395043075440702 Local number CH 5183 (l,c)	539
DELAWARE COUNTY	
Well 395040075341801 Local number DE 3 (l)	543
Well 395512075293701 Local number DE 723 (l)	544
LEBANON COUNTY	
Well 402207076180801 Local number LB 372 (l)	545
LEHIGH COUNTY	
Well 403429075392401 Local number LE 644 (l)	546
MONROE COUNTY	
Well 411223075234901 Local number MO 190 (l)	547

GROUND-WATER WELLS, BY COUNTY, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

GROUND WATER RECORDS--Continued

	Page
MONTGOMERY COUNTY	
Well 401456075173001 Local number MG 67 (l)	548
Well 401415075175101 Local number MG 68 (l)	550
Well 401442075171501 Local number MG 81 (l)	552
Well 401523075171801 Local number MG 82 (l)	554
Well 400808075210401 Local number MG 225 (l)	556
Well 401506075163501 Local number MG 618 (l)	557
Well 401532075170801 Local number MG 704 (l)	559
Well 401733075171401 Local number MG 917 (l)	561
PHILADELPHIA COUNTY	
Well 395342075102101 Local number PH 12 (l)	562
PIKE COUNTY	
Well 410940074583401 Local number PI 200 (l)	563
SCHUYLKILL COUNTY	
Well 404708076070701 Local number SC 296 (l)	564
WAYNE COUNTY	
Well 414333075153201 Local number WN 64 (l)	565

The following continuous-record surface-water discharge stations (listed by river basin in alphabetical order by stream name) have been discontinued. Daily streamflow records were collected and published for the period of record shown for each station. Discontinued stations with less than 3 years of record have not been included. Information regarding these stations may be obtained from the District Office at the address given on the back of the title page of this report.

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS

Station name	Station number	Drainage area (mi ²)	Period of record (water years)
DELAWARE RIVER BASIN			
Ariel Creek near Ledgedale	01431673	15.6	1992-94
Byberry Creek at Chalfont Road, Philadelphia	01465790	5.34	1966-77
Byberry Creek at Grant Avenue, Philadelphia	01465795	7.13	1965-70
Cobbs Creek at Darby	01475550	22.0	1964-90
Cobbs Creek at US Highway No. 1 at Philadelphia	01475530	4.78	1965-80
Cobbs Creek below Indian Creek near Upper Darby	01475540	10.6	1965-73
Cooks Creek at Durham Furnace	01457790	29.4	1991-93
Cooks Run at New Britain	01464741	3.08	1985-89
Crum Creek at Woodlyn	01476000	33.3	1932-37
Darby Creek at Waterloo Mills near Devon	01475300	5.1	1972-97
Darby Creek near Darby	01475510	37.4	1964-90
Delaware River below Tocks Island Damsite, near Delaware Water Gap	01440200	3,850	1964-96
Dilldown Creek near Long Pond	01448500	2.39	1949-96
East Branch Brandywine Creek at Downingtown	01480800	81.6	1958-68
East Branch Monocacy Creek near Bath	01452300	5.35	1963-68
Frankford Creek at Torresdale Avenue, Philadelphia	01467089	33.8	1967-80
Jenkintown Creek at Elkins Park	01467085	1.17	1974-78
Lackawaxen River at West Hawley	01430500	206	1922-37
Lehigh River at Tannery	01448000	322	1919-58
Little Lehigh Creek near East Texas	01451420	51.2	1987-94
Little Neshaminy Cr at Walton Road near Jacksonville	01464984	40.1	1986-92
Little Schuylkill River at Drehersville	01470000	122	1948-50,1964-65
Maiden Creek Tributary at Lenhartsville	01470720	7.46	1966-79
Maiden Creek at Virginville	01470756	159	1973-94
Marsh Creek near Lyndell	01480680	17.8	1961-69
Martins Creek near East Bangor	01446600	10.4	1962-77
McMichaels Creek at Stroudsburg	01441000	65.3	1912-37
Middle Creek near Hawley	01431000	78.4	1945-59

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS (Continued)

Station name	Station number	Drainage area (mi ²)	Period of record (water years)
Mill Creek near Wycombe	01465050	14.0	1990-93
Naylor Creek at West Chester Pike near Philadelphia	01475545	1.10	1974-78
Neshaminy Creek at Rushland	01465000	134	1885-1912,32-33
Neshaminy Creek near Rushland	01464750*	91.0	1987-92
North Branch Calkins Creek near Damascus	01427650	7.02	1965-73
Paunacussing Creek at Carversville	01460800	6.49	1991-93
Pennypack Creek at Pine Road, Philadelphia	01467042	37.9	1965-80
Pennypack Creek below Verree Road, Philadelphia	01467045	42.8	1965-70
Perkiomen Creek near Frederick	01472500	152	1885-1912
Pickering Creek near Chester Springs	01472174	5.98	1967-82
Pine Run at Chalfont	01464710	11.6	1990-92
Pocono Creek near Stroudsburg	01441500	41.0	1912-19
Pohopoco Creek near Parryville	01450000	109	1941-69
Poquessing Creek at Trevoise Road, Philadelphia	01465780	13.2	1965-70
Purdy Creek at Lakeville	01431685	8.18	1992-94
Ridley Creek at Media	01476480	30.5	1987-95
Ridley Creek at Moylan	01476500	31.9	1932-54
Rock Creek above Curtis Arboretum near Philadelphia	01467084	1.15	1972-78
Saucon Creek at Friedensville	01454500	26.6	1948-53
Saucon Creek at Lanark	01453500	12.1	1948-53
Schuylkill River above Passayunk Ave. at Philadelphia	01474505	1,900	1979-93
Schuylkill River at Norristown	01473500	1,760	1928-32
Schuylkill River at Pottsville	01467500	53.4	1944-69
Shohola Creek near Shohola	01432500	83.6	1920-28
Skippack Creek near Collegeville	01473120	53.7	1966-94
South Branch Saucon Creek at Friedensville	01454000	10.3	1948-53
Stevens Creek near Sterling	01431620	0.68	1992-94
Tacony Creek above Adams Avenue, Philadelphia	01467086	16.7	1966-86
Tacony Creek near Jenkintown	01467083	5.25	1973-78
Tinicum Creek near Ottsville	01458900	14.7	1991-93
Tohickon Creek at Point Pleasant	01460000	107	1884-98,1901-12
Unnamed tributary to Purdy Creek near Lakeville	01431683	0.34	1992-94

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS (Continued)

Station name	Station number	Drainage area (mi ²)	Period of record (water years)
Valley Creek at Ravine Road near Downingtown	01480887	14.5	1990-97
Walton Run at Philadelphia	01465785	2.17	1965-77
Wild Creek at Hatchery	01449500	16.8	1941-78
Wissahickon Creek at Bells Mill Road, Philadelphia	01473950	53.6	1966-70,1974-81
Wissahickon Creek at Fort Washington	01473900	40.8	1962-68
Wissahickon Creek at Livezey Lane, Philadelphia	01473980	59.2	1967-70
Wooden Bridge Run at Philadelphia	01467050	3.35	1966-80

* Currently operated as a partial-record station.

The following continuous-record water-quality stations (listed in alphabetical order by stream name) have been discontinued. Daily records were collected and published for the period shown for each constituent. Discontinued stations with less than 3 years of record, or stations with data collection less than daily, have not been included. If a station had one constituent with 3 or more years of record, all constituents having daily values will be listed for that station regardless of the length of record. Information regarding these stations may be obtained from the District Office at the address given on the back of the title page of this report.

The following are used to identify the record type: SC (specific conductance); pH; Temp (water temperature); DO (dissolved oxygen); Turb (Turbidity); Sed (sediment concentration and discharge); Biol (biological); --- (not determined).

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS

Station name	Station number	Drainage area (mi ²)	Type of Record	Period of record (water years)
DELAWARE RIVER BASIN				
Brandywine Creek at Chadds Ford	01481000	287	Sed	1963-70
Byberry Creek at Chalfont Road, Philadelphia	01465790	5.34	Sed	1966-68,1970
Byberry Creek at Grant Avenue, Philadelphia	01465795	7.13	Sed	1965-70
Cobbs Creek at US Highway 1 near Philadelphia	01465530	4.78	Sed	1965-70
Cobbs Creek below Indian Creek near Upper Darby	01475540	9.65	Sed	1965-69
Cobbs Creek at Darby	01475550	22.0	Sed	1965-69
Crum Creek near Paoli	01475830	6.16	Biol	1970-83
Darby Creek near Darby	01475510	37.4	Sed	1965-69
Delaware River at Belvidere, N.J.	01448000	4,535	Temp SC	1944-47, 1962-63 1962-63
Delaware River at Burlington-Bristol Bridge	01464600	7,163	Temp DO SC,pH	1954-75, 1979-80 1961-75, 1978-80 1967-75, 1978-80
Delaware River at Delaware Memorial Bridge, Del.	01482100	11,030	Temp DO SC pH	1956-81 1962-81 1963-81 1968-81
Delaware River at Dingmans Ferry	01439000	3,542	Temp,SC,pH	1950-53
Delaware River at Dunnfield, N.J.	01442750	4,120	Sed	1964-75
Delaware River at Easton	01446700	4,636	SC,DO,Temp,pH	1967-77
Delaware River at Eddystone	01476200	10,190	SC,DO,Temp,pH	1949-68
Delaware River at League Island, Philadelphia	01467400	8,072	SC,DO,Temp,pH	1949-68
Delaware River at Lehigh Avenue, Philadelphia	01467100	7,935	SC,DO,Temp,pH	1949-68
Delaware River at Lordville, N.Y.	01427207	1,590	Temp	1968-71, 1973-96
Delaware River at Marcus Hook	01477200	10,370	SC,DO,Temp,pH	1949-77

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS (Continued)

Station name	Station number	Drainage area (mi ²)	Type of Record	Period of record (water years)
Delaware River at Montague, N.J.	01438500	3,480	Temp SC,pH	1956-57 1956-73
Delaware River at Narrowsburg, N.Y.	01427740	2,023	SC,pH	1948-51
Delaware River at Palmyra, N.J.	01467060	7,850	Sed	1962-64
Delaware River at Port Jervis, N.Y.	01434000	3,070	Temp	1957-60, 1973-94
Delaware Bay at Ship John Shoal Light, N.J.	01412350	---	SC,Temp	1968-86
Delaware River at Torresdale Intake, Philadelphia	01467030	7,781	Temp DO SC pH	1956-57, 1960-81 1961-81 1963-81 1968-81
Delaware River at Wharton Street, Philadelphia	01467300	7,998	Temp,SC,pH,DO	1949-68
Delaware River near East Stroudsburg	01440090	3,830	SC,DO,Temp pH	1966-78 1972-78
East Branch Brandywine Creek near Struble Dam	01480647	4.36	Biol	1972-82
Frankford Creek at Torresdale Avenue, Philadelphia	01467088	33.8	Sed	1966-70
French Creek at Trythall	01472126	5.06	Biol	1971-83
French Creek near Knauertown	01472129	11.7	Biol	1970-83
Jordan Creek at Allentown	01452000	75.8	Sed	1967-69
Jordan Cfreek near Schnecksville	01451800	53.0	Sed	1967-69
Lehigh River at Bethlehem	01453000	1,279	SC,pH	1906-07, 1956-72
Lehigh River at Walnutport	01451000	889	Sed	1948-53
Little Schuylkill River at Drehersville	01470000	122	SC,pH,Temp,Sed	1947-51, 1963-65
Little Schuylkill River at South Tamaqua	01469700	65.7	SC,pH Sed	1948-51,1963 1950-53,1963
Maiden Creek near East Berkley	01470760	192	Sed	1963-65
Maiden Creek tributary at Lenhartsville	01470720	7.46	Sed	1963-65
Marsh Creek near Downingtown	01480695	20.3	Temp	1973-87
Marsh Creek near Lyndell	01480680	17.8	Temp Sed	1965-66 1965-66,1968
Neshaminy Creek near Langhorne	01465500	210	Sed	1956-58, 1965-69
Pennypack Creek at Pine Road, Philadelphia	01467042	37.9	Sed	1965-69
Pennypack Creek below Verree Road, Philadelphia	01467045	42.8	Sed	1965-69

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS (Continued)

Station name	Station number	Drainage area (mi ²)	Type of Record	Period of record (water years)
Perkiomen Creek at Graterford	01473000	279	SC,pH,Temp Sed	1946-51, 1948-53 1963-66
Pickering Creek near Chester Springs	01472174*	5.98	Sed	1967-69
Pigeon Creek at Porters Mill	01472065	6.97	Biol	1970-83
Pigeon Creek near Bucktown	01472054	4.20	Biol	1970-83
Poquessing Creek above Byberry Creek, Philadelphia	01465780	13.2	Sed	1965-70
Poquessing Creek at Grant Avenue, Philadelphia	01465798	21.4	Sed	1965-70
Poquessing Creek at Trevoise Road, Philadelphia	01465770	5.08	Sed	1965-69
Schuylkill River at Auburn	01469000	160	Sed,SC,pH	1947-51, 1963-65
Schuylkill River at Berne	01470500	355	Temp SC,pH Sed	1948-53, 1957-81 1963-81 1947-81
Schuylkill River at Black Rock Dam at Mont Clare	01472119	---	SC,DO	1986-90
Schuylkill River at Flat Rock Dam at West Manayunk	01473780	---	SC,DO	1985-90
Schuylkill River at Landingville	01468500	133	SC,pH,Temp Sed	1947-53 1947-53, 1963-65
Schuylkill River at Manayunk	01473800	893	SC,pH Sed Temp	1947-70 1947-86 1956-70
Schuylkill River at Norristown Dam at Bridgeport	01473499	---	SC,DO	1985-90
Schuylkill River at Plymouth Dam	01473675	---	SC,DO	1985-90
Schuylkill River at Port Carbon	01467470	27.1	SC,pH,Sed	1949-51,1963
Schuylkill River at Pottstown	01472000	1,147	Temp Sed,pH SC	1944-51, 1956, 1963-66 1948-51, 1963-66 1948-51, 1963-66, 1985-89
Schuylkill River at Pottsville	01467500	53.4	SC,pH Sed	1948-51, 1963-66 1963-66
Stony Run at Spring City	01472110	4.07	Biol	1970-83
Tacony Creek at County Line, Philadelphia	01467084	16.2	Sed	1966-69
Tulpehocken Creek near Reading	01471000	211	Sed	1963-65

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS (Continued)

Station name	Station number	Drainage area (mi ²)	Type of Record	Period of record (water years)
Wissahickon Creek at Bells Mill Road, Philadelphia	01473950	53.6	Sed	1966-69
Wissahickon Creek at Fort Washington	01473900	40.8	Sed	1963-69
Wissahickon Creek at Livezey Lane, Philadelphia	01473980	59.2	Sed	1966-69
Wissahickon Creek at mouth, Philadelphia	01474000	64.0	Sed	1966-69
Walton Run at Philadelphia	01465785	2.17	Sed	1965-68
West Branch Brandywine Creek near Honey Brook	01480300	18.7	Sed	1965-66,1968
West Branch Schuylkill River at Cressona	01467950	52.5	Sed	1963-66
Wooden Bridge Run at Philadelphia	01467049	3.35	Sed	1965-70

* Currently operated as a partial-record station.

INTRODUCTION

The Water Resources Division of the U.S. Geological Survey, in cooperation with State, municipal, and Federal agencies, collects a large amount of data pertaining to the water resources of Pennsylvania each water year. These data, accumulated during many water years, constitute a valuable data base for developing an improved understanding of the water resources of the State. To make these data readily available to interested parties outside the Geological Survey, these data are published annually in this report series entitled "Water Resources Data - Pennsylvania, Volumes 1, 2, and 3." Volume 1 contains data for the Delaware River Basin; Volume 2, the Susquehanna and Potomac River Basins; and Volume 3, the Ohio River and St. Lawrence River Basins.

This report, Volume 1, contains: (1) discharge records for 74 continuous-record streamflow-gaging stations, 7 partial-record stations, and 13 special study and miscellaneous streamflow sites; (2) elevation and contents records for 14 lakes and reservoirs; (3) water-quality records for 29 gaging stations and 11 ungaged streamsites; (4) water-quality records for 87 special-study stations; (5) water-level records for 55 network observation wells; and (6) water-quality analyses of ground water from 11 ground-water wells. Additional water data collected at various sites not involved in the systematic data-collection program may also be presented.

Publications similar to this report are published annually by the Geological Survey for all States. For the purpose of archiving, these official reports have an identification number consisting of the two-letter State abbreviation, the last two digits of the water year, and the volume number. For example, this volume is identified as "U.S. Geological Survey Water-Data Report PA-99-1." These water data reports, beginning with the 1971 water year, are for sale as paper copy or microfiche by the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The annual series of Water Data Reports for Pennsylvania began with the 1961 water-year report and contained only data relating to quantities of surface water. With the 1964 water year, a companion report (part 2) was introduced that contained only data relating to water quality. Beginning with the 1975 water year the report was changed to its present format of three volumes (by river basin), with each volume containing data on quantities of surface water, quality of surface and ground water, and ground-water levels.

Prior to the introduction of this series and for several years concurrent with it, water-resources data for Pennsylvania were published in U.S. Geological Survey Water-Supply Papers. Data on stream discharge and stage, and on lake or reservoir contents and stage, through September 1960, were published annually under the title "Surface-Water Supply of the United States," which was released in numbered parts as determined by natural drainage basins. For the 1961-70 water years, these data were published in two 5-year reports. Data prior to 1961 are included in two reports: "Compilation of Records of Surface Waters of the United States through 1950," and "Compilation of Records of Surface Waters of the United States, October 1950 to September 1960." Data for Pennsylvania are published in Parts 1, 3, and 4. Data on chemical quality, temperature, and suspended sediment for the 1941-70 water years were published annually under the title "Quality of Surface Waters of the United States," and ground-water levels for the 1935-74 water years were published under the title "Ground-Water Levels in the United States." The above mentioned Water-Supply Papers may be consulted in the libraries of the principal cities of the United States and may be purchased from the U.S. Geological Survey, Information Services, Box 25286, Denver, CO 80225.

Information for ordering specific reports may be obtained from the Pennsylvania District Office at the address given on the back of the title page or by phoning the Scientific and Technical Products Section, at (717) 730-6940. Information on the availability of unpublished data or statistical analyses may be obtained from the District Information Specialist by telephone at (717) 730-6916 or by FAX at (717) 730-6997.

COOPERATION

The U.S. Geological Survey (USGS) and organizations of the Commonwealth of Pennsylvania have had cooperative agreements for the systematic collection of surface-water records during the periods 1919-21 and 1931 to date, water-quality records from 1944 to date, and ground-water records from 1925 to date. Organizations that supplied data are acknowledged in station manuscripts. Organizations that assisted in collecting data for this report through cooperative agreements with the USGS are listed below.

The Commonwealth of Pennsylvania, Department of Environmental Protection, James M. Seif, Secretary through the following:
Office of Water Management, Lawrence C. Tropea, Jr., Deputy Secretary;
Bureau of Water Supply Management, Frederick Marrocco, Acting Director;
Bureau of Water Quality Protection, Frederick Marrocco, Acting Director;
Bureau of Watershed Conservation, Stuart I. Gansell, Director;
Bucks County Commissioners, Michael G. Fitzpatrick, Chairman;
Chester County Water Resources Authority, Janet L. Bowers, Executive Director;
City of Allentown, William L. Heydt, Mayor;
City of Bethlehem, Donald T. Cunningham, Jr., Mayor;
City of Philadelphia, Water Department, Kumar Kishinchand, Water Commissioner;
Delaware County Solid Waste Authority, Joseph W. Vasturia, Chief Executive Officer;

COOPERATION--Continued

Delaware River Basin Commission, Carol R. Collier, Executive Director;
Doylestown Township Municipal Authority, Richard E. John, Director of Operations;
Hazelton City Authority, Water Department, Randy J. Cahalan, Operation Manager;
North Penn Water Authority, Anthony J. Bellitto, Jr., Executive Director;
North Wales Water Authority, Peter. S. Lukens, Executive Director;
Forest Park Water Company;

Federal Energy Regulatory Commission Licensee:
 Pennsylvania Power and Light Company,

The following Federal agency assisted in the data-collection program by providing funds or services: Corps of Engineers, U.S. Army, Philadelphia District.

The following organizations aided in collecting records: Palmer Water Company, Philadelphia Suburban Water Company, Borough of Tamaqua, Womelsdorf-Robeson Joint Water Authority, and the City of Coatesville.

SUMMARY OF HYDROLOGIC CONDITIONS

Surface Water

The Delaware River Basin extends from the river's east and west branch headwaters in the New York Catskill Mountains southward about 400 miles to the Atlantic Ocean. In addition to Pennsylvania, the Delaware River drains parts of the states of New York, New Jersey, Delaware, and Maryland. Of the nearly 13,500-mi² (square mile) drainage basin, 6,420 mi² (50 percent of the basin's total area) are within the Commonwealth of Pennsylvania.

Precipitation and Streamflow

Precipitation and streamflow for the 1999 water year reached both maximum and minimum extremes. Data from 34 selected National Oceanic and Atmospheric Administration climatological sites, located within 3 climatological regions in the Delaware River Basin in Pennsylvania, indicate the annual total precipitation for the Delaware River Basin in Pennsylvania was slightly below average. Annual precipitation at two index stations in the Delaware River Basin (fig. 1) was about 10 percent less than average.

The 1999 monthly precipitation was compared with the 1961-90 mean monthly precipitation recorded at Pleasant Mount and Allentown, Pennsylvania (fig. 1). The precipitation data are from the National Oceanic and Atmospheric Administration (U.S. Department of Commerce, 1998-99) and National Weather Service records. The basin generally received below normal precipitation for all months except October, January, March, and September. The greatest deficit basinwide, with an average of 2.78 inches below normal, was in July. During three other months--November, December, and June, the basinwide precipitation deficit was greater than 2 inches. Based on 105 years of record, the precipitation received in the months of December, June, and July ranked in the top ten of the least ever recorded for those months.





Figure 1.--Comparison of monthly precipitation in the Delaware River Basin at Pleasant Mount and Allentown, Pa. during the 1999 water year with mean monthly precipitation for the period 1961 through 1990.

On the contrary, the month of September ranked as the wettest ever recorded during the last 105 years. In mid-September, Hurricane Floyd passed through the middle and lower Delaware River Basin leaving behind anywhere from 6 to 10 inches of precipitation. Some localized rainfall amounts as high as 12 inches were measured. For the month, average precipitation in most of the Delaware River Basin was 6 to 8 inches above normal. This record precipitation in September provided the beginning of recovery from one of the worst droughts in modern Pennsylvania history.

Streamflow varied seasonably throughout the basin and generally reflected the precipitation patterns within the basin unless the stream was regulated. Following a pattern defined by the much below and much above normal precipitation that fell in the basin during the 1999 water year, the mean annual streamflow for unregulated Delaware River Basin streams during the 1999 water year was generally below normal. (Normal annual streamflows are defined as streamflows between the 25th and 75th percentiles as compared to the annual mean streamflows for 1961-90.) Also as a result of precipitation variations, some record minimum monthly streamflows and record maximum peak streamflows were observed during the year.

Two U.S. Geological Survey streamflow-gaging stations within the basin were selected as indicators of basinwide streamflow conditions. Figure 2 compares the 1999 water year monthly and annual mean streamflows with the median of the monthly and annual mean streamflows for 1961 through 1990 at the indicator sites. The 1999 water year annual mean streamflow of the Bush Kill at Shoemakers in the upper Delaware River Basin was about 60 percent of the 1961-90 median of the mean annual streamflows. The mean annual streamflow of the Schuylkill River at Philadelphia in the lower Delaware River Basin was about 90 percent of the 1961-90 median of the mean annual streamflows. In the Schuylkill River Basin, streamflows are regulated. The higher flows near the mouth of the Schuylkill River at Philadelphia are partially a result of flows released by upstream reservoirs.





Figure 2.--Comparison of streamflow at two long-term streamflow-gaging stations during the 1999 water year with the median monthly and annual mean streamflow for the period 1961 through 1990.

Monthly streamflows were below to much below the median of monthly mean streamflows in the Bush Kill for the entire water year, with the exception of the months of January, February, and September (fig. 2). The monthly mean streamflows recorded in December and July were the lowest ever measured since record began in 1909. Monthly streamflows were below the median of monthly mean streamflows in the Schuylkill River at Philadelphia for the entire water year, with the exception of the months of October, January, and September (fig. 2). Streamflows measured during the low-flow periods in the fall and summer were not record low flows. Once again, streamflows augmented by impoundment releases in the Schuylkill River basin probably contributed to higher flows than those measured during the drought in the mid-1960's.

The Governor of Pennsylvania made several Drought Declarations during the 1999 water year. Beginning in early December 1998, all counties within the Delaware River Basin were placed into the first of three drought conditions--a "drought watch" status. By mid-December, water-supply conditions had degraded a sufficient amount for all Delaware River Basin counties to be placed in a "drought warning" status. The declaration was upgraded to a "drought watch" status in March following normal precipitation amounts during late winter. Below normal precipitation in early spring created streamflow and ground-water conditions that resulted in a "drought warning" status once again over the entire basin. By mid-July, the situation had degraded to a point where the entire basin was placed in the most severe status--a "drought emergency", which requires water use restrictions. In part, as a result of the precipitation from Hurricane Floyd, the emergency condition was removed at the end of September (Pennsylvania Department of Environmental Protection, 1999).

Reservoirs

Total combined capacity of the major reservoirs in the Delaware River Basin within Pennsylvania is 659,390 acre-feet. Total combined drainage areas into these reservoirs is about 1,130 square miles or 18 percent of the total drainage area in the Delaware River Basin. Combined storage in 13 major reservoirs in the Delaware River Basin within Pennsylvania increased significantly from 194,224 acre-feet (29.5 percent of total combined capacity) on September 30, 1998, to 252,214 acre-feet (38.2 percent of total combined capacity) on September 30, 1999. This relatively large increase in water storage in the basin for the year is largely an artifact of the measures taken by controlled impoundments to store the extreme amount of precipitation received from Hurricane Floyd in mid-September. By the end of the month (and the water year) the additional storage had not yet been entirely released to the streams. A comparison of August 1998 to August 1999 reservoir storage shows relatively little change (about 2.5 percent) on an annual basis.

Water Quality

As part of an ongoing program, the USGS maintains a network of continuous-record water-quality monitoring sites along the Delaware River and its tributaries. Water temperature, dissolved oxygen, pH, and specific conductance are monitored at most sites from April through November. A primary concern to water-resource managers of the lower Delaware River Basin is the upstream migration of saline water from the Delaware Bay. The salinity and dissolved-solid content in the water are indirectly measured by specific conductance.

Water quality of the Delaware Estuary was monitored between Trenton, New Jersey, and Reedy Island Jetty, Delaware. Streamflow is a vital factor that influences the water quality of the estuary. Increased streamflow usually results in better water quality by limiting salt-water intrusion and diluting the concentration of dissolved minerals, both of which contribute to a lower specific conductance and chloride level. Increased freshwater streamflow also aids in maintaining lower water temperature during warm weather and in supporting higher dissolved-oxygen levels.

In general, streamflow for the Delaware River was low in the fall of 1998, near-normal in the winter of 1998-99, and extremely low in the summer of 1999. The highest sustained streamflows occurred in late winter of 1999 and the highest momentary streamflows (peaks) occurred in September 1999. As a result of these streamflows, the specific conductance at the U.S. Geological Survey water-quality monitoring station on the Delaware River at Reedy Island Jetty, Delaware, was lowest in late winter and early spring and highest in late summer.

Figure 3 compares the 1999 water year monthly mean specific conductance with the mean monthly values for the period 1965 through 1998. Except for the month of February, mean monthly values of specific conductance were higher than the mean for the period of record and were generally in the range of values that would be expected only 25 percent of the time. In the months of May, July, August, and September, the mean monthly specific conductance values were the highest ever observed during the 34 years of record. In August, the mean specific conductance value for the month (18,100 microsiemens per centimeter) exceeded the previous high mean (recorded in 1965) by slightly more than 25 percent. The migration of saline water (commonly known as "The Salt Line") reached River Mile 89, which is located near the Philadelphia International Airport. For perspective, the most upstream point of the Salt Line ever recorded (River Mile 102) occurred during the drought of the mid 1960's (Delaware River Basin Commission, 1999). Specific conductance data, along with other water-quality data from the Delaware River at Reedy Island Jetty, Delaware, can be found on pages 378-387.




Figure 3.--Monthly mean specific conductance measured in the Delaware River at Reedy Island Jetty, De. for the 1999 water year and the mean monthly specific conductance for the period 1965 through 1998.

Ground Water

With some lag time, seasonal ground-water levels during the year generally reflect seasonal precipitation variations. A comparison of the monthly precipitation variation received in the Delaware River Basin in the 1999 water year (fig. 1) and recorded ground-water levels shows that this scenario was the case for this year. Ground-water levels, which were generally normal (8 out of 10 observation wells) throughout all of the Delaware River Basin at the end of the 1998 water year (Durlin and Schaffstall, 1999), had fallen sharply into the below-normal range by the end of the fall season of the 1999 water year (October through December 1998). During the fall season, water levels in 7 of the 10 observation wells were either below normal or much below normal. A comparison between seasonal ground-water levels for the 1999 water year and long-term seasonal ground-water levels is shown in figure 4.

During the winter season, with the assistance of near-normal to above-normal precipitation, ground-water levels recovered to the point where water levels in the majority of the observation wells (8 of 10) were normal for that season and water levels in two wells were below normal. Throughout the spring and continuing into summer, ground-water levels gradually declined. By the end of the spring season and into early summer, water levels were generally below normal. Ground-water levels in 7 of the 10 wells were either below normal or much below normal in the spring. In July and August, water levels measured in 6 of the 10 wells were the lowest ever recorded. By the end of September and as a result of Hurricane Floyd, water levels in 8 of the 10 wells were higher than at the end of August, although water levels in two of the wells were still at record lows.

References

Delaware River Basin Commission, 1999, Delaware River Basin Selected Flow and Storage Data, accessed May 4, 2000, at URL <http://www.state.nj.us/drbc/data.htm>

Durlin, R. R., and Schaffstall, W. P., 1999, Water resources data, Pennsylvania, water year 1998: U.S. Geological Survey Water-Data Report PA-98-1, 405 p.

U.S. Department of Commerce, 1998-99, Climatological data for Pennsylvania, Volume 102-103: National Oceanic and Atmospheric Administration, National Environmental Satellite, Data, and Information Service.

Pennsylvania Department of Environmental Protection, 1999, Drought News Room, accessed April 21, 2000, at URL <http://www.dep.state.pa.us/dep/subject/hotopics/drought/news.htm>




Figure 4.--Relation between 1999 seasonal ground-water levels and long-term ground-water levels [Seasonal percentile values were determined by ranking the average monthly water levels for each month in the season from highest to lowest for all years of record and averaging the ranks for the three months. A water level that is higher than the seasonal 10th percentile value would be expected to occur only once in a ten-year period. Conversely, a water level that is lower than the seasonal 90th percentile value also would be expected to occur only once during a ten-year period.]

SPECIAL NETWORKS AND PROGRAMS

The **Hydrologic Bench-Mark Network** is a network of 50 sites in small drainage basins throughout the country that provides consistent data on hydrology, water quality, and related factors in representative undeveloped watersheds nationwide. This network also provides analyses on a continuing basis to compare and contrast conditions observed in basins more obviously affected by human activities. There are no stations in the Delaware River Basin in Pennsylvania participating in this program.

The **National Stream-Quality Accounting Network** (NASQAN) monitors the water quality of large rivers within four of the Nation's largest river basins--the Mississippi, Columbia, Colorado, and Rio Grande. The network consists of 39 stations. Samples are collected with sufficient frequency that the flux of a wide range of constituents can be estimated. The objective of NASQAN is to characterize the water quality of these large rivers by measuring concentration and mass transport of a wide range of dissolved and suspended constituents, including nutrients, major ions, dissolved and sediment-bound heavy metals, common pesticides, and inorganic and organic forms of carbon. This information will be used (1) to describe the long-term trends and changes in concentration and transport of these constituents; (2) to test findings of the National Water-Quality Assessment Program (NAWQA); (3) to characterize processes unique to large-river systems such as storage and re-mobilization of sediments and associated contaminants; and (4) to refine existing estimates of off-continent transport of water, sediment, and chemicals for assessing human effects on the world's oceans and for determining global cycles of carbon, nutrients, and other chemicals. There are no stations in the Delaware River Basin in Pennsylvania currently participating in this program.

The **National Atmospheric Deposition Program/National Trends Network** (NADP/NTN) provides continuous measurement and assessment of the chemical climate of precipitation throughout the United States. As the lead federal agency, the USGS works together with over 100 organizations to accomplish the following objectives: (1) Provide a long-term, spatial and temporal record of atmospheric deposition generated from a network of 191 precipitation chemistry monitoring sites. (2) Provide the mechanism to evaluate the effectiveness of the significant reduction in SO₂ emissions that began in 1995 as implementation of the Clean Air Act Amendments (CAAA) occurred, and (3) Provide the scientific basis and nationwide evaluation mechanism for implementation of the Phase II CAAA emission reductions for SO₂ and NO_x scheduled to begin in year 2000.

Data from the network, as well as information about individual sites, are available through the World Wide Web at [<http://nadp.sws.uiuc.edu>].

The **National Water-Quality Assessment** (NAWQA) Program of the U.S. Geological Survey is a long-term program with goals to describe the status and trends of water-quality conditions for a large, representative part of the Nation's ground- and surface-water resources; provide an improved understanding of the primary natural and human factors affecting these observed conditions and trends; and provide information that supports development and evaluation of management, regulatory, and monitoring decisions by other agencies.

Assessment activities are being conducted in 53 study units (major watersheds and aquifer systems) that represent a wide range of environmental settings nationwide and that account for a large percentage of the Nation's water use. A wide array of chemical constituents will be measured in ground water, surface water, streambed sediments, and fish tissues. The coordinated application of comparative hydrologic studies at a wide range of spatial and temporal scales will provide information for decision making by water-resources managers and a foundation for aggregation and comparison of findings to address water-quality issues of regional and national interest.

Communication and coordination between USGS personnel and other local, State, and federal interests are critical components of the NAWQA Program. Each study unit has a local liaison committee consisting of representatives from key federal, State, and local water-resources agencies, Indian nations, and universities in the study unit. Liaison committees typically meet semiannually to discuss their information needs, monitoring plans and progress, desired information products, and opportunities to collaborate efforts among the agencies. Additional information about the NAWQA Program is available through the world wide web at [<http://pubs.water.usgs.gov/nawqa>].

EXPLANATION OF THE RECORDS

The surface-water and ground-water records in this report are for the 1999 water year that began October 1, 1998, and ended September 30, 1999. A calendar of the water year is provided on the inside of the front cover. The records contain streamflow data, stage and content data for lakes and reservoirs, water-quality data for streamflow stations, and ground-water-level data. The location of these stations and wells are shown in figures 6-14. The following sections of the introductory text are presented to provide users with a more detailed explanation of how these hydrologic data published in this report were collected, analyzed, computed, and arranged for presentation.

Station Identification Numbers

Each data station in this report, whether a streamsite or a well, is assigned a unique identification number. This number is unique in that it applies specifically to a given station and to no other. The number usually is assigned when a station is first established and is retained for that station indefinitely. The systems used by the U.S. Geological Survey to assign identification numbers for surface-water stations and for ground-water well sites differ, but both are based on geographic location. The "downstream order" system is used for regular surface-water stations and the "latitude-longitude" system is used for wells and, in Pennsylvania, for some miscellaneous surface-water sites where only random water-quality samples or discharge measurements are made.

Downstream-Order System

Since October 1, 1950, the order of listing hydrologic-station records in Survey reports is in a downstream direction along the main stream. All stations on a tributary entering upstream from a main-stream station are listed before that station. A station on a tributary that enters between two main-stream stations is listed between them. A similar order is followed in listing stations on first rank, second rank, and other ranks of tributaries. The rank of any tributary on which a station is situated with respect to the stream to which it is immediately tributary is indicated by an indentation in a list of stations in the front of the report. Each indentation represents one rank. This downstream-order system of indentation shows which stations are on tributaries between any two stations and the rank of the tributary on which each station is situated.

The station-identification number is assigned in downstream order. In assigning station numbers, no distinction is made between partial-record and continuous-record stations; therefore, the station number for a partial-record station indicates downstream-order position in a list made up of both types of stations. Gaps are left in the series of numbers to allow for new stations that may be established; hence, the numbers are not consecutive. A station number can be from 8 to 15 digits in length and normally appears to the left of the station name. For example, an 8-digit number for a station such as 01570500, includes a 2-digit part number "01" plus a 6-digit downstream-order number "570500." The part number designates major river basins; for example, part "01" is the North Atlantic Slope Basin.

Latitude-Longitude System

The identification numbers for wells and miscellaneous surface-water sites are assigned based on the grid system of latitude and longitude. The system provides the geographic location of the well or miscellaneous site and a unique number for each site. The number consists of 15 digits. The first six digits denote the degrees, minutes, and seconds of latitude, the next seven digits denote the degrees, minutes, and seconds of longitude, and the last two digits (assigned sequentially) identify the wells or other sites within a 1-second grid (fig. 5).




Figure 5.--System for numbering wells and miscellaneous sites (latitude and longitude).

A local well number is also assigned to the wells and consists of a 2-letter abbreviation of the county in which the well is located and a sequential number assigned at the time the well was scheduled.

Records of Stage and Water Discharge

Records of stage and water discharge may be continuous or partial. Continuous records of discharge are those obtained using a continuous stage-recording device through which either instantaneous water discharges may be computed for any time, or mean discharges may be computed for any period of time, during the period of record. Because daily mean discharges or end-of-day contents for reservoirs commonly are published for such stations, they are referred to as "*daily stations*" or "*continuous-record stations*."

By contrast, partial records are obtained through discrete measurements without using a continuous stage-recording device and pertain only to a few flow characteristics, or perhaps only one. The nature of the partial record is indicated by table titles such as "*Crest-stage partial-record stations*," or "*Low-flow partial-record stations*." Records of miscellaneous discharge measurements or of measurements from special studies, such as low-flow seepage studies, may be considered as partial records, but they are presented separately in this report. Location of all continuous-record and partial-record stations for which data are given in this report are shown in figures 6-14.

Data Collection and Computation

Those data obtained at a continuous-record gaging station on a stream consist of a continuous record of stage, individual measurements of discharge throughout a range of stages, and notations regarding factors that may affect the relation between stage and discharge. These data, together with supplemental information, such as weather records, are used to compute daily discharges.

Continuous records of stage are obtained with analog recorders that trace continuous graphs of stage, with solid-state electronic data loggers, or with data collection platforms (DCPs) that electronically record and transmit the data via satellite to ground receiving stations. Measurements of discharge are made with current meters using methods adopted by the Geological Survey as a result of experience accumulated since 1880. These methods are described in standard textbooks, in Water-Supply Paper 2175, and U.S. Geological Survey Techniques of Water-Resources Investigations (TWRIs), Book 3, Chapter A1 through A19 and Book 8, Chapters A2 and B2. The methods are consistent with the American Society for Testing and Materials (ASTM) standards and generally follow the standards of the International Organization for Standards (ISO).

In computing discharge records, results of individual measurements are plotted against the corresponding stages, and stage-discharge relation curves are then constructed. From these curves, rating tables indicating the approximate discharge for any stage within the range of the measurements are prepared. If it is necessary to define extremes of discharge outside the range of the current-meter measurements, the curves are extended using: (1) logarithmic plotting; (2) velocity-area studies; (3) results of indirect measurements of peak discharge, such as slope-area or contracted-opening measurements, and computations of flow-over-dams or weirs; or (4) step-backwater techniques.

Daily mean discharges are computed by applying each recorded stage value (gage height) to the stage-discharge curves or tables. If the stage-discharge relation is subject to change because of frequent or continual change in the physical features that form the control, the daily mean discharge is determined by the shifting-control method, in which correction factors based on the individual discharge measurements and notes of the personnel making the measurements are applied to the gage heights before the discharges are determined from the curves or tables. This shifting-control method also is used if the stage-discharge relation is changed temporarily because of aquatic growth or debris on the control. For some stations, formation of ice in the winter may so obscure the stage-discharge relation that daily mean discharges must be estimated from other information such as temperature and precipitation records, notes of observations, and records for other stations in the same or nearby basins for comparable periods.

At some stream-gaging stations, the stage-discharge relation is affected by the backwater from reservoirs, tributary streams, or other sources. This necessitates the use of the slope method in which the slope or fall in a reach of the stream is a factor in computing discharge. The slope or fall is obtained by means of an auxiliary gage set at some distance from the base gage. At some stations, the stage-discharge relation is affected by changing stage; at these stations, the rate of change in stage is used as a factor to compute discharge.

When computing records of lake or reservoir contents, it is necessary to have available from surveys, curves or tables defining the relation between stage and content. The application of stage to the stage-content curves or tables gives the contents from which daily, monthly, or yearly changes then are determined. If the stage-content relation changes because of deposition of sediment in the lake or reservoir, periodic surveys may be necessary to redefine the relation. Even when this is done, the contents computed may increase in error as the time elapsed since the last survey increases. Discharges over lake or reservoir spillways are computed from stage-discharge relation much as other stream discharges are computed.

For some gaging stations, there are periods when no gage-height data are collected or when the recorded gage height is so imprecise or incorrect that it cannot be used to compute daily mean discharge or end-of-day contents. This happens when the recorder stops or otherwise fails to operate properly, intakes are plugged, the float is frozen in the well, or for various other reasons. For such periods, the daily discharges are estimated from the recorded range in stage, previous or following record, discharge measurements, weather records, and comparison with other station records from the same or nearby basins. Likewise, daily contents may be estimated from operator's logs, previous or following record, inflow-outflow studies, and other information. Information explaining how estimated daily-discharge values are identified in station records is included in the next two sections, "*Data Presentation*" (REMARKS paragraph) and "*Identifying Estimated Daily Discharge*."

Data Presentation

The records published for each continuous-record surface-water discharge station (gaging station) consist of four parts; (1) the manuscript or station description; (2) the data table of daily mean discharge values for the current water year with summary data; (3) a tabular statistical summary of monthly mean flow data for a designated period; and (4) a summary statistics table for a designated period that includes statistical data of annual, daily, and instantaneous flows as well as data pertaining to annual runoff, 7-day low-flow minimums, and flow duration.

Station manuscript

For each continuous-record station, the manuscript provides, under various headings, descriptive information such as station location, period of record, historical extremes outside the period of record, record accuracy, and other remarks pertinent to station operation and regulation. The following comments, as appropriate, clarify information presented under the various headings of the station description.

LOCATION.--Information on locations is obtained from the most accurate maps available. The location of the gaging station with respect to the cultural and physical features in the vicinity and with respect to the reference place mentioned in the station name is given. River mileages, listed for only a few stations, were determined by methods given in "River Mileage Measurement," Bulletin 14, Revision of October 1968, prepared by the Water Resources Council or were provided by the U.S. Army Corps of Engineers.

DRAINAGE AREA.--Drainage areas are measured using the most accurate maps available. Because the type of maps available varies from one drainage basin to another, the accuracy of drainage areas likewise varies. Drainage areas are updated as better maps become available.

PERIOD OF RECORD.--This indicates the period for which records have been published for the station or for an equivalent station. An equivalent station is one that was in operation at a time that the present station was not and whose location was such that its streamflow can reasonably be considered equivalent to the streamflow at the present station.

REVISED RECORDS.--Because of new information, published records occasionally are found to be incorrect, and revisions are printed in later reports. Listed under this heading are all the reports in which revisions have been published for the station and the water years to which the revisions apply. If a revision did not include daily, monthly, or annual figures of discharge, that fact is noted after the year dates as follows; "(M)" means that only the instantaneous maximum discharge was revised; "(m)" that only the instantaneous minimum was revised; and "(P)" that only peak discharges were revised. If the drainage area has been revised, the report in which the most recently revised figure was first published is given.

GAGE.--The type of gage in current use, the datum of the current gage referred to sea level (see Definition of Terms), and a condensed history of the types, locations, and datums of previous gages are given under this heading.

REMARKS.--This paragraph is used to present information relative to the accuracy of the records, to special methods of computation, and to conditions that affect natural flow at the station. For reservoir stations, information is given on the dam forming the reservoir, the capacity, outlet works and spillway, and purpose and use of the reservoir.

COOPERATION.--Records provided by a cooperating organization or obtained for the U.S. Geological Survey by a cooperating organization are identified here.

EXTREMES OUTSIDE PERIOD OF RECORD.--Included here is information concerning major floods or unusually low flows that occurred outside the stated period of record. The information may or may not have been obtained by the U.S. Geological Survey.

PEAK DISCHARGES FOR CURRENT YEAR.--Peaks given here are similar to those found in the summary statistics table, except the peak discharge listing may include secondary peaks. For stations meeting certain criteria, all peak discharges and stages occurring during the water year and greater than a selected base discharge (see Definition of Terms) are presented under this heading. The peaks greater than the base discharge, excluding the highest one, are referred to as secondary peaks. Peak discharges are not published for streams for which the peaks are subject to substantial control by man. The time of occurrence for peaks is expressed in 24-hour local standard time. For example, 12:30 a.m. is 0030, and 1:30 p.m. is 1330.

REVISIONS.--If a critical error in published records is discovered, a revision is included in the first report published following discovery of the error.

Although rare, occasionally the records of a discontinued gaging station may need revision. Because, for these stations, there would be no current or, possibly, future station manuscript published to document the revision in a "*Revised Records*" entry, users of data for these stations who obtained the record from previously published data reports may wish to contact the District Office (address given on the back of the title page of this report) to determine if the published records were ever revised after the station was discontinued. Of course, if those data for a discontinued station were obtained by computer retrieval, these data would be current and accurate because published revisions of data are always accompanied by revisions of those data in computer storage.

Beginning with the 1991 annual State Data report, headings for AVERAGE DISCHARGE, EXTREMES FOR PERIOD OF RECORD, AND EXTREMES FOR CURRENT YEAR have been deleted and the information contained in these paragraphs, except for the listing of secondary instantaneous peak discharges in the PEAK DISCHARGES FOR CURRENT YEAR paragraph, is now presented in the tabular summaries following the discharge table or in the REMARKS paragraph, as appropriate. No changes have been made to the data presentations of lake contents. In order to present all the data collected on the Delaware River, data collected by the U.S. Geological Survey offices in New Jersey, New York and Delaware have been included in this report. These data are presented as published by each state, although the format differs slightly from that published in this volume.

Data table of daily mean values

The daily table of discharge records for stream-gaging stations gives mean discharge for each day of the water year. In the monthly summary for the table, the line headed "TOTAL" gives the sum of the daily figures for each month; the line headed "MEAN" gives the average flow in cubic feet per second for the month; and the lines headed "MAX" and "MIN" give the maximum and minimum daily mean discharges, respectively, for each month. Discharge for the month also is usually expressed in cubic feet per second per square mile (line headed "CFSM"); or in inches (line headed "IN."). Figures for cubic feet per second per square mile and runoff in inches may be omitted if there is extensive regulation or diversion or if the drainage area includes large noncontributing areas. At some stations both monthly and yearly observed discharges are adjusted for reservoir storage or diversion, or diversion data or reservoir contents are given. These figures are identified by a symbol and corresponding footnote.

Statistics of monthly mean data

A tabular summary of the mean (line headed "MEAN"), maximum (line headed "MAX"), and minimum (line headed "MIN") of monthly mean flows for each month for a designated period is provided below the daily values table. The water years of the first occurrence of the maximum and minimum monthly flows are provided immediately below those figures. The designated period will be expressed as "FOR WATER YEARS ____-____, BY WATER YEAR (WY)," and will list the first and last water years of the range of years selected from the PERIOD OF RECORD paragraph in the station manuscript. It will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript.

Summary statistics

A table titled "SUMMARY STATISTICS" follows the statistics of monthly mean data tabulation. This table consists of four columns, with the first column containing the line headings of the statistics being reported. The table provides a statistical summary of yearly, daily, and instantaneous flows, not only for the current water year but also for the previous calendar year and for a designated period, as appropriate. The designated period selected, "WATER YEARS ____-____," will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript. All of the calculations for the statistical characteristics designated ANNUAL (See line headings below.), except for the "ANNUAL 7-DAY MINIMUM" statistic, are calculated for the designated period using complete water years. The other statistical characteristics may be calculated using partial water years.

The date or water year, as appropriate, of the first occurrence of each statistic reporting extreme values of discharge is provided adjacent to the statistic. Repeated occurrences may be noted in the REMARKS paragraph of the manuscript or in footnotes. Because the designated period for the statistics may not be the same as the period of record published in the manuscript, occasionally the dates of occurrence listed for the daily and instantaneous extremes may not be within the designated period. Selected streamflow duration statistics and runoff data are also given. Runoff data may be omitted if there is extensive regulation or diversion of flow in the drainage basin.

The summary statistics data, as appropriate, are provided with each continuous record of discharge. The following comments clarify information presented under the various line headings of the summary statistics table.

ANNUAL TOTAL.--The sum of the daily mean values of discharge for the year. At some stations the annual total discharge may be affected by reservoir storage or diversion. The monthly adjusting figures for known regulation or diversions may be shown 1) at the bottom of the daily values table, or 2) in the appropriate lake or reservoir table.

ANNUAL MEAN.--The arithmetic mean of the individual daily mean discharges for the year noted or for the designated period. At some stations the annual total discharge may be affected by reservoir storage or diversion. The monthly adjusting figures for known regulation or diversions may be shown 1) at the bottom of the daily values table, or 2) in the appropriate lake or reservoir table.

HIGHEST ANNUAL MEAN.--The maximum annual mean discharge occurring for the designated period.

LOWEST ANNUAL MEAN.--The minimum annual mean discharge occurring for the designated period.

HIGHEST DAILY MEAN.--The maximum daily mean discharge for the year or for the designated period.

LOWEST DAILY MEAN.--The minimum daily mean discharge for the year or for the designated period.

ANNUAL 7-DAY MINIMUM.--The lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1-March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

INSTANTANEOUS PEAK FLOW.--The maximum instantaneous discharge occurring for the water year or for the designated period. Note that secondary instantaneous peak discharges above a selected base discharge are stored in computer files for stations meeting certain criteria. Those discharge values may be obtained by writing to the District Office or on the World Wide Web at [<http://pa.water.usgs.gov/>]. (See address on back of title page of this report.)

INSTANTANEOUS PEAK STAGE.--The maximum instantaneous stage occurring for the water year or for the designated period. If the dates of occurrence for the instantaneous peak flow and instantaneous peak stage differ, the REMARKS paragraph in the manuscript or a footnote may be used to provide further information.

INSTANTANEOUS LOW FLOW.--The minimum instantaneous discharge occurring for the water year or for the designated period.

ANNUAL RUNOFF.--Indicates the total quantity of water in runoff for a drainage area for the year. Runoff figures may be omitted if there is extensive regulation or diversion. Data reports may use any of the following units of measurements in presenting annual runoff data:

Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or about 326,000 gallons or 1,233 cubic meters.

Cubic feet per second per square mile (CFSM) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.

Inches (IN) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.

10 PERCENT EXCEEDS.--The discharge that has been exceeded 10 percent of the time for the designated period.

50 PERCENT EXCEEDS.--The discharge that has been exceeded 50 percent of the time for the designated period.

90 PERCENT EXCEEDS.--The discharge that has been exceeded 90 percent of the time for the designated period.

Data collected at partial-record stations follow the information for continuous-record sites. Data for partial-record discharge stations are presented in two tables. The first is a table of annual maximum stage and discharge at crest-stage stations, and the second is a table of discharge measurements at low-flow partial-record stations. The tables of partial-record stations are followed by a listing of discharge measurements made at sites other than continuous-record or partial-record stations. These measurements are generally made in times of drought or flood to give better areal coverage to those events. Those measurements and others collected for some special reason are called measurements at miscellaneous sites.

Identifying Estimated Daily Discharge

Beginning with the 1987 annual State data report, estimated daily discharge values published in the water-discharge tables are identified by flagging individual daily values with the letter symbol "e" and printing a table footnote, "e Estimated".

Accuracy of the Records

The accuracy of streamflow records depends primarily on (1) The stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements; and (2) the accuracy of measurements of stage, measurements of discharge, and interpretation of records.

The accuracy attributed to the records is indicated under "REMARKS." "Excellent" means that about 95 percent of the daily discharges are within 5 percent of their true values; "good," within 10 percent; and "fair," within 15 percent. Records that do not meet the criteria mentioned are rated "poor." Different accuracies may be attributed to different parts of a given record.

Daily mean discharges in this report are given to the nearest thousandth of a cubic foot per second for sites where the streamflow is often less than .01 ft³/s (cubic foot per second); to the nearest hundredth of a cubic foot per second for values less than 1 ft³/s for other sites where the streamflow is rarely less than .01 ft³/s; to the nearest tenth from 1.0 to 10 ft³/s; to whole numbers from 10 to 1,000 ft³/s; and to 3 significant figures when greater than 1,000 ft³/s. The number of significant figures used is based solely on the magnitude of the discharge value. The same rounding rules apply to discharges listed for partial-record stations and miscellaneous sites.

Discharge at many stations, as indicated by the monthly mean, may not reflect natural runoff due to the effects of diversion, consumption, regulation by storage, increase or decrease in evaporation due to artificial causes, or to other factors. For such stations, figures of cubic feet per second per square mile and of runoff, in inches, are not published unless satisfactory adjustments can be made for diversions, for changes in contents of reservoirs, or for other changes incident to use and control. Evaporation from a reservoir is not included in the adjustments for changes in reservoir contents, unless it is so stated. Even at those stations where adjustments are made, large errors in computed runoff may occur if adjustments or losses are large in comparison with the observed discharge.

Other Records Available

Information of a more detailed nature than that published for most of the gaging stations such as observations of water temperature, discharge measurements, gage-height records, and rating tables is on file in the District's offices. Most gaging-station records are available in computer-usable form and many statistical analyses have been made.

Information on the availability of unpublished data or statistical analyses may be obtained from the District Information Specialist (telephone (717) 730-6916).

Records of Surface-Water Quality

Records of surface-water quality ordinarily are obtained at or near stream-gaging stations because interpretation of records of surface-water quality nearly always requires corresponding discharge data. Records of surface-water quality in this report may involve a variety of types of data and measurement frequencies.

Classification of Records

Water-quality data for surface-water sites are grouped into one of three classifications. A continuing-record station is a site where data are collected on a regularly scheduled basis. Specifically, a continuing record station is a specified site which meets one or all conditions listed: (1) When chemical samples are collected daily or monthly for 10 or more months during the water year. (2) When water temperature records include observations taken one or more times daily. (3) When sediment discharge records include periods for which sediment loads are computed and are considered to be representative of the runoff for the water year. A partial-record station is a site where limited water-quality data are collected systematically over a period of years. Frequency of sampling is usually less than quarterly. A miscellaneous sampling site is a location other than a continuing or partial-record station, where random samples are collected to give better areal coverage to define water-quality conditions in the river basin.

A careful distinction needs to be made between "continuing records" as used in this report and "continuous recordings," which refers to a continuous graph or a series of discrete values punched at short intervals on a paper tape. Some records of water quality, such as temperature and specific conductance, may be obtained through continuous recordings; however, because of costs, most data are obtained only monthly or less frequently. Location of stations for which records on the quality of surface water appear in this report are shown in figures 6-14.

Arrangement of Records

Water-quality records collected at a surface-water daily record station are published immediately following that record, regardless of the frequency of sample collection. Station number and name are the same for both records. Where a surface-water daily record station is not available or where the water quality differs significantly from that at the nearby surface-water station, the continuing water-quality record is published with its own station number and name in the regular downstream-order sequence. Water-quality data for partial-record stations and for miscellaneous sampling sites appear in separate tables following the table of discharge measurements at miscellaneous sites.

On-site Measurements and Sample Collection

During the collection of water-quality data, assurance that the data obtained represent the in-situ quality of the water is a major concern. Certain measurements, such as water temperature, pH, and dissolved oxygen, need to be made onsite when the samples are collected. To assure that measurements made in the laboratory also represent the in-situ water quality, carefully prescribed procedures need to be followed when collecting the samples, when treating the samples to prevent changes in quality pending analysis, and when shipping the samples to the laboratory. Procedures for onsite measurements and for collecting, treating, and shipping samples are detailed in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, and A4. These references are listed in the PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS section of this report. These methods are consistent with ASTM standards and generally follow ISO standards. Also, detailed information on collecting, treating, and shipping samples may be obtained from the U.S. Geological Survey District Office.

One sample can define adequately the water quality at a given time if the mixture of solutes throughout the stream cross section is homogeneous. However, the concentration of solutes at different locations in the cross section may vary widely with different rates of water discharge, depending on the source of material and the turbulence and mixing of the stream. Some streams must be sampled through several vertical sections to obtain a representative sample needed for an accurate mean concentration and for use in calculating load. All samples collected for the National Water Quality Assessment Program (see Definition of Terms) are obtained from several verticals. Whether samples are obtained from the centroid of flow or from several verticals, depends on flow conditions and other factors that must be evaluated by the collector.

Chemical-quality data published in this report are considered to be the most representative values available for the stations listed. The values reported represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis. In the rare case where an apparent inconsistency exists between a reported pH value and the relative abundance of carbon dioxide species (carbonate and bicarbonate), the inconsistency is the result of a slight uptake of carbon dioxide from the air by the sample between measurement of pH in the field and determination of carbonate and bicarbonate in the laboratory.

For chemical-quality stations equipped with digital monitors, the records consist of daily maximum, minimum, and mean values for each constituent measured and are determined from data that are recorded at 15-, 30-, or 60-minute intervals with solid-state electronic data loggers, or with Data Collection Platforms (DCPs). More detailed records (hourly values) may be obtained from the U.S. Geological Survey District Office at the address given on the back of the title page of this report.

Water Temperature

Water temperatures are measured at most of the water-quality stations. At stations where recording instruments are used, maximum, minimum, and mean temperatures for each day are published. In addition, water temperatures are measured at the time of discharge measurements for most water-discharge stations and are on file in the District's offices. For stations where water temperature is measured manually once or twice daily, it is usually measured at about the same time each day. Large streams have a small diurnal temperature change; temperatures in shallow streams may have a daily range of several degrees and may follow closely the changes in air temperature. Some streams may be affected by heated waste-water discharges.

Sediment

Suspended-sediment concentrations are determined from samples collected by hand or by pump samplers. Hand samples utilize the appropriate sampler (dependent on stream depth and velocity) and are collected using the depth-integrating method at single or multiple verticals in the cross section. Samples collected by pump samplers use an intake set to a fixed location in the cross section. The intake is located at a site that best represents the entire cross section on the basis of simultaneous samples collected at various stages by the pumping sampler and by hand. During periods of rapidly changing flow or rapidly changing concentration, samples may have been collected more frequently (twice daily or, in some instances, every 15 minutes). The published sediment discharges for days of rapidly changing flow or concentration were computed by the subdivided-day method (time-discharge weighted average). Therefore, for those days when the published sediment discharge value differs from the value computed as the product of discharge, mean concentration, and the constant 0.0027, the reader can assume that the sediment discharge for that day was computed by the subdivided-day method. For periods when no samples were collected, daily discharges of suspended sediment were estimated on the basis of water discharge, sediment concentrations observed immediately before and after the periods, and suspended-sediment loads for other periods of similar discharge. Methods used in the computation of sediment records are described in the TWRI Book 3, Chapters C1 and C3. These methods are consistent with ASTM standards and generally follow ISO standards.

At other stations, suspended-sediment samples were collected periodically at many verticals in the stream cross section. Although data collected periodically may represent conditions only at the time of observations, such data are useful in establishing seasonal relations between quality and streamflow and in predicting long-term sediment-discharge characteristics of the stream.

In addition to the records of suspended-sediment discharge, records of the periodic measurements of the particle-size distribution of the suspended sediment and bed material are included for some stations.

Laboratory Measurements

Sediment samples, samples for biochemical-oxygen demand (BOD), samples for indicator bacteria, and daily samples for specific conductance are analyzed locally. The remaining samples are analyzed in the Geological Survey laboratory in Denver, Colorado. If other laboratories are used, they are identified in the "Remarks" or "Cooperation" paragraph of each water-quality station manuscript. Methods used to analyze sediment samples and to compute sediment records are described in the TWRI Book 5, Chapter C1. Methods used by the U.S. Geological Survey laboratories are given in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, A4, and A5. These methods are consistent with ASTM standards and generally follow ISO standards. Methods used by other laboratories are approved by the U.S. Geological Survey, Water Resources Division.

Data Presentation

For continuing-record stations, information pertinent to the history of station operation is provided in descriptive headings preceding the tabular data. These descriptive headings give details regarding location, drainage area, period of record, type of data available, instrumentation, general remarks, cooperation, and extremes for constituents currently measured daily. Tables of chemical, physical, biological, radiochemical, and other data, obtained at a frequency less than daily are presented first. Tables of "daily values" of specific conductance, pH, water temperature, dissolved oxygen, and suspended sediment then follow in sequence.

In the descriptive headings, if the location is identical to that of the streamflow-gaging station, neither the LOCATION nor the DRAINAGE AREA statements are repeated. The following information, as appropriate, is provided with each continuous-record station. Comments that follow clarify information presented under the various headings of the station description.

LOCATION.--See Data Presentation under "Records of Stage and Water Discharge"; same comments apply.

DRAINAGE AREA.--See Data Presentation under "Records of Stage and Water Discharge"; same comments apply.

PERIOD OF RECORD.--This indicates the periods for which there are published water-quality records for the station. The periods are shown separately for records of constituents measured daily or continuously and those measured less often than daily. For those measured daily or continuously, periods of record are given for the constituents individually.

INSTRUMENTATION.--Information on instrumentation is given only if a water-quality monitor, temperature recorder, pumping sampler, or other sampling device is in operation at a station.

REMARKS.--Remarks provide added information pertinent to the collection, analysis, or computation of the records.

COOPERATION.--Records provided by a cooperating organization or obtained for the Geological Survey by a cooperating organization are identified here.

EXTREMES.--Maximums and minimums are given only for constituents measured daily or more frequently. None are given for constituents measured less frequently, because the true maximums or minimums may not have been sampled. Extremes, when given, are provided for both the period of record and for the current water year.

REVISIONS.--If errors in published water-quality records are discovered after publication, appropriate updates are made to the Water-Quality File in the U.S. Geological Survey's computerized data system and subsequently by monthly transfer of update transactions to the U.S. Environmental Protection Agency's STORET system. Because the usual volume of updates makes it impractical to document individual changes in the State data-report series or elsewhere, potential users of U.S. Geological Survey water-quality data are encouraged to obtain all required data from the appropriate computer file to insure the most recent updates.

The surface-water-quality records for partial-record stations and miscellaneous sampling sites are published in separate tables following the table of discharge measurements at miscellaneous sites. No descriptive statements are given for these records. Each station is published with its own station number and name in the regular downstream-order sequence.

Remark Codes

The following remark codes may appear with the data tables in this report:

<u>PRINTED OUTPUT</u>	<u>REMARK</u>
E,e	Estimated value.
>	Actual value is known to be greater than the value shown.
<	Actual value is known to be less than the value shown.
K	Results based on colony count outside the acceptance range (non-ideal colony count).
L	Biological organism count less than 0.5 percent (organism may be observed rather than counted).
D	Biological organism count equal to or greater than 15 percent (dominant).
&	Biological organism estimated as dominant.
ND	Material specifically analyzed for but not detected.
V	Analyte was detected in both the environmental sample and the associated blanks.

Water Quality-Control Data

Data generated from quality-control (QC) samples are a requisite for evaluating the quality of the sampling and processing techniques as well as data from the actual samples themselves. Without QC data, environmental sample data cannot be adequately interpreted because the errors associated with the sample data are unknown. The various types of QC samples collected by this district are described in the following section. Procedures have been established for the storage of water-quality-control data within the USGS. These procedures allow for storage of all derived QC data and are identified so that they can be related to corresponding environmental samples.

BLANK SAMPLES.--Blank samples are collected and analyzed to ensure that environmental samples have not been contaminated by the overall data-collection process. The blank solution used to develop specific types of blank samples is a solution that is free of the analytes of interest. Any measured value in a blank sample for an analyte (a specific component measured in a chemical analysis) that was absent in the blank solution is believed to be due to contamination. There are many types of blank samples possible, each designed to segregate a different part of the overall data-collection process. The types of blank samples collected in this district are:

Ambient blank--a blank solution that is put in the same type of sample container used for an environmental sample, kept with the set of sample bottles before sample collection, and opened at the site and exposed to the ambient conditions.

Field blank--a blank solution that is subjected to all aspects of sample collection, field processing, preservation, transportation, and laboratory handling as an environmental sample.

Trip blank--a blank solution that is put in the same type of sample container used for an environmental sample and kept with the set of samples bottles before and after sample collection.

Equipment blank--a blank solution that is processed through all equipment used for collecting and processing an environmental sample (similar to a field blank but normally done in the more controlled conditions of the office).

Sampler blank--a blank solution that is poured or pumped through the same field sampler used for collecting an environmental sample.

Filter blank--a blank solution that is filtered in the same manner and through the same filter apparatus used for an environmental sample.

Splitter blank--a blank solution that is mixed and separated using a field sample splitter in the same manner and through the same apparatus used for an environmental sample.

Preservation blank--a blank solution that is treated with the same preservatives used for an environmental sample.

Canister blank--a blank solution that is taken directly from a stainless steel canister just before the VOC sampler is submerged to obtain a field sample.

REFERENCE SAMPLES.--Reference material samples are solutions or materials having a known composition that is certified by a laboratory. Samples of reference material are submitted for analysis to ensure that an analytical method is accurate for the known properties of the reference material. Generally, the selected reference material properties are similar to the environmental sample properties.

REPLICATE SAMPLES.--Replicate samples are a set of environmental samples collected in a manner such that the samples are thought to be essentially identical in composition. Replicate is the general case for which a duplicate is the special case consisting of two samples. Replicate samples are collected and analyzed to establish the amount of variability in the data contributed by some part of the collection and analytical process. There are many types of replicate samples possible, each of which may yield slightly different results in a dynamic hydrologic setting, such as a flowing stream. The types of replicate samples collected in this district are:

Sequential samples--a type of replicate sample in which environmental samples are collected one after the other, typically within a short time.

Split sample--a type of replicate sample in which an environmental sample is split into subsamples contemporaneous in time and space.

SPIKE SAMPLES.--Spike samples are samples to which known quantities of a solution with one or more well-established analyte concentrations have been added. These samples are analyzed to determine the extent of matrix interference or degradation on the analyte concentration during sample processing and analysis.

Records of Ground-Water Levels

Ground-water level data from an observation well network and from ground-water projects are published herein. Locations of observation wells in the basic network are shown in figures 6 and 7. Ground-water data are grouped by counties, arranged in alphabetical order, and are listed on pages x and xi. Those with an (l) following the well number have water-level data published in the report. Miscellaneous or short-term ground-water data collection projects are published following the basic network data.

Data Collection and Computation

Water levels are measured in many types of wells under varying conditions, but the methods of measurement are standardized to the extent possible. The equipment and measuring techniques used at each observation well ensure that measurements at each well are of consistent accuracy and reliability.

The prime identification number for a given well is the 15-digit number that appears above the station description. The secondary identification number is the local well number, an alphanumeric number, derived from the county location of the well.

Water-level records are obtained from direct measurements with a steel tape, from the graph, with solid-state electronic data loggers, or with Data Collection Platforms (DCPs). The water-level measurements in this report are given in feet with reference to land-surface datum (lsd). Land-surface datum is a datum plane that is approximately at land surface at each well. If known, the elevation of the land-surface datum is given in the well description. The height of the measuring point (MP) above or below land-surface datum is given in each well description. Water levels in wells equipped with recording gages are reported for each day.

Water levels are reported to as many significant figures as can be justified by the local conditions. Accordingly, most measurements are reported to a hundredth of a foot, but some may be given to a tenth of a foot.

Data Presentation

Each well record consists of three parts; (1) the station description, (2) the data table of water levels observed during the current water year, and (3) a graph of the water levels for the last 3 years. The description of the well is presented first through use of descriptive headings preceding the tabular data. The comments that follow clarify information presented under the various headings of the station description.

LOCATION.--This paragraph follows the well-identification number and reports the latitude and longitude (given in degrees, minutes, and seconds), the hydrologic-unit number, the distance and direction from a geographic point of reference, and the owner's name.

AQUIFER.--This entry designates by name (if a name exists) and geologic age the aquifer(s) open to the well.

WELL CHARACTERISTICS.--This entry describes the well in terms of depth, diameter, casing depth or screened interval, method of construction, use, and additional information such as casing breaks, collapsed screen, and other changes since construction.

INSTRUMENTATION.--This paragraph provides information on both the frequency of measurement and the collection method, allowing the user to better evaluate the reported water-levels by knowing whether they are based on hourly, daily, or some other frequency of measurement.

DATUM.--This entry describes both the measuring point and the land-surface elevation at the well. The measuring point is described physically (such as top of collar, notch in top of casing, plug in pump base and so on), and in relation to land surface (such as 1.3 ft above land-surface datum). The elevation of the land-surface datum is described in feet above (or below) sea level; it is reported with a precision relative to the method of determination.

REMARKS.--This entry describes factors that may influence the water level in a well or the measurement of the water level. It should identify wells that also are water-quality observation wells, and may be used to acknowledge the assistance of local (non-Survey) observers.

PERIOD OF RECORD.--This entry indicates the period for which there are published records for the well. It reports the month and year of the start of publication of water-level records by the U.S. Geological Survey and the words "*to current year*" if the records are to be continued into the following year. Periods for which water-level records are available, but are not published by the Geological Survey, may be noted.

EXTREMES FOR PERIOD OF RECORD.--This entry contains the highest and lowest values of one daily water-level statistic (maximum, mean, or instantaneous) reported in the data tables for the period of published record with respect to land-surface datum, (or occasionally sea level), and the dates of their occurrence. For example, if the daily maximum depth below land surface is reported in the table of water levels, this paragraph would reflect the highest and lowest of these daily maximum values for the period of record. Depending on the statistic reported in the table of water levels, extremes would be determined from daily maximum, mean, or instantaneous values.

Data table of water levels

A table of water levels follows the station description for each well. These tables usually report water-level data as maximum depth (in feet) above or below land-surface datum, but may report daily mean or instantaneous values depending upon the method used to obtain the record and how the record was published in the past. If water-level record is obtained from electronic data loggers, or DCPs, in addition to data published in the table of water levels, the daily maximum, minimum, and mean water-levels are stored in computer files and available from the District Office as noted in the REMARKS paragraph for that well. The extremes of the water-levels reported in the table for the water year and their dates of occurrence are shown on a line below the table. Missing records are indicated by dashes in place of the water level. A hydrograph showing the last three years of water levels follows each water-level table.

Records of Ground-Water Quality

Records of ground-water quality are obtained at wells and springs included in ground-water projects. Records of ground-water quality in this report may involve a variety of types of data and measurement frequencies. Those wells with a (c) following the well number in the list of ground-water wells on pages x and xi, have water-quality data published in the report. Miscellaneous or short-term ground-water data collection projects are published following the basic network data.

Data Collection and Computation

The records of ground-water quality in this report were obtained mostly as a part of special studies in specific areas. Consequently, a number of chemical analyses are presented for some counties but none are presented for others. As a result, the records for this year, by themselves, do not provide a balanced view of ground-water quality basinwide. Such a view can be attained only by considering records for this year in context with similar records obtained for these and other counties in previous years.

Most methods for collecting and analyzing water samples are described in the U.S. Geological survey TWRI publications referred to in the "*On-site Measurements and Sample Collection*" and the "*Laboratory Measurements*" sections in this data report. In addition, the TWRI Book 1, Chapter D2, describes guidelines for the collection and field analysis of ground-water samples for selected unstable constituents. The values reported in this report represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and method of analysis. These methods are consistent with ASTM standards and generally follow ISO standards. All samples were obtained by trained personnel. The wells sampled were pumped long enough to assure that the water collected came directly from the aquifer and had not stood for a long time in the well casing where it would have been exposed to the atmosphere and to the material, possibly metal, comprising the casings.

Data Presentation

Ground-water-quality data are published with ground-water-level data at stations where level data are collected. Data collected at partial-record stations and miscellaneous sites follow the information for continuous ground-water record stations. Data for each section are listed alphabetically by county, and are identified by well number. The prime identification number for wells sampled is the 15-digit number derived from the latitude-longitude locations. No descriptive statements are given for ground-water-quality records; however, the well number, depth of well, date of sampling, and other pertinent data are given in the table containing the chemical analyses of the ground water. The REMARK codes listed for surface-water-quality records are also applicable to ground-water-quality records.

ACCESS TO USGS WATER DATA

The U.S. Geological Survey is the principal Federal water-data agency and, as such, collects and disseminates about 70 percent of the water data currently being used by numerous State, local, private, and other Federal agencies to develop and manage our water resources. The Geological Survey provides near real-time stage and discharge data for many of the gaging stations equipped with the necessary telemetry and historic daily-mean and peak-flow discharge data for most current or discontinued gaging stations through the World Wide Web (WWW). These data may be accessed at [<http://water.usgs.gov>].

Some water-quality and ground-water data also are available through the WWW. In addition, data can be provided in various machine-readable formats on magnetic tape or 3-1/2 inch floppy disk. Information about the availability of specific types of data or products, and user charges, can be obtained locally from each of the Water Resources Division District Offices (See address on the back of the title page.)

For most streamgages, "*real-time*" streamflow conditions are available on the World Wide Web (WWW) Pennsylvania District Home Page at [<http://pa.water.usgs.gov/>]. Daily streamflow values for the period of record, annual peak stream discharges, and streamflow conditions for surrounding states may also be obtained at this WWW address.

A wide variety of additional information, such as ordering U.S. Geological Survey maps and publications, is available at the U.S. Geological Survey Home Page at [<http://www.usgs.gov/>].

DEFINITION OF TERMS

Terms related to streamflow, water-quality, and other hydrologic data, as used in this report, are defined below. See also the table for converting Inch-pound units to International System (SI) Units on the inside of the back cover.

Acid neutralizing capacity (ANC) is the equivalent sum of all bases or base-producing materials, solutes plus particulates, in an aqueous system that can be titrated with acid to an equivalence point. This term designates titration of an *unfiltered* sample (formerly reported as alkalinity).

Acre-foot (AC-FT, acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or 325,851 gallons or 1,233 cubic meters.

Adenosine triphosphate (ATP) is an organic, phosphate-rich, compound important in the transfer of energy in organisms. Its central role in living cells makes it an excellent indicator of the presence of living material in water. A measure of ATP therefore provides a sensitive and rapid estimate of biomass. ATP is reported in micrograms per liter.

Algae are mostly aquatic single-celled, colonial, or multi-celled plants, containing chlorophyll and lacking roots, stems, and leaves.

Algal growth potential (AGP) is the maximum algal dry weight biomass that can be produced in a natural water sample under standardized laboratory conditions. The growth potential is the algal biomass present at stationary phase and is expressed as milligrams dry weight of algae produced per liter of sample.

Alkalinity is the capacity of solutes in an aqueous system to neutralize acid. This term designates titration of a *filtered* sample.

Annual runoff indicates the total quantity of water in runoff for a drainage area for the year. Data reports may use any of the following units of measurements in presenting annual runoff data:

Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or 325,851 gallons or 1,233 cubic meters.

Cubic foot per second per square mile (CFSM, ft³/s/mi²) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.

Inch (IN., in.) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.

Aquifer is a geologic formation, group of formations, or part of a formation that contains sufficient saturated permeable material to yield significant quantities of water to wells and springs.

Artesian means confined and is used to describe a well in which the water level stands above the top of the aquifer tapped by the well. A flowing artesian well is one in which the water level is above the land surface.

Bacteria are microscopic unicellular organisms, typically spherical, rodlike, or spiral and threadlike in shape, often clumped into colonies. Some bacteria cause disease while others perform an essential role in nature in the recycling of materials; for example, by decomposing organic matter into a form available for reuse by plants.

Escherichia coli (*E. coli*) are bacteria of the fecal coliform groups. The presence of these organisms in water is indicative of fecal contamination from humans or other warm-blooded animals. Some strains of *E. coli* are themselves pathogens. In the laboratory, these bacteria are defined as organisms that produce yellow or yellow-brown colonies that remain so when placed on a filter pad saturated with urea substrate broth for 15 minutes after resuscitation at 35°C for two hours and incubation for 24 hours at 44.5°C on m-TEC medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal coliform bacteria are bacteria that are present in the intestines or feces of warm-blooded animals. They are often used as indicators of the sanitary quality of the water. In the laboratory they are defined as all organisms that produce blue colonies within 24 hour when incubated at 44.5°C ± 0.2°C on M-FC medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal streptococcal bacteria are bacteria found also in intestines of warm-blooded animals. Their presence in water is considered to verify fecal pollution. They are characterized as gram-positive, cocci bacteria which are capable of growth in brain-heart infusion broth. In the laboratory they are defined as all the organisms which produce red or pink colonies within 48 hours at $35^{\circ}\text{C} \pm 1.0^{\circ}\text{C}$ on KF-streptococcus medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Total coliform bacteria are a particular group of bacteria that are used as indicators of possible sewage pollution. They are characterized as aerobic or facultative anaerobic, gram-negative, nonspore-forming, rod-shaped bacteria which ferment lactose with gas formation within 48 hours at 35°C . In the laboratory these bacteria are defined as the organisms that produce colonies with a golden-green metallic sheen within 24 hours when incubated at $35^{\circ}\text{C} \pm 1.0^{\circ}\text{C}$ on M-Endo medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Bed material is the sediment mixture of which a streambed, lake, pond, reservoir, or estuary bottom is composed.

Benthic invertebrates are invertebrate animals inhabiting the bottoms of lakes, streams and other water bodies. They are useful as indicators of water quality.

Biochemical oxygen demand (BOD) is a measure of the quantity of dissolved oxygen, in milligrams per liter, necessary for the decomposition of organic matter by microorganisms, such as bacteria.

Biomass is the amount of living matter present at any given time, expressed as the mass per unit area or volume of habitat.

Ash mass is the mass or amount of residue present after the residue from the dry mass determination has been ashed in a muffle furnace at a temperature of 500°C for 1 hour. The ash mass values of zooplankton and phytoplankton are expressed in grams per cubic meter (g/m^3), and periphyton and benthic organisms in grams per square meter (g/m^2).

Dry mass refers to the mass of residue present after drying in an oven at 105°C for zooplankton and periphyton, until the mass remains unchanged. This mass represents the total organic matter, ash and sediment, in the sample. Dry mass values are expressed in the same units as ash mass.

Organic mass or volatile mass of the living substance is the difference between the dry mass and ash mass, and represents the actual mass of the living matter. The organic mass is expressed in the same units as for ash mass and dry mass.

Wet mass is the mass of living matter plus contained water.

Bottom material: See Bed material.

Cells/volume refers to the number of cells of any organism which is counted by using a microscope and grid or counting cell. Many planktonic organisms are multicelled and are counted according to the number of contained cells per sample, usually milliliters (mL) or liters (L).

Cfs-day is the volume of water represented by flow of 1 cubic foot per second for 24 hours. It is equivalent to 86,400 cubic feet, 1.9835 acre-feet, or about 646,000 gallons.

Chemical oxygen demand (COD) is a measure of the chemically oxidizable material in the water, and furnishes an approximation of the amount of organic and reducing material present. The determined value may correlate with BOD or with carbonaceous organic pollution from sewage or industrial wastes.

Chlorophyll refers to the green pigments of plants. Chlorophyll **a** and **b** are the two most common green pigments in plants.

Color unit is produced by one milligram per liter of platinum in the form of the chloroplatinate ion. Color is expressed in units of the platinum-cobalt scale.

Contents is the volume of water in a reservoir or lake. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

Continuing-record station is a specified site which meets one or all conditions listed:

1. When chemical samples are collected daily or monthly for 10 or more months during the water year.
2. When water temperature records include observations taken one or more times daily.
3. When sediment discharge records include periods for which sediment loads are computed and are considered to be representative of the runoff for the water year.

Continuous-record station is a station where streamflow and/or water-quality data are collected systematically over a period of years for use in hydrologic analyses. Data may be collected continuously or periodically.

Control designates a feature in the channel downstream from the gage that determines the stage-discharge relation at the gage. This feature may be a natural constriction of the channel, an artificial structure, or a uniform cross section over a long reach of the channel.

Control structure as used in this report is a structure on a stream or canal that is used to regulate the flow or stage of the stream or to prevent the intrusion of salt water.

Cubic feet per second per square mile (CFSM) [(ft³/s)/mi²] is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming that the runoff is distributed uniformly in time and area.

Cubic foot per second (CFS) (ft³/s) is the rate of discharge representing a volume of 1 cubic foot passing a given point during 1 second and is equivalent to approximately 7.48 gallons per second or 448.8 gallons per minute.

Data Collection Platform (DCP) is an electronic instrument which collects, processes, stores, and transmits data from various sensors to an earth-orbiting Geostationary Operational Environmental Satellite (GOES) and/or through landline telemetry.

Data logger is a microprocessor based data acquisition system designed specifically to acquire, process, and store data. Data are usually downloaded from onsite data loggers for entry into office data systems.

Discharge is the volume of water (or more broadly, volume of fluid plus suspended sediment) that passes a given point within a given period of time.

Annual 7-day minimum is the lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1-March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

Base discharge is an arbitrary instantaneous discharge value, determined for stations meeting certain criteria, that will be exceeded about three times per year.

Instantaneous discharge is the discharge at a particular instant of time.

Mean discharge (MEAN) is the arithmetic mean of individual daily mean discharges during a specific period.

Dissolved refers to that material in a representative water sample which passes through a 0.45-micrometer (µm) membrane filter. This is a convenient operational definition used by Federal agencies that collect water data. Determinations of "dissolved" constituents are made on subsamples of the filtrate.

Dissolved-solids concentration of water is determined either analytically by the "residue-on-evaporation" method, or mathematically by totaling the concentrations of individual constituents reported in a comprehensive chemical analysis. During the analytical determination of dissolved solids, the bicarbonate (generally a major dissolved component of water) is converted to carbonate. Therefore, in the mathematical calculation of dissolved-solids concentration, the bicarbonate value, in milligrams per liter, is multiplied by 0.492 to reflect the change.

Drainage area of a stream at a specific location is that area, measured in a horizontal plane, enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above the specified point. Figures of drainage area given herein include all closed basins, or noncontributing areas, within the area unless otherwise noted.

Drainage basin is a part of the surface of the earth that is occupied by a drainage system, which consists of a surface stream or a body of impounded surface water together with all tributary surface streams and bodies of impounded surface water.

Estimated (E) values is when an analyte is detected and all criteria for a positive result are met, the concentration is reported. If the concentration is less than the method detection limit (MDL), an 'E' code will be reported with the value. If the analyte is qualitatively identified as present, but the quantitative determination is substantially more uncertain, the National Water Quality Laboratory will identify the result with an 'E' code even though the measured value is greater than the MDL. A value reported with an 'E' code should be used with caution. When no analyte is detected in a sample, the default reporting value is the MDL preceded by a less than sign (<).

Gage height (G.H.) is the water-surface elevation referred to some arbitrary gage datum. Gage height is often used interchangeably with the more general term "*stage*," although gage height is more appropriate when used with a reading on a gage.

Gaging station is a particular site on a stream, canal, lake, or reservoir where systematic observations of hydrologic data are obtained.

Hardness of water is a physical-chemical characteristic that is commonly recognized by the increased quantity of soap required to produce lather. It is computed as the sum of equivalents of polyvalent cations and is expressed as the equivalent concentration of calcium carbonate (CaCO_3).

High tide is the maximum height reached by each rising tide.

The **Hydrologic Bench-mark station** is one that provides hydrologic data for a basin in which the hydrologic regimen will likely be governed solely by natural conditions. Data collected at a benchmark station may be used to separate effects of natural from human-induced changes in other basins that have been developed and in which the physiography, climate, and geology are similar to those in the undeveloped benchmark basin.

Hydrologic unit is a geographic area representing part or all of a surface drainage basin or distinct hydrologic feature as delineated by the Office of Water Data Coordination on the State Hydrologic Unit Maps; each hydrologic unit is identified by an 8-digit number.

Land-surface datum (lsd) is a datum plane that is approximately at land surface at each ground-water observation well.

Low tide is the minimum height reached by each falling tide.

Measuring point (MP) is an arbitrary permanent reference point from which the distance to the water surface in a well is measured to obtain the water level.

Membrane filter is a thin microporous material of specific pore size used to filter bacteria, algae, and other very small particles from water.

Metamorphic stage refers to stage of development that an organism exhibits during its transformation from an immature form to an adult form. This developmental process exists for most insects, and the degree of difference from the immature stage to the adult form varies from relatively slight to pronounced, with many intermediates. Examples of metamorphic stages of insects are egg-larva-adult or egg-nymph-adult.

Methylene blue active substance (MBAS) are apparent detergents. The determination depends on the formation of a blue color when methylene blue dye reacts with synthetic anionic detergent compounds.

Micrograms per gram ($\mu\text{g/g}$) is a unit expressing the concentration of a chemical constituent as the mass (micrograms) of the element per unit mass (gram) of material analyzed.

Micrograms per liter (UG/L , $\mu\text{g/L}$) is a unit expressing the concentration of chemical constituents in solution as mass (micrograms) of solute per unit volume (liter) of water. One thousand micrograms per liter is equivalent to one milligram per liter.

Microsiemens per centimeter ($\mu\text{S/cm}$, US/CM) is a unit expressing the amount of electrical conductivity of a solution as measured between opposite faces of a centimeter cube of solution at a specified temperature. Siemens is the International System of Units nomenclature. It is synonymous with mhos and is the reciprocal of resistance in ohms.

Milligrams per liter (MG/L , mg/L) is a unit for expressing the concentration of chemical constituents in solution. Milligrams per liter represent the mass of solute per unit volume (liter) of water. Concentration of suspended sediment also is expressed in mg/L , and is based on the mass of sediment per liter of water-sediment mixture.

Miscellaneous-record site is a site where limited streamflow and/or water-quality data are collected on a random basis for use in hydrologic analyses.

Most probable number (MPN) is an index of the number of coliform bacteria that, more probably than any other number, would give the results shown by the laboratory examination; it is not an actual enumeration. MPN is determined from the distribution of gas-positive cultures among multiple inoculated tubes.

Multiple-plate samplers are artificial substrates of known surface area used for obtaining benthic-invertebrate samples. They consist of a series of spaced, hardboard plates on an eyebolt.

The **National Geodetic Vertical Datum of 1929** (NGVD of 1929) is a geodetic datum derived from a general adjustment of the first order level nets of both the United States and Canada. It was formerly called "*Sea Level Datum of 1929*" or "*mean sea level*" in this series of reports. Although the datum was derived from the average sea level over a period of many years at 26 tide stations along the Atlantic, Gulf of Mexico, and Pacific Coasts, it does not necessarily represent local mean sea level at any particular place.

The **National Stream Quality Accounting Network** (NASQAN) monitors the water quality of large rivers within four of the Nation's largest river basins--the Mississippi, Columbia, Colorado, and Rio Grande. The network consists of 39 stations. Samples are collected with sufficient frequency that the flux of a wide range of constituents can be estimated. The objective of NASQAN is to characterize the water quality of these large rivers by measuring concentration and mass transport of a wide range of dissolved and suspended constituents, including nutrients, major ions, dissolved and sediment-bound heavy metals, common pesticides, and inorganic and organic forms of carbon. This information will be used (1) to describe the long-term trends and changes in concentration and transport of these constituents; (2) to test findings of the National Water-Quality Assessment Program (NAWQA); (3) to characterize processes unique to large-river systems such as storage and re-mobilization of sediments and associated contaminants; and (4) to refine existing estimates for assessing human effects on the world's oceans and for determining global cycles of carbon, nutrients, and other chemicals.

The **National Atmospheric Deposition Program/National Trends Network** (NADP/NTN) provides continuous measurement and assessment of the chemical climate of precipitation throughout the United States. As the lead federal agency, the USGS works together with over 100 organizations to accomplish the following objectives; (1) Provide a long-term, spatial and temporal record of atmospheric deposition generated from a network of 191 precipitation chemistry monitoring sites. (2) Provide the mechanism to evaluate the effectiveness of the significant reduction in SO₂ emissions that began in 1995 as implementation of the Clean Air Act Amendments (CAAA) occurred. (3) Provide the scientific basis and nationwide evaluation mechanism for implementation of the Phase II CAAA emission reductions for SO₂ and NO_x scheduled to begin in 2000.

The **National Water-Quality Assessment** (NAWQA) Program of the U.S. Geological Survey is a long-term program with goals to describe the status and trends of water-quality conditions for a large, representative part of the Nation's ground- and surface-water resources; provide an improved understanding of the primary natural and human factors affecting these observed conditions and trends; and provide information that supports development and evaluation of management, regulatory, and monitoring decisions by other agencies.

The **North American Vertical Datum of 1988** (NAVD of 1988) is a geodetic datum derived from the releveling of about 131,000 miles of existing first-order leveling lines to strengthen the network in the conterminous United States. The releveling was correlated with the total network and adjusted by the least squares method. The adjusted network includes about 600,000 permanent benchmarks. The assumption of zero NGVD as being mean sea level at the 26 appointed tide stations produced a distortion in the network. To remove this distortion in the network, a definition that could be reproduced readily at any location was established. This definition is an equipotential surface, that is, the surface represented by a constant value of the acceleration due to gravity.

Organism is any living entity.

Organism count/area refers to the number of organisms collected and enumerated in a sample and adjusted to the number per unit area habitat, usually square meters (m²), acres, or hectare. Periphyton, benthic organisms, and macrophytes are expressed in these terms.

Organism count/volume refers to the number of organisms collected and enumerated in a sample and adjusted to the number per sample volume, usually milliliters (mL) or liters (L). Numbers of planktonic organisms can be expressed in these terms.

Total organism count is the total number of organisms collected and enumerated in any particular sample.

Parameter Code is a 5-digit number used in the U.S. Geological Survey computerized data system, National Water Information System (NWIS), to uniquely identify a specific constituent.

Partial-record station is a particular site where limited streamflow and/or water-quality data are collected systematically over a period of years for use in hydrologic analyses.

Particle size is the diameter, in millimeters (mm), of a particle determined by either sieve or sedimentation methods. Sedimentation methods (pipet, bottom-withdrawal tube, visual-accumulation tube) determine fall diameter of particles in either distilled water (chemically dispersed) or in native water (the river water collected at the time and point of sampling).

Particle-size classification used in this report agrees with recommendations made by the American Geophysical Union Subcommittee on Sediment Terminology. The classification is as follows:

Classification	Size (mm)	Method of analysis
Clay	0.00024 - 0.004	Sedimentation
Silt	0.004 - .062	Sedimentation
Sand	.062 - 2.0	Sedimentation or sieve
Gravel	2.0 - 64.0	Sieve

The particle-size distributions given in this report are not necessarily representative of all particles in transport in the stream. Most of the organic material is removed, and the sample is subjected to mechanical and chemical dispersion before analysis in distilled water. Chemical dispersion is not used for native-water analysis.

Percent composition is a unit for expressing the ratio of a particular part of a sample or population to the total sample or population, in terms of types, numbers, mass, or volume.

Periphyton is the assemblage of microorganisms attached to and living upon submerged solid surfaces. While primarily consisting of algae, they also include bacteria, fungi, protozoa, rotifers, and other small organisms.

Pesticides are chemical compounds used to control undesirable organisms. Major categories of pesticides include insecticides, miticides, fungicides, herbicides, and rodenticides.

Picocurie (PC, pCi) is one trillionth (1×10^{-12}) of the amount of radioactivity represented by a curie (Ci). A curie is the amount of radioactivity that yields 3.7×10^{10} radioactive disintegrations per second. A picocurie yields 2.22 dpm (disintegrations per minute).

Plankton is the community of suspended, floating, or weakly swimming organisms that live in the open water of lakes and rivers.

Phytoplankton is the plant part of the plankton. They are usually microscopic and their movement is subject to the water currents. Phytoplankton growth is dependent upon solar radiation and nutrient substances. Because they are able to incorporate as well as release materials to the surrounding water, the phytoplankton have a profound effect upon the quality of the water. They are the primary food producers in the aquatic environment, and are commonly known as algae.

Blue-green algae are a group of phytoplankton organisms having a blue pigment, in addition to the green pigment called chlorophyll. Blue-green algae often cause nuisance conditions in water.

Diatoms are the unicellular or colonial algae having a siliceous shell. Their concentrations are expressed as number of cells per milliliter (cells/mL) of sample.

Green algae have chlorophyll pigments similar in color to those of higher green plants. Some forms produce algal mats or floating "moss" in lakes. Their concentrations are expressed as the number of cells per milliliter (cells/mL) of sample.

Zooplankton is the animal part of the plankton. Zooplankton are capable of extensive movements within the water column, and are often large enough to be seen with the unaided eye. Zooplankton are secondary consumers feeding upon bacteria, phytoplankton, and detritus. Because they are the grazers in the aquatic environment, the zooplankton are a vital part of the aquatic food web. The zooplankton community is dominated by small crustaceans and rotifers.

Primary productivity is a measure of the rate at which new organic matter is formed and accumulated through photosynthetic and chemosynthetic activity of producer organisms (chiefly, green plants). The rate of primary production is estimated by measuring the amount of oxygen released (oxygen method) or the amount of carbon assimilated by the plants (carbon method).

Milligrams of carbon per area or volume per unit time [$\text{mg C}/(\text{m}^2/\text{time})$] for periphyton and macrophytes and [$\text{mg C}/(\text{m}^3/\text{time})$] for phytoplankton are units for expressing primary productivity. They define the amount of carbon dioxide consumed as measured by radioactive carbon (carbon 14). The carbon 14 method is of greater sensitivity than the oxygen light and dark bottle method, and is preferred for use in unenriched waters. Unit time may be either the hour or day, depending on the incubation period.

Milligrams of oxygen per area or volume per unit time [$\text{mg O}/(\text{m}^2/\text{time})$] for periphyton and macrophytes and [$\text{mg O}/(\text{m}^3/\text{time})$] for phytoplankton are the units for expressing primary productivity. They define production and respiration rates as estimated from changes in the measured dissolved-oxygen concentration. The oxygen light and dark bottle method is preferred if the rate of primary production is sufficient for accurate measurements to be made within 24 hours. Unit time may be either the hour or day, depending on the incubation period.

Polychlorinated biphenyls (PCBs) are industrial chemicals that are mixtures of chlorinated biphenyl compounds having various percentages of chlorine. They are similar in structure to organochlorine insecticides.

Radiochemical program is a network of regularly sampled water-quality stations where samples are collected to be analyzed for radioisotopes. The streams that are sampled represent major drainage basins in the conterminous United States.

Recoverable from bottom material is the amount of a given constituent that is in solution after a representative sample of bottom material has been digested by a method (usually using an acid or mixture of acids) that results in dissolution of only readily soluble substances. Complete dissolution of all bottom material is not achieved by the digestion treatment and thus the determination represents less than the total amount (that is, less than 95 percent) of the constituent in the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Recurrence interval is the average time interval between occurrences of a hydrological event of a given or greater magnitude, usually expressed in years. May also be called return period.

River mile is the distance of a point on a river measured in miles from the river's mouth along the low-water channel.

Runoff: See Annual runoff.

Sea level: In this report, unless otherwise noted in the GAGE paragraph, "*sea level*" refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)--a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called Sea Level Datum of 1929.

Sediment is solid material that originates mostly from disintegrated rocks and is transported by, suspended in, or deposited from water; it includes chemical and biochemical precipitates and decomposed organic material such as humus. The quantity, characteristics, and cause of the occurrence of sediment in streams are influenced by environmental factors. Some major factors are degree of slope, length of slope, soil characteristics, land usage, and quantity and intensity of precipitation.

Bed load is the sediment that is transported in a stream by rolling, sliding, or skipping along the bed and very close to it. In this report, bed load is considered to consist of particles in transit within 0.25 ft of the streambed.

Bed load discharge (tons per day) is the quantity of bed load measured by dry weight that moves past a section as bed load in a given time.

Suspended sediment is the sediment that at any given time is maintained in suspension by the upward components of turbulent currents or that exists in suspension as a colloid.

Suspended-sediment concentration is the velocity-weighted concentration of suspended sediment in the sampled zone (from the water surface to a point approximately 0.3 ft above the bed) expressed as milligrams of dry sediment per liter of water-sediment mixture (mg/L).

Mean concentration is the time-weighted concentration of suspended sediment passing a stream section during a 24-hour day.

Suspended-sediment discharge (tons/day) is the rate at which dry mass of sediment passes a section of a stream or is the quantity of sediment, as measured by dry mass or volume, that passes a section in a given time. It is calculated in units of tons per day as follows: concentration (mg/L) x discharge (ft^3/s) x 0.0027.

Suspended-sediment load is a general term that refers to material in suspension. It is not synonymous with either discharge or concentration.

Total-sediment discharge (tons/day) is the sum of the suspended-sediment discharge and the bed-load discharge. It is the total quantity of sediment, as measured by dry mass or volume, that passes a section during a given time.

Total-sediment load or total load is a term which refers to the total sediment (bed load plus suspended-sediment load) that is in transport. It is not synonymous with total-sediment discharge.

7-day 10-year low flow (Q7,10) is the discharge at the 10-year recurrence interval taken from a frequency curve of annual values of the lowest mean discharge for 7 consecutive days (the 7-day low flow).

Sodium-adsorption-ratio (SAR) is the expression of relative activity of sodium ions in exchange reactions within soil and is an index of sodium or alkali hazard to the soil. Waters range in respect to sodium hazard from those which can be used for irrigation on almost all soils to those which are generally unsatisfactory for irrigation.

Solute is any substance that is dissolved in water.

Specific conductance is a measure of the ability of a water to conduct an electrical current. It is expressed in microsiemens per centimeter at 25°C. Specific conductance is related to the type and concentration of ions in the solution and can be used for approximating the dissolved-solids content of the water. Commonly, the concentration of dissolved solids (in milligrams per liter) is about 55 to 75 percent of the specific conductance (in microsiemens). This relation is not constant from stream to stream, and it may vary in the same source with changes in the composition of the water.

Stage-discharge relation is the relation between gage height (stage) and volume of water, per unit of time, flowing in a channel.

Streamflow is the discharge that occurs in a natural channel. Although the term "*discharge*" can be applied to the flow of a canal, the word "*streamflow*" uniquely describes the discharge in a surface stream course. The term "*streamflow*" is more general than "*runoff*" as streamflow may be applied to discharge whether or not it is affected by diversion or regulation.

Substrate is the physical surface upon which an organism lives.

Artificial substrate is a device which is purposely placed in a stream or lake for colonization of organisms. The artificial substrate simplifies the community structure by standardizing the substrate from which each sample is taken. Examples of artificial substrates are basket samplers (made of wire cages filled with clean streamside rocks) and multi-plate samplers (made of hardboard) for benthic organism collection, and plexiglass strips for periphyton collection.

Natural substrate refers to any naturally occurring immersed or submersed solid surface, such as a rock or tree, upon which an organism lives.

Surface area of a lake is that area (in acres) outlined on the latest USGS topographic map as the boundary of the lake and measured by a planimeter. In localities not covered by topographic maps, the areas are computed from the best maps available at the time planimetered. All areas shown are those for the stage when the planimetered map was made.

Surficial bed material is the top 0.1 to 0.2 ft of the bed material that is sampled using U.S. Series Bed-Material Samplers.

Suspended (as used in tables of chemical analyses) refers to the amount (concentration) of undissolved material in a water-sediment mixture. It is associated with the material retained on a 0.45 μm filter.

Suspended, recoverable is the amount of a given constituent that is in solution after the part of a representative water-suspended sediment sample that is retained on a 0.45 μm membrane filter has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all the particulate matter is not achieved by the digestion treatment and thus the determination represents something less than the "*total*" amount (that is, less than 95 percent) of the constituent present in the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Determinations of "*suspended, recoverable*" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total recoverable concentrations of the constituent.

Suspended, total is the total amount of a given constituent in the part of a representative water-suspended sediment sample that is retained on a 0.45 µm membrane filter. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent determined. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to determine when the results should be reported as "*suspended, total*."

Determinations of "*suspended, total*" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total concentrations of the constituent.

Synoptic studies are short-term investigations of specific water-quality conditions during selected seasonal or hydrologic periods to provide improved spatial resolution for critical water-quality conditions. For the period and conditions sampled, they assess the spatial distribution of selected water-quality conditions in relation to causative factors, such as land use and contaminant sources.

Taxonomy is the division of biology concerned with the classification and naming of organisms. The classification of organisms is based upon a hierarchical scheme beginning with Kingdom and ending with Species at the base. The higher the classification level, the fewer features the organisms have in common. For example, the taxonomy of a particular mayfly, Hexagenia limbata is the following:

Kingdom	Animal
Phylum	Arthropoda
Class	Insecta
Order	Ephemeroptera
Family	Ephemeridae
Genus	Hexagenia
Species	Hexagenia Limbata

Time-weighted average is computed by multiplying the number of days in the sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the total number of days. A time-weighted average represents the composition of water that would be contained in a vessel or reservoir that had received equal quantities of water from the stream each day for the year.

Tons per acre-foot indicates the dry mass of dissolved solids in 1 acre-foot of water. It is computed by multiplying the concentration, in milligrams per liter, by 0.00136.

Tons per day (T/day) is the quantity of substance in solution or suspension that passes a stream section during a 24-hour period.

Total is the total amount of a given constituent in a representative water-suspended sediment sample, regardless of the constituent's physical or chemical form. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent present in both the dissolved and suspended phases of the sample. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to judge when the results should be reported as "*total*." (Note that the word "*total*" does double duty here, indicating both that the sample consists of a water-suspended sediment mixture and that the analytical method determines all of the constituent in the sample).

Total discharge is the total quantity of any individual constituent, as measured by dry mass or volume, that passes through a stream cross-section per unit of time. This term needs to be qualified, such as "*total sediment discharge*," "*total chloride discharge*," and so on.

Total recoverable is the amount of a given constituent that is in solution after a representative water-suspended sediment sample has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all particulate matter is not achieved by the digestion treatment, and thus the determination represents something less than the "*total*" amount (that is, less than 95 percent) of the constituent present in the dissolved and suspended phases of the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

The **Tritium Network** is a network of stations which has been established to provide baseline information on the occurrence of tritium in the Nation's surface waters. In addition to the surface-water stations in the network, tritium data are also obtained at a number of precipitation stations. The purpose of the precipitation stations is to provide an estimate sufficient for hydrologic studies of the tritium input to the United States.

Volatile Organic Compounds (VOCs) are organic compounds that can be isolated from the water phase of a sample by purging the water sample with inert gas, such as helium, and subsequently analyzed by gas chromatography. Many VOCs are man-made chemicals that are used and produced in the manufacture of paints, adhesives, petroleum products, pharmaceuticals, and refrigerants. They are often components of fuels, solvents, hydraulic fluids, paint thinners, and dry cleaning agents commonly used in urban settings. VOC contamination of drinking-water supplies is a human health concern because many are toxic and are known or suspected human carcinogens (U.S. Environmental Protection Agency, 1996).

Water year as used in Geological Survey reports, is the 12-month period October 1 through September 30. The water year is designated by the calendar year in which it ends and which includes 9 of the 12 months. Thus, the year ending September 30, 1999, is called the "*1999 water year*."

WDR is used as an abbreviation for "*Water-Data Report*" in the REVISED RECORDS paragraph to refer to a State's annual hydrologic-data reports. (WRD was used as an abbreviation for "Water Resources Data" in reports published prior to 1976.)

Weighted average is used in this report to indicate discharge-weighted average. It is computed by multiplying the discharge for a sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the sum of the discharges. A discharge-weighted average approximates the composition of water that would be found in a reservoir containing all the water passing a given location during the water year after thorough mixing in the reservoir.

WSP is used as an abbreviation for "*Water-Supply Paper*" in references to previously published reports.

PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS

The U.S. Geological Survey publishes a series of manuals describing procedures for planning and conducting specialized work in water-resources investigations. The material is grouped under major subject headings called books and is further divided into sections and chapters. For example, Section A of Book 3 (Applications of Hydraulics) pertains to surface water. The chapter, the unit of publication, is limited to a narrow field of subject matter. This format permits flexibility in revision and publication as the need arises.

The reports listed below are for sale by the U.S. Geological Survey, Branch of Information Services, Box 25286, Federal Center, Denver, Colorado 80225 (authorized agent of the Superintendent of Documents, Government Printing Office). Prepayment is required. Remittance should be sent by check or money order payable to the U.S. Geological Survey. Prices are not included because they are subject to change. Current prices can be obtained by writing to the above address. When ordering or inquiring about prices for any of these publications, please give the title, book number, chapter number, and "U.S. Geological Survey Techniques of Water-Resources Investigations."

Book 1. Collection of Water Data by Direct Measurement

Section D. Water Quality

- 1-D1. *Water temperature—influential factors, field measurement, and data presentation*, by H.H. Stevens, Jr., J.F. Ficke, and G. F. Smoot: USGS–TWRI Book 1, Chapter D1. 1975. 65 pages.
- 1-D2. *Guidelines for collection and field analysis of ground-water samples for selected unstable constituents*, by W.W. Wood: USGS–TWRI Book 1, Chapter D2. 1976. 24 pages.

Book 2. Collection of Environmental Data

Section D. Surface Geophysical Methods

- 2-D1. *Application of surface geophysics to ground-water investigations*, by A.A.R. Zohdy, G.P. Eaton, and D.R. Mabey: USGS–TWRI Book 2, Chapter D1. 1974. 116 pages.
- 2-D2. *Application of seismic-refraction techniques to hydrologic studies*, by F.P. Haeni: USGS–TWRI Book 2, Chapter D2. 1988. 86 pages.

Section E. Subsurface Geophysical Methods

- 2-E1. *Application of borehole geophysics to water-resources investigations*, by W.S. Keys and L.M. MacCary: USGS–TWRI Book 2, Chapter E1. 1971. 126 pages.
- 2-E2. *Borehole geophysics applied to ground-water investigations*, by W.S. Keys: USGS–TWRI Book 2, Chapter E2. 1990. 150 pages.

Section F. Drilling and Sampling Methods

- 2-F1. *Application of drilling, coring, and sampling techniques to test holes and wells*, by Eugene Shuter and W.E. Teasdale: USGS–TWRI Book 2, Chapter F1. 1989. 97 pages.

Book 3. Applications of Hydraulics

Section A. Surface-Water Techniques

- 3-A1. *General field and office procedures for indirect discharge measurements*, by M.A. Benson and Tate Dalrymple: USGS–TWRI Book 3, Chapter A1. 1967. 30 pages.
- 3-A2. *Measurement of peak discharge by the slope-area method*, by Tate Dalrymple and M.A. Benson: USGS–TWRI Book 3, Chapter A2. 1967. 12 pages.
- 3-A3. *Measurement of peak discharge at culverts by indirect methods*, by G.L. Bodhaine: USGS–TWRI Book 3, Chapter A3. 1968. 60 pages.
- 3-A4. *Measurement of peak discharge at width contractions by indirect methods*, by H.F. Matthai: USGS–TWRI Book 3, Chapter A4. 1967. 44 pages.
- 3-A5. *Measurement of peak discharge at dams by indirect methods*, by Harry Hulsing: USGS–TWRI Book 3. Chapter A5. 1967. 29 pages.
- 3-A6. *General procedure for gaging streams*, by R.W. Carter and Jacob Davidian: USGS–TWRI Book 3, Chapter A6. 1968. 13 pages.
- 3-A7. *Stage measurement at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS–TWRI Book 3, Chapter A7. 1968. 28 pages.
- 3-A8. *Discharge measurements at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS–TWRI Book 3, Chapter A8. 1969. 65 pages.
- 3-A9. *Measurement of time of travel in streams by dye tracing*, by F.A. Kilpatrick and J.F. Wilson, Jr.: USGS–TWRI Book 3, Chapter A9. 1989. 27 pages.

- 3-A10. *Discharge ratings at gaging stations*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A10. 1984. 59 pages.
- 3-A11. *Measurement of discharge by the moving-boat method*, by G.F. Smoot and C.E. Novak: USGS–TWRI Book 3, Chapter A11. 1969. 22 pages.
- 3-A12. *Fluorometric procedures for dye tracing*, Revised, by J.F. Wilson, Jr., E.D. Cobb, and F.A. Kilpatrick: USGS–TWRI Book 3, Chapter A12. 1986. 34 pages.
- 3-A13. *Computation of continuous records of streamflow*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A13. 1983. 53 pages.
- 3-A14. *Use of flumes in measuring discharge*, by F.A. Kilpatrick and V.R. Schneider: USGS–TWRI Book 3, Chapter A14. 1983. 46 pages.
- 3-A15. *Computation of water-surface profiles in open channels*, by Jacob Davidian: USGS–TWRI Book 3, Chapter A15. 1984. 48 pages.
- 3-A16. *Measurement of discharge using tracers*, by F.A. Kilpatrick and E.D. Cobb: USGS–TWRI Book 3, Chapter A16. 1985. 52 pages.
- 3-A17. *Acoustic velocity meter systems*, by Antonius Laenen: USGS–TWRI Book 3, Chapter A17. 1985. 38 pages.
- 3-A18. *Determination of stream reaeration coefficients by use of tracers*, by F.A. Kilpatrick, R.E. Rathbun, Nobuhiro Yotsukura, G.W. Parker, and L.L. DeLong: USGS–TWRI Book 3, Chapter A18. 1989. 52 pages.
- 3-A19. *Levels at streamflow gaging stations*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A19. 1990. 31 pages.
- 3-A20. *Simulation of soluble waste transport and buildup in surface waters using tracers*, by F.A. Kilpatrick: USGS–TWRI Book 3, Chapter A20. 1993. 38 pages.
- 3-A21. *Stream-gaging cableways*, by C. Russell Wagner: USGS–TWRI Book 3, Chapter A21. 1995. 56 pages.

Section B. Ground-Water Techniques

- 3-B1. *Aquifer-test design, observation, and data analysis*, by R.W. Stallman: USGS–TWRI Book 3, Chapter B1. 1971. 26 pages.
- 3-B2. *Introduction to ground-water hydraulics, a programmed text for self-instruction*, by G.D. Bennett: USGS–TWRI Book 3, Chapter B2. 1976. 172 pages.
- 3-B3. *Type curves for selected problems of flow to wells in confined aquifers*, by J.E. Reed: USGS–TWRI Book 3, Chapter B3. 1980. 106 pages.
- 3-B4. *Regression modeling of ground-water flow*, by R.L. Cooley and R.L. Naff: USGS–TWRI Book 3, Chapter B4. 1990. 232 pages.
- 3-B4. *Supplement 1. Regression modeling of ground-water flow --Modifications to the computer code for nonlinear regression solution of steady-state ground-water flow problems*, by R.L. Cooley: USGS–TWRI Book 3, Chapter B4. 1993. 8 pages.
- 3-B5. *Definition of boundary and initial conditions in the analysis of saturated ground-water flow systems—An introduction*, by O.L. Franke, T.E. Reilly, and G.D. Bennett: USGS–TWRI Book 3, Chapter B5. 1987. 15 pages.
- 3-B6. *The principle of superposition and its application in ground-water hydraulics*, by T.E. Reilly, O.L. Franke, and G.D. Bennett: USGS–TWRI Book 3, Chapter B6. 1987. 28 pages.
- 3-B7. *Analytical solutions for one-, two-, and three-dimensional solute transport in ground-water systems with uniform flow*, by E.J. Wexler: USGS–TWRI Book 3, Chapter B7. 1992. 190 pages.

Section C. Sedimentation and Erosion Techniques

- 3-C1. *Fluvial sediment concepts*, by H.P. Guy: USGS–TWRI Book 3, Chapter C1. 1970. 55 pages.
- 3-C2. *Field methods for measurement of fluvial sediment*, by H.P. Guy and V.W. Norman: USGS–TWRI Book 3, Chapter C2. 1970. 59 pages.
- 3-C3. *Computation of fluvial-sediment discharge*, by George Porterfield: USGS–TWRI Book 3, Chapter C3. 1972. 66 pages.

Book 4. Hydrologic Analysis and Interpretation

Section A. Statistical Analysis

- 4-A1. *Some statistical tools in hydrology*, by H.C. Riggs: USGS–TWRI Book 4, Chapter A1. 1968. 39 pages.
- 4-A2. *Frequency curves*, by H.C. Riggs: USGS–TWRI Book 4, Chapter A2. 1968. 15 pages.

Section B. Surface Water

- 4-B1. *Low-flow investigations*, by H.C. Riggs: USGS–TWRI Book 4, Chapter B1. 1972. 18 pages.
- 4-B2. *Storage analyses for water supply*, by H.C. Riggs and C.H. Hardison: USGS–TWRI Book 4, Chapter B2. 1973. 20 pages.
- 4-B3. *Regional analyses of streamflow characteristics*, by H.C. Riggs: USGS–TWRI Book 4, Chapter B3. 1973. 15 pages.

Section D. Interrelated Phases of the Hydrologic Cycle

- 4-D1. *Computation of rate and volume of stream depletion by wells*, by C.T. Jenkins: USGS–TWRI Book 4, Chapter D1. 1970. 17 pages.

Book 5. Laboratory Analysis**Section A. Water Analysis**

- 5-A1. *Methods for determination of inorganic substances in water and fluvial sediments*, by M.J. Fishman and L.C. Friedman, editors: USGS–TWRI Book 5, Chapter A1. 1989. 545 pages.
- 5-A2. *Determination of minor elements in water by emission spectroscopy*, by P.R. Barnett and E.C. Mallory, Jr.: USGS–TWRI Book 5, Chapter A2. 1971. 31 pages.
- 5-A3. *Methods for the determination of organic substances in water and fluvial sediments*, edited by R.L. Wershaw, M.J. Fishman, R.R. Grabbe, and L.E. Lowe: USGS–TWRI Book 5, Chapter A3. 1987. 80 pages.
- 5-A4. *Methods for collection and analysis of aquatic biological and microbiological samples*, by L.J. Britton and P.E. Greeson, editors: USGS–TWRI Book 5, Chapter A4. 1989. 363 pages.
- 5-A5. *Methods for determination of radioactive substances in water and fluvial sediments*, by L.L. Thatcher, V.J. Janzer, and K.W. Edwards: USGS–TWRI Book 5, Chapter A5. 1977. 95 pages.
- 5-A6. *Quality assurance practices for the chemical and biological analyses of water and fluvial sediments*, by L.C. Friedman and D.E. Erdmann: USGS–TWRI Book 5, Chapter A6. 1982. 181 pages.

Section C. Sediment Analysis

- 5-C1. *Laboratory theory and methods for sediment analysis*, by H.P. Guy: USGS–TWRI Book 5, Chapter C1. 1969. 58 pages.

Book 6. Modeling Techniques**Section A. Ground Water**

- 6-A1. *A modular three-dimensional finite-difference ground-water flow model*, by M.G. McDonald and A.W. Harbaugh: USGS–TWRI Book 6, Chapter A1. 1988. 586 pages.
- 6-A2. *Documentation of a computer program to simulate aquifer-system compaction using the modular finite-difference ground-water flow model*, by S.A. Leake and D.E. Prudic: USGS–TWRI Book 6, Chapter A2. 1991. 68 pages.
- 6-A3. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 1: Model Description and User's Manual*, by L.J. Torak: USGS–TWRI Book 6, Chapter A3. 1993. 136 pages.
- 6-A4. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 2: Derivation of finite-element equations and comparisons with analytical solutions*, by R.L. Cooley: USGS–TWRI Book 6, Chapter A4. 1992. 108 pages.
- 6-A5. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 3: Design philosophy and programming details*, by L.J. Torak: USGS–TWRI Book 6, Chapter A5, 1993. 243 pages.
- 6-A6. *A coupled surface-water and ground-water flow model (MODBRANCH) for simulation of stream-aquifer interaction*, by Eric D. Swain and Eliezer J. Wexler. 1996. 125 pages.

Book 7. Automated Data Processing and Computations**Section C. Computer Programs**

- 7-C1. *Finite difference model for aquifer simulation in two dimensions with results of numerical experiments*, by P.C. Trescott, G.F. Pinder, and S.P. Larson: USGS–TWRI Book 7, Chapter C1. 1976. 116 pages.
- 7-C2. *Computer model of two-dimensional solute transport and dispersion in ground water*, by L.F. Konikow and J.D. Bredehoeft: USGS–TWRI Book 7, Chapter C2. 1978. 90 pages.
- 7-C3. *A model for simulation of flow in singular and interconnected channels*, by R.W. Schaffranek, R.A. Baltzer, and D.E. Goldberg: USGS–TWRI Book 7, Chapter C3. 1981. 110 pages.

Book 8. Instrumentation**Section A. Instruments for Measurement of Water Level**

- 8-A1. *Methods of measuring water levels in deep wells*, by M.S. Garber and F.C. Koopman: USGS–TWRI Book 8, Chapter A1. 1968. 23 pages.
- 8-A2. *Installation and service manual for U.S. Geological Survey manometers*, by J.D. Craig: USGS–TWRI Book 8, Chapter A2. 1983. 57 pages.

Section B. Instruments for Measurement of Discharge

- 8-B2. *Calibration and maintenance of vertical-axis type current meters*, by G.F. Smoot and C.E. Novak: USGS–TWRI Book 8, Chapter B2. 1968. 15 pages.

Book 9. Handbooks for Water-Resources Investigations**Section A. National Field Manual for the Collection of Water-Quality Data**

- 9-A1. *National Field Manual for the Collection of Water-Quality Data: Preparations for Water Sampling*, by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A1. 1998. 47 p.
- 9-A2. *National Field Manual for the Collection of Water-Quality Data: Selection of Equipment for Water Sampling*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A2. 1998. 94 p.
- 9-A3. *National Field Manual for the Collection of Water-Quality Data: Cleaning of Equipment for Water Sampling*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A3. 1998. 75 p.
- 9-A5. *National Field Manual for the Collection of Water-Quality Data: Processing of Water Samples*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A5. 1999, 149 p.
- 9-A6. *National Field Manual for the Collection of Water-Quality Data: Field Measurements*, edited by F.D. Wilde and D.B. Radtke: USGS-TWRI Book 9, Chapter A6. 1998. Variously paginated.
- 9-A7. *National Field Manual for the Collection of Water-Quality Data: Biological Indicators*, by D.N. Myers and F.D. Wilde: USGS-TWRI Book 9, Chapter A7.1. 1997. 49 pages.
- 9-A7. *National Field Manual for the Collection of Water-Quality Data: Five-Day Biochemical Oxygen Demand*, by G.C. Delzer and S.W. McKenzie: USGS-TWRI Book 9, Chapter A7.2 1999. 28 p.
- 9-A8. *National Field Manual for the Collection of Water-Quality Data: Bottom-Material Samples*, by D.B. Radtke: USGS-TWRI Book 9, Chapter A8. 1998. 48 pages.
- 9-A9. *National Field Manual for the Collection of Water-Quality Data: Safety in Field Activities*, by S.L. Lane and R.G. Fay: USGS-TWRI Book 9, Chapter A9. 1998. 60 pages.




Figure 6.--Location of continuous-record data-collection stations in the upper Delaware River Basin.




Figure 8.--Location of partial-record data-collection stations in the upper Delaware River Basin.




Figure 9.--Location of partial-record data-collection stations in the lower Delaware River Basin.




Figure 10.--Location of stations in the Delaware River Basin National Water-Quality Assessment Program surface-water fixed site network.

SPECIAL NOTES, REMARK CODES, AND SELECTED CONSTITUENT DEFINITIONS

NOTES--Traditionally, dissolved trace-element concentrations have been reported at the microgram per liter ($\mu\text{G/L}$) level. Recent evidence, mostly from large rivers, indicates that actual dissolved-phase concentrations for a number of trace elements are within the range of 10's to 100's of nanograms per liter (ng/L). Data above the $\mu\text{G/L}$ level should be viewed with caution. Such data may actually represent elevated environmental concentrations from natural or human causes; however, these data could reflect contamination introduced during sampling, processing, or analysis. To confidently produce dissolved trace-element data with insignificant contamination, the U.S. Geological Survey began using new trace-element protocols at some stations in water year 1994. Full implementation of the protocols took place during the 1995 water year.

--Sample handling procedures at all **National Trends Network** stations were changed substantially on January 11, 1994, in order to reduce contamination from the sample shipping container. The data for samples before and after that date are different and not directly comparable. A tabular summary of the differences based on a special intercomparison study, is available from the NADP/NTN Coordination Office, Colorado State University, Fort Collins, CO 80523 (Telephone: 303-491-5643).

--In March 1989 a bias was discovered in the turbidimetric method for sulfate analysis for those samples analyzed by the U.S. Geological Survey National Water-Quality Laboratory indicating that values below 75 mg/L have a median positive bias of 2 mg/L above the true value for the period between 1982 and 1989.

--**Methylene blue active substance (MBAS)** determinations made from January 1, 1970, through August 29, 1993, at the National Water Quality Laboratory in Denver (Analyzing Agency Code 80020) are positively biased. These data can be corrected on the basis of the following equation, if concentrations of dissolved nitrate plus nitrite, as nitrogen, and dissolved chloride, determined concurrently with the MBAS data are applied:

$$\text{MBASCOR} = \text{M} - 0.0088\text{N} - 0.00019\text{C}$$

where:

MBASCOR = corrected MBAS concentration, in mg/L ;
 M = reported MBAS concentration, in mg/L ;
 N = dissolved nitrate plus nitrite, as nitrogen, in mg/L ; and
 C = dissolved chloride concentration, in mg/L .

The detection limit of the new method is 0.02 mg/L , whereas the detection limit for the old method was 0.01 mg/L . A detection limit of 0.02 mg/L should be used with corrected MBAS data from January 1, 1970, through August 29, 1993.

Remark Codes--The following remark codes may appear with the data tables in this report:

PRINTED OUTPUT

REMARK

E,e	Estimated value.
>	Actual value is known to be greater than the value shown.
<	Actual value is known to be less than the value shown.
K	Results based on colony count outside the acceptance range (non-ideal colony count).
L	Biological organism count less than 0.5 percent (organism may be observed rather than counted).
D	Biological organism count equal to or greater than 15 percent (dominant).
&	Biological organism estimated as dominant.
ND	Material specifically analyzed for but not detected.
V	Analyte was detected in both the environmental sample and the associated blanks.

EXPLANATION OF CODES USED TO DEFINE SAMPLE COLLECTION PROCEDURES (partial listing)

(71999) SAMPLE PURPOSE CODES:

10--Routine
 15--NAWQA
 20--NASQAN
 30--Benchmark

(84164) SAMPLER TYPE: (partial list)

110--Sewage sampler
 3011--US D-77
 3035--DH-76 Trace metal sampler with
 teflon gasket and nozzle

(82398) SAMPLE METHOD CODES:

10--Equal width increment
 20--Equal discharge increment
 30--Single vertical
 40--Multiple verticals
 50--Point sample
 70--Grab sample
 120--Velocity integrated

3039--D-77 Trace metal
 3040--D-77 Trace metal modified teflon
 bag sampler
 3045--DH-81 with Teflon cap and
 nozzle
 8010--Other (other than a defined sampler type)

SPECIAL NOTES, REMARK CODES AND SELECTED CONSTITUENT DEFINITIONS--Continued**Explanation of selected abbreviations used in constituent definitions in water-quality tables:**

AC-FT	acre-feet
BOT MAT	bottom material (Unconsolidated material of which a streambed, lake, pond, reservoir, or estuary bottom is composed.)
COLS/100 ML	colonies per 100 milliliters
DIS	dissolved
FET	fixed end-point titration
FLD	field (Measurement determined at field site.)
F/S	feet per second
G/M	gallons per minute
G/SQM; MG/M2	grams or milligrams per square meter
IT	incremental titration
KF AGAR	nutrient medium for growth of fecal streptococcal bacteria
μG/L	micrograms per liter
μS/CM	microsiemens per centimeter
MG/L	milligrams per liter
MG/M2	milligrams per square meter
MM OF HG	millimeters of mercury
NONCARB	noncarbonate
NTU	nephelometric turbidity unit
PCI/L	picocuries per liter
REC	recoverable
TOT	total
T/DAY	tons per day
WH IT	whole water, incremental titration (Alkalinity, bicarbonate, and carbonate as determined by incremental titration of unfiltered water at the field site.)
2 SIGMA	Counting statistic that represents error in the reported radon, uranium, or tritium value caused by variations in sample counting, background radiation, volume of sample, and decay since sample was collected.
0.7μ GF	0.7 micron glass-fiber filter (Water filtered through a glass-fiber membrane filter with openings that are 0.7 microns in size.)

(00027) AGENCY COLLECTING SAMPLE CODES: (partial listing)

1028 --U.S. Geological Survey

(00028) AGENCY ANALYZING SAMPLE CODES: (partial listing)

1028 --U.S. Geological Survey
80020 --U.S. Geological Survey, National Water-Quality Laboratory, Denver, Colorado
9813 --Pennsylvania Department of Environmental Protection