


Water Resources Data Pennsylvania Water Year 1999

Volume 2. Susquehanna and Potomac River Basins

By R.R. Durlin and W.P. Schaffstall

Water-Data Report PA-99-2



Prepared in cooperation with the Pennsylvania Department of Environmental Protection, the Baltimore District of the U.S. Army Corps of Engineers, and with other State, municipal, and Federal agencies.

PREFACE

This volume of the annual hydrologic data report of Pennsylvania is one of a series of annual reports that document hydrologic data gathered from the U.S. Geological Survey's surface- and ground-water data-collection networks in each State, Puerto Rico, and the Trust Territories. These records of streamflow, ground-water levels, and quality of water provide the hydrologic information needed by State, local, and Federal agencies, and the private sector for developing and managing our Nation's land and water resources. Hydrologic data for Pennsylvania are contained in 3 volumes.

- Volume 1. Delaware River Basin
- Volume 2. Susquehanna and Potomac River Basins
- Volume 3. Ohio and St. Lawrence River Basins

Volume 2 was prepared in cooperation with the Commonwealth of Pennsylvania and other agencies under the general supervision of William H. Werkheiser, District Chief, Pennsylvania District; Robert A. Hainly, Assistant District Chief for Hydrologic Surveillance and Data Management; Randall R. Durlin, Chief of the Hydrologic Surveillance Program, Lemoyne District Office, and William P. Schaffstall, Chief, Williamsport Project Office. It is the product of a team effort by dedicated personnel of the U.S. Geological Survey who collected, compiled, analyzed, verified, and organized these data, and who typed, edited, and assembled the report. In addition to the authors, who had primary responsibility for assuring that the information contained herein is accurate, complete, and adheres to Geological Survey policy and established guidelines, the following individuals contributed significantly to the collection, processing, and tabulation of these data:

| | | |
|----------------|------------------|-----------------|
| M. R. Beaver | J. D. Hollenbach | L. A. Reed |
| J. K. Bender | K. S. Housel | A. G. Reif |
| T. M. Bickford | J. V. Irvin | J. D. Riggle |
| R. T. Campbell | M. Janiszewski | J. J. Rote |
| J. J. Chaplin | M. E. Jones | W. K. Schachner |
| C. A. Cravotta | D. G. Kelley | M. D. Schuster |
| E. R. Eismont | E. H. Koerkle | R. W. Siwicki |
| L. J. Fekula | B. D. Lindsey | T. Spanish |
| J. T. Fisher | C. A. Loper | K. E. Tuers |
| D. G. Galeone | R. A. Ludlow | M. V. Truhlar |
| J. S. Grover | T. M. Noonan | J. B. Weitzel |

CONTENTS

| | Page |
|---|-------------|
| Preface | iii |
| List of surface-water stations, in downstream order, for which records are published in this volume | vii |
| List of ground-water wells, by county, for which records are published in this volume | x |
| List of discontinued continuous-record surface-water discharge stations | xi |
| List of discontinued continuous-record surface-water-quality stations | xv |
| Pennsylvania District office locations and addresses | xx |
| Introduction | 1 |
| Cooperation | 1 |
| Summary of hydrologic conditions | 3 |
| Surface water | 3 |
| Reservoirs | 6 |
| Ground water | 6 |
| References..... | 6 |
| Special networks and programs | 8 |
| Explanation of the records | 8 |
| Station identification numbers | 9 |
| Downstream-order system | 9 |
| Latitude-longitude system..... | 9 |
| Records of stage and water discharge..... | 10 |
| Data collection and computation | 10 |
| Data presentation | 11 |
| Station manuscript | 11 |
| Data table of daily mean values | 12 |
| Statistics of monthly mean data | 12 |
| Summary statistics | 12 |
| Identifying estimated daily discharge | 13 |
| Accuracy of the records | 14 |
| Other records available | 14 |
| Records of surface-water quality | 14 |
| Classification of records | 14 |
| Arrangement of records | 14 |
| On-site measurements and sample collection | 15 |
| Water temperature..... | 15 |
| Sediment | 15 |
| Laboratory measurements..... | 16 |
| Data presentation | 16 |
| Remark codes..... | 17 |
| Water quality-control data | 17 |
| Records of ground-water levels | 18 |
| Data collection and computation | 18 |
| Data presentation | 18 |
| Data table of water-levels | 19 |
| Records of ground-water quality | 19 |
| Data collection and computation | 19 |
| Data presentation | 20 |
| Access to USGS Water Data | 20 |
| Definition of terms | 21 |
| Publications on Techniques of Water-Resources Investigations | 31 |
| Special Notes, Remark Codes, and Selected Constituent Definitions | 38 |

CONTENTS--Continued

| | Page |
|---|-------------|
| Station records, surface water | |
| Continuous water-discharge and water-quality station records | 40 |
| Discharge at partial-record stations and miscellaneous sites | |
| Crest-stage partial-record stations..... | 328 |
| Miscellaneous sites | 332 |
| Analyses of streamflow samples collected at partial-record stations | 337 |
| Analyses of samples collected at special-study sites | |
| Chesapeake Bay Ecosystem Project..... | 340 |
| Swatara Creek Project..... | 342 |
| Special Notes, Remark Codes, and Selected Constituent Definitions | 388 |
| Station records, ground water | |
| Water-level and water-quality..... | 390 |
| Analyses of ground-water samples collected at special-study sites | |
| Mill Creek Basin, Streambank Fencing Project..... | 435 |
| Index | 439 |

ILLUSTRATIONS

| | |
|---|-----|
| Figure 1. Comparison of monthly precipitation at two National Oceanic and Atmospheric Administration climatological stations during the 1999 water year and mean monthly precipitation for the period 1961 through 1990 | 4 |
| 2. Comparison of streamflow at two long-term streamflow-gaging stations during the 1999 water year and the median monthly and annual mean streamflow for the period 1961 through 1990..... | 5 |
| 3. Relation between 1999 seasonal ground-water levels and long-term ground-water levels..... | 7 |
| 4. System for numbering wells and miscellaneous sites..... | 9 |
| 5-8. Maps showing: | |
| 5. Location of continuous-record data-collection stations and network observation wells, Susquehanna River Basin | 35 |
| 6. Location of partial-record data-collection stations, Susquehanna River Basin | 36 |
| 7. Location of continuous- and partial-record data-collection stations, Potomac River Basin..... | 37 |
| 8. Location of water-quality and streamflow monitoring stations in the Swatara Creek Basin | 343 |

TABLES

| | |
|--|-----|
| Table 1. Swatara Creek Project station list | 344 |
| 2. Mill Creek Basin, Streambank Fencing Project station list | 435 |

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

[Letters after station name designate type of data: (d) discharge, (c) chemical, (b) biological, (t) water temperature, (sc) specific conductance, (s) sediment, (e) elevation, gage heights, or contents.]

NORTH ATLANTIC SLOPE BASINS

| | Station number | Page |
|---|---------------------------|-------------|
| SUSQUEHANNA RIVER BASIN | | |
| CHEMUNG RIVER BASIN | | |
| Tioga River near Mansfield (d)..... | 01516350 | 40 |
| Corey Creek near Mainesburg (d)..... | 01516500 | 42 |
| Tioga River at Tioga (d) | 01518000 | 44 |
| Tioga River at Tioga Junction (d)..... | 01518700 | 46 |
| Cowanesque River at Westfield (d) | 01518862 | 48 |
| Cowanesque River near Lawrenceville (d)..... | 01520000 | 50 |
| Reservoirs in Chemung River Basin (e) | | 52 |
| Susquehanna River at Towanda (d) | 01531500 | 54 |
| TOWANDA CREEK BASIN | | |
| Towanda Creek near Monroeton (d)..... | 01532000 | 56 |
| Susquehanna River at Meshoppen (d) | 01533400 | 58 |
| TUNKHANNOCK CREEK BASIN | | |
| Tunkhannock Creek near Tunkhannock (d) | 01534000 | 60 |
| LACKAWANNA RIVER BASIN | | |
| Stillwater Lake near Forest City (e)..... | 01534180 | 63 |
| Lackawanna River near Forest City (d)..... | 01534300 | 64 |
| Lackawanna River at Archbald (d)..... | 01534500 | 66 |
| Lackawanna River at Old Forge (d)..... | 01536000 | 68 |
| Susquehanna River at Wilkes-Barre (d) | 01536500 | 70 |
| WAPWALLOPEN CREEK BASIN | | |
| Wapwallopen Creek near Wapwallopen (d)..... | 01538000 | 72 |
| FISHING CREEK BASIN | | |
| Fishing Creek near Bloomsburg (d)..... | 01539000 | 74 |
| Susquehanna River at Danville (d) | 01540500 | 76 |
| WEST BRANCH SUSQUEHANNA RIVER BASIN | | |
| West Branch Susquehanna River at Bower (d)..... | 01541000 | 78 |
| West Branch Susquehanna River at Curwensville (d)..... | 01541200 | 80 |
| West Branch Susquehanna River at Hyde (d)..... | 01541303 | 82 |
| Clearfield Creek at Dimeling (d) | 01541500 | 84 |
| Bennett Branch Sinnemahoning Creek (head of Sinnemahoning Creek): | | |
| Driftwood Branch Sinnemahoning Creek: | | |
| North Creek: | | |
| Waldy Run near Emporium (d) | 01542810 | 86 |
| Driftwood Branch Sinnemahoning Creek at Sterling Run (d)..... | 01543000 | 88 |
| Sinnemahoning Creek at Sinnemahoning (d) | 01543500 | 90 |
| First Fork Sinnemahoning Creek near Sinnemahoning (d) | 01544000 | 92 |
| Kettle Creek at Cross Fork (d)..... | 01544500 | 94 |
| Kettle Creek near Westport (d)..... | 01545000 | 96 |
| West Branch Susquehanna River at Renovo (d)..... | 01545500 | 98 |
| Young Womans Creek near Renovo (d,c)..... | 01545600 | 100 |

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

NORTH ATLANTIC SLOPE BASINS--Continued

| | Station number | Page |
|--|---------------------------|-------------|
| SUSQUEHANNA RIVER BASIN --Continued | | |
| Bald Eagle Creek: | | |
| Spring Creek at Houserville (d) | 01546400 | 104 |
| Spring Creek near Axemann (d) | 01546500 | 106 |
| Spring Creek at Milesburg (d) | 01547100 | 108 |
| Bald Eagle Creek below Spring Creek at Milesburg (d) | 01547200 | 110 |
| Bald Eagle Creek at Blanchard (d) | 01547500 | 112 |
| Marsh Creek at Blanchard (d) | 01547700 | 114 |
| Beech Creek at Monument (d) | 01547950 | 116 |
| Pine Creek at Cedar Run (d) | 01548500 | 118 |
| Little Pine Creek: | | |
| Blockhouse Creek near English Center (d) | 01549500 | 120 |
| Pine Creek below Little Pine Creek near Waterville (d) | 01549700 | 122 |
| Lycoming Creek near Trout Run (d) | 01550000 | 124 |
| West Branch Susquehanna River at Williamsport (d) | 01551500 | 126 |
| Loyalsock Creek at Loyalsockville (d) | 01552000 | 128 |
| Muncy Creek near Sonestown (d) | 01552500 | 130 |
| West Branch Susquehanna River at Lewisburg (d) | 01553500 | 132 |
| Chillisquaque Creek at Washingtonville (d) | 01553700 | 134 |
| Reservoirs in West Branch Susquehanna River Basin (e) | | 136 |
| Susquehanna River at Sunbury (d) | 01554000 | 138 |
| PENNS CREEK BASIN | | |
| Penns Creek at Penns Creek (d) | 01555000 | 140 |
| EAST MAHANTANGO CREEK BASIN | | |
| East Mahantango Creek at Klingerstown (d,c,b,t) | 01555400 | 142 |
| East Mahantango Creek near Dalmatia (d) | 01555500 | 158 |
| JUNIATA RIVER BASIN | | |
| Frankstown Branch Juniata River (head of Juniata River): | | |
| Frankstown Branch Juniata River at Williamsburg (d) | 01556000 | 160 |
| Little Juniata River: | | |
| Bald Eagle Creek at Tyrone (d) | 01557500 | 162 |
| Little Juniata River at Spruce Creek (d) | 01558000 | 164 |
| Juniata River at Huntingdon (d) | 01559000 | 166 |
| Raystown Branch Juniata River: | | |
| Dunning Creek: | | |
| Bobs Creek near Pavia (d,c,b,t) | 01559795 | 168 |
| Dunning Creek at Belden (d) | 01560000 | 182 |
| Raystown Branch Juniata River at Saxton (d) | 01562000 | 184 |
| Raystown Lake near Huntingdon (e) | 01563100 | 187 |
| Raystown Branch Juniata River below Raystown Dam near Huntingdon (d) | 01563200 | 188 |
| Juniata River at Mapleton Depot (d) | 01563500 | 190 |
| Aughwick Creek near Three Springs (d) | 01564500 | 192 |
| Juniata River at Newport (d) | 01567000 | 194 |
| SHERMAN CREEK BASIN | | |
| Sherman Creek: | | |
| Bixler Run near Loysville (d) | 01567500 | 196 |
| Sherman Creek at Shermans Dale (d) | 01568000 | 198 |
| CONODOGUINET CREEK BASIN | | |
| Conodoguinet Creek: | | |
| Letort Spring Run near Carlisle (d) | 01569800 | 200 |
| Conodoguinet Creek near Hogestown (d,c) | 01570000 | 202 |
| Susquehanna River at Harrisburg (d) | 01570500 | 208 |

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

NORTH ATLANTIC SLOPE BASINS--Continued

| | Station number | Page |
|--|-------------------|------|
| SUSQUEHANNA RIVER BASIN --Continued | | |
| YELLOW BREECHES CREEK BASIN | | |
| Yellow Breeches Creek: | | |
| Yellow Breeches Creek near Camp Hill (d) | 01571500 | 210 |
| SWATARA CREEK BASIN | | |
| Swatara Creek, Site C1, near Newtown (c,sc,pH,t) | 0157155010 | 212 |
| Swatara Creek, Site C3, near Newtown (d,c,sc,pH,t) | 0157155014 | 220 |
| Rowe Drainage Tunnel, Site E2-244, near Joliett (c,sc,pH,t) | 403542076263201 | 234 |
| Lorberry Creek, Site E2-0, at Lorberry (c,sc,pH,t) | 01571774 | 239 |
| Swatara Creek at Ravine (d,c,sc,pH,t) | 01571820 | 244 |
| Swatara Creek near Pine Grove (d,c) | 01572025 | 260 |
| Swatara Creek near Inwood (d) | 01572190 | 270 |
| Swatara Creek at Harper Tavern (d) | 01573000 | 272 |
| Swatara Creek near Hershey (d) | 01573560 | 274 |
| WEST CONEWAGO CREEK BASIN | | |
| West Conewago Creek near Manchester (d) | 01574000 | 276 |
| CODORUS CREEK BASIN | | |
| Codorus Creek at Spring Grove (d) | 01574500 | 278 |
| Reservoirs in Codorus Creek Basin (e) | | 281 |
| Susquehanna River at Marietta (d) | 01576000 | 282 |
| CONESTOGA RIVER BASIN | | |
| Conestoga River: | | |
| Conestoga River at Lancaster (d) | 01576500 | 284 |
| Mill Creek: | | |
| Big Spring Run below Willow Branch near Willow Street (c,b) | 01576519 | 287 |
| Big Spring Run near Willow Street (d,c,b) | 01576521 | 290 |
| Unnamed Tributary: | | |
| South Fork Unnamed Tributary to Big Spring Run at Lampeter (c) | 01576525 | 297 |
| North Fork Unnamed Tributary to Big Spring Run near Willow Street (c,b) | 01576526 | 299 |
| North Fork Unnamed Tributary to Big Spring Run near Lampeter (d,c) | 015765265 | 302 |
| North Fork Unnamed Tributary to Big Spring Run at Lampeter (d,c) | 01576527 | 306 |
| Unnamed Tributary to Big Spring Run near Willow Street (c,b) | 01576528 | 311 |
| Unnamed Tributary to Big Spring Run near Lampeter (d,c,b) | 01576529 | 314 |
| Mill Creek at Eshelman Mill Road near Lyndon (d) | 01576540 | 322 |
| Conestoga River at Conestoga (d) | 01576754 | 324 |
| POTOMAC RIVER BASIN | | |
| TONOLOWAY CREEK BASIN | | |
| Tonoloway Creek near Needmore (d) | 01613050 | 326 |
| <hr/> | | |
| Discharge at partial-record stations and miscellaneous sites | | |
| Crest-stage partial-record stations | | 328 |
| Miscellaneous sites | | 332 |
| Analysis of streamflow samples collected at partial-record and special-study sites | | |
| Analysis of streamflow samples collected at partial-record stations | | 337 |
| Analysis of samples collected at special-study sites | | |
| Chesapeake Bay Ecosystem Project | | 340 |
| Swatara Creek Project | | 342 |

GROUND-WATER WELLS, BY COUNTY, FOR WHICH RECORDS ARE PUBLISHED IN THIS VOLUME

(Letters after local well number designate type of data: (l) water level, (c) chemical)

GROUND-WATER RECORDS**Page****ADAMS COUNTY**

Well 395846077040601 Local number AD 146 (l) 390

BEDFORD COUNTY

Well 400217078281901 Local number BD 150 (l) 391

BLAIR COUNTY

Well 402452078271301 Local number BA 74 (l) 392

BRADFORD COUNTY

Well 414330076280501 Local number BR 92 (l) 393

CAMERON COUNTY

Well 412732078034201 Local number CM 13 (l) 394

CENTRE COUNTY

Well 404518077575501 Local number CE 118 (l) 395

CLINTON COUNTY

Well 411424077462201 Local number CN 1 (l) 396

CUMBERLAND COUNTY

Well 400209077183301 Local number CU 2 (l) 397

DAUPHIN COUNTY

Well 402118076462201 Local number DA 350 (l) 398

FRANKLIN COUNTY

Well 394731077411701 Local number FR 332 (l) 399

HUNTINGDON COUNTY

Well 401843078075401 Local number HU 301 (l) 400

JUNIATA COUNTY

Well 402411077374801 Local number JU 351 (l) 401

LANCASTER COUNTY

Well 400506076235201 Local number LN 514 (l) 402

Well 395947076145901 Local number LN 2037 (l,c) 403

Well 395947076145902 Local number LN 2038 (l,c) 406

Well 395947076145903 Local number LN 2039 (l,c) 409

Well 395947076145904 Local number LN 2040 (l,c) 411

Well 395957076155201 Local number LN 2041 (l,c) 414

Well 395957076155202 Local number LN 2042 (l,c) 417

Well 395957076155203 Local number LN 2043 (l,c) 420

Well 395957076155204 Local number LN 2044 (l,c) 422

LUZERNE COUNTY

Well 411756076162701 Local number LU 294 (l) 425

LYCOMING COUNTY

Well 412427076594401 Local number LY 112 (l) 426

MIFFLIN COUNTY

Well 404140077354001 Local number MF 344 (l) 427

POTTER COUNTY

Well 414640077493801 Local number PO 72 (l) 428

SNYDER COUNTY

Well 403939076591001 Local number SN 130 (l) 429

SULLIVAN COUNTY

Well 413026076352901 Local number SU 34 (l) 430

SUSQUEHANNA COUNTY

Well 415323077451301 Local number SQ 61 (l) 431

TIOGA COUNTY

Well 414513077333701 Local number TI 100 (l) 432

UNION COUNTY

Well 405928077115501 Local number UN 51 (l) 433

GROUND-WATER DATA COLLECTED AT SPECIAL-STUDY SITES

Mill Creek Basin, Streambank Fencing Project..... 435

The following continuous-record surface-water discharge stations (listed by river basin in alphabetical order by stream name) have been discontinued. Daily streamflow records were collected and published for the period of record shown for each station. Discontinued stations with less than 3 years of record have not been included. Information regarding these stations may be obtained from the District Office at the address given on the back of the title page of this report.

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS

| Station name | Station number | Drainage area (mi ²) | Period of record (water years) |
|--|----------------|----------------------------------|--------------------------------|
| SUSQUEHANNA RIVER BASIN | | | |
| Anna S mine discharge #1 near Antrim | 01548416 | mine discharge | 1978-81 |
| Antes Creek near Jersey Shore | 01549755 | 53.3 | 1974-77 |
| Applemans Run above Light Street | 01539200 | 1.72 | 1972-74 |
| Applemans Run below Light Street | 01539210 | 1.99 | 1972-74 |
| Aughwick Creek near Orbisonia | 01564000 | 174 | 1930-38 |
| Bachman Run at Annville | 01573095 | 7.3 | 1993-95 |
| Bald Eagle Creek near Beech Creek Station | 01548005* | 562 | 1910-95 |
| Bald Eagle Creek near Fawn Grove | 01577400 | .43 | 1986-89 |
| Beck Creek near Cleona | 01573086 | 7.87 | 1963-81 |
| Blockhouse Creek at Buttonwood | 01549300 | 22.3 | 1973-77 |
| Blockhouse Creek tributary at Liberty | 01549100 | 1.08 | 1973-77 |
| Bowery Run near Quarryville | 01578400 | 5.98 | 1963-81 |
| Bradley Run near Ashville | 01541308 | 6.77 | 1968-80 |
| Brush Creek at Gapsville | 01561000 | 36.8 | 1930-58 |
| Brush Run, Site 2, near McSherrystown | 01573810 | .38 | 1985-91 |
| Butler Creek at Gibson | 01533800 | 7.38 | 1974-79 |
| Cedar Run at Eberlys Mill | 01571490 | 12.6 | 1993-95 |
| Clark Creek near Carsonville | 01568500 | 22.5 | 1937-96 |
| Cocalamus Creek near Millerstown | 01566500 | 57.2 | 1931-58 |
| Codorus Creek at Pleasureville | 01575585 | 267 | 1985-90 |
| Codorus Creek near York | 01575500* | 222 | 1940-96 |
| Conodoguinet Creek tributary No. 1 near Enola | 01570100 | .77 | 1969-76 |
| Conodoguinet Creek tributary No. 2 near Enola | 01570200 | .76 | 1969-76 |
| Conodoguinet Creek tributary No. 2A near Enola | 01570230 | .70 | 1969-76 |
| Conodoguinet Creek tributary No. 2B near Enola | 01570260 | .65 | 1969-76 |
| Conodoguinet Creek tributary No. 3 near Enola | 01570300 | .38 | 1969-76 |
| Crooked Creek at Tioga | 01518500 | 122 | 1954-74 |
| Dunning Creek at Yount | 01560500 | 191 | 1930-39 |

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS (Continued)

| Station name | Station number | Drainage area (mi ²) | Period of record (water years) |
|--|----------------|----------------------------------|--------------------------------|
| East Branch Chillisquaque Creek near Washingtonville | 01553600 | 9.48 | 1960-78 |
| East Branch Codorus Creek tributary near Winterstown | 01574800 | 5.17 | 1969-75 |
| Elk Run near Mainesburg | 01517000 | 10.2 | 1955-78 |
| Fishing Creek at Bloomsburg | 01540000 | 355 | 1914-28 |
| Great Trough Creek near Marklesburg | 01562500 | 84.6 | 1930-57 |
| Hunter Drift discharge near Antrim | 01548418 | mine discharge | 1978-81 |
| Kishacoquillas Creek at Reedsville | 01565000* | 164 | 1940-70, 1984-85 |
| Lackawanna River at Moosic | 01535500 | 264 | 1914-28 |
| Larrys Creek at Cogan House | 01549780 | 6.80 | 1961-78 |
| Little Conestoga Creek near Churchtown | 01576085 | 5.82 | 1982-95 |
| Little Conestoga Creek, Site 3A, near Morgantown | 0157608335 | 1.42 | 1984-91 |
| Little Fishing Creek at Eyers Grove | 01539500 | 56.5 | 1941-58 |
| Little Juniata River at Tipton | 01556500 | 93.7 | 1946-62 |
| Little Juniata River near Tyrone | 01557000 | 101 | 1940-45 |
| Little Lost Creek at Oakland Mills | 01565700 | 6.52 | 1964-81 |
| Little Nescopeck Creek tributary near Freeland | 01538510 | mine discharge | 1974-79, 1996-98 |
| Lower Little Swatara Creek at Pine Grove | 01572000 | 34.3 | 1920-32, 1981-84 |
| Manada Creek at Manada Gap | 01573500 | 13.5 | 1938-58 |
| Middle Br. Wyalusing Creek trib. near Birchardsville | 01532850 | 5.67 | 1965-79 |
| Mitchell Mine discharge #2 near Antrim | 01548413 | mine discharge | 1978-81 |
| Moshannon Creek at Osceola Mills | 01542000 | 68.8 | 1941-93 |
| Muddy Creek at Castle Fin | 01577500 | 133 | 1929-38, 1968-71 |
| Muddy Run at Weavertown | 01576520 | 6.68 | 1993-97 |
| Nescopeck Creek near St. Johns | 01538500 | 49.0 | 1920-26 |
| North Bald Eagle Creek at Milesburg | 01546000 | 119 | 1911-28, 1934 |
| North Branch Mehoopany Creek near Lovelton | 01533500 | 35.2 | 1941-58 |
| N. Branch Sugar Creek trib. near Columbia Crossroads | 01531250 | 8.83 | 1963-68 |
| Paxton Creek near Penbrook | 01571000‡ | 11.2 | 1940-50, 1985-89 1992-95 |
| Pequea Creek at Martic Forge | 01576787 | 148 | 1977-81, 1993-95 |
| Pequea Creek tributary near Mt. Nebo | 01576788 | 0.20 | 1979-86 |
| Pine Creek near Waterville | 01549000 | 750 | 1909-20 |
| Quittapahilla Creek near Bellegrove | 01573160 | 74.2 | 1976-94 |

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS (Continued)

| Station name | Station number | Drainage area (mi ²) | Period of record (water years) |
|--|-----------------------|----------------------------------|--------------------------------|
| Raystown Branch Juniata River near Huntingdon | 01563000 ^a | 957 | 1947-71 |
| Sand Spring Run near White Deer | 01553130 | 4.93 | 1968-81 |
| Schell Run at Tyrone | 01557100 | 1.68 | 1958-62 |
| Shamokin Creek near Shamokin | 01554500 | 54.2 | 1938-93 |
| Shaver Creek near Petersburg | 01558500 | 46.4 | 1930-38 |
| Solomon Creek at Wilkes-Barre | 01537500 | 15.7 | 1940-90 |
| South Branch Codorus Creek near York | 01575000 | 117 | 1928-95 |
| South Branch Tunkhannock Creek near Montdale | 01533950 | 12.6 | 1961-78 |
| South Fork Beech Creek near Snow Shoe | 01547800 | 12.2 | 1969-81 |
| Spring Creek near Bellefonte | 01547000 | 136 | 1911-19 |
| Standing Stone Creek near Huntingdon | 01559500 | 128 | 1930-58 |
| Steam Valley Run at Buttonwood | 01549350 | 5.34 | 1973-77 |
| Stony Cr. above Pump-storage Reservoir near Dauphin | 01568700 | 11.5 | 1974-80 |
| Stony Creek at Water Tank Trail near Dauphin | 01568750 | 21.9 | 1974-76, 1985-86 |
| Stony Creek near Dauphin | 01569000 | 33.2 | 1938-45, 1967-74 |
| Sulphur Springs Creek near Manns Choice | 01559700 | 5.28 | 1962-78 |
| Susquehanna River near McCalls Ferry | 01577000 | 26,800 | 1904-11 |
| Swarr Run near Landisville | 01576697 | 8.67 | 1985-89 |
| Swatara Creek above highway bridge 895 at Pine Grove | 01571919 | 72.6 | 1982-84 |
| Swatara Creek below Ravine | 01571827 | 46.3 | 1985-87 |
| Swatara Creek near Suedberg | 01572030 | 124 | 1985-87 |
| Toby Creek at Luzerne | 01537000 | 32.4 | 1941-93 |
| Trexler Run near Ringtown | 01540200 | 1.77 | 1963-81 |
| Tuscarora Creek near Port Royal | 01566000* | 214 | 1911-58 |
| West Branch Susquehanna River at Karthaus | 01542500* | 1,462 | 1940-95 |
| White Deer Cr. above Sand Spring Run near White Deer | 01553120 | 17.8 | 1968-73 |
| White Deer Creek near White Deer | 01553140 | 40.0 | 1968-73 |
| Wilson Creek above Sand Run near Antrim | 01548408 | 12.6 | 1978-82 |
| POTOMAC RIVER BASIN | | | |
| Conococheague Creek near Fayetteville | 01614090* | 5.05 | 1961-81 |
| Evitts Creek near Centerville | 01603500 | 30.2 | 1933-82 |
| Licking Creek near Sylvan | 01613500* | 158 | 1930-41 |

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER DISCHARGE STATIONS (Continued)

| Station name | Station number | Drainage area (mi ²) | Period of record (water years) |
|---------------------------|----------------|----------------------------------|--------------------------------|
| Wills Creek below Hyndman | 01601000 | 146 | 1951-67 |

‡ Operated from October 1991 to September 1995 as a continuous-record surface-water discharge station and water-quality site.

* Currently operated as a partial-record station.

^a Records considered equivalent with station 01563200 Raystown Branch Juniata River below Raystown Dam near Huntingdon, published in this volume.

The following continuous-record water-quality stations (listed in alphabetical order by stream name) have been discontinued. Daily records were collected and published for the period shown for each constituent. Discontinued stations with less than 3 years of record, or stations with data collection less than daily, have not been included. If a station had one constituent with 3 or more years of record, all constituents having daily values will be listed for that station regardless of the length of record. Information regarding these stations may be obtained from the District Office at the address given on the back of the title page of this report.

The following are used to identify the record type: SC (specific conductance); pH; Temp (water temperature); DO (dissolved oxygen); Turb (turbidity, in JCU); Sed (sediment concentration and discharge).

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS

| Station name | Station number | Drainage area (mi ²) | Type of Record | Period of record (water years) |
|--|----------------|----------------------------------|--|---|
| SUSQUEHANNA RIVER BASIN | | | | |
| Applemans Run above Light Street | 01539200 | 1.72 | Turb, Sed | 1972-74 |
| Applemans Run below Light Street | 01539210 | 1.99 | Turb, Sed | 1972-74 |
| Bald Eagle Creek at Blanchard | 01547500 | 339 | Temp Temp ^b Temp ^a Sed | 1957 1967-81 1982-85 1956-58 |
| Bald Eagle Creek below Spring Creek at Milesburg | 01547200 | 265 | Temp Temp ^b Sed | 1956-58 1967-68 1956-58 |
| Bald Eagle Creek near Milesburg | 01547400 | 296 | Temp ^a | 1967-90 |
| Basswood Run near Antrim | 01548417 | .57 | Sed | 1978-80 |
| Beech Creek at Monument | 01547950 | 152 | SC ^a , pH ^a , Temp ^a DO ^a | 1969-80 1976-78 |
| Bixler Run near Loysville | 01567500 | 15.0 | Temp Temp ^b Sed | 1957-62 1963-65 1954-71 |
| Blockhouse Creek at Buttonwood | 01549300 | 22.3 | Temp ^a , Turb, Sed | 1973-77 |
| Blockhouse Creek near English Center | 01549500 | 37.7 | Temp ^a , Turb, Sed | 1973-77 |
| Blockhouse Creek tributary at Liberty | 01549100 | 1.08 | Temp ^a , Turb, Sed | 1973-77 |
| Cedar Run at Eberlys Mill | 01571490 | 12.6 | SC ^a , Temp ^a | 1993-95 |
| Conestoga River at Lancaster | 01576500 | 324 | SC Temp Sed | 1948-50, 1964-70, 1974-75 1948-50, 1959-70, 1974-75 1974-75 |
| Conodoguinet Creek tributary No. 1 near Enola | 01570100 | .77 | Turb Sed | 1972-75 1969-76 |

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS (Continued)

| Station name | Station number | Drainage area (mi ²) | Type of Record | Period of record (water years) |
|--|----------------|----------------------------------|-------------------------------------|--|
| Conodoguinet Creek tributary No. 2 near Enola | 01570200 | .76 | Turb Sed | 1973-75 1973-76 |
| Conodoguinet Creek tributary No. 2A near Enola | 01570230 | .70 | Turb Sed | 1973-75 1973-76 |
| Conodoguinet Creek tributary No. 2B near Enola | 01570260 | .65 | Turb Sed | 1973-75 1973-76 |
| Conodoguinet Creek tributary No. 3 near Enola | 01570300 | .38 | Turb Sed | 1972-75 1969-76 |
| Corey Creek near Mainesburg | 01516500 | 12.2 | Temp ^b Temp Sed | 1960-61 1959,1962 1954-67 ^c |
| Cowanesque River near Lawrenceville | 01520000 | 298 | Temp ^a | 1972-86 |
| East Mahantango Creek at Klingerstown | 01555400 | 44.7 | SC ^a | 1993-95 |
| Elk Run near Mainesburg | 01517000 | 10.2 | Temp ^b Temp Sed | 1958-59 1957, 1960-62 1955-67 |
| Fishing Creek near Bloomsburg | 01539000 | 274 | Sed | 1967-69 |
| Juniata River at Huntingdon | 01559000 | 816 | Temp | 1948-51, 1981-86 ^c |
| Lackawanna River at Old Forge | 01536000 | 332 | Temp | 1949-51 |
| Lower Little Swatara Creek at Pine Grove | 01572000 | 34.3 | SC Temp, Sed | 1981, 1983-84 1981-84 |
| Marsh Creek at Blanchard | 01547700 | 44.1 | Temp Sed | 1957 1956-58 |
| Muddy Creek at Muddy Creek Forks | 01577300 | 71.9 | SC ^a , Temp ^a | 1993-95 |
| Raystown Branch Juniata River below Raystown Dam near Huntingdon | 01563200 | 960 | Temp ^a | 1978-86 ^c |
| Raystown Branch Juniata River near Huntingdon | 01563000 | 957 | Temp | 1947-50 |
| Shamokin Creek near Shamokin | 01554500 | 54.2 | Temp | 1959-61 |
| Sherman Creek at Shermans Dale | 01568000 | 200 | Temp ^b | 1954-56 |
| Steam Valley Run at Buttonwood | 01549350 | 5.34 | Temp ^a , Turb, Sed | 1973-77 |
| Stony Creek at Water Tank Trail near Dauphin | 01568750 | 21.9 | Temp ^b | 1974-76 |

DISCONTINUED CONTINUOUS-RECORD SURFACE-WATER-QUALITY STATIONS (Continued)


| Station name | Station number | Drainage area (mi ²) | Type of Record | Period of record (water years) |
|--|----------------|----------------------------------|---|---|
| Susquehanna River at Danville | 01540500 | 11,220 | SC Temp Sed | 1946-52, 1963-76 1948-53, 1957-70, 1975-76 1974-76 |
| Susquehanna River at Falls | 01534090 | 9,440 | SC Temp | 1945-51 1947-53 |
| Susquehanna River at Harrisburg | 01570500 | 24,100 | SC ^a , pH ^a , Temp ^a , DO ^a Sed | 1974-79 1964-81 ^c |
| Susquehanna River at Towanda | 01531500 | 7,797 | Sed | 1951-54 |
| Swatara Creek above Hwy bridge 895 at Pine Grove | 01571919 | 72.6 | SC Temp, Sed | 1983-84 1982-84 |
| Swatara Creek at Harper Tavern | 01573000 | 337 | SC Temp Sed | 1977-79 1959-61, 1977-79 1959-60, 1977-79 |
| Tioga River at Tioga Junction | 01518700 | 446 | SC ^a , pH ^a , Temp ^a , DO ^a | 1977-88 |
| Tioga River near Mansfield | 01516350 | 153 | SC ^a , pH ^a , Temp ^a DO ^a | 1977-88 ^c 1977-78 |
| West Branch Susquehanna River at Bower | 01541000 | 315 | Sed | 1964-67 |
| West Branch Susquehanna River at Lewisburg | 01553500 | 6,847 | SC, Temp Sed | 1944-53 ^c , 1957-58, 1975-76 1975-76 |
| West Branch Susquehanna River at Lock Haven | 01545800 | 3,337 | SC pH Temp | 1946-51, 1959, 1964-72 1963-72 1946-51, 1958-72 |
| West Branch Susquehanna River at Renovo | 01545500 | 2,975 | SC ^a , pH ^a , Temp ^a DO | 1967-88 ^c 1975-78 |
| West Branch Susquehanna River at Williamsport | 01551500 | 5,682 | SC ^a , pH ^a , Temp ^a | 1980-88 ^c |
| Wilson Creek above Sand Run near Antrim | 01548408 | 12.6 | Sed | 1978-82 |

^a Max, Min, Mean values.

^b Max, Min values.

^c Most years.

PENNSYLVANIA DISTRICT OFFICE LOCATIONS AND ADDRESSES



Lemoyne District Office:
 U.S. Geological Survey
 Water Resources Division
 840 Market Street
 Lemoyne, PA 17043-1586
 (717) 730-6900
 FAX (717) 730-6997

Williamsport Project Office:
 U.S. Geological Survey
 Water Resources Division
 439 Hepburn Street
 Williamsport, PA 17701
 (570) 323-7127
 FAX (570) 323-2137

Pittsburgh Project Office:
 U.S. Geological Survey
 Water Resources Division
 1000 Church Hill Road
 Pittsburgh, PA 15205
 (412) 490-3800
 FAX (412) 490-3828

Malvern Project Office:
 U.S. Geological Survey
 Water Resources Division
 Great Valley Corporate Center
 111 Great Valley Parkway
 Malvern, PA 19355
 (610) 647-9008
 FAX (610) 647-4594

INTRODUCTION

The Water Resources Division of the U.S. Geological Survey, in cooperation with State, municipal, and Federal agencies, collects a large amount of data pertaining to the water resources of Pennsylvania each water year. These data, accumulated during many water years, constitute a valuable data base for developing an improved understanding of the water resources of the State. To make these data readily available to interested parties outside the Geological Survey, these data are published annually in this report series entitled "Water Resources Data - Pennsylvania, Volumes 1, 2, and 3." Volume 1 contains data for the Delaware River Basin; Volume 2, the Susquehanna and Potomac River Basins; and Volume 3, the Ohio River and St. Lawrence River Basins.

This report, Volume 2, contains: (1) discharge records for 83 continuous-record streamflow-gaging stations, 16 partial-record stations, and 24 special study and miscellaneous streamflow sites; (2) elevation and contents records for 12 lakes and reservoirs; (3) water-quality records for 11 streamflow gaging stations and 45 partial-record and project stations; and (4) water-level records for 30 ground-water network observation wells and water-quality analyses of ground water from 8 wells; and (5) water-quality analyses at 44 special study ground-water wells. Additional water data collected at various sites not involved in the systematic data-collection program may also be presented.

Publications similar to this report are published annually by the Geological Survey for all States. For the purpose of archiving, these official reports have an identification number consisting of the two-letter State abbreviation, the last two digits of the water year, and the volume number. For example, this volume is identified as "U.S. Geological Survey Water-Data Report PA-99-2." These water-data reports, beginning with the 1971 water year, are for sale as paper copy or microfiche by the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The annual series of Water Data Reports for Pennsylvania began with the 1961 water-year report and contained only data relating to quantities of surface water. With the 1964 water year, a companion report (part 2) was introduced that contained only data relating to water quality. Beginning with the 1975 water year the report was changed to three volumes (by river basin), with each volume containing data on quantities of surface water, quality of surface and ground water, and ground-water levels.

Prior to the introduction of this series and for several years concurrent with it, water-resources data for Pennsylvania were published in U.S. Geological Survey Water-Supply Papers. Data on stream discharge and stage, and on lake or reservoir contents and stage, through September 1960, were published annually under the title "Surface-Water Supply of the United States," which was released in numbered parts as determined by natural drainage basins. For the 1961-70 water years, these data were published in two 5-year reports. Data prior to 1961 are included in two reports: "Compilation of Records of Surface Waters of the United States through 1950," and "Compilation of Records of Surface Waters of the United States, October 1950 to September 1960." Data for Pennsylvania are published in Parts 1, 3, and 4. Data on chemical quality, temperature, and suspended sediment for the 1941-70 water years were published annually under the title "Quality of Surface Waters of the United States," and ground-water levels for the 1935-74 water years were published annually under the title "Ground-Water Levels in the United States." The above mentioned Water-Supply Papers may be consulted in the libraries of the principal cities of the United States and may be purchased from the U.S. Geological Survey, Information Services, Box 25286, Denver, CO 80225.

Information for ordering specific reports may be obtained from the Pennsylvania District Office at the address on the back of the title page or by phoning the Scientific and Technical Products Section at (717) 730-6940. Information on the availability of unpublished data or statistical analyses may be obtained from the District Information Specialist (telephone (717) 730-6916) or FAX (717) 730-6997.

COOPERATION

The U.S. Geological Survey (USGS) and organizations of the Commonwealth of Pennsylvania have had cooperative agreements for the systematic collection of surface-water records during the periods 1919-21 and 1931 to date, water-quality records from 1944 to date, and ground-water records from 1925 to date. Organizations that supplied data are acknowledged in station manuscripts. Organizations that assisted in collecting data for this report through cooperative agreements with the USGS are listed below.

The Commonwealth of Pennsylvania, Department of Environmental Protection, James M. Seif, Secretary, through the following:
Office of Water Management, Lawrence C. Tropea, Jr., Deputy Secretary;
 Bureau of Water Supply Management, Frederick Marrocco, Acting Director;
 Bureau of Water Quality Protection, Frederick Marrocco, Acting Director;
 Bureau of Watershed Conservation, Stuart I. Gansell, Director;
Office of Mineral Resources Management, Robert C. Dolence, Deputy Secretary;
 Bureau of Mining and Reclamation, Roderick A. Fletcher, Director.
Office of Management and Technical Services, Kenwood Giffhorn, Deputy Secretary;
 Bureau of Laboratories, Floyd D. Kefford, Director.
Borough of Chambersburg, Robert P. Morris, Mayor.
City of Sunbury, David L. Persing, Mayor.
City of Williamsport, Steven W. Cappelli, Mayor.

COOPERATION--Continued

Franklin County Watershed Association, Mark Dubin, Director.
Letort Regional Authority, Brian Fischbach, Executive Director.
Luzerne County Emergency Management Agency, Albert Bardar, Acting Director.
New Oxford Municipal Authority, Earl E. Mummert, Chairman.
Susquehanna River Basin Commission, Paul O. Swartz, Executive Director.
Town of Bloomsburg, Mary Lenzini Howe, Mayor.
Union County Commissioners, Ruth W. Zimmerman, Chairman.
University Area Joint Authority, Cory R. Miller, Executive Director.

Federal Energy Regulatory Commission Licensees:
Susquehanna Electric Company.
Safe Harbor Water Power Corporation.

The following Federal agencies assisted in the data-collection program by providing funds or services: Corps of Engineers, U.S. Army, Baltimore District; National Weather Service, NOAA, U.S. Department of Commerce.

The following organizations aided in collecting records: City of Lancaster, City of Lebanon, Hershey Chocolate U.S.A., Mechanicsburg Water Co., P.H. Glatfelter Co., Pennsylvania American Water Co., Pennsylvania Gas and Water Co., and York Water Co.

SUMMARY OF HYDROLOGIC CONDITIONS

Surface Water

The Susquehanna River flows generally southward from southern New York to the Chesapeake Bay in Maryland. At the point where the river enters Maryland, it drains 27,215 mi² (square miles). Most of this area, 20,962 mi², is in north- and southcentral Pennsylvania. Streams in the basin are located in the Appalachian Plateau, Valley and Ridge, and Piedmont Physiographic Provinces. The underlying geology includes rocks of Precambrian to Triassic age.

Precipitation and Streamflow

Precipitation and streamflow for the 1999 water year reached both maximum and minimum extremes. Data from 32 selected National Oceanic and Atmospheric Administration climatological sites, located within 6 climatic regions in the Susquehanna River Basin in Pennsylvania, indicated the annual precipitation for the Susquehanna River Basin in central Pennsylvania was slightly below normal. The basin generally received below normal precipitation for all months except January, March, April, and September. Two periods of much below normal precipitation occurred basinwide--from November through December and from May through July. The departure from normal precipitation during these two periods was 4.2 and 4.5 inches. If not for the 3.4 inches of above normal precipitation in September, the annual deficit for the Basin would have been almost 7.5 inches--an amount equivalent to nearly 20 percent of the average annual precipitation.

In mid-September, Hurricane Floyd passed through the lower Susquehanna River basin, leaving behind anywhere from 6 to 10 inches of precipitation in a 2-day period. For the month, average precipitation in most of the Susquehanna River Basin was 3 to 6 inches above normal. This record or near-record precipitation provided the beginning of recovery from one of the worst droughts in modern Pennsylvania history.

As an example of the variability of precipitation in the basin in the 1999 water year, monthly and annual precipitation were compared with the 1961-90 mean monthly and annual precipitation recorded at Lancaster and Williamsport, Pennsylvania (fig. 1). The precipitation data are from the National Oceanic and Atmospheric Administration (U.S. Department of Commerce, 1998-99) and National Weather Service records.

Following a pattern defined by the much below and much above normal precipitation that fell in the basin during the 1999 water year, the annual mean streamflow for Susquehanna River Basin streams during the 1999 water year was normal, but record minimum and maximum values were observed throughout the year. (Normal streamflows are defined as those between the 25th and 75th percentiles as compared to the annual mean streamflows for 1961-1990).

Two U.S. Geological Survey streamflow-gaging stations within the basin were selected as indicators of basinwide streamflow conditions. Figure 2 compares the 1999 water year monthly and annual mean streamflows with the median of the monthly and annual mean streamflows for 1961 through 1990 at the indicator sites. The 1999 water year annual mean streamflow was about 65 percent of the 1961-90 median of the mean annual streamflows in the West Branch Susquehanna River at Williamsport, and about 75 percent of the 1961-90 median of the mean annual streamflows in the Conestoga River at Lancaster.

Monthly mean streamflows for January, February, and April were above normal in the West Branch Susquehanna River and in the Conestoga River they were above normal for the months of October, January, and September. Below normal streamflows that were less than 50 percent of the median of the monthly mean streamflow were recorded in the West Branch Susquehanna River and in the Conestoga River during the months of November, December, and May through August (fig. 2). These two periods of extremely low flow identify the drought that occurred in the basin during the 1999 water year. The monthly mean streamflow recorded in the West Branch Susquehanna River at Williamsport in June was the lowest ever recorded since 1895. At Lancaster, the Conestoga River monthly mean streamflow for July was the lowest ever recorded since 1929. At another site in the lower Susquehanna River basin, the June monthly mean streamflow by the stream gage on the Susquehanna River at Harrisburg was the lowest ever measured since record began in 1891.

The Governor of Pennsylvania made several Drought Declarations during the 1999 water year. Beginning in mid-December 1998, all counties within the Susquehanna River basin were placed into the second of three drought conditions--a "drought warning" status. A few days later, seven of the 27 counties within the Susquehanna River basin were placed in a "drought emergency" status which requires mandatory water use restrictions. The declaration was upgraded to a "drought watch" status in March following normal precipitation during late winter. Below normal precipitation in early spring created streamflow and ground-water conditions that initiated a Drought Declaration of "drought warning" status in the entire Susquehanna River basin. By mid-July, the situation had degraded to a point where the entire basin was placed in "drought emergency" status. This was the second instance of this severe condition in the same year for seven of the lower Susquehanna River basin counties. The emergency condition was removed at the end of September and only the western part of the basin remained in a "drought warning" status (Pennsylvania Department of Environmental Protection, 1999).




Figure 1.--Comparison of monthly precipitation at two National Oceanic and Atmospheric Administration climatological stations during the 1999 water year and mean monthly precipitation for the period 1961 through 1990.





Figure 2.--Comparison of streamflow at two long-term streamflow-gaging stations during the 1999 water year and the median monthly and annual mean streamflow for the period 1961 through 1990.

Precipitation and Streamflow--Continued

Evidence of the passage of the remnants of Hurricane Floyd through southcentral Pennsylvania is provided by the extremely high mean flow during the month of September in the Conestoga River (fig. 2). The 1-day, 6.5-inch precipitation produced a monthly mean streamflow that was slightly more than 10 times higher than the median of 1961-90 monthly mean streamflows and was about 80 percent of the highest monthly mean streamflow ever recorded. The runoff from this storm into Susquehanna River basin streams began the recovery of streamflows from the mid-summer drought levels.

Reservoirs

The combined storage of 12 major reservoirs in the Susquehanna River Basin within Pennsylvania decreased slightly from 668,187 acre-feet (45 percent of total combined capacity) on September 30, 1998, to 656,061 acre-feet (44.2 percent of total combined capacity) on September 30, 1999. Maximum and minimum storage in individual reservoirs varied throughout the year depending on the purpose and capacity of each reservoir.

Ground Water

Ground-water levels, which were generally normal to above-normal (16 out of 21 observation wells) throughout all of the Susquehanna River basin at the end of the 1998 water year (Durlin and Schaffstall, 1999), had fallen sharply into the below-normal range by the end of the fall season of the 1999 water year (October through December 1998). The water levels in 13 of the 21 observation wells were either below normal or much below normal. Ground-water levels during the water year generally reflected the seasonal precipitation variations (fig. 1). A comparison between ground-water levels for the 1999 water year and long-term seasonal ground-water levels is shown in figure 3.

During the winter season, with the assistance of normal to above-normal precipitation, water levels recovered to the point where the majority of the observation wells (12 of 21) had water levels that were normal for that season and only 3 wells had water levels that were considered to be much-below-normal. Throughout the spring and continuing into summer, ground-water levels gradually declined. By the end of summer, water levels were generally below normal. Ground-water levels in 11 of the 21 wells were either below normal or much below normal. In July, water levels measured in two wells were the lowest ever recorded. As a result of Hurricane Floyd, by the end of September, 15 of the 21 wells had water levels that were higher than at the end of August.

References

Durlin, R. R., and Schaffstall W. P., 1999, Water resources data, Pennsylvania, water year 1998: U.S. Geological Survey Water-Data Report PA-98-2, 456 p.

U.S. Department of Commerce, 1998-99, Climatological Data for Pennsylvania, Volume 102-103: National Oceanic and Atmospheric Administration, National Environmental Satellite, Data, and Information Service.

Pennsylvania Department of Environmental Protection, 1999, Drought News Room, accessed April 21, 2000, at URL <http://www.dep.state.pa.us/dep/subject/hotopics/drought/news.htm>




Figure 3.--Relation between 1999 seasonal ground-water levels and long-term ground-water levels [Seasonal percentile values were determined by ranking the average monthly water levels for each month in the season from highest to lowest for all years of record and averaging the ranks for the three months. A water level that is higher than the seasonal 10th percentile value would be expected to occur only once in a ten-year period. Conversely, a water level that is lower than the seasonal 90th percentile value also would be expected to occur only once during a ten-year period.]

SPECIAL NETWORKS AND PROGRAMS

The **Hydrologic Bench-Mark Network** is a network of 50 sites in small drainage basins throughout the country that provide consistent data on hydrology, water quality, and related factors in representative undeveloped watersheds nationwide. This network also provides analyses on a continuing basis to compare and contrast conditions observed in basins more obviously affected by human activities. The station operated as part of this program in the Susquehanna River Basin in Pennsylvania is Young Womans Creek near Renovo (01545600). There are no stations in the Potomac River Basin in Pennsylvania participating in this program.

The **National Stream-Quality Accounting Network** (NASQAN) monitors the water quality of large rivers within four of the Nation's largest river basins--the Mississippi, Columbia, Colorado, and Rio Grande. The network consists of 39 stations. Samples are collected with sufficient frequency that the flux of a wide range of constituents can be estimated. The objective of NASQAN is to characterize the water quality of these large rivers by measuring concentration and mass transport of a wide range of dissolved and suspended constituents, including nutrients, major ions, dissolved and sediment-bound heavy metals, common pesticides, and inorganic and organic forms of carbon. This information will be used (1) to describe the long-term trends and changes in concentration and transport of these constituents; (2) to test findings of the National Water-Quality Assessment Program (NAWQA); (3) to characterize processes unique to large-river systems such as storage and re-mobilization of sediments and associated contaminants; and (4) to refine existing estimates of off-continent transport of water, sediment, and chemicals for assessing human effects on the world's oceans and for determining global cycles of carbon, nutrients, and other chemicals. There are no stations in the Susquehanna or Potomac River Basins in Pennsylvania currently participating in this program.

The **National Atmospheric Deposition Program/National Trends Network** (NADP/NTN) provides continuous measurement and assessment of the chemical climate of precipitation throughout the United States. As the lead federal agency, the USGS works together with over 100 organizations to accomplish the following objectives; (1) Provide a long-term, spatial and temporal record of atmospheric deposition generated from a network of 191 precipitation chemistry monitoring sites. (2) Provide the mechanism to evaluate the effectiveness of the significant reduction in SO₂ emissions that began in 1995 as implementation of the Clean Air Act Amendments (CAAA) occurred, and (3) Provide the scientific basis and nationwide evaluation mechanism for implementation of the Phase II CAAA emission reductions for SO₂ and NO_x scheduled to begin in year 2000.

Data from the network, as well as information about individual sites, are available through the World Wide Web at [<http://nadp.sws.uiuc.edu>].

The **National Water-Quality Assessment (NAWQA) Program** of the U.S. Geological Survey is a long-term program with goals to describe the status and trends of water-quality conditions for a large, representative part of the Nation's ground- and surface-water resources; provide an improved understanding of the primary natural and human factors affecting these observed conditions and trends; and provide information that supports development and evaluation of management, regulatory, and monitoring decisions by other agencies.

Assessment activities are being conducted in 53 study units (major watersheds and aquifer systems) that represent a wide range of environmental settings nationwide and that account for a large percentage of the Nation's water use. A wide array of chemical constituents will be measured in ground water, surface water, streambed sediments, and fish tissues. The coordinated application of comparative hydrologic studies at a wide range of spatial and temporal scales will provide information for decision making by water-resources managers and a foundation for aggregation and comparison of findings to address water-quality issues of regional and national interest.

Communication and coordination between USGS personnel and other local, State, and federal interests are critical components of the NAWQA Program. Each study unit has a local liaison committee consisting of representatives from key federal, State, and local water-resources agencies, Indian nations, and universities in the study unit. Liaison committees typically meet semiannually to discuss their information needs, monitoring plans and progress, desired information products, and opportunities to collaborate efforts among the agencies. Additional information about the NAWQA Program is available through the world wide web at [<http://pubs.water.usgs.gov/nawqa>].

EXPLANATION OF THE RECORDS

The surface-water and ground-water records in this report are for the 1999 water year that began October 1, 1998, and ended September 30, 1999. A calendar of the water year is provided on the inside of the front cover. The records contain streamflow data, stage and content data for lakes and reservoirs, water-quality data for surface and ground water, and ground-water-level data. The locations of these stations and wells are shown in figures throughout the report. The following sections of the introductory text are presented to provide users with a more detailed explanation of how these hydrologic data published in this report were collected, analyzed, computed, and arranged for presentation.

Station Identification Numbers

Each data station in this report, whether a streamsite or a well, is assigned a unique identification number. This number is unique in that it applies specifically to a given station and to no other. The number usually is assigned when a station is first established and is retained for that station indefinitely. The systems used by the U.S. Geological Survey to assign identification numbers for surface-water stations and for ground-water well sites differ, but both are based on geographic location. The "downstream order" system is used for regular surface-water stations and the "latitude-longitude" system is used for wells and, in Pennsylvania, for some miscellaneous surface-water sites where only random water-quality samples or discharge measurements are made.

Downstream-Order System

Since October 1, 1950, the order of listing hydrologic-station records in Survey reports is in a downstream direction along the main stream. All stations on a tributary entering upstream from a main-stream station are listed before that station. A station on a tributary that enters between two main-stream stations is listed between them. A similar order is followed in listing stations on first rank, second rank, and other ranks of tributaries. The rank of any tributary on which a station is situated with respect to the stream to which it is immediately tributary is indicated by an indentation in a list of stations in the front of the report. Each indentation represents one rank. This downstream-order system of indentation shows which stations are on tributaries between any two stations and the rank of the tributary on which each station is situated.

The station-identification number is assigned in downstream order. In assigning station numbers, no distinction is made between partial-record stations and continuous-record stations; therefore, the station number for a partial-record station indicates downstream-order position in a list made up of both types of stations. Gaps are left in the series of numbers to allow for new stations that may be established; hence, the numbers are not consecutive. A station number can be from 8 to 15 digits in length and normally appears to the left of the station name. For example, an 8-digit number for a station such as 01570500, includes a 2-digit part number "01" plus a 6-digit downstream-order number "570500." The part number designates major river basins; for example, part "01" is the North Atlantic Slope Basin.

Latitude-Longitude System

The identification numbers for wells and miscellaneous surface-water sites are assigned based on the grid system of latitude and longitude. The system provides the geographic location of the well or miscellaneous site and a unique number for each site. The number consists of 15 digits. The first six digits denote the degrees, minutes, and seconds of latitude, the next seven digits denote the degrees, minutes, and seconds of longitude, and the last two digits (assigned sequentially) identify the wells or other sites within a 1-second grid (fig. 4).




Figure 4.--System for numbering wells and miscellaneous sites (latitude and longitude).

A local well number is also assigned to the wells and consists of a 2-letter abbreviation of the county in which the well is located and a sequential number assigned at the time the well was scheduled.

Records of Stage and Water Discharge

Records of stage and water discharge may be continuous or partial. Continuous records of discharge are those obtained using a continuous stage-recording device through which either instantaneous water discharges may be computed for any time, or mean discharges may be computed for any period of time, during the period of record. Because daily mean discharges or end-of-day contents for reservoirs commonly are published for such stations, they are referred to as "*daily stations*" or "*continuous-record stations*."

By contrast, partial records are obtained through discrete measurements without using a continuous stage-recording device and pertain only to a few flow characteristics, or perhaps only one. The nature of the partial record is indicated by table titles such as "*Crest-stage partial-record stations*," or "*Low-flow partial-record stations*." Records of miscellaneous discharge measurements or of measurements from special studies, such as low-flow seepage studies, may be considered as partial records, but they are presented separately in this report. Location of all continuous-record and partial-record stations for which data are given in this report are shown in figures 5-8.

Data Collection and Computation

Those data obtained at a continuous-record gaging station on a stream consist of a continuous record of stage, individual measurements of discharge throughout a range of stages, and notations regarding factors that may affect the relation between stage and discharge. These data, together with supplemental information, such as weather records, are used to compute daily discharges. Continuous records of stage are obtained with analog recorders that trace continuous graphs of stage, with solid-state electronic data loggers, or with data collection platforms (DCPs) that electronically record and transmit the data via satellite to ground receiving stations. Measurements of discharge are made with current meters using methods adopted by the Geological Survey as a result of experience accumulated since 1880. These methods are described in standard textbooks, in Water-Supply Paper 2175, and the U.S. Geological Survey Techniques of Water-Resources Investigations (TWRIs), Book 3, Chapter A1 through A19 and Book 8, Chapters A2 and B2. The methods are consistent with the American Society for Testing and Materials (ASTM) standards and generally follow the standards of the International Organization for Standards (ISO).

In computing discharge records, results of individual measurements are plotted against the corresponding stages, and stage-discharge relation curves are then constructed. From these curves, rating tables indicating the approximate discharge for any stage within the range of the measurements are prepared. If it is necessary to define extremes of discharge outside the range of the current-meter measurements, the curves are extended using: (1) logarithmic plotting; (2) velocity-area studies; (3) results of indirect measurements of peak discharge, such as slope-area or contracted-opening measurements, and computations of flow-over-dams or weirs; or (4) step-backwater techniques.

Daily mean discharges are computed by applying each recorded stage value (gage height) to the stage-discharge curves or tables. If the stage-discharge relation is subject to change because of frequent or continual change in the physical features that form the control, the daily mean discharge is determined by the shifting-control method, in which correction factors based on the individual discharge measurements and notes of the personnel making the measurements are applied to the gage heights before the discharges are determined from the curves or tables. This shifting-control method also is used if the stage-discharge relation is changed temporarily because of aquatic growth or debris on the control. For some stations, formation of ice in the winter may so obscure the stage-discharge relation that daily mean discharges must be estimated from other information such as temperature and precipitation records, notes of observations, and records for other stations in the same or nearby basins for comparable periods.

At some stream-gaging stations, the stage-discharge relation is affected by the backwater from reservoirs, tributary streams, or other sources. This necessitates the use of the slope method in which the slope or fall in a reach of the stream is a factor in computing discharge. The slope or fall is obtained by means of an auxiliary gage set at some distance from the base gage. At some stations, the stage-discharge relation is affected by changing stage; at these stations, the rate of change in stage is used as a factor to compute discharge.

When computing records of lake or reservoir contents, it is necessary to have available from surveys, curves or tables defining the relation between stage and content. The application of stage to the stage-content curves or tables gives the contents from which daily, monthly, or yearly changes then are determined. If the stage-content relation changes because of deposition of sediment in the lake or reservoir, periodic surveys may be necessary to redefine the relation. Even when this is done, the contents computed may increase in error as the time elapsed since the last survey increases. Discharges over lake or reservoir spillways are computed from stage-discharge relation much as other stream discharges are computed.

For some gaging stations, there are periods when no gage-height data are collected or when the recorded gage height is so imprecise or incorrect that it cannot be used to compute daily mean discharge or end-of-day contents. This happens when the recorder stops or otherwise fails to operate properly, intakes are plugged, the float is frozen in the well, or for various other reasons. For such periods, the daily discharges are estimated from the recorded range in stage, previous or following record, discharge measurements, weather records, and comparison with other station records from the same or nearby basins. Likewise, daily contents may be estimated from operator's logs, previous or following record, inflow-outflow studies, and other information. Information explaining how estimated daily-discharge values are identified in station records is included in the next two sections, "*Data Presentation*" (REMARKS paragraph) and "*Identifying Estimated Daily Discharge*."

Data Presentation

The records published for each continuous-record surface-water discharge station (gaging station) consist of four parts; (1) the manuscript or station description; (2) the data table of daily mean discharge values for the current water year with summary data; (3) a tabular statistical summary of monthly mean flow data for a designated period; and (4) a summary statistics table for a designated period that includes statistical data of annual, daily, and instantaneous flows as well as data pertaining to annual runoff, 7-day low-flow minimums, and flow duration.

Station manuscript

For each continuous-record station, the manuscript provides, under various headings, descriptive information such as station location, period of record, historical extremes outside the period of record, record accuracy, and other remarks pertinent to station operation and regulation. The following comments, as appropriate, clarify information presented under the various headings of the station description.

LOCATION.--Information on locations is obtained from the most accurate maps available. The location of the gaging station with respect to the cultural and physical features in the vicinity and with respect to the reference place mentioned in the station name is given. River mileages, listed for only a few stations, were determined by methods given in "*River Mileage Measurement*," Bulletin 14, Revision of October 1968, prepared by the Water Resources Council or were provided by the U.S. Army Corps of Engineers.

DRAINAGE AREA.--Drainage areas are measured using the most accurate maps available. Because the type of maps available varies from one drainage basin to another, the accuracy of drainage areas likewise varies. Drainage areas are updated as better maps become available.

PERIOD OF RECORD.--This indicates the period for which records have been published for the station or for an equivalent station. An equivalent station is one that was in operation at a time that the present station was not and whose location was such that its streamflow can reasonably be considered equivalent to the streamflow at the present station.

REVISED RECORDS.--Because of new information, published records occasionally are found to be incorrect, and revisions are printed in later reports. Listed under this heading are all the reports in which revisions have been published for the station and the water years to which the revisions apply. If a revision did not include daily, monthly, or annual figures of discharge, that fact is noted after the year dates as follows; "(M)" means that only the instantaneous maximum discharge was revised; "(m)" that only the instantaneous minimum was revised; and "(P)" that only peak discharges were revised. If the drainage area has been revised, the report in which the most recently revised figure was first published is given.

GAGE.--The type of gage in current use, the datum of the current gage referred to sea level (see Definition of Terms), and a condensed history of the types, locations, and datums of previous gages are given under this heading.

REMARKS.--This paragraph is used to present information relative to the accuracy of the records, to special methods of computation, and to conditions that affect natural flow at the station. For reservoir stations, information is given on the dam forming the reservoir, the capacity, outlet works and spillway, and purpose and use of the reservoir.

COOPERATION.--Records provided by a cooperating organization or obtained for the U.S. Geological Survey by a cooperating organization are identified here.

EXTREMES OUTSIDE PERIOD OF RECORD.--Included here is information concerning major floods or unusually low flows that occurred outside the stated period of record. The information may or may not have been obtained by the U.S. Geological Survey.

PEAK DISCHARGES FOR CURRENT YEAR.--Peaks given here are similar to those found in the summary statistics table, except the peak discharge listing may include secondary peaks. For stations meeting certain criteria, all peak discharges and stages occurring during the water year and greater than a selected base discharge (see Definition of Terms) are presented under this heading. The peaks greater than the base discharge, excluding the highest one, are referred to as secondary peaks. Peak discharges are not published for streams for which the peaks are subject to substantial control by man. The time of occurrence for peaks is expressed in 24-hour local standard time. For example, 12:30 a.m. is 0030, and 1:30 p.m. is 1330.

REVISIONS.--If a critical error in published records is discovered, a revision is included in the first report published following discovery of the error.

Although rare, occasionally the records of a discontinued gaging station may need revision. Because, for these stations, there would be no current or, possibly, future station manuscript published to document the revision in a "*Revised Records*" entry, users of data for these stations who obtained the record from previously published data reports may wish to contact the District Office (address given on the back of the title page of this report) to determine if the published records were ever revised after the station was discontinued. Of course, if those data for a discontinued station were obtained by computer retrieval, these data would be current and accurate because published revisions of data are always accompanied by revisions of those data in computer storage.

Beginning with the 1991 annual State Data report, headings for AVERAGE DISCHARGE, EXTREMES FOR PERIOD OF RECORD, AND EXTREMES FOR CURRENT YEAR have been deleted and the information contained in these paragraphs, except for the listing of secondary instantaneous peak discharges in the PEAK DISCHARGES FOR CURRENT YEAR paragraph, is now presented in the tabular summaries following the discharge table or in the REMARKS paragraph, as appropriate. No changes have been made to the data presentations of lake contents.

Data table of daily mean values

The daily table of discharge records for stream-gaging stations gives mean discharge for each day of the water year. In the monthly summary for the table, the line headed "TOTAL" gives the sum of the daily figures for each month; the line headed "MEAN" gives the average flow in cubic feet per second for the month; and the lines headed "MAX" and "MIN" give the maximum and minimum daily mean discharges, respectively, for each month. Discharge for the month also is usually expressed in cubic feet per second per square mile (line headed "CFSM"); or in inches (line headed "IN."). Figures for cubic feet per second per square mile and runoff in inches may be omitted if there is extensive regulation or diversion or if the drainage area includes large noncontributing areas. At some stations streamflow is affected by regulation or diversion. The monthly adjusting figure for known regulation or diversion may be shown at the bottom of the daily values table or in the appropriate lake or reservoir table.

Statistics of monthly mean data

A tabular summary of the mean (line headed "MEAN"), maximum (line headed "MAX"), and minimum (line headed "MIN") of monthly mean flows for each month for a designated period is provided below the daily values table. The water years of the first occurrence of the maximum and minimum monthly flows are provided immediately below those figures. The designated period will be expressed as "FOR WATER YEARS ____-____, BY WATER YEAR (WY)," and will list the first and last water years of the range of years selected from the PERIOD OF RECORD paragraph in the station manuscript. It will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript.

Summary statistics

A table titled "SUMMARY STATISTICS" follows the statistics of monthly mean data tabulation. This table consists of four columns, with the first column containing the line headings of the statistics being reported. The table provides a statistical summary of yearly, daily, and instantaneous flows, not only for the current water year but also for the previous calendar year and for a designated period, as appropriate. The designated period selected, "WATER YEARS ____-____," will consist of all of the station record within the specified water years, inclusive, including complete months of record for partial water years, if any, and may coincide with the period of record for the station. The water years for which the statistics are computed will be consecutive, unless a break in the station record is indicated in the manuscript. All of the calculations for the statistical characteristics designated ANNUAL (See line headings below.), except for the "ANNUAL 7-DAY MINIMUM" statistic, are calculated for the designated period using complete water years. The other statistical characteristics may be calculated using partial water years.

The date or water year, as appropriate, of the first occurrence of each statistic reporting extreme values of discharge is provided adjacent to the statistic. Repeated occurrences may be noted in the REMARKS paragraph of the manuscript or in footnotes. Because the designated period for the statistics may not be the same as the period of record published in the manuscript, occasionally the dates of occurrence listed for the daily and instantaneous extremes may not be within the designated period. Selected streamflow duration statistics and runoff data are also given. Runoff data may be omitted if there is extensive regulation or diversion of flow in the drainage basin.

The summary statistics data, as appropriate, are provided with each continuous record of discharge. The following comments clarify information presented under the various line headings of the summary statistics table.

ANNUAL TOTAL.--The sum of the daily mean values of discharge for the year. At some stations the annual total discharge may be affected by reservoir storage or diversion. The monthly adjusting figures for known regulation or diversions may be shown 1) at the bottom of the daily values table, or 2) in the appropriate lake or reservoir table.

ANNUAL MEAN.--The arithmetic mean of the individual daily mean discharges for the year noted or for the designated period. At some stations the annual total discharge may be affected by reservoir storage or diversion. The monthly adjusting figures for known regulation or diversions may be shown 1) at the bottom of the daily values table, or 2) in the appropriate lake or reservoir table.

HIGHEST ANNUAL MEAN.--The maximum annual mean discharge occurring for the designated period.

LOWEST ANNUAL MEAN.--The minimum annual mean discharge occurring for the designated period.

HIGHEST DAILY MEAN.--The maximum daily mean discharge for the year or for the designated period.

LOWEST DAILY MEAN.--The minimum daily mean discharge for the year or for the designated period.

ANNUAL 7-DAY MINIMUM.--The lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1 - March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year, low-flow statistic.)

INSTANTANEOUS PEAK FLOW.--The maximum instantaneous discharge occurring for the water year or for the designated period. Note that secondary instantaneous peak discharges above a selected base discharge are stored in computer files for stations meeting certain criteria. Those discharge values may be obtained by writing to the District Office or from the World Wide Web at [<http://pa.water.usgs.gov/>]. (See address on back of title page of this report.)

INSTANTANEOUS PEAK STAGE.--The maximum instantaneous stage occurring for the water year or for the designated period. If the dates of occurrence for the instantaneous peak flow and instantaneous peak stage differ, the REMARKS paragraph in the manuscript or a footnote may be used to provide further information.

INSTANTANEOUS LOW FLOW.--The minimum instantaneous discharge occurring for the water year or for the designated period.

ANNUAL RUNOFF.--Indicates the total quantity of water in runoff for a drainage area for the year. Runoff figures may be omitted if there is extensive regulation or diversion. Data reports may use any of the following units of measurements in presenting annual runoff data:

Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or about 326,000 gallons or 1,233 cubic meters.

Cubic feet per second per square mile (CFSM) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.

Inches (IN.,in.) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.

10 PERCENT EXCEEDS.--The discharge that has been exceeded 10 percent of the time for the designated period.

50 PERCENT EXCEEDS.--The discharge that has been exceeded 50 percent of the time for the designated period.

90 PERCENT EXCEEDS.--The discharge that has been exceeded 90 percent of the time for the designated period.

Data collected at partial-record stations follow the information for continuous-record sites. Data for partial-record discharge stations are presented in two tables. The first is a table of annual maximum stage and discharge at crest-stage stations, and the second is a table of discharge measurements at low-flow partial-record stations. The tables of partial-record stations are followed by a listing of discharge measurements made at sites other than continuous-record or partial-record stations. These measurements are generally made in times of drought or flood to give better areal coverage to those events. Those measurements and others collected for some special reason are called measurements at miscellaneous sites.

Identifying Estimated Daily Discharge

Beginning with the 1987 annual State data report, estimated daily discharge values published in the water-discharge tables are identified by flagging individual daily values with the letter symbol "e" and printing a table footnote, "e *Estimated*".

Accuracy of the Records

The accuracy of streamflow records depends primarily on (1) The stability of the stage-discharge relation or, if the control is unstable, the frequency of discharge measurements; and (2) the accuracy of measurements of stage, measurements of discharge, and interpretation of records.

The accuracy attributed to the records is indicated under "REMARKS." "*Excellent*" means that about 95 percent of the daily discharges are within 5 percent of their true values; "*good*," within 10 percent; and "*fair*," within 15 percent. Records that do not meet the criteria mentioned are rated "*poor*." Different accuracies may be attributed to different parts of a given record.

Daily mean discharges in this report are given to the nearest hundredth of a cubic foot per second for values less than 1 ft³/s (cubic foot per second); to the nearest tenth from 1.0 to 10 ft³/s; to whole numbers from 10 to 1,000 ft³/s; and to 3 significant figures when greater than 1,000 ft³/s. The number of significant figures used is based solely on the magnitude of the discharge value. The same rounding rules apply to discharges listed for partial-record stations and miscellaneous sites.

Discharge at many stations, as indicated by the monthly mean, may not reflect natural runoff due to the effects of diversion, consumption, regulation by storage, increase or decrease in evaporation due to artificial causes, or to other factors. For such stations, figures of cubic feet per second per square mile and of runoff, in inches, are not published unless satisfactory adjustments can be made for diversions, for changes in contents of reservoirs, or for other changes incident to use and control. Evaporation from a reservoir is not included in the adjustments for changes in reservoir contents, unless it is so stated. Even at those stations where adjustments are made, large errors in computed runoff may occur if adjustments or losses are large in comparison with the observed discharge.

Other Records Available

Information of a more detailed nature than that published for most of the gaging stations such as observations of water temperature, discharge measurements, gage-height records, and rating tables is on file in the District's offices. Most gaging-station records are available in computer-usable form and many statistical analyses have been made.

Information on the availability of unpublished data or statistical analyses may be obtained from the District Information Specialist (telephone (717) 730-6916).

Records of Surface-Water Quality

Records of surface-water quality ordinarily are obtained at or near stream-gaging stations because interpretation of records of surface-water quality nearly always requires corresponding discharge data. Records of surface-water quality in this report may involve a variety of types of data and measurement frequencies.

Classification of Records

Water-quality data for surface-water sites are grouped into one of three classifications. A continuing-record station is a site where data are collected on a regularly scheduled basis. Specifically, a continuing record station is a site which meets one or all of the following conditions: (1) When chemical samples are collected daily or monthly for 10 or more months during the water year. (2) When water temperature records include observations taken one or more times daily. (3) When sediment discharge records include periods for which sediment loads are computed and are considered to be representative of the runoff for the water year. A partial-record station is a site where limited water-quality data are collected systematically over a period of years. Frequency of sampling is usually less than quarterly. A miscellaneous sampling site is a location other than a continuing or partial-record station, where random samples are collected to give better areal coverage to define water-quality conditions in the river basin.

A careful distinction needs to be made between "*continuing records*" as used in this report and "*continuous recordings*," which refers to a continuous graph or a series of discrete values recorded at short intervals. Some records of water quality, such as temperature and specific conductance, may be obtained through continuous recordings; however, because of costs, most data are obtained only monthly or less frequently. Location of stations for which records on the quality of surface water appear in this report are shown in figures 5, 6, and 8.

Arrangement of Records

Water-quality records collected at a surface-water daily record station are published immediately following that record, regardless of the frequency of sample collection. Station number and name are the same for both records. Where a surface-water daily record station is not available or where the water quality differs significantly from that at the nearby surface-water station, the continuing water-quality record is published with its own station number and name in the regular downstream-order sequence. Water-quality data for partial-record stations and for miscellaneous sampling sites appear in separate tables following the table of discharge measurements at miscellaneous sites.

On-site Measurements and Sample Collection

During the collection of water-quality data, assurance that the data obtained represent the in-situ quality of the water is a major concern. Certain measurements, such as water temperature, pH, and dissolved oxygen, need to be made onsite when the samples are collected. To assure that measurements made in the laboratory also represent the in-situ water quality, carefully prescribed procedures need to be followed when collecting the samples, when treating the samples to prevent changes in quality pending analysis, and when shipping the samples to the laboratory. Procedures for onsite measurements and for collecting, treating, and shipping samples are detailed in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, and A4. These references are listed in the PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS section of this report. These methods are consistent with ASTM standards and generally follow ISO standards. Also, detailed information on collecting, treating, and shipping samples may be obtained from the U.S. Geological Survey District Office.

One sample can define adequately the water quality at a given time if the mixture of solutes throughout the stream cross section is homogeneous. However, the concentration of solutes at different locations in the cross section may vary widely with different rates of water discharge, depending on the source of material and the turbulence and mixing of the stream. Some streams must be sampled through several vertical sections to obtain a representative sample needed for an accurate mean concentration and for use in calculating load. All samples collected for the National Water Quality Assessment Program (see Definition of Terms) are obtained from several verticals. Whether samples are obtained from the centroid of flow or from several verticals, depends on flow conditions and other factors that must be evaluated by the collector.

Chemical-quality data published in this report are considered to be the most representative values available for the stations listed. The values reported represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis. In the rare case where an apparent inconsistency exists between a reported pH value and the relative abundance of carbon dioxide species (carbonate and bicarbonate), the inconsistency is the result of a slight uptake of carbon dioxide from the air by the sample between measurement of pH in the field and determination of carbonate and bicarbonate in the laboratory.

For chemical-quality stations equipped with digital monitors, the records consist of daily maximum, minimum, and mean values for each constituent measured and are determined from data that are recorded at 15-, 30-, or 60-minute intervals by solid-state electronic data loggers, or with Data Collection Platforms (DCPs). More detailed records (hourly values) may be obtained from the U.S. Geological Survey District Office at the address given on the back of the title page of this report.

Water Temperature

Water temperatures are measured at most of the water-quality stations. At stations where recording instruments are used, maximum, minimum, and mean temperatures for each day are published. In addition, water temperatures are measured at the time of discharge measurements for most water-discharge stations and are on file in the District's offices. For stations where water temperature is measured manually once or twice daily, it is usually measured at about the same time each day. Large streams have a small diurnal temperature change; temperatures in shallow streams may have a daily range of several degrees and may follow closely the changes in air temperature. Some streams may be affected by heated waste-water discharges.

Sediment

Suspended-sediment concentrations are determined from samples collected by hand or by pump samplers. Hand samples utilize the appropriate sampler (dependent on stream depth and velocity) and are collected using the depth-integrating method at single or multiple verticals in the cross section. Samples collected by pump samplers use an intake set to a fixed location in the cross section. The intake is located at a site that best represents the entire cross section on the basis of simultaneous samples collected at various stages by the pumping sampler and by hand. During periods of rapidly changing flow or rapidly changing concentration, samples may have been collected more frequently (twice daily or, in some instances, every 15 minutes). The published sediment discharges for days of rapidly changing flow or concentration were computed by the subdivided-day method (time-discharge weighted average). Therefore, for those days when the published sediment discharge value differs from the value computed as the product of discharge, mean concentration, and the constant 0.0027, the reader can assume that the sediment discharge for that day was computed by the subdivided-day method. For periods when no samples were collected, daily discharges of suspended sediment were estimated on the basis of water discharge, sediment concentrations observed immediately before and after the periods, and suspended-sediment loads for other periods of similar discharge. Methods used in the computation of sediment records are described in the TWRI Book 3, Chapters C1 and C3. These methods are consistent with ASTM standards and generally follow ISO standards.

At other stations, suspended-sediment samples were collected periodically at many verticals in the stream cross section. Although data collected periodically may represent conditions only at the time of observations, such data are useful in establishing seasonal relations between quality and streamflow and in predicting long-term sediment-discharge characteristics of the stream.

In addition to the records of suspended-sediment discharge, records of the periodic measurements of the particle-size distribution of the suspended sediment and bed material are included for some stations.

Laboratory Measurements

Sediment samples, samples for biochemical-oxygen demand (BOD), samples for indicator bacteria, and daily samples for specific conductance are analyzed locally. The remaining samples are analyzed in the Geological Survey laboratory in Denver, Colorado. If other laboratories are used, they are identified in the "Remarks" or "Cooperation" paragraph of each water-quality station manuscript. Methods used to analyze sediment samples and to compute sediment records are described in TWRI Book 5, Chapter C1. Methods used by the Geological Survey laboratories are given in the TWRI Book 1, Chapter D2; Book 3, Chapter C2; and Book 5, Chapters A1, A3, A4 and A5. These methods are consistent with ASTM standards and generally follow ISO standards. Methods used by other laboratories are approved by the U.S. Geological Survey, Water Resources Division.

Data Presentation

For continuing-record stations, information pertinent to the history of station operation is provided in descriptive headings preceding the tabular data. These descriptive headings give details regarding location, drainage area, period of record, type of data available, instrumentation, general remarks, cooperation, and extremes for constituents currently measured daily. Tables of chemical, physical, biological, radiochemical, and other data, obtained at a frequency less than daily are presented first. Tables of "daily values" of specific conductance, pH, water temperature, dissolved oxygen, and suspended sediment then follow in sequence.

In the descriptive headings, if the location is identical to that of the streamflow-gaging station, neither the LOCATION nor the DRAINAGE AREA statements are repeated. The following information, as appropriate, is provided with each continuous-record station. Comments that follow clarify information presented under the various headings of the station description.

LOCATION.--See Data Presentation under "*Records of Stage and Water Discharge*"; same comments apply.

DRAINAGE AREA.--See Data Presentation under "*Records of Stage and Water Discharge*"; same comments apply.

PERIOD OF RECORD.--This indicates the periods for which there are published water-quality records for the station. The periods are shown separately for records of constituents measured daily or continuously and those measured less often than daily. For those measured daily or continuously, periods of record are given for the constituents individually.

INSTRUMENTATION.--Information on instrumentation is given only if a water-quality monitor, temperature recorder, pumping sampler, or other sampling device is in operation at a station.

REMARKS.--Remarks provide added information pertinent to the collection, analysis, or computation of the records.

COOPERATION.--Records provided by a cooperating organization or obtained for the Geological Survey by a cooperating organization are identified here.

EXTREMES.--Maximums and minimums are given only for constituents measured daily or more frequently. None are given for constituents measured less frequently, because the true maximums or minimums may not have been sampled. Extremes, when given, are provided for both the period of record and for the current water year.

REVISIONS.--If errors in published water-quality records are discovered after publication, appropriate updates are made to the Water-Quality File in the U.S. Geological Survey's computerized data system and subsequently by monthly transfer of update transactions to the U.S. Environmental Protection Agency's STORET system. Because the usual volume of updates makes it impractical to document individual changes in the State data-report series or elsewhere, potential users of U.S. Geological Survey water-quality data are encouraged to obtain all required data from the appropriate computer file to insure the most recent updates.

The surface-water-quality records for partial-record stations and miscellaneous sampling sites are published in separate tables following the table of discharge measurements at miscellaneous sites. No descriptive statements are given for these records. Each station is published with its own station number and name in the regular downstream-order sequence.

Remark Codes

The following remark codes may appear with the data tables in this report:

| <u>PRINTED OUTPUT</u> | <u>REMARK</u> |
|-----------------------|---|
| E,e | Estimated value. |
| > | Actual value is known to be greater than the value shown. |
| < | Actual value is known to be less than the value shown. |
| K | Results based on colony count outside the acceptance range (non-ideal colony count). |
| L | Biological organism count less than 0.5 percent (organism may be observed rather than counted). |
| D | Biological organism count equal to or greater than 15 percent (dominant). |
| & | Biological organism estimated as dominant. |
| ND | Material specifically analyzed for but not detected. |
| V | Analyte was detected in both the environmental sample and the associated blanks. |

Water Quality-Control Data

Data generated from quality-control (QC) samples are a requisite for evaluating the quality of the sampling and processing techniques as well as data from the actual samples themselves. Without QC data, environmental sample data cannot be adequately interpreted because the errors associated with the sample data are unknown. The various types of QC samples collected by this district are described in the following section. Procedures have been established for the storage of water-quality-control data within the USGS. These procedures allow for storage of all derived QC data and are identified so that they can be related to corresponding environmental samples.

BLANK SAMPLES.--Blank samples are collected and analyzed to ensure that environmental samples have not been contaminated by the overall data-collection process. The blank solution used to develop specific types of blank samples is a solution that is free of the analytes of interest. Any measured value in a blank sample for an analyte (a specific component measured in a chemical analysis) that was absent in the blank solution is believed to be due to contamination. There are many types of blank samples possible, each designed to segregate a different part of the overall data-collection process. The types of blank samples collected in this district are:

Ambient blank--a blank solution that is put in the same type of sample container used for an environmental sample, kept with the set of sample bottles before sample collection, and opened at the site and exposed to the ambient conditions.

Field blank--a blank solution that is subjected to all aspects of sample collection, field processing, preservation, transportation, and laboratory handling as an environmental sample.

Trip blank--a blank solution that is put in the same type of sample container used for an environmental sample and kept with the set of samples bottles before and after sample collection.

Equipment blank--a blank solution that is processed through all equipment used for collecting and processing an environmental sample (similar to a field blank but normally done in the more controlled conditions of the office).

Sampler blank--a blank solution that is poured or pumped through the same field sampler used for collecting an environmental sample.

Filter blank--a blank solution that is filtered in the same manner and through the same filter apparatus used for an environmental sample.

Splitter blank--a blank solution that is mixed and separated using a field sample splitter in the same manner and through the same apparatus used for an environmental sample.

Preservation blank--a blank solution that is treated with the same preservatives used for an environmental sample.

Canister blank--a blank solution that is taken directly from a stainless steel canister just before the VOC sampler is submerged to obtain a field sample.

REFERENCE SAMPLES.--Reference material samples are solutions or materials having a known composition that is certified by a laboratory. Samples of reference material are submitted for analysis to ensure that an analytical method is accurate for the known properties of the reference material. Generally, the selected reference material properties are similar to the environmental sample properties.

REPLICATE SAMPLES.--Replicate samples are a set of environmental samples collected in a manner such that the samples are thought to be essentially identical in composition. Replicate is the general case for which a duplicate is the special case consisting of two samples. Replicate samples are collected and analyzed to establish the amount of variability in the data contributed by some part of the collection and analytical process. There are many types of replicate samples possible, each of which may yield slightly different results in a dynamic hydrologic setting, such as a flowing stream. The types of replicate samples collected in this district are:

Sequential samples--a type of replicate sample in which environmental samples are collected one after the other, typically within a short time.

Split sample--a type of replicate sample in which an environmental sample is split into subsamples contemporaneous in time and space.

SPIKE SAMPLES.--Spike samples are samples to which known quantities of a solution with one or more well-established analyte concentrations have been added. These samples are analyzed to determine the extent of matrix interference or degradation on the analyte concentration during sample processing and analysis.

Records of Ground-Water Levels

Ground-water level data from an observation well network and from ground-water projects are published herein. Locations of observation wells in the basic network are shown in figures 5 and 7. Ground-water data are grouped by counties, arranged in alphabetical order, and are listed on page x. Those with an (l) following the well number have water-level data published in the report. Miscellaneous or short-term ground-water data collection projects are published following the basic network data.

Data Collection and Computation

Water levels are measured in many types of wells under varying conditions, but the methods of measurement are standardized to the extent possible. The equipment and measuring techniques used at each observation well ensure that measurements at each well are of consistent accuracy and reliability.

The prime identification number for a given well is the 15-digit number that appears above the station description. The secondary identification number is the local well number, an alphanumeric number, derived from the county location of the well.

Water-level records are obtained from direct measurements with a steel tape, from the graph of a water-level recorder, with solid-state electronic data loggers, or with Data Collection Platforms (DCPs). The water-level measurements in this report are given in feet with reference to land-surface datum (lsd). Land-surface datum is a datum plane that is approximately at land surface at each well. If known, the elevation of the land-surface datum is given in the well description. The height of the measuring point (MP) above or below land-surface datum is given in each well description. Water levels for most wells, especially historical network wells, are reported in feet above or below land surface datum. For some short term project wells the water levels may be reported as elevation (feet above sea level) for convenience of the project work. Water levels are reported daily for all wells equipped with recording gages.

Water levels are reported to as many significant figures as can be justified by the local conditions. Accordingly, most measurements are reported to a hundredth of a foot, but some may be given to a tenth of a foot.

Data Presentation

Each well record consists of three parts; (1) the station description, (2) the data table of water levels observed during the current water year, and (3) a graph of the water levels for the last 3 years. The description of the well is presented first through use of descriptive headings preceding the tabular data. The comments that follow clarify information presented under the various headings of the station description.

LOCATION.--This paragraph follows the well-identification number and reports the latitude and longitude (given in degrees, minutes, and seconds), the hydrologic-unit number, the distance and direction from a geographic point of reference, and the owner's name.

AQUIFER.--This entry designates by name (if a name exists) and geologic age the aquifer(s) open to the well.

WELL CHARACTERISTICS.--This entry describes the well in terms of depth, diameter, casing depth or screened interval, method of construction, use, and additional information such as casing breaks, collapsed screen, and other changes since construction.

INSTRUMENTATION.--This paragraph provides information on both the frequency of measurement and the collection method, allowing the user to better evaluate the reported water-levels by knowing whether they are based on hourly, daily, or some other frequency of measurement.

DATUM.--This entry describes both the measuring point and the land-surface elevation at the well. The measuring point is described physically (such as top of collar, notch in top of casing, plug in pump base and so on), and in relation to land surface (such as 1.3 ft above land-surface datum). The elevation of the land-surface datum is described in feet above (or below) sea level; it is reported with a precision relative to the method of determination.

REMARKS.--This entry describes factors that may influence the water level in a well or the measurement of the water level. It should identify wells that also are water-quality observation wells, and may be used to acknowledge the assistance of local (non-Survey) observers.

PERIOD OF RECORD.--This entry indicates the period for which there are published records for the well. It reports the month and year of the start of publication of water-level records by the U.S. Geological Survey and the words "*to current year*" if the records are to be continued into the following year. Periods for which water-level records are available, but are not published by the Geological Survey, may be noted.

EXTREMES FOR PERIOD OF RECORD.--This entry contains the highest and lowest values of one daily water-level statistic (maximum, mean, or instantaneous) reported in the data tables for the period of published record with respect to land-surface datum, (or occasionally sea level), and the dates of their occurrence. For example, if the daily maximum depth below land surface is reported in the table of water levels, this paragraph would reflect the highest and lowest of these daily maximum values for the period of record. Depending on the statistic reported in the table of water levels, extremes would be determined from daily maximum, mean, or instantaneous values.

Data table of water levels

A table of water levels follows the station description for each well. These tables usually report water-level data as maximum depth (in feet) above or below land-surface datum, but may report daily mean or instantaneous values depending upon the method used to obtain the record and how the record was published in the past. If water-level record is obtained from electronic data loggers or DCPs, in addition to data published in the table of water levels, the daily maximum, minimum, and mean water-levels are stored in computer files and available from the District Office as noted in the REMARKS paragraph for that well. The extremes of the water-levels reported in the table for the water year and their dates of occurrence are shown on a line below the table. Missing records are indicated by dashes in place of the water level. A hydrograph showing the last three years of water levels follows each water-level table.

Records of Ground-Water Quality

Records of ground-water quality are obtained at wells and springs included in ground-water projects. Records of ground-water quality in this report may involve a variety of types of data and measurement frequencies. Those wells with a (c) following the well number in the list of ground-water wells on page x, have water-quality data published in the report. Miscellaneous or short-term ground-water data collection projects are published following the basic network data.

Data Collection and Computation

The records of ground-water quality in this report were obtained mostly as a part of special studies in specific areas. Consequently, a number of chemical analyses are presented for some counties but none are presented for others. As a result, the records for this year, by themselves, do not provide a balanced view of ground-water quality Statewide. Such a view can be attained only by considering records for this year in context with similar records obtained for these and other counties in previous years.

Most methods for collecting and analyzing water samples are described in the U.S. Geological Survey TWRI publications referred to in the "*On-site Measurements and Sample Collection*" and the "*Laboratory Measurements*" sections in this data report. In addition, the TWRI Book 1, Chapter D2, describes guidelines for the collection and field analysis of ground-water samples for selected unstable constituents. The values reported in this report represent water-quality conditions at the time of sampling as much as possible, consistent with available sampling techniques and methods of analysis. These methods are consistent with ASTM standards and generally follow ISO standards. All samples were obtained by trained personnel. The wells sampled were pumped long enough to assure that the water collected came directly from the aquifer and had not stood for a long time in the well casing where it would have been exposed to the atmosphere and to the material, possibly metal, comprising the casings.

Data Presentation

Ground-water-quality data are published with ground-water-level data at stations where level data are collected. Data collected at partial-record stations and miscellaneous sites follow the information for continuous ground-water record stations. Data for each section are listed alphabetically by county, and are identified by well number. The prime identification number for wells sampled is the 15-digit number derived from the latitude-longitude locations. No descriptive statements are given for ground-water-quality records; however, the well number, depth of well, date of sampling, and other pertinent data are given in the table containing the chemical analyses of the ground water. The REMARK codes listed for surface-water-quality records are also applicable to ground-water-quality records.

ACCESS TO USGS WATER DATA

The U.S. Geological Survey is the principal Federal water-data agency and, as such, collects and disseminates about 70 percent of the water data currently being used by numerous State, local, private, and other Federal agencies to develop and manage our water resources. The Geological Survey provides near real-time stage and discharge data for many of the gaging stations equipped with the necessary telemetry and historic daily-mean and peak-flow discharge data for most current or discontinued gaging stations through the World Wide Web (WWW). These data may be accessed at [<http://water.usgs.gov>].

Some water-quality and ground-water data also are available through the WWW. In addition, data can be provided in various machine-readable formats on magnetic tape or 3-1/2 inch floppy disk. Information about the availability of specific types of data or products, and user charges, can be obtained locally from each of the Water Resources Division District Offices (See address on the back of the title page.)

For most streamgages, "*real-time*" streamflow conditions are available on the World Wide Web (WWW) Pennsylvania District Home Page at [<http://pa.water.usgs.gov/>]. Daily streamflow values for the period of record, annual peak stream discharges, and streamflow conditions for surrounding states may also be obtained at this WWW address.

A wide variety of additional information, such as ordering U.S. Geological Survey maps and publications is available at the U.S. Geological Survey Home Page at [<http://www.usgs.gov/>].

DEFINITION OF TERMS

Terms related to streamflow, water-quality, and other hydrologic data, as used in this report, are defined below. See also the table for converting Inch-pound units to International System (SI) Units on the inside of the back cover.

Acid neutralizing capacity (ANC) is the equivalent sum of all bases or base-producing materials, solutes plus particulates, in an aqueous system that can be titrated with acid to an equivalence point. This term designates titration of an *unfiltered* sample (formerly reported as alkalinity).

Acre-foot (AC-FT, acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or 325,851 gallons or 1,233 cubic meters.

Adenosine triphosphate (ATP) is an organic, phosphate-rich, compound important in the transfer of energy in organisms. Its central role in living cells makes it an excellent indicator of the presence of living material in water. A measure of ATP therefore provides a sensitive and rapid estimate of biomass. ATP is reported in micrograms per liter of the original water sample.

Algae are mostly aquatic single-celled, colonial, or multi-celled plants, containing chlorophyll and lacking roots, stems, and leaves.

Algal growth potential (AGP) is the maximum algal dry weight biomass that can be produced in a natural water sample under standardized laboratory conditions. The growth potential is the algal biomass present at stationary phase and is expressed as milligrams dry weight of algae produced per liter of sample.

Alkalinity is the capacity of solutes in an aqueous system to neutralize acid. This term designates titration of a *filtered* sample.

Annual runoff indicates the total quantity of water in runoff for a drainage area for the year. Data reports may use any of the following units of measurements in presenting annual runoff data:

Acre-foot (AC-FT) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equal to 43,560 cubic feet or 325,851 gallons or 1,233 cubic meters.

Cubic foot per second per square mile (CFSM, $\text{ft}^3/\text{s}/\text{mi}^2$) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming the runoff is distributed uniformly in time and area.

Inch (IN., in.) indicates the depth to which the drainage area would be covered if all of the runoff for a given time period were uniformly distributed on it.

Aquifer is a geologic formation, group of formations, or part of a formation that contains sufficient saturated permeable material to yield significant quantities of water to wells and springs.

Artesian means confined and is used to describe a well in which the water level stands above the top of the aquifer tapped by the well. A flowing artesian well is one in which the water level is above the land surface.

Bacteria are microscopic unicellular organisms, typically spherical, rodlike, or spiral and threadlike in shape, often clumped into colonies. Some bacteria cause disease while others perform an essential role in nature in the recycling of materials; for example, by decomposing organic matter into a form available for reuse by plants.

Escherichia coli (*E. coli*) are bacteria of the fecal coliform groups. The presence of these organisms in water is indicative of fecal contamination from humans or other warm-blooded animals. Some strains of *E. coli* are themselves pathogens. In the laboratory, these bacteria are defined as organisms that produce yellow or yellow-brown colonies that remain so when placed on a filter pad saturated with urea substrate broth for 15 minutes after resuscitation at 35°C for two hours and incubation for 24 hours at 44.5°C on m-TEC medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal coliform bacteria are bacteria that are present in the intestines or feces of warm-blooded animals. They are often used as indicators of the sanitary quality of the water. In the laboratory they are defined as all organisms that produce blue colonies within 24 hour when incubated at 44.5°C \pm 0.2°C on M-FC medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Fecal streptococcal bacteria are bacteria found also in intestines of warm-blooded animals. Their presence in water is considered to verify fecal pollution. They are characterized as gram-positive, cocci bacteria which are capable of growth in brain-heart infusion broth. In the laboratory they are defined as all the organisms which produce red or pink colonies within 48 hours at $35^{\circ}\text{C} \pm 1.0^{\circ}\text{C}$ on KF-streptococcus medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Total coliform bacteria are a particular group of bacteria that are used as indicators of possible sewage pollution. They are characterized as aerobic or facultative anaerobic, gram-negative, nonspore-forming, rod-shaped bacteria which ferment lactose with gas formation within 48 hours at 35°C . In the laboratory these bacteria are defined as the organisms that produce colonies with a golden-green metallic sheen within 24 hours when incubated at $35^{\circ}\text{C} \pm 1.0^{\circ}\text{C}$ on M-Endo medium (nutrient medium for bacterial growth). Their concentrations are expressed as number of colonies per 100 mL of sample.

Bed material is the sediment mixture of which a streambed, lake, pond, reservoir, or estuary bottom is composed.

Benthic invertebrates are invertebrate animals inhabiting the bottoms of lakes, streams and other water bodies. They are useful as indicators of water quality.

Biochemical oxygen demand (BOD) is a measure of the quantity of dissolved oxygen, in milligrams per liter, necessary for the decomposition of organic matter by microorganisms, such as bacteria.

Biomass is the amount of living matter present at any given time, expressed as the mass per unit area or volume of habitat.

Ash mass is the mass or amount of residue present after the residue from the dry mass determination has been ashed in a muffle furnace at a temperature of 500°C for 1 hour. The ash mass values of zooplankton and phytoplankton are expressed in grams per cubic meter (g/m^3), and periphyton and benthic organisms in grams per square meter (g/m^2).

Dry mass refers to the mass of residue present after drying in an oven at 105°C for zooplankton and periphyton, until the mass remains unchanged. This mass represents the total organic matter, ash and sediment, in the sample. Dry mass values are expressed in the same units as ash mass.

Organic mass or volatile mass of the living substance is the difference between the dry mass and ash mass, and represents the actual mass of the living matter. The organic mass is expressed in the same units as for ash mass and dry mass.

Wet mass is the mass of living matter plus contained water.

Bottom material: See Bed material.

Cells/volume refers to the number of cells of any organism which is counted by using a microscope and grid or counting cell. Many planktonic organisms are multicelled and are counted according to the number of contained cells per sample, usually milliliters (mL) or liters (L).

Cfs-day is the volume of water represented by flow of 1 cubic foot per second for 24 hours. It is equivalent to 86,400 cubic feet, 1.9835 acre-feet, or about 646,000 gallons.

Chemical oxygen demand (COD) is a measure of the chemically oxidizable material in the water, and furnishes an approximation of the amount of organic and reducing material present. The determined value may correlate with BOD or with carbonaceous organic pollution from sewage or industrial wastes.

Chlorophyll refers to the green pigments of plants. Chlorophyll *a* and *b* are the two most common green pigments in plants.

Color unit is produced by one milligram per liter of platinum in the form of the chloroplatinate ion. Color is expressed in units of the platinum-cobalt scale.

Contents is the volume of water in a reservoir or lake. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

Continuing-record station is a specified site which meets one or all conditions listed:

1. When chemical samples are collected daily or monthly for 10 or more months during the water year.
2. When water temperature records include observations taken one or more times daily.
3. When sediment discharge records include periods for which sediment loads are computed and are considered to be representative of the runoff for the water year.

Continuous-record station is a station where streamflow and/or water-quality data are collected systematically over a period of years for use in hydrologic analyses. Data may be collected continuously or periodically.

Control designates a feature in the channel downstream from the gage that determines the stage-discharge relation at the gage. This feature may be a natural constriction of the channel, an artificial structure, or a uniform cross section over a long reach of the channel.

Control structure as used in this report is a structure on a stream or canal that is used to regulate the flow or stage of the stream or to prevent the intrusion of salt water.

Cubic feet per second per square mile (CFSM) [(ft³/s)/mi²] is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming that the runoff is distributed uniformly in time and area.

Cubic foot per second (CFS) (ft³/s) is the rate of discharge representing a volume of 1 cubic foot passing a given point during 1 second and is equivalent to approximately 7.48 gallons per second or 448.8 gallons per minute.

Data Collection Platform (DCP) is an electronic instrument which collects, processes, stores, and transmits data from various sensors to an earth-orbiting Geostationary Operational Environmental Satellite (GOES) and/or through landline telemetry.

Data logger is a microprocessor based data acquisition system designed specifically to acquire, process, and store data. Data are usually downloaded from onsite data loggers for entry into office data systems.

Discharge is the volume of water (or more broadly, volume of fluid plus suspended sediment) that passes a given point within a given period of time.

Annual 7-day minimum is the lowest mean discharge for 7 consecutive days for a calendar year or a water year. Note that most low-flow frequency analyses of annual 7-day minimum flows use a climatic year (April 1-March 31). The date shown in the summary statistics table is the initial date of the 7-day period. (This value should not be confused with the 7-day 10-year low-flow statistic.)

Base discharge is an arbitrary instantaneous discharge value, determined for stations meeting certain criteria, that will be exceeded about three times per year.

Instantaneous discharge is the discharge at a particular instant of time.

Mean discharge (MEAN) is the arithmetic mean of individual daily mean discharges during a specific period.

Dissolved refers to that material in a representative water sample which passes through a 0.45-micrometer (µm) membrane filter. This is a convenient operational definition used by Federal agencies that collect water data. Determinations of "dissolved" constituents are made on subsamples of the filtrate.

Dissolved-solids concentration of water is determined either analytically by the "residue-on-evaporation" method, or mathematically by totaling the concentrations of individual constituents reported in a comprehensive chemical analysis. During the analytical determination of dissolved solids, the bicarbonate (generally a major dissolved component of water) is converted to carbonate. Therefore, in the mathematical calculation of dissolved-solids concentration, the bicarbonate value, in milligrams per liter, is multiplied by 0.492 to reflect the change.

Drainage area of a stream at a specific location is that area, measured in a horizontal plane, enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above the specified point. Figures of drainage area given herein include all closed basins, or noncontributing areas, within the area unless otherwise noted.

Drainage basin is a part of the surface of the earth that is occupied by a drainage system, which consists of a surface stream or a body of impounded surface water together with all tributary surface streams and bodies of impounded surface water.

Estimated (E) values is when an analyte is detected and all criteria for a positive result are met, the concentration is reported. If the concentration is less than the method detection limit (MDL), an 'E' code will be reported with the value. If the analyte is qualitatively identified as present, but the quantitative determination is substantially more uncertain, the National Water Quality Laboratory will identify the result with an 'E' code even though the measured value is greater than the MDL. A value reported with an 'E' code should be used with caution. When no analyte is detected in a sample, the default reporting value is the MDL preceded by a less than sign (<).

Gage height (G.H.) is the water-surface elevation referred to some arbitrary gage datum. Gage height is often used interchangeably with the more general term "stage," although gage height is more appropriate when used with a reading on a gage.

Gaging station is a particular site on a stream, canal, lake, or reservoir where systematic observations of hydrologic data are obtained.

Hardness of water is a physical-chemical characteristic that is commonly recognized by the increased quantity of soap required to produce lather. It is computed as the sum of equivalents of polyvalent cations and is expressed as the equivalent concentration of calcium carbonate (CaCO_3).

High tide is the maximum height reached by each rising tide.

The **Hydrologic Bench-mark station** is one that provides hydrologic data for a basin in which the hydrologic regimen will likely be governed solely by natural conditions. Data collected at a bench-mark station may be used to separate effects of natural from human-induced changes in other basins that have been developed and in which the physiography, climate, and geology are similar to those in the undeveloped bench-mark basin.

Hydrologic unit is a geographic area representing part or all of a surface drainage basin or distinct hydrologic feature as delineated on the State Hydrologic Unit Maps by the U.S. Geological Survey. Each hydrologic unit is identified by an 8-digit number.

Land-surface datum (lsd) is a datum plane that is approximately at land surface at each ground-water observation well.

Low tide is the minimum height reached by each falling tide.

Measuring point (MP) is an arbitrary permanent reference point from which the distance to the water surface in a well is measured to obtain the water level.

Membrane filter is a thin microporous material of specific pore size used to filter bacteria, algae, and other very small particles from water.

Metamorphic stage refers to the stage of development that an organism exhibits during its transformation from an immature form to an adult form. This developmental process exists for most insects, and the degree of difference from the immature stage to the adult form varies from relatively slight to pronounced, with many intermediates. Examples of metamorphic stages of insects are egg-larva-adult or egg-nymph-adult.

Methylene blue active substance (MBAS) are apparent detergents. The determination depends on the formation of a blue color when methylene blue dye reacts with synthetic anionic detergent compounds.

Micrograms per gram ($\mu\text{g/g}$) is a unit expressing the concentration of a chemical constituent as the mass (micrograms) of the element per unit mass (gram) of material analyzed.

Micrograms per liter (UG/L, $\mu\text{g/L}$) is a unit expressing the concentration of chemical constituents in solution as mass (micrograms) of solute per unit volume (liter) of water. One thousand micrograms per liter is equivalent to one milligram per liter.

Microsiemens per centimeter ($\mu\text{S/cm}$, US/CM) is a unit expressing the amount of electrical conductivity of a solution as measured between opposite faces of a centimeter cube of solution at a specified temperature. Siemens is the International System of units nomenclature. It is synonymous with mhos and is the reciprocal of resistance in ohms.

Milligrams per liter (MG/L, mg/L) is a unit for expressing the concentration of chemical constituents in solution. Milligrams per liter represent the mass of solute per unit volume (liter) of water. Concentration of suspended sediment also is expressed in mg/L , and is based on the mass of sediment per liter of water-sediment mixture.

Miscellaneous-record site is a site where limited streamflow and/or water-quality data are collected on a random basis for use in hydrologic analyses.

Most probable number (MPN) is an index of the number of coliform bacteria that, more probably than any other number, would give the results shown by the laboratory examination; it is not an actual enumeration. MPN is determined from the distribution of gas-positive cultures among multiple inoculated tubes.

Multiple-plate samplers are artificial substrates of known surface area used for obtaining benthic-invertebrate samples. They consist of a series of spaced, hardboard plates on an eyebolt.

The **National Geodetic Vertical Datum of 1929** (NGVD of 1929) is a geodetic datum derived from a general adjustment of the first order level nets of both the United States and Canada. It was formerly called "*Sea Level Datum of 1929*" or "*mean sea level*" in this series of reports. Although the datum was derived from the average sea level over a period of many years at 26 tide stations along the Atlantic, Gulf of Mexico, and Pacific Coasts, it does not necessarily represent local mean sea level at any particular place.

The **National Stream Quality Accounting Network** (NASQAN) monitors the water quality of large rivers within four of the Nation's largest river basins--the Mississippi, Columbia, Colorado, and Rio Grande. The network consists of 39 stations. Samples are collected with sufficient frequency that the flux of a wide range of constituents can be estimated. The objective of NASQAN is to characterize the water quality of these large rivers by measuring concentration and mass transport of a wide range of dissolved and suspended constituents, including nutrients, major ions, dissolved and sediment-bound heavy metals, common pesticides, and inorganic and organic forms of carbon. This information will be used (1) to describe the long-term trends and changes in concentration and transport of these constituents; (2) to test findings of the National Water-Quality Assessment Program (NAWQA); (3) to characterize processes unique to large-river systems such as storage and re-mobilization of sediments and associated contaminants; and (4) to refine existing estimates for assessing human effects on the world's oceans and for determining global cycles of carbon, nutrients, and other chemicals.

The **National Atmospheric Deposition Program/National Trends Network** (NADP/NTN) provides continuous measurement and assessment of the chemical climate of precipitation throughout the United States. As the lead federal agency, the USGS works together with over 100 organizations to accomplish the following objectives; (1) Provide a long-term, spatial and temporal record of atmospheric deposition generated from a network of 191 precipitation chemistry monitoring sites. (2) Provide the mechanism to evaluate the effectiveness of the significant reduction in SO₂ emissions that began in 1995 as implementation of the Clean Air Act Amendments (CAAA) occurred. (3) Provide the scientific basis and nationwide evaluation mechanism for implementation of the Phase II CAAA emission reductions for SO₂ and NO_x scheduled to begin in 2000.

The **National Water-Quality Assessment** (NAWQA) Program of the U.S. Geological Survey is a long-term program with goals to describe the status and trends of water-quality conditions for a large, representative part of the Nation's ground- and surface-water resources; provide an improved understanding of the primary natural and human factors affecting these observed conditions and trends; and provide information that supports development and evaluation of management, regulatory, and monitoring decisions by other agencies.

The **North American Vertical Datum of 1988** (NAVD of 1988) is a geodetic datum derived from the releveling of about 131,000 miles of existing first-order leveling lines to strengthen the network in the conterminous United States. The releveling was correlated with the total network and adjusted by the least squares method. The adjusted network includes about 600,000 permanent benchmarks. The assumption of zero NGVD as being mean sea level at the 26 appointed tide stations produced a distortion in the network. To remove this distortion in the network, a definition that could be reproduced readily at any location was established. This definition is an equipotential surface, that is, the surface represented by a constant value of the acceleration due to gravity.

Organism is any living entity.

Organism count/area refers to the number of organisms collected and enumerated in a sample and adjusted to the number per unit area habitat, usually square meters (m²), acres, or hectare. Periphyton, benthic organisms, and macrophytes are expressed in these terms.

Organism count/volume refers to the number of organisms collected and enumerated in a sample and adjusted to the number per sample volume, usually milliliters (mL) or liters (L). Numbers of planktonic organisms can be expressed in these terms.

Total organism count is the total number of organisms collected and enumerated in any particular sample.

Parameter Code is a 5-digit number used in the U.S. Geological Survey computerized data system, National Water Information System (NWIS), to uniquely identify a specific constituent.

Partial-record station is a particular site where limited streamflow and/or water-quality data are collected systematically over a period of years for use in hydrologic analyses.

Particle size is the diameter, in millimeters (mm), of a particle determined by either sieve or sedimentation methods. Sedimentation methods (pipet, bottom-withdrawal tube, visual-accumulation tube) determine fall diameter of particles in either distilled water (chemically dispersed) or in native water (the river water collected at the time and point of sampling).

Particle-size classification used in this report agrees with recommendations made by the American Geophysical Union Subcommittee on Sediment Terminology. The classification is as follows:

| Classification | Size (mm) | Method of analysis |
|----------------|-----------------|------------------------|
| Clay | 0.00024 - 0.004 | Sedimentation |
| Silt | 0.004 - .062 | Sedimentation |
| Sand | .062 - 2.0 | Sedimentation or sieve |
| Gravel | 2.0 - 64.0 | Sieve |

The particle-size distributions given in this report are not necessarily representative of all particles in transport in the stream. Most of the organic material is removed, and the sample is subjected to mechanical and chemical dispersion before analysis in distilled water. Chemical dispersion is not used for native-water analysis.

Percent composition is a unit for expressing the ratio of a particular part of a sample or population to the total sample or population, in terms of types, numbers, mass, or volume.

Periphyton is the assemblage of microorganisms attached to and living upon submerged solid surfaces. While primarily consisting of algae, they also include bacteria, fungi, protozoa, rotifers, and other small organisms.

Pesticides are chemical compounds used to control undesirable organisms. Major categories of pesticides include insecticides, miticides, fungicides, herbicides, and rodenticides.

Picocurie (PC, pCi) is one trillionth (1×10^{-12}) of the amount of radioactivity represented by a curie (Ci). A curie is the amount of radioactivity that yields 3.7×10^{10} radioactive disintegrations per second. A picocurie yields 2.22 dpm (disintegrations per minute).

Plankton is the community of suspended, floating, or weakly swimming organisms that live in the open water of lakes and rivers.

Phytoplankton is the plant part of the plankton. They are usually microscopic and their movement is subject to the water currents. Phytoplankton growth is dependent upon solar radiation and nutrient substances. Because they are able to incorporate as well as release materials to the surrounding water, the phytoplankton have a profound effect upon the quality of the water. They are the primary food producers in the aquatic environment, and are commonly known as algae.

Blue-green algae are a group of phytoplankton organisms having a blue pigment, in addition to the green pigment called chlorophyll. Blue-green algae often cause nuisance conditions in water.

Diatoms are the unicellular or colonial algae having a siliceous shell. Their concentrations are expressed as number of cells per milliliter (cells/mL) of sample.

Green algae have chlorophyll pigments similar in color to those of higher green plants. Some forms produce algal mats or floating "moss" in lakes. Their concentrations are expressed as the number of cells per milliliter (cells/mL) of sample.

Zooplankton is the animal part of the plankton. Zooplankton are capable of extensive movements within the water column, and are often large enough to be seen with the unaided eye. Zooplankton are secondary consumers feeding upon bacteria, phytoplankton, and detritus. Because they are the grazers in the aquatic environment, the zooplankton are a vital part of the aquatic food web. The zooplankton community is dominated by small crustaceans and rotifers.

Primary productivity is a measure of the rate at which new organic matter is formed and accumulated through photosynthetic and chemosynthetic activity of producer organisms (chiefly, green plants). The rate of primary production is estimated by measuring the amount of oxygen released (oxygen method) or the amount of carbon assimilated by the plants (carbon method).

Milligrams of carbon per area or volume per unit time [$\text{mg C}/(\text{m}^2/\text{time})$] for periphyton and macrophytes and [$\text{mg C}/(\text{m}^3/\text{time})$] for phytoplankton are units for expressing primary productivity. They define the amount of carbon dioxide consumed as measured by radioactive carbon (carbon 14). The carbon 14 method is of greater sensitivity than the oxygen light and dark bottle method, and is preferred for use in unenriched waters. Unit time may be either the hour or day, depending on the incubation period.

Milligrams of oxygen per area or volume per unit time [mg O/(m²/time)] for periphyton and macrophytes and [mg O/(m³/time)] for phytoplankton are the units for expressing primary productivity. They define production and respiration rates as estimated from changes in the measured dissolved-oxygen concentration. The oxygen light and dark bottle method is preferred if the rate of primary production is sufficient for accurate measurements to be made within 24 hours. Unit time may be either the hour or day, depending on the incubation period.

Polychlorinated biphenyls (PCBs) are industrial chemicals that are mixtures of chlorinated biphenyl compounds having various percentages of chlorine. They are similar in structure to organochlorine insecticides.

Radiochemical program is a network of regularly sampled water-quality stations where samples are collected to be analyzed for radioisotopes. The streams that are sampled represent major drainage basins in the conterminous United States.

Recoverable from bottom material is the amount of a given constituent that is in solution after a representative sample of bottom material has been digested by a method (usually using an acid or mixture of acids) that results in dissolution of only readily soluble substances. Complete dissolution of all bottom material is not achieved by the digestion treatment and thus the determination represents less than the total amount (that is, less than 95 percent) of the constituent in the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Recurrence interval is the average time interval between occurrences of a hydrological event of a given or greater magnitude, usually expressed in years. May also be called return period.

River mile is the distance of a point on a river measured in miles from the river's mouth along the low-water channel.

Runoff: See Annual runoff.

Sea level: In this report, unless otherwise noted in the GAGE paragraph, "*sea level*" refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)--a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called Sea Level Datum of 1929.

Sediment is solid material that originates mostly from disintegrated rocks and is transported by, suspended in, or deposited from water; it includes chemical and biochemical precipitates and decomposed organic material such as humus. The quantity, characteristics, and cause of the occurrence of sediment in streams are influenced by environmental factors. Some major factors are degree of slope, length of slope, soil characteristics, land usage, and quantity and intensity of precipitation.

Bed load is the sediment that is transported in a stream by rolling, sliding, or skipping along the bed and very close to it. In this report, bed load is considered to consist of particles in transit within 0.25 ft of the streambed.

Bed load discharge (tons per day) is the quantity of bed load measured by dry weight that moves past a section as bed load in a given time.

Suspended sediment is the sediment that at any given time is maintained in suspension by the upward components of turbulent currents or that exists in suspension as a colloid.

Suspended-sediment concentration is the velocity-weighted concentration of suspended sediment in the sampled zone (from the water surface to a point approximately 0.3 ft above the bed) expressed as milligrams of dry sediment per liter of water-sediment mixture (mg/L).

Mean concentration is the time-weighted concentration of suspended sediment passing a stream section during a 24-hour day.

Suspended-sediment discharge (tons/day) is the rate at which dry mass of sediment passes a section of a stream or is the quantity of sediment, as measured by dry mass or volume, that passes a section in a given time. It is calculated in units of tons per day as follows: concentration (mg/L) x discharge (ft³/s) x 0.0027.

Suspended-sediment load is a general term that refers to material in suspension. It is not synonymous with either discharge or concentration.

Total-sediment discharge (tons/day) is the sum of the suspended-sediment discharge and the bed-load discharge. It is the total quantity of sediment, as measured by dry mass or volume, that passes a section during a given time.

Total-sediment load or total load is a term which refers to the total sediment (bed load plus suspended-sediment load) that is in transport. It is not synonymous with total-sediment discharge.

7-day 10-year low flow (Q7,10) is the discharge at the 10-year recurrence interval taken from a frequency curve of annual values of the lowest mean discharge for 7 consecutive days (the 7-day low flow).

Sodium-adsorption-ratio (SAR) is the expression of relative activity of sodium ions in exchange reactions within soil and is an index of sodium or alkali hazard to the soil. Waters range in respect to sodium hazard from those which can be used for irrigation on almost all soils to those which are generally unsatisfactory for irrigation.

Solute is any substance that is dissolved in water.

Specific conductance is a measure of the ability of a water to conduct an electrical current. It is expressed in microsiemens per centimeter at 25°C. Specific conductance is related to the type and concentration of ions in the solution and can be used for approximating the dissolved-solids content of the water. Commonly, the concentration of dissolved solids (in milligrams per liter) is from 55 to 75 percent of the specific conductance (in microsiemens). This relation is not constant from stream to stream, and it may vary in the same source with changes in the composition of the water.

Stage-discharge relation is the relation between gage height (stage) and volume of water, per unit of time, flowing in a channel.

Streamflow is the discharge that occurs in a natural channel. Although the term "*discharge*" can be applied to the flow of a canal, the word "*streamflow*" uniquely describes the discharge in a surface stream course. The term "*streamflow*" is more general than "*runoff*" as streamflow may be applied to discharge whether or not it is affected by diversion or regulation.

Substrate is the physical surface upon which an organism lives.

Artificial substrate is a device which is purposely placed in a stream or lake for colonization of organisms. The artificial substrate simplifies the community structure by standardizing the substrate from which each sample is taken. Examples of artificial substrates are basket samplers (made of wire cages filled with clean streamside rocks) and multi-plate samplers (made of hardboard) for benthic organism collection, and plexiglass strips for periphyton collection.

Natural substrate refers to any naturally occurring immersed or submersed solid surface, such as a rock or tree, upon which an organism lives.

Surface area of a lake is that area (in acres) outlined on the latest USGS topographic map as the boundary of the lake and measured by a planimeter. In localities not covered by topographic maps, the areas are computed from the best maps available at the time planimetered. All areas shown are those for the stage when the planimetered map was made.

Surficial bed material is the top 0.1 to 0.2 ft of the bed material that is sampled using U.S. Series Bed-Material Samplers.

Suspended (as used in tables of chemical analyses) refers to the amount (concentration) of undissolved material in a water-sediment mixture. It is associated with the material retained on a 0.45 µm filter.

Suspended, recoverable is the amount of a given constituent that is in solution after the part of a representative suspended-sediment sample that is retained on a 0.45 µm membrane filter has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all the particulate matter is not achieved by the digestion treatment and thus the determination represents something less than the "*total*" amount (that is, less than 95 percent) of the constituent present in the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

Determinations of "*suspended, recoverable*" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total recoverable concentrations of the constituent.

Suspended, total is the total amount of a given constituent in the part of a representative suspended-sediment sample that is retained on a 0.45 µm membrane filter. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent determined. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to determine when the results should be reported as "*suspended, total*."

Determinations of "*suspended, total*" constituents are made either by analyzing portions of the material collected on the filter or, more commonly, by difference, based on determinations of (1) dissolved and (2) total concentrations of the constituent.

Synoptic Studies are short-term investigations of specific water-quality conditions during selected seasonal or hydrologic periods to provide improved spatial resolution for critical water-quality conditions. For the period and conditions sampled, they assess the spatial distribution of selected water-quality conditions in relation to causative factors, such as land use and contaminant sources.

Taxonomy is the division of biology concerned with the classification and naming of organisms. The classification of organisms is based upon a hierarchical scheme beginning with Kingdom and ending with Species at the base. The higher the classification level, the fewer features the organisms have in common. For example, the taxonomy of a particular mayfly, *Hexagenia limbata* is the following:

| | |
|----------------|--------------------------|
| Kingdom | Animal |
| Phylum | Arthropoda |
| Class | Insecta |
| Order | Ephemeroptera |
| Family | Ephemeridae |
| Genus | Hexagenia |
| Species | Hexagenia Limbata |

Time-weighted average is computed by multiplying the number of days in the sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the total number of days. A time-weighted average represents the composition of water that would be contained in a vessel or reservoir that had received equal quantities of water from the stream each day for the year.

Tons per acre-foot indicates the dry mass of dissolved solids in 1 acre-foot of water. It is computed by multiplying the concentration, in milligrams per liter, by 0.00136.

Tons per day (T/day) is the quantity of substance in solution or suspension that passes a stream section during a 24-hour period.

Total is the total amount of a given constituent in a representative water-suspended sediment sample, regardless of the constituent's physical or chemical form. This term is used only when the analytical procedure assures measurement of at least 95 percent of the constituent present in both the dissolved and suspended phases of the sample. A knowledge of the expected form of the constituent in the sample, as well as the analytical methodology used, is required to judge when the results should be reported as "total." (Note that the word "total" does double duty here, indicating both that the sample consists of a water-suspended sediment mixture and that the analytical method determines all of the constituent in the sample).

Total discharge is the total quantity of any individual constituent, as measured by dry mass or volume, that passes through a stream cross-section per unit of time. This term needs to be qualified, such as "total sediment discharge," "total chloride discharge," and so on.

Total recoverable is the amount of a given constituent that is in solution after a representative water-suspended sediment sample has been digested by a method (usually using a dilute acid solution) that results in dissolution of only readily soluble substances. Complete dissolution of all particulate matter is not achieved by the digestion treatment, and thus the determination represents something less than the "total" amount (that is, less than 95 percent) of the constituent present in the dissolved and suspended phases of the sample. To achieve comparability of analytical data, equivalent digestion procedures would be required of all laboratories performing such analyses because different digestion procedures are likely to produce different analytical results.

The **Tritium Network** is a network of stations which has been established to provide baseline information on the occurrence of tritium in the Nation's surface waters. In addition to the surface-water stations in the network, tritium data are also obtained at a number of precipitation stations. The purpose of the precipitation stations is to provide an estimate sufficient for hydrologic studies of the tritium input to the United States.

Volatile Organic Compounds (VOCs) are organic compounds that can be isolated from the water phase of a sample by purging the water sample with inert gas, such as helium, and subsequently analyzed by gas chromatography. Many VOCs are man-made chemicals that are used and produced in the manufacture of paints, adhesives, petroleum products, pharmaceuticals, and refrigerants. They are often components of fuels, solvents, hydraulic fluids, paint thinners, and dry cleaning agents commonly used in urban settings. VOC contamination of drinking-water supplies is a human health concern because many are toxic and are known or suspected human carcinogens (U.S. Environmental Protection Agency, 1996).

Water year as used in Geological Survey reports, is the 12-month period October 1 through September 30. The water year is designated by the calendar year in which it ends and which includes 9 of the 12 months. Thus, the year ending September 30, 1999, is called the "*1999 water year*."

WDR is used as an abbreviation for "*Water-Data Report*" in the REVISED RECORDS paragraph to refer to a State's annual hydrologic-data reports. (WRD was used as an abbreviation for "Water Resources Data" in reports published prior to 1976.)

Weighted average is used in this report to indicate discharge-weighted average. It is computed by multiplying the discharge for a sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the sum of the discharges. A discharge-weighted average approximates the composition of water that would be found in a reservoir containing all the water passing a given location during the water year after thorough mixing in the reservoir.

WSP is used as an abbreviation for "*Water-Supply Paper*" in references to previously published reports.

PUBLICATIONS ON TECHNIQUES OF WATER-RESOURCES INVESTIGATIONS

The U.S. Geological Survey publishes a series of manuals describing procedures for planning and conducting specialized work in water-resources investigations. The material is grouped under major subject headings called books and is further divided into sections and chapters. For example, Section A of Book 3 (Applications of Hydraulics) pertains to surface water. The chapter, the unit of publication, is limited to a narrow field of subject matter. This format permits flexibility in revision and publication as the need arises.

The reports listed below are for sale by the U.S. Geological Survey, Branch of Information Services, Box 25286, Federal Center, Denver, Colorado 80225 (authorized agent of the Superintendent of Documents, Government Printing Office). Prepayment is required. Remittance should be sent by check or money order payable to the U.S. Geological Survey. Prices are not included because they are subject to change. Current prices can be obtained by writing to the above address. When ordering or inquiring about prices for any of these publications, please give the title, book number, chapter number, and "U.S. Geological Survey Techniques of Water-Resources Investigations."

Book 1. Collection of Water Data by Direct Measurement

Section D. Water Quality

- 1-D1. *Water temperature—influential factors, field measurement, and data presentation*, by H.H. Stevens, Jr., J.F. Ficke, and G. F. Smoot: USGS–TWRI Book 1, Chapter D1. 1975. 65 pages.
- 1-D2. *Guidelines for collection and field analysis of ground-water samples for selected unstable constituents*, by W.W. Wood: USGS–TWRI Book 1, Chapter D2. 1976. 24 pages.

Book 2. Collection of Environmental Data

Section D. Surface Geophysical Methods

- 2-D1. *Application of surface geophysics to ground-water investigations*, by A.A.R. Zohdy, G.P. Eaton, and D.R. Mabey: USGS–TWRI Book 2, Chapter D1. 1974. 116 pages.
- 2-D2. *Application of seismic-refraction techniques to hydrologic studies*, by F.P. Haeni: USGS–TWRI Book 2, Chapter D2. 1988. 86 pages.

Section E. Subsurface Geophysical Methods

- 2-E1. *Application of borehole geophysics to water-resources investigations*, by W.S. Keys and L.M. MacCary: USGS–TWRI Book 2, Chapter E1. 1971. 126 pages.
- 2-E2. *Borehole geophysics applied to ground-water investigations*, by W.S. Keys: USGS–TWRI Book 2, Chapter E2. 1990. 150 pages.

Section F. Drilling and Sampling Methods

- 2-F1. *Application of drilling, coring, and sampling techniques to test holes and wells*, by Eugene Shuter and W.E. Teasdale: USGS–TWRI Book 2, Chapter F1. 1989. 97 pages.

Book 3. Applications of Hydraulics

Section A. Surface-Water Techniques

- 3-A1. *General field and office procedures for indirect discharge measurements*, by M.A. Benson and Tate Dalrymple: USGS–TWRI Book 3, Chapter A1. 1967. 30 pages.
- 3-A2. *Measurement of peak discharge by the slope-area method*, by Tate Dalrymple and M.A. Benson: USGS–TWRI Book 3, Chapter A2. 1967. 12 pages.
- 3-A3. *Measurement of peak discharge at culverts by indirect methods*, by G.L. Bodhaine: USGS–TWRI Book 3, Chapter A3. 1968. 60 pages.
- 3-A4. *Measurement of peak discharge at width contractions by indirect methods*, by H.F. Matthai: USGS–TWRI Book 3, Chapter A4. 1967. 44 pages.
- 3-A5. *Measurement of peak discharge at dams by indirect methods*, by Harry Hulsing: USGS–TWRI Book 3, Chapter A5. 1967. 29 pages.
- 3-A6. *General procedure for gaging streams*, by R.W. Carter and Jacob Davidian: USGS–TWRI Book 3, Chapter A6. 1968. 13 pages.
- 3-A7. *Stage measurement at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS–TWRI Book 3, Chapter A7. 1968. 28 pages.
- 3-A8. *Discharge measurements at gaging stations*, by T.J. Buchanan and W.P. Somers: USGS–TWRI Book 3, Chapter A8. 1969. 65 pages.
- 3-A9. *Measurement of time of travel in streams by dye tracing*, by F.A. Kilpatrick and J.F. Wilson, Jr.: USGS–TWRI Book 3, Chapter A9. 1989. 27 pages.

- 3-A10. *Discharge ratings at gaging stations*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A10. 1984. 59 pages.
- 3-A11. *Measurement of discharge by the moving-boat method*, by G.F. Smoot and C.E. Novak: USGS–TWRI Book 3, Chapter A11. 1969. 22 pages.
- 3-A12. *Fluorometric procedures for dye tracing*, Revised, by J.F. Wilson, Jr., E.D. Cobb, and F.A. Kilpatrick: USGS–TWRI Book 3, Chapter A12. 1986. 34 pages.
- 3-A13. *Computation of continuous records of streamflow*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A13. 1983. 53 pages.
- 3-A14. *Use of flumes in measuring discharge*, by F.A. Kilpatrick and V.R. Schneider: USGS–TWRI Book 3, Chapter A14. 1983. 46 pages.
- 3-A15. *Computation of water-surface profiles in open channels*, by Jacob Davidian: USGS–TWRI Book 3, Chapter A15. 1984. 48 pages.
- 3-A16. *Measurement of discharge using tracers*, by F.A. Kilpatrick and E.D. Cobb: USGS–TWRI Book 3, Chapter A16. 1985. 52 pages.
- 3-A17. *Acoustic velocity meter systems*, by Antonius Laenen: USGS–TWRI Book 3, Chapter A17. 1985. 38 pages.
- 3-A18. *Determination of stream reaeration coefficients by use of tracers*, by F.A. Kilpatrick, R.E. Rathbun, Nobuhiro Yotsukura, G.W. Parker, and L.L. DeLong: USGS–TWRI Book 3, Chapter A18. 1989. 52 pages.
- 3-A19. *Levels at streamflow gaging stations*, by E.J. Kennedy: USGS–TWRI Book 3, Chapter A19. 1990. 31 pages.
- 3-A20. *Simulation of soluble waste transport and buildup in surface waters using tracers*, by F.A. Kilpatrick: USGS–TWRI Book 3, Chapter A20. 1993. 38 pages.
- 3-A21. *Stream-gaging cableways*, by C. Russell Wagner: USGS–TWRI Book 3, Chapter A21. 1995. 56 pages.

Section B. Ground-Water Techniques

- 3-B1. *Aquifer-test design, observation, and data analysis*, by R.W. Stallman: USGS–TWRI Book 3, Chapter B1. 1971. 26 pages.
- 3-B2. *Introduction to ground-water hydraulics, a programmed text for self-instruction*, by G.D. Bennett: USGS–TWRI Book 3, Chapter B2. 1976. 172 pages.
- 3-B3. *Type curves for selected problems of flow to wells in confined aquifers*, by J.E. Reed: USGS–TWRI Book 3, Chapter B3. 1980. 106 pages.
- 3-B4. *Regression modeling of ground-water flow*, by R.L. Cooley and R.L. Naff: USGS–TWRI Book 3, Chapter B4. 1990. 232 pages.
- 3-B4. *Supplement 1. Regression modeling of ground-water flow --Modifications to the computer code for nonlinear regression solution of steady-state ground-water flow problems*, by R.L. Cooley: USGS–TWRI Book 3, Chapter B4. 1993. 8 pages.
- 3-B5. *Definition of boundary and initial conditions in the analysis of saturated ground-water flow systems—An introduction*, by O.L. Franke, T.E. Reilly, and G.D. Bennett: USGS–TWRI Book 3, Chapter B5. 1987. 15 pages.
- 3-B6. *The principle of superposition and its application in ground-water hydraulics*, by T.E. Reilly, O.L. Franke, and G.D. Bennett: USGS–TWRI Book 3, Chapter B6. 1987. 28 pages.
- 3-B7. *Analytical solutions for one-, two-, and three-dimensional solute transport in ground-water systems with uniform flow*, by E.J. Wexler: USGS–TWRI Book 3, Chapter B7. 1992. 190 pages.

Section C. Sedimentation and Erosion Techniques

- 3-C1. *Fluvial sediment concepts*, by H.P. Guy: USGS–TWRI Book 3, Chapter C1. 1970. 55 pages.
- 3-C2. *Field methods for measurement of fluvial sediment*, by H.P. Guy and V.W. Norman: USGS–TWRI Book 3, Chapter C2. 1970. 59 pages.
- 3-C3. *Computation of fluvial-sediment discharge*, by George Porterfield: USGS–TWRI Book 3, Chapter C3. 1972. 66 pages.

Book 4. Hydrologic Analysis and Interpretation

Section A. Statistical Analysis

- 4-A1. *Some statistical tools in hydrology*, by H.C. Riggs: USGS–TWRI Book 4, Chapter A1. 1968. 39 pages.
- 4-A2. *Frequency curves*, by H.C. Riggs: USGS–TWRI Book 4, Chapter A2. 1968. 15 pages.

Section B. Surface Water

- 4-B1. *Low-flow investigations*, by H.C. Riggs: USGS–TWRI Book 4, Chapter B1. 1972. 18 pages.
- 4-B2. *Storage analyses for water supply*, by H.C. Riggs and C.H. Hardison: USGS–TWRI Book 4, Chapter B2. 1973. 20 pages.
- 4-B3. *Regional analyses of streamflow characteristics*, by H.C. Riggs: USGS–TWRI Book 4, Chapter B3. 1973. 15 pages.

Section D. Interrelated Phases of the Hydrologic Cycle

- 4-D1. *Computation of rate and volume of stream depletion by wells*, by C.T. Jenkins: USGS–TWRI Book 4, Chapter D1. 1970. 17 pages.

Book 5. Laboratory Analysis**Section A. Water Analysis**

- 5-A1. *Methods for determination of inorganic substances in water and fluvial sediments*, by M.J. Fishman and L.C. Friedman, editors: USGS–TWRI Book 5, Chapter A1. 1989. 545 pages.
- 5-A2. *Determination of minor elements in water by emission spectroscopy*, by P.R. Barnett and E.C. Mallory, Jr.: USGS–TWRI Book 5, Chapter A2. 1971. 31 pages.
- 5-A3. *Methods for the determination of organic substances in water and fluvial sediments*, edited by R.L. Wershaw, M.J. Fishman, R.R. Grabbe, and L.E. Lowe: USGS–TWRI Book 5, Chapter A3. 1987. 80 pages.
- 5-A4. *Methods for collection and analysis of aquatic biological and microbiological samples*, by L.J. Britton and P.E. Greeson, editors: USGS–TWRI Book 5, Chapter A4. 1989. 363 pages.
- 5-A5. *Methods for determination of radioactive substances in water and fluvial sediments*, by L.L. Thatcher, V.J. Janzer, and K.W. Edwards: USGS–TWRI Book 5, Chapter A5. 1977. 95 pages.
- 5-A6. *Quality assurance practices for the chemical and biological analyses of water and fluvial sediments*, by L.C. Friedman and D.E. Erdmann: USGS–TWRI Book 5, Chapter A6. 1982. 181 pages.

Section C. Sediment Analysis

- 5-C1. *Laboratory theory and methods for sediment analysis*, by H.P. Guy: USGS–TWRI Book 5, Chapter C1. 1969. 58 pages.

Book 6. Modeling Techniques**Section A. Ground Water**

- 6-A1. *A modular three-dimensional finite-difference ground-water flow model*, by M.G. McDonald and A.W. Harbaugh: USGS–TWRI Book 6, Chapter A1. 1988. 586 pages.
- 6-A2. *Documentation of a computer program to simulate aquifer-system compaction using the modular finite-difference ground-water flow model*, by S.A. Leake and D.E. Prudic: USGS–TWRI Book 6, Chapter A2. 1991. 68 pages.
- 6-A3. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 1: Model Description and User's Manual*, by L.J. Torak: USGS–TWRI Book 6, Chapter A3. 1993. 136 pages.
- 6-A4. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 2: Derivation of finite-element equations and comparisons with analytical solutions*, by R.L. Cooley: USGS–TWRI Book 6, Chapter A4. 1992. 108 pages.
- 6-A5. *A modular finite-element model (MODFE) for areal and axisymmetric ground-water-flow problems, Part 3: Design philosophy and programming details*, by L.J. Torak: USGS–TWRI Book 6, Chapter A5, 1993. 243 pages.
- 6-A6. *A coupled surface-water and ground-water flow model (MODBRANCH) for simulation of stream-aquifer interaction*, by Eric D. Swain and Eliezer J. Wexler. 1996. 125 pages.

Book 7. Automated Data Processing and Computations**Section C. Computer Programs**

- 7-C1. *Finite difference model for aquifer simulation in two dimensions with results of numerical experiments*, by P.C. Trescott, G.F. Pinder, and S.P. Larson: USGS–TWRI Book 7, Chapter C1. 1976. 116 pages.
- 7-C2. *Computer model of two-dimensional solute transport and dispersion in ground water*, by L.F. Konikow and J.D. Bredehoeft: USGS–TWRI Book 7, Chapter C2. 1978. 90 pages.
- 7-C3. *A model for simulation of flow in singular and interconnected channels*, by R.W. Schaffranek, R.A. Baltzer, and D.E. Goldberg: USGS–TWRI Book 7, Chapter C3. 1981. 110 pages.

Book 8. Instrumentation**Section A. Instruments for Measurement of Water Level**

- 8-A1. *Methods of measuring water levels in deep wells*, by M.S. Garber and F.C. Koopman: USGS–TWRI Book 8, Chapter A1. 1968. 23 pages.
- 8-A2. *Installation and service manual for U.S. Geological Survey manometers*, by J.D. Craig: USGS–TWRI Book 8, Chapter A2. 1983. 57 pages.



Section B. Instruments for Measurement of Discharge

- 8-B2. *Calibration and maintenance of vertical-axis type current meters*, by G.F. Smoot and C.E. Novak: USGS–TWRI Book 8, Chapter B2. 1968. 15 pages.

Book 9. Handbooks for Water-Resources Investigations**Section A. National Field Manual for the Collection of Water-Quality Data**

- 9-A1. *National Field Manual for the Collection of Water-Quality Data: Preparations for Water Sampling*, by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A1. 1998. 47 p.
- 9-A2. *National Field Manual for the Collection of Water-Quality Data: Selection of Equipment for Water Sampling*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A2. 1998. 94 p.
- 9-A3. *National Field Manual for the Collection of Water-Quality Data: Cleaning of Equipment for Water Sampling*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A3. 1998. 75 p.
- 9-A5. *National Field Manual for the Collection of Water-Quality Data: Processing of Water Samples*, edited by F.D. Wilde, D.B. Radtke, Jacob Gibs, and R.T. Iwatsubo: USGS-TWRI Book 9, Chapter A5. 1999, 149 p.
- 9-A6. *National Field Manual for the Collection of Water-Quality Data: Field Measurements*, edited by F.D. Wilde and D.B. Radtke: USGS-TWRI Book 9, Chapter A6. 1998. Variously paginated.
- 9-A7. *National Field Manual for the Collection of Water-Quality Data: Biological Indicators*, by D.N. Myers and F.D. Wilde: USGS-TWRI Book 9, Chapter A7.1. 1997. 49 pages.
- 9-A7. *National Field Manual for the Collection of Water-Quality Data: Five-Day Biochemical Oxygen Demand*, by G.C. Delzer and S.W. McKenzie: USGS-TWRI Book 9, Chapter A7.2 1999. 28 p.
- 9-A8. *National Field Manual for the Collection of Water-Quality Data: Bottom-Material Samples*, by D.B. Radtke: USGS-TWRI Book 9, Chapter A8. 1998. 48 pages.
- 9-A9. *National Field Manual for the Collection of Water-Quality Data: Safety in Field Activities*, by S.L. Lane and R.G. Fay: USGS-TWRI Book 9, Chapter A9. 1998. 60 pages.

SUSQUEHANNA RIVER BASIN



EXPLANATION




- ▲ 5755 STREAMFLOW STATION AND NUMBER
- △ 5747 LAKE AND NUMBER
- ◆ 5760 STREAMFLOW AND WATER-QUALITY STATION AND NUMBER
- ▼ 57654 WATER-QUALITY STATION AND NUMBER
- CU2 OBSERVATION WELL AND NUMBER


NOTE: Downstream station numbers are abbreviated; the first two digits (part number) and the last two digits (if zeros) are omitted (for example, station number 01573560 is shown as 57356, and station number 01570500 is shown as 5705).

Figure 5.--Location of continuous-record data-collection stations and network observation wells, Susquehanna River Basin.

SUSQUEHANNA RIVER BASIN



- LN2071
- LN2072
- LN2073
- LN2074
- LN2075
- LN2076
- LN2090
- LN2092
- LN2096
- LN2097
- LN2098
- LN2099
- LN2100
- LN2101
- LN2102
- LN2103
- LN2104
- LN2105
- LN2106
- LN2107
- LN2108
- LN2109
- LN2110
- LN2111
- LN2112
- LN2113
- LN2114
- LN2115
- LN2116
- LN2117
- LN2118
- LN2119
- LN2120
- LN2121
- LN2122
- LN2123
- LN2124
- LN2125
- LN2126
- LN2127
- LN2128
- LN2129
- LN2130
- LN2131
- LN2132
- LN2133
- LN2134
- LN2135
- LN2136
- LN2137
- LN2138
- LN2139
- LN2140
- LN2141
- LN2142
- LN2143
- LN2144
- LN2145
- LN2146
- LN2147
- LN2148
- LN2149
- LN2150
- LN2151
- LN2152
- LN2153
- LN2154
- LN2155
- LN2156
- LN2157
- LN2158
- LN2159
- LN2160
- LN2161
- LN2162
- LN2163
- LN2164
- LN2165
- LN2166
- LN2167
- LN2168
- LN2169
- LN2170
- LN2171
- LN2172
- LN2173
- LN2174
- LN2175
- LN2176
- LN2177
- LN2178
- LN2179
- LN2180
- LN2181
- LN2182
- LN2183
- LN2184
- LN2185
- LN2186
- LN2187
- LN2188
- LN2189
- LN2190
- LN2191
- LN2192
- LN2193
- LN2194
- LN2195
- LN2196
- LN2197
- LN2198
- LN2199
- LN2200
- LN2201
- LN2202
- LN2203
- LN2204
- LN2205
- LN2206
- LN2207
- LN2208
- LN2209
- LN2210
- LN2211
- LN2212
- LN2213
- LN2214
- LN2215
- LN2216
- LN2217
- LN2218
- LN2219
- LN2220
- LN2221
- LN2222
- LN2223
- LN2224
- LN2225
- LN2226
- LN2227
- LN2228
- LN2229
- LN2230
- LN2231
- LN2232
- LN2233
- LN2234
- LN2235
- LN2236
- LN2237
- LN2238
- LN2239
- LN2240
- LN2241
- LN2242
- LN2243
- LN2244
- LN2245
- LN2246
- LN2247
- LN2248
- LN2249
- LN2250
- LN2251
- LN2252
- LN2253
- LN2254
- LN2255
- LN2256
- LN2257
- LN2258
- LN2259
- LN2260
- LN2261
- LN2262
- LN2263
- LN2264
- LN2265
- LN2266
- LN2267
- LN2268
- LN2269
- LN2270
- LN2271
- LN2272
- LN2273
- LN2274
- LN2275
- LN2276
- LN2277
- LN2278
- LN2279
- LN2280
- LN2281
- LN2282
- LN2283
- LN2284
- LN2285
- LN2286
- LN2287
- LN2288
- LN2289
- LN2290
- LN2291
- LN2292
- LN2293
- LN2294
- LN2295
- LN2296
- LN2297
- LN2298
- LN2299
- LN2300



EXPLANATION



- ▲ 5775 STREAMFLOW STATION AND NUMBER
- ▼ 57834 WATER-QUALITY STATION AND NUMBER
- ▼ LN2070 WATER-QUALITY STATION AND WELL NUMBER

NOTE: Downstream station numbers are abbreviated; the first two digits (part number) and the last two digits (if zeros) are omitted (for example, station number 01570280 is shown as 57028, and station number 01577500 is shown as 5775).

Figure 6.--Location of partial-record data-collection stations, Susquehanna River Basin.

POTOMAC RIVER BASIN




Figure 7.--Location of continuous- and partial-record data-collection stations, Potomac River Basin.

SPECIAL NOTES, REMARK CODES, AND SELECTED CONSTITUENT DEFINITIONS

NOTES--Traditionally, dissolved trace-element concentrations have been reported at the microgram per liter($\mu\text{G/L}$) level. Recent evidence, mostly from large rivers, indicates that actual dissolved-phase concentrations for a number of trace elements are within the range of 10's to 100's of nanograms per liter (ng/L). Data above the $\mu\text{G/L}$ level should be viewed with caution. Such data may actually represent elevated environmental concentrations from natural or human causes; however, these data could reflect contamination introduced during sampling, processing, or analysis. To confidently produce dissolved trace-element data with insignificant contamination, the U.S. Geological Survey began using new trace-element protocols at some stations in water year 1994. Full implementation of the protocols took place during the 1995 water year.

--Sample handling procedures at all **National Trends Network** stations were changed substantially on January 11, 1994, in order to reduce contamination from the sample shipping container. The data for samples before and after that date are different and not directly comparable. A tabular summary of the differences based on a special intercomparison study, is available from the NADP/NTN Coordination Office, Colorado State University, Fort Collins, CO 80523 (Telephone: 303-491-5643).

--In March 1989 a bias was discovered in the turbidimetric method for sulfate analysis for those samples analyzed by the U.S. Geological Survey National Water-Quality Laboratory indicating that values below 75 mg/L have a median positive bias of 2 mg/L above the true value for the period between 1982 and 1989.

--**Methylene blue active substance (MBAS)** determinations made from January 1, 1970, through August 29, 1993, at the National Water Quality Laboratory in Denver (Analyzing Agency Code 80020) are positively biased. These data can be corrected on the basis of the following equation, if concentrations of dissolved nitrate plus nitrite, as nitrogen, and dissolved chloride, determined concurrently with the MBAS data are applied:

$$\text{MBASCOR} = \text{M} - 0.0088\text{N} - 0.00019\text{C}$$

where:

- MBASCOR = corrected MBAS concentration, in mg/L;
- M = reported MBAS concentration, in mg/L;
- N = dissolved nitrate plus nitrite, as nitrogen, in mg/L; and
- C = dissolved chloride concentration, in mg/L.

The detection limit of the new method is 0.02 mg/L, whereas the detection limit for the old method was 0.01 mg/L. A detection limit of 0.02 mg/L should be used with corrected MBAS data from January 1, 1970, through August 29, 1993.

Remark Codes--The following remark codes may appear with the data tables in this report:

PRINTED OUTPUT

REMARK

| | |
|-----|---|
| E,e | Estimated value. |
| > | Actual value is known to be greater than the value shown. |
| < | Actual value is known to be less than the value shown. |
| K | Results based on colony count outside the acceptance range (non-ideal colony count). |
| L | Biological organism count less than 0.5 percent (organism may be observed rather than counted). |
| D | Biological organism count equal to or greater than 15 percent (dominant). |
| & | Biological organism estimated as dominant. |
| ND | Material specifically analyzed for but not detected. |
| V | Analyte was detected in both the environmental sample and the associated blanks. |

EXPLANATION OF CODES USED TO DEFINE SAMPLE COLLECTION PROCEDURES (partial listing)

(71999) SAMPLE PURPOSE CODES:

- 10--Routine
- 15--NAWQA
- 20--NASQAN
- 30--Benchmark

(84164) SAMPLER TYPE: (partial list)

- 110--Sewage sampler
- 3011--US D-77
- 3035--DH-76 Trace metal sampler with teflon gasket and nozzle
- 3039--D-77 Trace metal
- 3040--D-77 Trace metal modified teflon bag sampler
- 3045--DH-81 with Teflon cap and nozzle
- 8010--Other (other than a defined sampler type)

(82398) SAMPLE METHOD CODES:

- 10--Equal width increment
- 20--Equal discharge increment
- 30--Single vertical
- 40--Multiple verticals
- 50--Point sample
- 70--Grab sample
- 120--Velocity integrated
- 8010--Other

SPECIAL NOTES, REMARK CODES AND SELECTED CONSTITUENT DEFINITIONS--Continued**Explanation of selected abbreviations used in constituent definitions in water-quality tables:**

| | |
|--------------|--|
| AC-FT | acre-feet |
| BOT MAT | bottom material (Unconsolidated material of which a streambed, lake, pond, reservoir, or estuary bottom is composed.) |
| COLS/100 ML | colonies per 100 milliliters |
| DIS | dissolved |
| FET | fixed end-point titration |
| FLD | field (Measurement determined at field site.) |
| F/S | feet per second |
| G/M | gallons per minute |
| G/SQM; MG/M2 | grams or milligrams per square meter |
| IT | incremental titration |
| KF AGAR | nutrient medium for growth of fecal streptococcal bacteria |
| µG/L | micrograms per liter |
| µS/CM | microsiemens per centimeter |
| MG/L | milligrams per liter |
| MG/M2 | milligrams per square meter |
| MM OF HG | millimeters of mercury |
| NONCARB | noncarbonate |
| NTU | nephelometric turbidity unit |
| PCI/L | picocuries per liter |
| REC | recoverable |
| TOT | total |
| T/DAY | tons per day |
| WH IT | whole water, incremental titration (Alkalinity, bicarbonate, and carbonate as determined by incremental titration of unfiltered water at the field site.) |
| 2 SIGMA | Counting statistic that represents error in the reported radon, uranium, or tritium value caused by variations in sample counting, background radiation, volume of sample, and decay since sample was collected. |
| 0.7µ GF | 0.7 micron glass-fiber filter (Water filtered through a glass-fiber membrane filter with openings that are 0.7 microns in size.) |

(00027) AGENCY COLLECTING SAMPLE CODES:

1028 --U.S. Geological Survey

(00028) AGENCY ANALYZING SAMPLE CODES:

1028 --U.S. Geological Survey
80020 --U.S. Geological Survey, National Water-Quality Laboratory, Denver, Colorado
9813 --Pennsylvania Department of Environmental Protection
83613 --District Water-Quality Laboratory, Troy, New York