

GROUND-WATER LEVEL DATA

YUKON ALASKA

FAIRBANKS NORTH STAR BOROUGH

644402147150401. Local number, FD00200224ABBA1002.

LOCATION.--Lat 64°44'02", Long 147°15'04", in NW¹/₄ NW¹/₄ NE¹/₄ sec. 24, T.2 S., R.2 E., (Fairbanks C-1 NW quad), Fairbanks Meridian, Hydrologic Unit 19040506. Well located approximately 0.1 mi east of Laurance Road and Nelson Road intersection, then 50 ft east of road behind grove of trees towards levee, North Pole.

Owner: U.S. Army Corps of Engineers.

AQUIFER.--Chena Alluvium of Quaternary age.

WELL CHARACTERISTICS.--Diameter 2-in. PVC casing, depth 19.4 ft, screen openings from 9.4 to 13.9 ft and 14.4 to 18.9 ft.

INSTRUMENTATION.--Intermittent measurements by USGS personnel July 2001 to current year; submersible pressure transducer/electronic data logger from October 5, 2001 to current year.

DATUM.--Elevation of land-surface datum is 504.74 ft above NGVD of 1929 (revised; levels by US Army Corps of Engineers, adjusted to 1992 survey of benchmarks by U.S. Coast and Geodetic Survey). Measuring point: top of inner casing 2.57 ft above land surface datum.

REMARKS.--Observation well drilled March 12, 1995 by the U.S. Army Corps of Engineers and designated as DSAP-11.

PERIOD OF RECORD.--July 2001 to current year.

EXTREMES FOR PERIOD OF RECORD.--Highest water level measured, 10.74 ft below land-surface datum, September 17-18, 2003; lowest, 13.31 ft below land-surface datum, April 19 and 21-25, 2002.

EXTREMES FOR CURRENT YEAR.--Highest water level measured, 11.00 ft below land-surface datum, October 1; lowest, 13.26 ft below land-surface datum, April 8.

DEPTH BELOW LAND SURFACE (WATER LEVEL) (FEET), WATER YEAR OCTOBER 2003 TO SEPTEMBER 2004
DAILY HIGHEST WATER LEVEL

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	11.00	11.68	12.17	12.54	12.85	13.06	13.21	12.62	12.02	11.84	11.94	12.03
2	11.02	11.70	12.17	12.56	12.86	13.06	13.20	12.62	12.02	11.84	11.93	12.05
3	11.03	11.72	12.18	12.57	12.86	13.06	13.22	12.61	12.00	11.83	11.92	---
4	11.07	11.75	12.19	12.58	12.87	13.07	13.22	12.60	11.99	11.82	11.92	---
5	11.08	11.77	12.20	12.59	12.89	13.07	13.23	12.60	11.97	11.82	11.92	---
6	11.09	11.79	12.21	12.60	12.90	13.07	13.23	12.59	11.97	11.82	11.93	---
7	11.11	11.81	12.22	12.61	12.91	13.08	13.24	12.58	11.95	11.82	11.94	---
8	11.13	11.82	12.23	12.61	12.90	13.08	13.24	12.54	11.95	11.83	11.96	12.14
9	11.15	11.85	12.24	12.62	12.93	13.08	13.24	12.52	11.93	11.82	11.97	12.15
10	11.17	11.87	12.25	12.62	12.93	13.09	13.24	12.49	11.92	11.82	11.97	12.16
11	11.20	11.90	12.26	12.64	12.94	13.10	13.21	12.45	11.90	11.83	11.98	12.17
12	11.22	11.91	12.27	12.65	12.95	13.10	13.17	12.41	11.89	11.84	11.98	12.19
13	11.24	11.94	12.29	12.67	12.96	13.11	13.13	12.37	11.89	11.85	11.99	12.22
14	11.27	11.97	12.30	12.67	12.97	13.11	13.08	12.33	11.88	11.87	12.00	12.24
15	11.28	11.99	12.31	12.68	12.97	13.12	13.03	12.31	11.87	11.88	11.99	12.26
16	11.29	12.02	12.32	12.70	12.98	13.13	13.00	12.28	11.87	11.90	12.00	---
17	11.31	12.04	12.34	12.70	12.99	13.13	12.96	12.26	11.87	11.90	---	---
18	11.33	12.05	12.35	12.71	12.99	13.14	12.93	12.24	11.87	11.91	---	12.32
19	11.35	12.07	12.36	12.72	13.00	13.15	12.88	12.21	11.86	11.92	---	12.33
20	11.38	12.09	12.38	12.72	13.00	13.15	12.85	12.19	11.86	11.92	---	12.35
21	11.40	12.09	12.39	12.74	13.00	13.15	12.80	12.17	11.86	11.92	---	12.37
22	11.43	12.11	12.39	12.76	13.01	13.15	12.77	12.15	11.86	11.93	---	12.38
23	11.44	12.11	12.42	12.77	13.02	13.16	12.75	12.14	11.86	11.92	---	12.41
24	11.47	12.11	12.43	12.78	13.03	13.16	12.72	12.12	11.86	11.91	---	12.43
25	11.49	12.13	12.45	12.79	13.03	13.18	12.70	12.11	11.87	11.91	---	12.45
26	11.52	12.14	12.47	12.79	13.03	13.18	12.68	12.10	11.86	11.90	---	12.46
27	11.56	12.13	12.47	12.80	13.04	13.18	12.66	12.08	11.86	11.90	---	12.49
28	11.58	12.13	12.49	12.81	13.05	13.18	12.65	12.07	11.86	11.91	---	---
29	11.61	12.15	12.49	12.82	13.05	13.19	12.64	12.06	11.85	11.93	---	---
30	11.63	12.15	12.51	12.83	---	13.20	12.62	12.05	11.84	11.95	---	12.55
31	11.65	---	12.53	12.84	---	13.20	---	12.03	---	11.95	---	---